# From Pixels to Titles: Video Game Identification by Screenshots using Convolutional Neural Networks

Fabricio Breve

Instituto de Geociências e Ciências Exatas, Universidade Estadual Paulista "Júlio de Mesquita Filho", Avenida 24A, 1515, Rio Claro, 13506-900, São Paulo, Brazil.

Contributing authors: fabricio.breve@unesp.br;

#### Abstract

This paper investigates video game identification through single screenshots, utilizing five convolutional neural network (CNN) architectures (MobileNet, DenseNet, EfficientNetB0, EfficientNetB2, and EfficientNetB3) across 22 home console systems, spanning from Atari 2600 to PlayStation 5, totalling 8,796 games and 170,881 screenshots. Confirming the hypothesis, CNNs autonomously extract image features, enabling the identification of game titles from screenshots without additional features. Using ImageNet pre-trained weights as initial weights, EfficientNetB3 achieves the highest average accuracy (74.51%), while DenseNet169 excels in 14 of the 22 systems. Employing alternative initial weights trained in an arcade screenshots dataset boosts accuracy for EfficientNetB2 and EfficientNetB3, with the latter reaching a peak accuracy of 76.36% and demonstrating reduced convergence epochs from 23.7 to 20.5 on average. Overall, the combination of optimal architecture and weights attains 77.67% accuracy, primarily led by EfficientNetB3 in 19 systems. These findings underscore the efficacy of CNNs in video game identification through screenshots.

 ${\bf Keywords:} \ {\it video \ game \ identification, \ convolutional \ neural \ networks, \ transfer \ learning, \ single \ screenshot \ analysis, \ automated \ game \ recognition }$ 

## 1 Introduction

Humans possess the remarkable ability to easily recognize their favorite video games or titles they have played frequently from a single screenshot. This proficiency is rooted in the presence of consistent visual elements, including sprites, heads-up displays (HUDs), and distinctive game scenarios. However, extending this capability to the automated identification of random video games from an extensive console library presents a formidable challenge, even for the most dedicated gamers. Therefore, the concept of automatically identifying video games from single screenshots holds immense appeal, not only for its technical complexity but also for its vast practical applications.

Automated game identification could offer substantial benefits to various sectors within the gaming industry. Video game databases, search engines, and online platforms stand to gain significantly from this technology. By analyzing user-uploaded screenshots, these platforms can automatically generate metadata, including game titles, release dates, and developer information. Such automation would not only improve the accuracy of their game libraries but also enhance cataloging efficiency. Moreover, online streaming platforms could harness screenshot recognition to provide real-time information to viewers about the games being played during live streams, enhancing the overall viewer experience. This technology opens doors to further innovation within the gaming ecosystem, potentially influencing game recommendation systems and aiding game-related research.

Most of the video games classification attempts so far aimed at genre classification. Augusto De Souza et al. [1] pioneering work classified game genre of gameplay videos. Their dataset comprises 700 gameplay videos spanning seven distinct game genres. In their research, they introduced novel descriptors known as Bossa Nova and BinBoost. The experimental outcomes demonstrated the effectiveness of their proposed approach, achieving an accuracy rate of 89.84%.

Göring et al. [2] also introduced a novel method for classifying video games genres based on content. They used a dataset comprising 351 gameplay videos spanning six different genres. They employed random forest and gradient boosting trees as underlying machine-learning techniques, combined with feature selection of imagebased features and motion-based features. The most promising results were achieved using the random forest classifier, which yielded an accuracy rate of 60.6%.

Zadtootaghaj et al. [3] introduced a game classification method based on graphical and video complexity. Their approach categorizes games into three distinct classes: low-complexity, medium-complexity, and high-complexity games. To achieve this classification, they developed a decision tree capable of accurately assigning a game to its appropriate complexity class with an accuracy rate of 96%. The classification process relies on the analysis of specific attributes within the gameplay video, including the observation of a static area, assessment of the degree of freedom (DoF), and quantification of camera movement.

While the majority of classification endeavors have typically focused on broader categories, there was a unique attempt to classify video games by their titles more than a decade ago. In this pioneering effort, Madani et al. [4] explored several fusion methods using a dataset containing 120,000 gameplay videos, with the objective of identifying game titles. Their approach integrated both audio and visual features to accurately pinpoint these specific game titles, ultimately achieving a F1-score of 0.82. Although their dataset is considerably large, they explored only a small number of games, identifying 30 distinct game titles. To the best of my knowledge, there has not been any other attempt to identify video games by their titles, especially in larger datasets with hundreds or thousands of titles, neither using video nor screenshots.

In the past decade, there has been a notable surge in the adoption of deep learning methods, as exemplified by the works of LeCun et al. [5], Goodfellow et al. [6], and Schmidhuber [7]. Among these methods, convolutional neural networks (CNNs) have played a pivotal role in driving advancements in automatic image classification, as initially demonstrated by Krizhevsky et al. [8]. CNNs represent a specific category of deep neural networks that find widespread use in the field of visual image analysis.

However, one of the inherent challenges associated with CNNs lies in their substantial appetite for annotated image samples, which are essential for estimating the millions of parameters required for network training. The process of annotating images can be both expensive and time-consuming, often presenting a significant bottleneck, particularly when dealing with problems characterized by limited available training data [9]. This limitation has, at times, hindered the widespread application of CNNs in scenarios where access to abundant training data is restricted.

Remarkably, Oquab et al. [9] addressed this predicament by unveiling a breakthrough approach. Their research demonstrated that image representations acquired through CNNs trained on extensive, annotated datasets could be judiciously leveraged for other visual recognition tasks, even in cases where only a limited amount of training data is available. This innovative method involved repurposing layers from a CNN model previously trained on a large dataset to compute mid-level image representations for a different dataset, yielding remarkable improvements in classification performance. This powerful technique, commonly referred to as transfer learning, has found successful application across various domains and scenarios, as exemplified by the works of Shin et al. [10] Huynh et al. [11] and Gopalakrishnan et al. [12].

CNNs have significantly influenced the landscape of automatic image classification, including game classification. Suatap and Patanukhom [13] used games screenshots and icons provided in game stores to classify them by genre using convolutional neural networks and ensemble techniques. They achieved 40.3% and 46.7% classification accuracies for single icon and screenshot classification tasks, respectively. They increased these results to 40.5% and 47.6%, respectively, in a later work [14], in which they also used features extracted from their trained models to perform other two tasks: similar game searching and quality assessment of game images based on the correctness of viewers' understanding of game content.

Recently, Jiang and Zheng [15] devised deep neural networks for the purpose of classifying game genres using either cover images or description text. Their dataset encompassed cover images and description texts sourced from a pool of 50,000 games, which they categorized into 15 distinct genres. In their approach, several pre-trained CNNs were fine-tuned for the cover image classification task. For the classification of description text, they employed Long Short-Term Memory (LSTM) networks and the Universal Sentence Encoder (USE). The image-based model yielded a highest accuracy rate of 31.4% when utilizing ResNet-50. They also achieved significant improvement in accuracy, up to 49.9%, by combining image and text features within a multi-modal model.

Both of these previous studies were limited to identifying game genres, and their accuracy was only moderate (below 50%). Until now, there has been no attempt to identify game titles using CNNs, which is a more challenging task than identifying only the game genres. In this paper, the primary focus revolves around the task of video game title classification based on single screenshots, utilizing CNN models. The hypothesis is that the inherent CNN capacity of automatically extracting relevant features from images is sufficient to identify video game titles from single screenshots in most scenarios, without relying on other features. To embark on this journey, a dataset encompassing 170,881 screenshots from 8,796 games of 22 popular home console systems was curated. The screenshots were sourced from

the reputable Moby Games Database [16]. The proposed dataset spans a wide spectrum of gaming history, ranging from iconic consoles like the 'Atari 2600' of the second generation to the cutting-edge 'PlayStation 5' and 'Xbox Series' of the current generation, carefully selecting the most sold consoles from each generation between them. Its richness and diversity make it an ideal playground for our research.

To tackle this ambitious task, well-established CNN architectures were selected: MobileNet [17], DenseNet [18], and EfficientNet [19]. These architectures have consistently demonstrated outstanding performance in previous works with different kinds of images [20, 21], making them prime candidates for this game title classification task. The initial weights of these CNNs were first initialized with pre-trained weights from the ImageNet dataset [22], a widely adopted approach in transfer learning [9]. Subsequently, the pre-trained weights from another dataset of screenshots were employed to enhance both classification accuracy and reduce training times.

What sets this research apart is its pioneering spirit. To the best of my knowledge, this marks the first attempt to tackle the intriguing challenge of game title classification using CNNs. By pushing the boundaries of automated video game identification, the aim is to contribute valuable insights to game-related research and practical applications to the ever-evolving gaming industry.

The remainder of this paper is organized as follows. Section 2 presents the Moby Games Database and how the dataset was sourced from it. Section 3 shows the CNN architectures employed in this paper. Section 4 displays the computer simulations comparing the CNN architectures in the task of identifying the games from their screenshots, initialized with pre-trained weights from the ImageNet dataset. Section 5 demonstrates computer simulations using weights pre-trained in another screenshots dataset, comparing the accuracy and training epochs with those obtained with the ImageNet weights. Finally, the conclusions are drawn in Section 6.

#### 2 The Dataset

The Moby Games Database [16], as stated on their website, is an ambitious project with the primary goal of meticulously cataloging comprehensive information about electronic games, encompassing computer, console, and arcade titles, on a gameby-game basis. This extensive catalog includes release details, credits, cover art, player-uploaded screenshots with captions, neutral descriptions, and much more. Impressively, the database boasts a collection of over one million screenshots, meticulously organized by game titles and systems. Additionally, they offer an API that simplifies the process of requesting and retrieving dataset entries and screenshot files. Given these advantages, the Moby Games Database was selected as the primary source for the screenshots used in this research.

To maintain a focused scope for this initial endeavor in video game identification using CNNs, the study exclusively considered home video game consoles. Handheld devices, arcade games, and computer-based titles will be addressed in future research. The selection process involved choosing the top 22 best-selling home video game consoles of all time [23]. These consoles originate from six different manufacturers and exhibit varying quantities of screenshots per game in the database, ranging from none to a few dozen. To ensure that each game has a minimum of five screenshots available for cross-validation purposes, only games meeting this criterion were selected. Table 1 provides an overview of the 22 chosen systems, detailing their total game and screenshot counts, as well as the specific number of games and screenshots selected to satisfy the "at least 5 screenshots" criterion. Figure 1 shows some screenshots from the built dataset.

# 3 CNN Architectures

In this section, the CNN architectures explored in this study are introduced, along with a description of the additional layers integrated to achieve successful screenshot classification. Table 2 offers an overview of the four architectures under examination, highlighting their input image resolution, the size of their output in the final convolutional layer, the quantity of parameters involved, and citations to their respective references in the literature.

The output from the final convolutional layer of the original CNN is directed into a global average pooling layer. Subsequently, a dropout layer is implemented with a rate of 20% to mitigate overfitting, followed by a large softmax classification layer with up to 1,236 outputs, which is the amount of game titles in the dataset for the NES console. This proposed architecture is visualized in Figure 2, with x representing the dimensions of the input size (image size), w, y, and z indicating the dimensions of the CNN output in its ultimate convolutional layer (as detailed in Table 2), and g denoting the output layer's dimensions, which depend on the number of games from the system being evaluated that are present in the dataset (as indicated in Table 1).

## 4 CNN Comparison

This section presents computer simulations that compare CNN models applied to the classification of screenshots from the 22 systems shown in Table 1. All simulations utilized Python and Tensor-Flow running on three distinct desktop computers equipped with NVIDIA GeForce GPU boards: GTX 970, GTX 1080, and RTX 2060 SUPER, respectively<sup>1</sup>.

For each CNN architecture, image preparation involved resizing to fit the CNN input size and normalizing the range, with no additional preprocessing. Networks commenced with pre-trained weights sourced from the Imagenet dataset [22], which boasts millions of images and hundreds of classes, widely used in transfer learning. These pre-trained weights are available in Tensorflow.

K-Fold Cross Validation, employing k = 5, was applied universally across all datasets. Training utilized the Adam optimizer [24], initiating with a learning rate of  $10^{-3}$  and halving whenever the validation accuracy stagnated for 2 epochs, down to a minimum of  $10^{-5}$ . Within the training subset, a random 20% of images were allocated to the validation subset, ensuring consistent class proportions through stratification. All models underwent training for up to 50 epochs, with an early stopping criterion to cease training if the validation set loss failed to decrease during the last 10 epochs.

The results, detailed in Table 3, denote averages derived from five different instances of each model, following the Cross Validation approach. They show that DenseNet169 achieved the best accuracy in 14 of the 22 systems. On the other

 $<sup>^1\</sup>mathrm{Access}$  the source code at <code>https://github.com/fbreve/videogame</code>

System	Manufacturer	Selected Games	Total Games	Selected Screenshots	Total Screenshots
Atari 2600	Atari	302	598	2148	2981
NES	Nintendo	1236	1426	18277	18579
Master System	Sega	322	357	4795	4850
PC Engine	NEC/Hudson Soft	213	276	3024	3099
Mega Drive	Sega	926	1016	15838	15943
Super Nintendo	Nintendo	1113	1216	20926	21079
Sega Saturn	Sega	249	809	4413	4536
PlayStation	Sony	1197	2815	26831	27095
Nintendo 64	Nintendo	172	378	2958	3125
Dreamcast	Sega	155	553	2147	2217
PlayStation 2	Sony	677	3430	14157	14590
GameCube	Nintendo	149	621	3061	3094
Xbox	Microsoft	161	1015	3351	3379
Xbox $360$	Microsoft	651	9357	9087	9426
PlayStation 3	Sony	255	15146	8358	8493
Wii	Nintendo	118	2680	2519	2655
Wii U	Nintendo	31	1590	775	798
PlayStation 4	Sony	625	22733	22695	22912
Xbox One	Microsoft	119	16545	2397	2661
Nintendo Switch	Nintendo	77	12374	1736	1787
Xbox Series	Microsoft	5	3256	37	44
PlayStation 5	Sony	43	2432	1351	1356
Total		8796	100623	170881	174699

 Table 1
 Home Console Video Game Systems, Their Manufacturers, and the Total/Selected Number of Games and

 Screenshots for the Study. Games with a minimum of five available screenshots in the database were chosen for analysis.

Model	Input Image Resolution	Output of Last Conv. Layer	Parameters	Reference
MobileNet	$224 \times 224$	$7\times7\times1024$	4.3M	Howard et al. [17]
DenseNet169	$224 \times 224$	$7 \times 7 \times 1664$	14.3M	Huang et al. $[18]$
EfficientNetB0	$224 \times 224$	$7\times7\times1280$	5.3M	Tan and Le $\begin{bmatrix} 19 \end{bmatrix}$
EfficientNetB2	$260 \times 260$	$9 \times 9 \times 1408$	9.2M	Tan and Le $\begin{bmatrix} 19 \end{bmatrix}$
EfficientNetB3	$300 \times 300$	$10\times10\times1536$	12.3M	Tan and Le $[19]$

 Table 2
 CNN architectures, some of their characteristics, and their references.

hand, the best average accuracy is attained by EfficientNetB3 (0.7451) which is only slightly higher than that achieved by the runner-up DenseNet169 (0.7446).

Regarding the systems, the best accuracy is achieved with the *Xbox Series* using Efficient-NetB3 (0.9714). However, it is worth noticing that this system only had 37 screenshots from a total of five games. Its results were markedly worse with DenseNet169 (0.6071), for example. The *Atari*  2600 is the system with the best average accuracy (0.8942). This is likely related to the simpler graphics of this second-generation console compared to newer systems. Most games for the *Atari* 2600 do not exhibit significant screen variation.

In simpler tasks, smaller architectures often perform as well as larger ones. It's valuable to consider these smaller networks when selecting the optimal architecture for a task because if a smaller network can yield comparable results in





Enduro - Atari 2600

Super Mario Bros. - NES

🎭 C 🔜 🚟



The Legend of Zelda -NES



Alex Kidd in Miracle World - Master System



Bonk's Adventure - PC Engine



Sonic the Hedgehog -Genesis



Super Mario 64 -Nintendo 64



0 x 400

Super Nintendo



Virtua Fighter 2 - Sega Saturn



Gran Turismo -PlayStation

4%



Final Fantasy VII -PlayStation



Halo: Combat Evolved -Xbox



Halo 3 - Xbox 360



Horizon: Zero Dawn -PlayStation 4



Sonic Adventure -

Dreamcast

PlayStation 3

Gears of War 4 - Xbox

One



Grand Theft Auto: San

Wii Sports - Wii

The Legend of Zelda:

Breath of the Wild -

Nintendo Switch



Super Smash Bros.:

Melee - GameCube

Mario Kart 8 - Wii U



Forza Horizon 5 - Xbox Series



The Witcher 3: Wild Hunt - PlayStation 4



Ratchet & Clank: Rift Apart - PlayStation 5

Fig. 1 Some examples of screenshots from the proposed dataset.

less computational time, there's no justification for employing a larger one. This rationale led to the inclusion of MobileNet and EfficientNetB0 in this comparison. However, in the context of video game detection by screenshot, it became evident that larger networks outperformed the smaller ones.

# **5** Alternative Initial Weights

The ImageNet weights are commonly used in many transfer learning scenarios with success. Through fine-tuning, these weights can be adapted to perform many different tasks. However, it is expected that transferring weights from a similar task might enhance accuracy and reduce training

System	Mobile- Net	Dense- Net169	Efficient- NetB0	Efficient- NetB2	Efficient- NetB3	Average
Atari 2600	0.8925	0.8939	0.8892	0.8920	0.9036	0.8942
NES	0.6550	0.6719	0.6845	0.6876	0.6780	0.6754
Master System	0.7070	0.7452	0.7124	0.7418	0.7429	0.7299
PC Engine	0.7543	0.7989	0.7771	0.7834	0.7890	0.7806
Mega Drive	0.6751	0.7307	0.7326	0.7246	0.7307	0.7188
Super Nintendo	0.6724	0.7247	0.7015	0.7142	0.7081	0.7042
Sega Saturn	0.6973	0.7494	0.6728	0.6841	0.7050	0.7017
PlayStation	0.6908	0.7079	0.6768	0.7227	0.7402	0.7077
Nintendo 64	0.7654	0.8327	0.7383	0.7681	0.7776	0.7764
Dreamcast	0.6521	0.7513	0.6349	0.6735	0.6758	0.6775
PlayStation 2	0.6939	0.7273	0.6836	0.7126	0.7345	0.7104
GameCube	0.7416	0.8233	0.7207	0.7540	0.7498	0.7579
Xbox	0.7804	0.8439	0.7386	0.7929	0.7860	0.7883
Xbox $360$	0.7413	0.7859	0.7339	0.7623	0.7768	0.7600
PlayStation 3	0.6218	0.7073	0.6658	0.6890	0.7182	0.6804
Wii	0.7638	0.8337	0.7555	0.7674	0.7840	0.7809
Wii U	0.6594	0.7264	0.6942	0.7006	0.7187	0.6999
PlayStation 4	0.5601	0.6151	0.5975	0.6273	0.6477	0.6096
Xbox One	0.5582	0.6458	0.5791	0.5858	0.6350	0.6008
Nintendo Switch	0.7362	0.8001	0.7511	0.7811	0.7886	0.7714
Xbox Series	0.7643	0.6071	0.9178	0.9714	0.9714	0.8464
PlayStation 5	0.5714	0.6580	0.5863	0.6188	0.6299	0.6129
Average	0.6979	0.7446	0.7111	0.7343	0.7451	0.7266

 Table 3
 Accuracy achieved by the five different CNN models in each of the 22 screenshots datasets. Each model is

executed five times following the Cross Validation approach. The highest accuracy for each dataset is highlighted in bold.



 ${\bf Fig. \ 2} \ \ {\rm The \ proposed \ CNN \ Transfer \ Learning \ architecture}.$ 

times compared to using the ImageNet weights. Hence, investigating whether this holds true for the game identification by screenshots task is worthwhile.

To conduct these simulations, Arcade screenshots were obtained from the Moby Games Database using the same criteria applied in sourcing screenshots from home console systems. Out of 3,125 games and 24,714 screenshots, 1,633 games and 24,235 screenshots were selected based on the criterion of 'at least five screenshots per game.' This Arcade dataset holds particular significance due to the inclusion of games contemporary to multiple home console generations, thereby presenting screenshots with highly diverse graphics.

From the architectures that exhibited the best performance in the previous section — DenseNet169, EfficientNetB2, and EfficientNetB3 — each was trained using the entire *Arcade* dataset, utilizing identical parameters as outlined earlier. The weights obtained from training on the *Arcade* dataset were subsequently employed as initial weights for training these architectures with screenshots from each of the 22 home console systems.

Tables 4, 5, and 6 display the accuracy achieved and the epochs required to train each network, using both the ImageNet and Arcade weights. For DenseNet169, employing the Arcade weights resulted in improved accuracy for only 6 out of the 22 systems. However, training times decreased for 21 of the 22 systems. Overall, while the average accuracy slightly decreased from 0.7446 to 0.7432, the average number of epochs needed to train the network decreased from 24.2 to 19.6.

For EfficientNetB2 (Table 5), employing the *Arcade* weights resulted in improved accuracy for 19 of the 22 systems. Additionally, training times decreased for 20 of the 22 systems. Overall, the average accuracy increased from 0.7343 to 0.7552, while the average number of epochs needed to train the network decreased from 24.4 to 19.9

Finally, with EfficientNetB3 (Table 6), employing the *Arcade* weights similarly led to improved accuracy for 19 of the 22 systems. Moreover, training times decreased for 20 of the 22 systems. Overall, the average accuracy increased from 0.7451 to 0.7636, while the average number of epochs required to train the network decreased from 23.7 to 20.5. It's worth noting that the systems showing improved accuracy or training times are consistent between EfficientNetB2 and EfficientNetB3.

Table 7 displays the highest accuracy achieved for each system, showcasing the best combination of architecture and initial weights. EfficientNetB3 notably outperforms other architectures, yielding the best results in 19 out of 22 systems, with one tie alongside EfficientNetB2. EfficientNetB2 and DenseNet169 excel in two systems each. Concerning the initial weights, the "Arcade weights" account for the best results in 17 out of 22 systems, while the remaining five systems attained their highest accuracy with the ImageNet initial weights.

#### 6 Conclusions

This paper explores the application of five distinct CNN architectures (MobileNet, DenseNet, EfficientNetB0, EfficientNetB2, and EfficientNetB3) for identifying video games through screenshots across 22 diverse home console systems, from Atari 2600 (first released in 1977) to PlayStation 5 (first released in 2020). This is a pioneering work as it is the first attempt to identify video game titles by their screenshots. The computer simulations confirmed the hypothesis that CNN's inherent capacity of automatically extracting relevant features from images is sufficient to identify video game titles from single screenshots in most scenarios, without relying on other features. Using pre-trained weights from the ImageNet dataset, an average accuracy of 74.51% over all the 22 systems is achieved with the EfficientNetB3 architecture. On the other hand, DenseNet169 architecture is the best in 14 of the 22 tested systems.

When weights pre-trained in another screenshot dataset (*Arcade*) are used as initial weights - instead of those from ImageNet - the accuracy improves for both EfficientNetB2 and Efficient-NetB3, at the same time that the amount of epochs required to converge lowers. The average accuracy over all the 22 systems increases from 74.51% to 76.36% with EfficientNetB3, while the number of epochs required for models to converge decreases from 23.7 to 20.5. On the other hand, the *Arcade* weights do not improve DenseNet169 in most scenarios.

Overall, considering only the best architecture and weights for each system, an accuracy of 77.67% is achieved. EfficientNetB3 is responsible for the best results in 19 from the 22 systems. The "Arcade weights" are responsible for the best results in 17 of the 22 systems, confirming the hypothesis that starting from weights trained on a different dataset but the same task are better than starting with the more general ImageNet weights in most scenarios.

The simulations performed for this paper showed evidence of the efficacy of CNNs in the task of video game identification by screenshots. Since the largest networks explored in this paper achieved the best results, future research will explore even larger CNN architectures and CNN ensembles to further enhance accuracy. Additionally, this study suggests potential applications in other screenshot-based tasks, such as genre classification or similar game searches, leveraging the efficacy of CNNs in video game identification.

#### References

[1] Augusto De Souza, R., Pereira De Almeida,

Weights	ImageNet		Arcade		
System	Epochs	Accuracy	Epochs	Accuracy	
Atari 2600	22.6	0.8939	21.8	0.8971	
NES	22.8	0.6719	14.4	0.7091	
Master System	24.6	0.7452	16.2	0.7454	
PC Engine	25.8	0.7989	17.0	0.8016	
Mega Drive	22.8	0.7307	14.2	0.7252	
Super Nintendo	23.8	0.7247	14.2	0.7209	
Sega Saturn	23.0	0.7494	17.6	0.7211	
PlayStation	23.0	0.7079	14.4	0.6838	
Nintendo 64	29.8	0.8327	19.8	0.7988	
Dreamcast	24.2	0.7513	19.0	0.7261	
PlayStation 2	26.2	0.7273	19.8	0.7170	
GameCube	25.0	0.8233	19.0	0.7942	
Xbox	24.0	0.8439	20.0	0.8177	
Xbox $360$	24.6	0.7859	20.4	0.7625	
PlayStation 3	23.2	0.7073	18.0	0.6767	
Wii	23.2	0.8337	19.2	0.8102	
Wii U	29.0	0.7264	22.4	0.7574	
PlayStation 4	22.6	0.6151	17.6	0.5740	
Xbox One	20.2	0.6458	17.0	0.6379	
Nintendo Switch	25.0	0.8001	21.2	0.7869	
Xbox Series	23.6	0.6071	50.0	0.8429	
PlayStation 5	23.0	0.6580	17.2	0.6447	
Average	24.2	0.7446	19.6	0.7432	

Table 4 Accuracy obtained and epochs needed to train the DenseNet169 architecture in each of the 22 screenshots datasets, with both the ImageNet weights and the Arcade dataset weights as the initial weights. Each model is executed five times following the Cross Validation approach. The highest accuracy and the lowest number of epochs for each dataset are highlighted in bold.

R., Moldovan, A.-N., Patrocínio, Z.K.G., Guimarães, S.J.F.: Gameplay genre video classification by using mid-level video representation. In: 2016 29th SIBGRAPI Conference on Graphics, Patterns and Images (SIBGRAPI), pp. 188–194 (2016). https:// doi.org/10.1109/SIBGRAPI.2016.034

- Göring, S., Steger, R., Rao Ramachandra Rao, R., Raake, A.: Automated genre classification for gaming videos. In: 2020 IEEE 22nd International Workshop on Multimedia Signal Processing (MMSP), pp. 1–6 (2020). https://doi.org/10.1109/ MMSP48831.2020.9287122
- [3] Zadtootaghaj, S., Schmidt, S., Barman, N., Möller, S., Martini, M.G.: A classification

of video games based on game characteristics linked to video coding complexity. In: 2018 16th Annual Workshop on Network and Systems Support for Games (NetGames), pp. 1–6 (2018). https://doi.org/ 10.1109/NetGames.2018.8463434

- [4] Madani, O., Georg, M., Ross, D.: On using nearly-independent feature families for high precision and confidence. In: Fourth Asian Machine Learning Conference, pp. 269–284 (2012). http://jmlr.csail.mit.edu/proceedings/papers/v25/
- [5] LeCun, Y., Bengio, Y., Hinton, G.: Deep learning. nature **521**(7553), 436 (2015)
- [6] Goodfellow, I., Bengio, Y., Courville, A.: Deep Learning. MIT press, ??? (2016)

Weights	ImageNet		Arcade	
System	Epochs	Accuracy	Epochs	Accuracy
Atari 2600	31.6	0.8920	22.4	0.9022
NES	16.6	0.6876	13.4	0.6935
Master System	22.0	0.7418	15.6	0.7489
PC Engine	21.6	0.7834	15.0	0.7996
Mega Drive	21.0	0.7246	13.4	0.7286
Super Nintendo	18.8	0.7142	13.6	0.7153
Sega Saturn	24.6	0.6841	19.0	0.7369
PlayStation	19.6	0.7227	15.8	0.7141
Nintendo 64	30.8	0.7681	21.4	0.8205
Dreamcast	24.4	0.6735	20.0	0.7499
PlayStation 2	20.4	0.7126	18.2	0.7354
GameCube	25.0	0.7540	18.8	0.8190
Xbox	36.8	0.7929	29.2	0.8389
Xbox 360	22.0	0.7623	20.4	0.7863
PlayStation 3	19.0	0.6890	17.8	0.6901
Wii	23.2	0.7674	19.2	0.8265
Wii U	25.8	0.7006	26.8	0.7677
PlayStation 4	20.2	0.6273	15.2	0.5838
Xbox One	19.4	0.5858	16.6	0.6525
Nintendo Switch	25.0	0.7811	19.2	0.8013
Xbox Series	40.6	0.9714	42.8	0.8429
PlayStation 5	29.4	0.6188	24.6	0.6602
Average	24.4	0.7343	19.9	0.7552

Table 5 Accuracy obtained and epochs needed to train the EfficientNetB2 architecture in each of the 22 screenshots datasets, with both the ImageNet weights and the Arcade dataset weights as the initial weights. Each model is executed five times following the Cross Validation approach. The highest accuracy and the lowest number of epochs for each dataset are highlighted in bold.

- Schmidhuber, J.: Deep learning in neural networks: An overview. Neural networks 61, 85–117 (2015)
- [8] Krizhevsky, A., Sutskever, I., Hinton, G.E.: Imagenet classification with deep convolutional neural networks. In: Pereira, F., Burges, C.J.C., Bottou, L., Weinberger, K.Q. (eds.) Advances in Neural Information Processing Systems 25, pp. 1097–1105. Curran Associates, Inc., ??? (2012). http://papers.nips.cc/paper/4824-imagenetclassification-with-deep-convolutional-neuralnetworks.pdf
- [9] Oquab, M., Bottou, L., Laptev, I., Sivic, J.: Learning and transferring mid-level image representations using convolutional neural networks. In: The IEEE Conference on Computer Vision and Pattern Recognition

(CVPR) (2014)

- [10] Shin, H., Roth, H.R., Gao, M., Lu, L., Xu, Z., Nogues, I., Yao, J., Mollura, D., Summers, R.M.: Deep convolutional neural networks for computer-aided detection: Cnn architectures, dataset characteristics and transfer learning. IEEE Transactions on Medical Imaging **35**(5), 1285–1298 (2016) https://doi.org/10. 1109/TMI.2016.2528162
- [11] Huynh, B.Q., Li, H., Giger, M.L.: Digital mammographic tumor classification using transfer learning from deep convolutional neural networks. Journal of Medical Imaging 3(3), 1–5 (2016) https://doi.org/10.1117/1. JMI.3.3.034501
- [12] Gopalakrishnan, K., Khaitan, S.K., Choudhary, A., Agrawal, A.: Deep convolutional

Weights	ImageNet		Arcade		
System	Epochs	Accuracy	Epochs	Accuracy	
Atari 2600	28.4	0.9036	24.8	0.9064	
NES	15.2	0.6780	13.6	0.7214	
Master System	22.0	0.7429	16.2	0.7562	
PC Engine	19.2	0.7890	15.4	0.8108	
Mega Drive	18.6	0.7307	13.8	0.7420	
Super Nintendo	18.2	0.7081	15.4	0.7395	
Sega Saturn	22.8	0.7050	15.2	0.7510	
PlayStation	21.2	0.7402	15.4	0.7356	
Nintendo 64	31.6	0.7776	23.8	0.8323	
Dreamcast	23.0	0.6758	21.6	0.7643	
PlayStation 2	21.6	0.7345	19.4	0.7531	
GameCube	24.2	0.7498	23.8	0.8396	
Xbox	29.8	0.7860	21.8	0.8511	
Xbox 360	20.8	0.7768	20.2	0.7955	
PlayStation 3	20.6	0.7182	18.0	0.7088	
Wii	22.6	0.7840	18.4	0.8170	
Wii U	22.0	0.7187	28.2	0.7652	
PlayStation 4	20.4	0.6477	14.8	0.6060	
Xbox One	24.4	0.6350	15.2	0.6596	
Nintendo Switch	32.4	0.7886	22.4	0.8180	
Xbox Series	40.0	0.9714	50.0	0.7571	
PlayStation 5	23.0	0.6299	22.8	0.6676	
Average	23.7	0.7451	20.5	0.7636	

Table 6 Accuracy obtained and epochs needed to train the EfficientNetB3 architecture in each of the 22 screenshots datasets, with both the ImageNet weights and the Arcade dataset weights as the initial weights. Each model is executed five times following the Cross Validation approach. The highest accuracy and the lowest number of epochs for each dataset are highlighted in bold.

neural networks with transfer learning for computer vision-based data-driven pavement distress detection. Construction and Building Materials **157**, 322–330 (2017) https://doi. org/10.1016/j.conbuildmat.2017.09.110

- [13] Suatap, C., Patanukhom, K.: Game genre classification from icon and screenshot images using convolutional neural networks. In: Proceedings of the 2019 2nd Artificial Intelligence and Cloud Computing Conference. AICCC '19, pp. 51–58. Association for Computing Machinery, New York, NY, USA (2020). https://doi.org/10.1145/3375959.3375988
  https://doi.org/10.1145/3375959.3375988
- [14] Suatap, C., Patanukhom, K.: Development of convolutional neural networks for analyzing game icon and screenshot images. International Journal of

Pattern Recognition and Artificial Intelligence 36(14), 2254023 (2022) https: //doi.org/10.1142/S0218001422540234

- [15] Jiang, Y., Zheng, L.: Deep learning for video game genre classification. Multimedia Tools and Applications, 1–15 (2023)
- [16] Moby Games: Moby Games. https: //www.mobygames.com/. Online; accessed from August to October, 2023 (2023)
- [17] Howard, A.G., Zhu, M., Chen, B., Kalenichenko, D., Wang, W., Weyand, T., Andreetto, M., Adam, H.: Mobilenets: Efficient convolutional neural networks for mobile vision applications. arXiv preprint arXiv:1704.04861 (2017)
- [18] Huang, G., Liu, Z., Maaten, L., Weinberger,

System	Architecture	Weights	Accuracy
Atari 2600	EfficientNetB3	Arcade	0.9064
NES	EfficientNetB3	Arcade	0.7214
Master System	EfficientNetB3	Arcade	0.7562
PC Engine	EfficientNetB3	Arcade	0.8108
Mega Drive	EfficientNetB3	Arcade	0.7420
Super Nintendo	EfficientNetB3	Arcade	0.7395
Sega Saturn	EfficientNetB3	Arcade	0.7510
PlayStation	EfficientNetB3	ImageNet	0.7402
Nintendo 64	DenseNet169	ImageNet	0.8327
Dreamcast	EfficientNetB3	Arcade	0.7643
PlayStation 2	EfficientNetB3	Arcade	0.7531
GameCube	EfficientNetB3	Arcade	0.8396
Xbox	EfficientNetB3	Arcade	0.8511
Xbox $360$	EfficientNetB3	Arcade	0.7955
PlayStation 3	EfficientNetB3	Arcade	0.7182
Wii	DenseNet169	ImageNet	0.8337
Wii U	EfficientNetB2	Arcade	0.7677
PlayStation 4	EfficientNetB3	ImageNet	0.6477
Xbox One	EfficientNetB3	Arcade	0.6596
Nintendo Switch	EfficientNetB3	Arcade	0.8180
Xbox Series	EfficientNetB2 / EfficientNetB3 (tie)	ImageNet	0.9714
PlayStation 5	EfficientNetB3	Arcade	0.6676
Average			0.7767

Table 7 The highest accuracy for each system, achieved with the best combination of architecture and initial weights.

K.Q.: Densely connected convolutional networks. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR) (2017)

- [19] Tan, M., Le, Q.: EfficientNet: Rethinking model scaling for convolutional neural networks. In: Chaudhuri, K., Salakhutdinov, R. (eds.) Proceedings of the 36th International Conference on Machine Learning. Proceedings of Machine Learning Research, vol. 97, pp. 6105–6114. PMLR, ??? (2019). https://proceedings.mlr.press/v97/tan19a.html
- [20] Breve, F.A.: Covid-19 detection on chest x-ray images: A comparison of cnn architectures and ensembles. Expert Systems with Applications 204, 117549 (2022) https://doi. org/10.1016/j.eswa.2022.117549
- [21] Breve, F.: Convolutional neural networks and

ensembles for visually impaired aid. In: Gervasi, O., Murgante, B., Taniar, D., Apduhan, B.O., Braga, A.C., Garau, C., Stratigea, A. (eds.) Computational Science and Its Applications – ICCSA 2023, pp. 520–534. Springer, Cham (2023)

- [22] Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M., Berg, A.C., Fei-Fei, L.: ImageNet Large Scale Visual Recognition Challenge. International Journal of Computer Vision (IJCV) 115(3), 211–252 (2015) https://doi.org/10.1007/s11263-015-0816-y
- [23] Wikipedia contributors: List of best-selling game consoles — Wikipedia, The Free Encyclopedia. https://en.wikipedia.org/ w/index.php?title=List\_of\_best-selling\_ game\_consoles&oldid=1178084645. [Online; accessed 10-October-2023] (2023)
- [24] Kingma, D.P., Ba, J.: Adam: A method

for stochastic optimization. arXiv preprint arXiv:1412.6980  $\left(2014\right)$