If you cite this paper, please use the original reference: Timo Häckel, Luca von Roenn, Nemo Juchmann, Alexander Fay, Rinie Akkermans, Tim Tiedemann, and Thomas C. Schmidt. "Coordinating Cooperative Perception in Urban Air Mobility for Enhanced Environmental Awareness," In: 2024 International Conference on Unmanned Aircraft Systems (ICUAS). IEEE, June 2024.

# Coordinating Cooperative Perception in Urban Air Mobility for Enhanced Environmental Awareness\*

Timo Häckel<sup>1</sup>, Luca von Roenn<sup>2</sup>, Nemo Juchmann<sup>3</sup>, Alexander Fay<sup>2</sup>, Rinie Akkermans<sup>3</sup>, Tim Tiedemann<sup>1</sup>, and Thomas C. Schmidt<sup>1</sup>

Abstract—The trend for Urban Air Mobility (UAM) is growing with prospective air taxis, parcel deliverers, and medical and industrial services. Safe and efficient UAM operation relies on timely communication and reliable data exchange. In this paper, we explore Cooperative Perception (CP) for Unmanned Aircraft Systems (UAS), considering the unique communication needs involving high dynamics and a large number of UAS. We propose a hybrid approach combining local broadcast with a central CP service, inspired by centrally managed U-space and broadcast mechanisms from automotive and aviation domains. In a simulation study, we show that our approach significantly enhances the environmental awareness for UAS compared to fully distributed approaches, with an increased communication channel load, which we also evaluate. These findings prompt a discussion on communication strategies for CP in UAM and the potential of a centralized CP service in future research.

#### I. INTRODUCTION

Urban Air Mobility (UAM) represents a prominent trend in aviation, aiming for efficient and safe aerial transportation within urban environments. It encompasses various applications including air taxis, package delivery services, medical transports, and industrial applications. Unmanned Aircraft Systems (UAS) play a crucial role in shaping the future of aerial transportation [1].

For (partially) autonomous UAS, it is expected that ensuring environmental perception is fundamental for the safe and reliable operation of UAM [2], [3]. The surveillance of static objects and potential conflicts within a large area becomes crucial for trajectory control, particularly at high speeds. A conflict occurs when two or more conflict elements overlap in space and time. Conflict elements may include objects like other airspace users, geofences, harsh weather conditions, or structures such as buildings [4]. Local sensors alone remain insufficient for reliable conflict detection due to possible interruptions of the line-of-sight, limited sensing range, and disruptive effects introduced by the urban environment [5]. Therefore, effective communication is required to enable robust environmental awareness tailored to UAS.

Connectivity is already vital for various aspects within the U-space airspace – a centrally managed airspace for UAS

operations [6] – such as mission planning and identity management. The U-space comprises diverse services including registration, network identification, and flight authorization. Cooperative obstacle detection is also envisioned but a unified data space structuring the available information to be shared and a suitable communication model are missing.

UAM communication differs significantly from conventional aircraft, consumer drones, and ground vehicles. The unique characteristics of UAM, including smaller separation, a denser environment, and proximity to urban factors including interfering with humans, and animals and quickly changing constraints, such as geofences, necessitate a specialized communication framework. The Automatic Dependent Surveillance-Broadcast (ADS-B) [7] enables receiving systems to locate the sending aircraft. Currently, information about the UAS surroundings is not shared among aircraft. This contrasts the automotive sector, where Vehicleto-X (V2X) communication has seen significant advancements [8]–[11]. UAS are usually operated by one person and only communicate with their operator. The centrally managed U-space further underscores the need for an efficient and standardized communication framework [6].

UAM communication is still at an early stage, requiring exploration of use cases and information exchange [6]. Investigation of combined sensing, Cooperative Perception (CP), and central U-space services are needed, and simulations can help with gaining insight into benefits and limitations. The lack of a unified and structured data space, a communication model, and standardized protocols motivate an investigation to unlock the full potential of UAS communication.

In this paper, we propose a hybrid approach to CP combining broadcast with a central service for coordination of CP in UAM. Therefore, we explore the CP data space for UAS by comparing existing solutions across the automotive, drone, and aircraft domains, with a specific focus on the environmental perception of autonomous UAS. We compare the performance of our hybrid approach to fully distributed mechanisms through simulations, focusing on the environmental awareness and the impact on the communication channel. With this, we aim to initiate a discussion on communication requirements for CP in UAM and the advantages of adopting a centralized CP service for future research.

The remainder of this paper is structured as follows. Section II provides an overview of related work. Section III presents our coordinated CP model and identifies a CP data space tailored for UAM. In Section IV, we investigate the performance of the proposed CP service in a simulation

<sup>\*</sup>This work was funded by the German Hamburg X initiative within the i-LUM project [LFF-HHX-04.2] for innovative airborne urban mobility. <sup>1</sup>Timo Häckel (corresponding author {timo.haeckel@haw-hamburg.de}), Tim Tiedemann, and Thomas C. Schmidt are with the Dept. of Computer

Science, Hamburg University of Applied Sciences, Hamburg, Germany <sup>2</sup>Luca von Roenn, and Alexander Fay are with the Institute of Automation Technology, Helmut Schmidt University, Hamburg, Germany <sup>3</sup>Nemo Juchmann, and Rinie Akkermans are with the Dept. of Automotive and Aeronautical Engineering, Hamburg University of Applied Sciences, Hamburg, Germany

scenario and compare to local perception and distributed approaches. Finally, Section V concludes the paper with an outlook on future work.

## II. BACKGROUND AND RELATED WORK

UAS in urban environments face an increasing risk of collisions due to reduced separation between UAS, low altitudes, and the vicinity of urban influences. To efficiently detect and avoid conflicts, UAS and the traffic management system require reliable environmental information, including traffic, geo data, weather, and geofences [4]. Sensors alone cannot ensure safety in obstructed line-of-sight scenarios [5] and a limited detection range decreases the chance for early counteractions to possible collisions.

Cooperative Awareness (CA) and CP facilitate real-time information sharing between UAS and infrastructure, enhancing situational awareness, reducing the risk of accidents, and improving traffic flow. CA focuses on exchanging information about the UAS itself, such as position, speed, and direction, while CP enables sharing environmental information, such as non-cooperative objects, extreme weather conditions, and animals (*e.g.*, flocks of birds). The following provides background and related work on the U-space and CP in the aviation and automotive domains.

## A. Communication in Urban Air Mobility

Communication technology is essential for cooperative UAS, enabling, for example, collaborative trajectory planning and collision avoidance [12]. The U-space is a centrally managed airspace aimed at integrating and managing UAS [13], consisting of four development phases [6]: Phase (i) involves basic services, including registration, identification, and geofencing. Phase (ii) focuses on flight management services, such as trajectory planning, approval, and monitoring. Phase (iii) adds support for more complex scenarios, including automatic conflict resolution between interfering aircraft, obstacle detection, and avoidance. Lastly, phase (iv) represents the complete implementation of all U-space services, incorporating a high level of automation and interconnection between aircraft, pilots, authorities, and other stakeholders. Currently, U-space concepts and ideas for phases (i) and (ii) are being implemented [6], [13], and phases (iii) and (iv) are expected in 2027 and 2035 [6].

UAM-related communication protocols are still in early development. Multi-access Edge Computing (MEC) minimizes communication latencies for autonomous flight control [14] and allows to offload detection algorithms to the mobile edge. Berling *et al.* [15] investigate the number of messages exchanged between UAS and Ground Stations (GSs) in an interdisciplinary toolchain that considers scenario generation, flight planning, and flight execution. Currently, there is a gap in analyzing environmental awareness with the introduction of a structured CP data space for UAM.

For efficient conflict detection and avoidance [3], [4] in U-space phase (*iii*), communication-based CP is necessary but not yet sufficiently evaluated. This paper collects a

structured data space for distributed conflict detection and proposes a centralized CP service for UAM.

## B. Cooperative Awareness in the Aviation Domain

Today, Air Traffic Control (ATC) relies on voice communication protocols between pilots and air traffic controllers, covering various topics such as flight planning, clearance delivery, departure, en route, and arrival procedures. However, voice communication does not apply to UAS.

ADS-B [7] is a surveillance technology broadcasting aircraft information to other aircraft and ground-based systems for traffic management and collision avoidance. This information includes the position, heading, registration, mission, and type of the aircraft. Environmental information, such as weather conditions, obstacles, and non-cooperative objects, is not shared, as it is often unnecessary due to the large separation between vehicles. To the best of our knowledge, there are no specific protocols and standards for CP in the aviation domain.

## C. Cooperative Perception in the Automotive Domain

In contrast to the aviation domain, the automotive community has established standards for information exchange between vehicles and infrastructure, such as the ETSI Cooperative Awareness Service (CAS) [8], and the evolving Collective Perception Service (CPS) [9]. In particular, the CPS defines messages for sharing data on detected objects, such as vehicles, pedestrians, or obstacles, including their position, velocity, heading, and other attributes. The term *Cooperative Perception (CP)* used in this paper further emphasizes the required collaboration between vehicles and infrastructure to obtain a comprehensive environmental picture.

The CPS can improve environmental awareness for road vehicles [10]. Still, current message generation rules may lead to detection latencies too high for safety-critical applications [10]. Changing message generation can improve detection latency, but at the same time increases channel load and may cause channel instability [16]. There is open potential for which objects are shared by which vehicles [10] that help to reduce data redundancy and thus optimize channel utilization [17].

In the automotive domain, common issues with CP include the market penetration rate [5], privacy concerns, and difficulties in defining a mission for private vehicles. These challenges do not translate to a centrally managed U-space airspace, where CP can be enforced, and private vehicles are not expected to be part of UAM. Nonetheless, concepts such as intent sharing and collaboration for trajectory optimization [18] are also central features of UAM.

Drawing from the automotive experience and existing standards, the centralized U-space provides a unique opportunity to implement CP in a scalable and efficient manner. Our analysis includes automotive protocols in the CP data space, discussing their applicability to UAM and highlighting domain differences and the potential for improved CP efficiency with central management.

## III. COORDINATING COOPERATIVE PERCEPTION IN URBAN AIR MOBILITY

During operation, UAS need to be aware of their environment. The combined local sensors provide environmental awareness for the direct vicinity of the UAS. For safe reaction time at high speeds objects must be detected early, *e.g.*, object detection at 500 m distance with a speed of 50 m/s leaves only 10 s for evasive maneuvers.

UAS can transmit various information to other UAS or the infrastructure for sharing their current state, mission, or perception of the environment. CA ensures that UAS are aware of each other by sharing metadata, kinematics, and mission information about themselves that allow to identify the UAS and predict future behavior. Beyond that, CP enables UAS to obtain a comprehensive environmental perception by sharing information about the environment, conflicts, and hazards. Such data is intended to improve situational awareness — particularly for UAS — and enable safer and more efficient operations.

CP in UAM should allow interoperability between different parties, avoiding vendor lock-in using open standards. Crowded areas should be handled without overloading the channel, while at the same time, larger distances between UAS should not lead to a lack of information. Additionally, the latency from object detection to sharing perception and receiving perception updates should be minimized to ensure data freshness. In the following, we identify relevant information for UAM, its freshness requirements, and compare appropriate distribution strategies.

## A. Cooperative Perception Model for Urban Air Mobility

UAS will use different communication models to interact with their surroundings. In a U-space, UAS utilize various centralized services to register and identify themselves, plan their missions, and receive flight authorizations. Conventional CA and CP systems, such as ADS-B [7] are distributed, broadcasting information to all vehicles in communication range. Drones utilize protocols such as Micro Air Vehicle Link (MAVLink) [19] for remote control and mission planning based on a closed peer-to-peer network of known parties limited in size (up to 255 concurrent systems).

Combining the approaches is promising for UAM to achieve central airspace control, distributed surveillance, and dedicated remote control for UAS. Central U-space services, however, commonly use peer-to-peer connections and do not benefit from CA and CP announcements. We propose a hybrid approach combining distributed and centralized elements using a limited broadcast range and long-range centralized management, thereby enhancing the environmental awareness for both UAS and central U-space providers.

Fig. 1 shows an example of the hybrid CP model for UAM. The ownship UAS (blue) perceives its immediate surroundings through a combination of local sensors. All UAS broadcast their position and status (CA) making the ownship UAS aware of the position of the purple UAS. In addition, UAS broadcast objects detected with their sensors



Fig. 1: Hybrid CP model integrating local perception, CP broadcast, and a central backend service. Ground stations connect UAS in range to the backend.

(CP). The ownship UAS detects the orange UAS through a message from the purple UAS.

Beyond the local broadcast (CA and CP), GSs function as gateways forwarding received messages broadcasts from the UAS to a central CP service in the backend. The backend caches and aggregates this information to track UAS and other detected objects across the urban area. The backend redistributes this aggregated information to all GS via unicast. Reducing the redistributed information to all GS via unicast. Reducing the redistributed information to a region of interest around the GS can reduce the channel load. The GSs provide the aggregated information to the UAS again using CP broadcast, which extends the detection range for all UAS in the communication range of GSs. In the example, the backend tells the ownship UAS about the two yellow UAS, providing complete environmental awareness. This supports functions such as automated trajectory control, conflict detection, and resolution mechanisms.

## B. Cooperative Perception Data Space

In UAM, existing aviation standards, such as ADS-B [7], lack comprehensive information and cooperative maneuvers for UAS. Automotive standards such as the ETSI CAS [8] and the evolving CPS [9] offer information exchange adaptable to UAS. Innovations such as MAVLink further enhance drone technology.

Table I compiles a data space from standards, protocols, and the state-of-the-art in the automotive, aviation, and drone domains. In our analysis, we focus on the CP use case for UAM. Additional services including weather data, mission planning, remote control, and direct UAS communication, *e.g.*, for conflict resolution, are out of the scope of this work.

Metadata encompasses the UAS type, dimensions, and operational status (*e.g.*, on a mission, take-off, or landing). Special vehicles, such as rescue helicopters, may inform their environment about an ongoing operation. A public ID is used for registration and network identification in a U-space. The current time and a time delta are shared to determine the age of information and synchronize the local clocks.

Kinematic information includes the position, velocity, acceleration, and speed of the UAS. Sharing heading or orientation helps to determine the intended direction of travel. In addition, UAS may communicate their intent [18] with mission information, such as the current plan, status, and changes from the planned route, which is essential for U-space operations. This includes transmitting information related to the mission or destination, such as delivery schedules or passenger pickup/drop-off locations.

UAS employ sensors (cameras, LIDARs, RADARs) and algorithms (*e.g.*, based on machine learning) for object detection and classification. By sharing detected objects, sensing capabilities (*e.g.*, field of view, range, and resolution), and confidence in classification, UAS can extend the perceived environment to detect and resolve conflict elements along the planned trajectory early on.

For road vehicles, information about traffic conditions, such as congestion, accidents, road closures, and empty road space helps vehicles plan their routes. This can also be applied to UAS operations, communicating obstacles on flight routes. Traffic signals and guidance convey UAM traffic, sector capacity, and geofences.

In the urban environment, not only UAS can cause conflicts but also other hazards, such as unknown or noncooperative UAS, construction sites, animals (*e.g.*, flocks of birds), or extreme weather conditions (*e.g.*, wind, rain, fog). A central database cashes and tracks these conflict elements across the urban area and helps to identify conflicts along the trajectory of the UAS.

Besides safety, the sound emission caused by UAS is one of the main concerns of the public regarding UAM [20]. For noise reduction purposes, it is advisable that UAS record and process acoustic signals during operation. A wireless acoustic sensor network is suitable for this context [21], [22]. By communicating the emitted sound based on practical metrics, *e.g.*, the Sound Pressure Level (SPL) or Effective Perceived Noise Levels (EPNL) [23], the central backend can create a noise map for the urban area. Areas with high noise can then be treated as a conflict.

Conflicts can affect UAS operation and require increased separation, for example. Detected conflicts are shared to avoid collisions, including UAS breakdowns, traffic rule violations, and hazards.

## C. Information Lifetime and Frequency

The frequency of information exchange varies depending on the specific use case and application. It is determined by factors, including the required level of situational awareness, the lifetime of the data object, the communication range and bandwidth of the wireless network, and the processing capabilities of the UAS and infrastructure involved. In general, UAS should reduce the number of transmissions to save resources, but the data must be fresh enough to be useful, especially for fast-moving objects.

TABLE I: UAM data space sourced from various automotive, aircraft, and drone protocols. Shows information that is shared  $[\checkmark]$ , not shared  $[\bigstar]$  in the respective domain, or shared but not sufficient  $[(\checkmark)]$  for UAS. The frequency describes how often the data is included in generated messages and is based on the highest in any industry. The frequency of NaN is not specified in a standard or not considered for this work.

Vel	nicle Information	Automotive	Aviation	Drone	Frequency [Hz]	
Metadata	Current time Time delta Type, dimensions Special vehicle Public ID Vehicle status	✓ ✓ ✓ ✓ ✓ ✓ (✓)	✓ ★ ✓ ✓	✓ ✓ ✓ ✓	every Msg every Msg 2 2 2 2 2	
Kinematic	Position Altitude Heading, velocity Acceleration Remote control	√ × √ ×	√ √ √ <b>×</b>	~ ~ ~ ~ ~ ~	1 to 10 1 to 10 1 to 10 1 to 10 <i>NaN</i>	
Mission	Service provider Public mission ID Plan Mission status Changes	× × × ×	(V) V X X X	> <b>x</b> > > >	2 on request / 2 on request / 2 <i>NaN</i>	
Environment	Objects, vehicles Traffic guidance Weather, wind Noise Stream sensor data	√ √ × ×	× × × ×	✓ ★ (✓) ★ ✓	1 to 10 1 to 10 <i>NaN</i> 1 to 10 <i>NaN</i>	
Conflict	Hazards Collision avoidance Vehicle break down Traffic rule violation	√ (√) √ √	× (√) ×	(✓) ✓ ✓ ¥	1 to 10 1 to 10 1 to 10 1 to 10 1 to 10	

Conventional aircraft use lower frequencies due to larger inter-vehicle distances and stable environments. In contrast, UAM demands higher frequencies for closer proximity and dynamic conditions. Ground vehicles typically use higher frequencies, reflecting their closer spacing and dynamic environment. Some standards adjust transmission frequency based on vehicle speed and channel congestion [8].

Table I presents the highest sharing frequency among industries considered, representing the most demanding use case. Metadata and mission information rarely change and are shared twice per second to allow identification of UAS.

UAS share their kinematics and speed at least once and up to ten times per second depending on the UAS dynamics and the channel congestion status. ADS-B requires a message every 5 s on the ground and twice per second when in the air. ETSI CA messages are triggered when the last message was sent more than 1 s ago, or when the current vehicle heading differs from the previously announced by more than  $4^{\circ}$ , the position differs by more than 4 m, and the speed differs by more than 0.5 m/s. This could be extended to include altitude changes.

CP is not established in the aircraft domain and detected objects are not communicated as it is often unnecessary due to the large separation between vehicles. Instead established voice communication protocols are used. In the automotive sector, the CPS [9] has attracted a lot of interest, so we base our assessment on the experience gained there. Information on detected objects is shared with a frequency of 1 Hz to 10 Hz depending on changes in their kinematics following the same rule set as CA messages.

GSs also share an aggregated view of detected moving objects in an area of interest at least once per second and up to 10 Hz. Traffic signals and guidance will also follow such rules, for changing geofences, traffic conditions, noise pollution, and sector capacity, making sure at least one message is sent while a UAS is in range. Static objects can be requested by the UAS at once when entering a new area, with deviations reported promptly.

#### D. Communication Model

Various standards coexist for vehicular communication. For instance, ADS-B broadcasts at a lower radio frequency (around 1 GHz) that can be received at a long distance especially for high-altitude flights, sacrificing transfer speed and data throughput. For road vehicles, different standards have prevailed in different regions, for example, large-scale deployments of the IEEE 802.11p WLAN-based V2X in the EU and Cellular-V2X (based on LTE and 5G) in the US with still few deployments. Both of which utilize higher radio frequencies (2.4 GHz or 5 GHz) allowing for larger data transfers at decreased range (a few 100 m).

Each of the different technologies has its advantages and disadvantages. Using long-range broadcast for the numerous UAS in a U-space airspace causes a significant increase in message volume, leading to potential channel congestion and interference with conventional aircraft. Limiting the broadcast range can reduce the congestion but also limits the number of UAS that can be reached directly. On the other hand, higher frequencies can allow for a larger data throughput, which will be required for large CP data.

To enable both direct interaction between UAS and communication with U-space services, the UAM communication system should support both direct device-to-device communication and Internet connectivity. Therefore, Cellular-V2X adds a direct device-to-device communication mode and WLAN-based V2X can use infrastructure as a gateway to U-space services. Regardless of the technology chosen, the cooperative perception model should be independent of the communication technology, as exemplified by ETSI ITS-G5 standards for intelligent road vehicles.

In our evaluation, we use IEEE 802.11p and the ITS-G5 protocols to communicate CA and CP messages to other UAS and via infrastructure to the backend. For a detailed comparison of IEEE 802.11p and LTE-V2X, we refer to [24]. We compare local perception without communication and the distributed CA and CP approaches for vehicles with our hybrid approach with centralized collection and distribution of CP data using a central backend entity. We focus on environmental awareness and side effects introduced by the centralized CP service, which should be unaffected by the chosen communication system.

## IV. CASE STUDY OF COOPERATIVE PERCEPTION IN URBAN AIR MOBILITY

We now evaluate the CP models (*cf.*, Sec. III-A) in a simulation case study comparing detection performance and communication metrics, along with assessing the impact of a central backend for CP. We utilize the Environment Awareness Ratio (EAR) as a common metric of perception performance [5] that represents the ratio between detected and existing objects in the simulation. Additionally, we investigate features such as the detection delay and the impact of caching in a central backend. For our communication analysis, we consider the number of messages, payload length, and receive (rx) channel load of the UAS.

#### A. Simulation Environment

We use OMNeT++ with the INET framework [25] and Artery [26] for V2X communication simulations based on IEEE 802.11 and ITS-G5 protocols. For a detailed evaluation of the 802.11p-based communication between vehicles we refer to [11]. Although we use WLAN-based communication (5.9 GHz), our results for environmental awareness directly apply to other communication technologies with similar range and bandwidth such as 5G or LTE C-V2X.

Unlike other V2X simulators, Artery offers an environment model that allows simulating sensor perception of vehicles. Recent work improved sensor simulation with more realistic models [27], but we stick to the original sensor models as they are sufficient for the evaluation of the different perception models for UAS. For our evaluations, we extend Artery with our centralized perception service in GSs and a backend node.

Artery uses the *Simulation of Urban MObility* (SUMO) traffic simulator [28] for vehicle simulation on a road network, but it cannot simulate UAS yet. Efforts for a UAS traffic simulation similar to SUMO [29] exist but are not integrated with Artery. A toolchain for UAM simulations is shown by Berling *et al.* [15] but is not publicly available. Our goal for future work is to integrate the used simulation environment with other simulators, *e.g.*, for demand modeling and trajectory planning, in an RCE <sup>1</sup> toolchain to enable a realistic evaluation of UAS perception models.

UAM aircraft, traffic guidelines, and regulations are still in active development and vary significantly between regions. Currently, the U-space and UAM are not deployed at a large scale which limits the availability of realistic models that include demand, trajectories, UAS behavior, vertiport locations, and geofences. The use of Artery and SUMO confines UAS and sensor simulation to two dimensions, projecting flight trajectories to ground level. This does not impact the communication behavior, which is modeled in all three dimensions but simplifies the sensor simulation. While sufficient for our comparison of the perception models for UAS, future work should extend simulations to three dimensions, considering UAS mobility modeled in all directions.

<sup>&</sup>lt;sup>1</sup> RCE integration environment: https://rcenvironment.de/

#### **B.** Scenarios

Fig. 2 shows the 4 km-by-4 km simulation area in a grid network. UAS move on predefined routes at a maximum speed of 70 m/s. During the first 20 s, 200 UAS spawn randomly distributed on the grid and despawn when they reach their destination. Each UAS is equipped with one front RADAR sensor, with a range of 1 km and a  $120^{\circ}$  field of view for precise object detection in front of the UAS. With this, we simulate a large range with perfect detection capabilities. Specific sensor characteristics or sensor fusion techniques for near and far object detection are out of the scope of this work. The communication range of the UAS and GSs depends on the interference and path loss and is determined by the transmitter power. We use common settings for our parameters such as a transmitter power of  $200 \,\mathrm{mW}$ , and a data rate of  $6 \,\mathrm{Mbit/s}$  [11]. This results in a maximum range of several hundred meters. The backend and GSs are connected using high-speed (100 Gbit/s) wired connections to eliminate a potential bottleneck. Message send frequency between 1 Hz to 10 Hz is determined during runtime by the ITS-G5 stack and depends on the channel load. For this evaluation, we focus on the transmission of UAS metadata and kinematics via CA and CP messages.

We simulate five coordination models for CP discussed in Sec. III-A for 100 s of simulation time. The scenarios follow the visualization of Fig. 1:

- 1) **Local perception**: UAS use only local sensors without communication.
- 2) CA: UAS share their metadata and kinematics.
- 3) CP: UAS share information about detected objects.
- 4) CA & CP: UAS share information about themselves and detected objects.
- 5) w/ central backend: UAS share information about themselves and detected objects. GSs covering the 16 km<sup>2</sup> simulation area forward incoming messages to a central backend service, which aggregates the perception of all UAS and sends aggregated CP messages to all UAS via the GSs.

## C. Results

First, we determine the number of GSs used for the scenario w/ central backend. Fig. 3 shows the average EAR for UAS and the backend, the average rx channel load, and the average number of messages per UAS, GS, and in total. The number of GSs is increased from 0 to 225 and equally distributed on the grid. For example, when five GSs are placed per row and column, the total number of GSs is 25. The backend EAR and message count per GS are only available if a GS is placed.

The average channel load increases with the number of GSs from 17% to 21%. The average EAR for the backend is around 100% already with 25 GSs. The average EAR for the UAS improves drastically when adding GSs, reaching 66% with 81 GSs. After that, it does not increase significantly and even decreases by about 15% when adding more GSs until it rises again. This can be explained when looking at the



Fig. 2: Evaluation setup consisting of 200 UAS randomly distributed on a 4 km-by-4 km grid network. Only the scenario w/ central backend adds GSs that cover the entire area.



Fig. 3: Impact of the number of ground stations on the average EAR, channel load, and message count. The ground stations are equally spaced along the grid.

number of messages sent. UAS and GSs reduce the number of messages sent when the channel load increases, which is the default behavior of the utilized ITS-G5 stack to reduce channel congestion. The optimal range and frequency of CP messages and the ideal number and placement of GSs remain open research questions for future work.

In the following analyses, we use 81 GSs with a spacing of 500 m for the scenario w/ central backend. Table II shows the condensed results for the EAR, payload length, and channel load for the five scenarios. The channel load in the local perception scenario is caused by simulated noise that is also



Fig. 4: Environment Awareness Ratio (EAR) for one UAS and the backend with different communication enabled. In the scenario w/ central backend, 81 ground stations are used.

present in all other scenarios. The minimum EAR is zero in all cases because no objects are detected in the beginning.

The EAR over time is shown in Fig. 4 for the perception models. Local perception has the lowest EAR as it depends on sensor range, which may vary for different sensor technologies. Adding communication increases the EAR. CA extends the range for detecting cooperative UAS, however, with a small range, a lot of UAS are already detected with local sensors. Noteworthily, UAS sharing their detection (CP) increases the EAR significantly compared to CA. Furthermore, CP adds the capability of sharing information about uncooperative objects. Combining CA and CP does not improve EAR compared to CP alone; in some cases, it may even reduce it due to increased channel congestion from higher message volume. Integrating GSs to relay CA and CP messages to a central perception service expands the perceivable area to 100%, demonstrating the substantial benefit of central coordination, even in a small  $16 \text{ km}^2$  area.

The payload of CP messages is significantly larger than CA messages, which is reflected in the channel load (*cf.*, Table II). Furthermore, the payload length of CP messages increases with the number of detected objects. This is especially the case for the scenario w/ central backend, where the backend aggregates the perception of all UAS and sends aggregated CP messages to all UAS via the GSs. The amount of data included in the CP messages should be carefully considered, as it directly impacts the channel load and transmission times, which in turn can lead to a reduced data freshness. Scaling to larger urban areas increases data and communication volume, suggesting the need for optimization strategies of the central perception model. These could include private unicast or restricting GS CP content to conflict elements in a specific range.

Fig. 4 also shows that although the average EAR for the UAS improves significantly with central coordination, it also decreases when no messages from the backend are received,



Fig. 5: Number of known UAS for one UAS and the backend in the scenario w/ central backend using 81 ground stations.

TABLE II: Comparison of the EAR, payload length, and channel load for the five scenarios. For the scenario w/ central backend, results are separated between UAS and GSs.

Scenario	EAR [%]		Payload [Byte]			Channel load [%]					
	avg	max	min	avg	max	min	avg	max			
Local perception	3.46	16.67	0	0	0	0.02	0.04	0.06			
CA	13.39	25.26	41	103	241	2.35	4.20	5.77			
СР	26.13	55.14	46	241	945	6.86	15.34	22.80			
CA & CP	26.86	58.03	41	193	945	8.96	16.58	22.51			
w/ central backend and 81 Ground Stations (GSs)											
4 UAS	66.24	100.51	41	192	945	11.40	19.49	25.73			
4 GSs	99.56	100.51	1661	5538	5837	8.64	16.90	21.80			

*e.g.*, due to congestion, and cached objects timeout. Still, the EAR stays at the level of the best case for the other scenarios, because of the hybrid approach combining local perception, broadcast communication, and central coordination. The EAR rises again when the next message arrives.

Fig. 5 further highlights the detection delay and caching, showing the number of known UAS w/ central backend. UAS known by a UAS, and the backend are compared to the active UAS in the simulation world. The detection follows the number of active UAS. The 200 UAS spawn in the first 20 s and start despawning in the last 20 s.

The delay between spawning and detection of a UAS is determined by the CP message frequency of 1 Hz to 10 Hz, which reports objects that arrive. The backend aggregates the objects and includes them in the next central CP message, again at 1 Hz to 10 Hz. Thus, the worst case for the detection time with central CP is between 0.2 s to 2 s plus a transmission delay.

The previously mentioned timeout causes a maximum EAR higher than 100% shown in Table II as despawning UAS are still cached. Cache eviction occurs when a UAS is not detected by sensing, CA, or CP and is removed from the cache after 1.1 s. This timeout reflects the freshness require-

ments for object information and depends on the minimum frequency for CP messages of 1 Hz (*cf.*, Table I) plus a 10% buffer for transmission delays, etc. The central backend increases this effect, extending the live time of detected objects by re-advertising. UAS have no impact on this as they only share objects detected with their own sensors. Further investigation can help to optimize the caching strategy.

## V. CONCLUSION AND OUTLOOK

In this work, we explored the CP for UAS in UAM. Based on existing standards from the aviation, automotive, and drone domains, we identified a CP data space and the desired frequency of information exchange. We proposed a hybrid approach for CP using local broadcast combined with a central CP service. GSs forward local CP messages that are collected and aggregated at a centralized service to be then shared with airspace users again.

In a case study, we evaluated the environmental awareness of the proposed CP service through simulations, comparing it to distributed approaches. We analyzed the impact of the number of GSs and the frequency of CP broadcasts on the EAR and the communication channel load. Our results show that with increased density of GSs the channel load increases, but the EAR also improves until the messages are reduced due to channel congestion. Continuing with a spacing of 500 m between GS, the centralized approach significantly improved the average EAR to 99% in the backend service and 66% at UAS from just 3.5% without communication and 27% with distributed CP. In turn, the channel load is also increased from an average of 16.5% with distributed CP to 19.5% with the centralized CP service. The increased environmental awareness can help with advanced conflict detection and resolution, enhancing the overall safety of UAM operations [3].

Our evaluation raised central research questions about the optimal CP broadcast range, frequency, and ideal GS number and placement. Future work shall investigate additional CP metrics such as the age of information, object redundancy, and consider the zone of interest for a UAS. Further improvements can be achieved through more realistic simulation scenarios and environments, *e.g.*, by providing realistic UAM traffic models. Our findings can aid in developing solutions for cooperative conflict detection and resolution in U-space airspace, aiding in identifying challenging objects such as animals or uncooperative entities [3]. Integrating knowledge about these objects into operations can enhance the overall safety of all airspace users by deliberately avoiding them.

#### REFERENCES

- A. Gupta *et al.*, "Advances of UAVs toward Future Transportation: The State-of-the-Art, Challenges, and Opportunities," *Future Transportation*, vol. 1, pp. 326–350, Sep. 2021.
- [2] X. Yu and Y. Zhang, "Sense and avoid technologies with applications to unmanned aircraft systems: Review and prospects," *Progress in Aerospace Sciences*, vol. 74, pp. 152–166, Apr. 2015.
- [3] L. von Roenn et al., "Concept for a Decentralized Tactical Conflict Management in a U-space Ecosystem," in 2024 New Trends in Civil Aviation (NTCA), 2024, IEEE, accepted for publication.

- [4] L. von Roenn et al., "Concept for an automated Detection of Conflicts in UAS Traffic Management," in 2023 International Conference on Unmanned Aircraft Systems (ICUAS). IEEE, Jun. 2023.
- [5] F. A. Schiegg *et al.*, "Collective Perception: A Safety Perspective," Sensors, vol. 21, p. 159, Dec. 2020.
- [6] EUROCONTROL, "U-SPACE Services Implementation Monitoring Report," EUROCONTROL, Tech. Rep., Nov. 2022.
- [7] RTCA, "Minimum Aviation System Performance Standards for Automatic Dependent Surveillance Broadcast (ADS B)," RTCA, Tech. Rep. DO-242A, Dec. 2006, including Change 1.
- [8] ETSI, "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service," ETSI, EN 302 637-2, Apr. 2019, v1.4.1.
- [9] ETSI, "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Analysis of the Collective Perception Service (CPS); Release 2," ETSI, TR 103 562, Dec. 2019, v2.1.1.
- [10] F. A. Schiegg *et al.*, "Analytical Performance Evaluation of the Collective Perception Service in IEEE 802.11p Networks," in *Wireless Communications and Networking Conf. (WCNC)*. IEEE, May 2020.
- [11] M. Sepulcre *et al.*, "Analytical Models of the Performance of IEEE 802.11p Vehicle to Vehicle Communications," *IEEE Transactions on Vehicular Technology*, vol. 71, pp. 713–724, 2022.
- [12] S. Javaid *et al.*, "Communication and Control in Collaborative UAVs: Recent Advances and Future Trends," *IEEE Transactions on Intelligent Transportation Systems*, pp. 1–21, 2023.
- [13] T. Grebner and A. Fay, "Concept for a U-Space Compliant UAS-Flight Authorization Service: The Flight Authorization and Activation Process," in 2022 International Conference on Unmanned Aircraft Systems (ICUAS). IEEE, Jun. 2022.
- [14] S. Solanki et al., "MEC-assisted Low Latency Communication for Autonomous Flight Control of 5G-Connected UAV," in Vehicular Technology Conference (VTC2023-Spring). IEEE, Jun. 2023.
- [15] J. Berling et al., "A Modular Urban Air Mobility Simulation Toolchain with Dynamic Agent Interaction," in *Deutscher Luft- und Raumfahrtkongress 2022*. DGLR - Lilienthal-Oberth e.V., 2022.
- [16] G. Thandavarayan et al., "Analysis of Message Generation Rules for Collective Perception in Connected and Automated Driving," in 2019 IEEE Intelligent Vehicles Symposium (IV). IEEE, Jun. 2019.
- [17] H. Huang et al., "Data Redundancy Mitigation in V2X Based Collective Perceptions," *IEEE Access*, vol. 8, pp. 13405–13418, 2020.
- [18] S. S. Avedisov et al., "Cooperative Perception Based on Intent Sharing Messages," in Vehicular Networking Conf. (VNC). IEEE, Apr. 2023.
- [19] Dronecode Project, "Micro Air Vehicle Communication Protocol (MAVLink)," Online, https://mavlink.io/en/, accessed Apr. 2023.
- [20] European Commission, "COMMUNICATION FROM THE COM-MISSION TO THE EUROPEAN PARLIAMENT, THE COUNCIL, THE EUROPEAN ECONOMIC AND SOCIAL COMMITTEE AND THE COMMITTEE OF THE REGIONS: 'A Drone Strategy 2.0 for a Smart and Sustainable Unmanned Aircraft Eco-System in Europe'." European Commission, 2022, {SWD(2022) 366 final}.
- [21] R. M. Alsina-Pagès *et al.*, "Design of a Mobile Low-Cost Sensor Network Using Urban Buses for Real-Time Ubiquitous Noise Monitoring," *Sensors*, vol. 17, 2017.
- [22] F. Alías et al., "Review of Wireless Acoustic Sensor Networks for Environmental Noise Monitoring in Smart Cities," *Journal of sensors*, vol. 2019, 2019.
- [23] M. J. T. Smith, Aircraft Noise, ser. Cambridge Aerospace Series. Cambridge University Press, 1989.
- [24] R. Molina-Masegosa *et al.*, "Comparison of IEEE 802.11p and LTE-V2X: An Evaluation With Periodic and Aperiodic Messages of Constant and Variable Size," *IEEE Access*, vol. 8, pp. 121526–121548, 2020.
- [25] OpenSim Ltd., "OMNeT++ Discrete Event Simulator and the INET Framework." [Online]. Available: https://omnetpp.org/
- [26] Raphael Riebl et al., "Artery: Large Scale Simulation Environment for ITS Applications," in *Recent Advances in Network Simulation*. Springer, 2019, pp. 365–406.
- [27] A. Willecke et al., "Towards Improving Realism of Perception in Artery," in Vehicular Technology Conference (VTC2023-Spring). IEEE, Jun. 2023.
- [28] openMobility Working Group, "Simulation of Urban MObility (SUMO)." [Online]. Available: https://sumo.dlr.de/
- [29] T. Hardes et al., "Towards an Open-Source Fully Modular Multi Unmanned Aerial Vehicle Simulation Framework," in 15th IEEE Int. WS on Wireless Sensor, Robot and UAV Networks. IEEE, Jul. 2022.