RGI-NET: 3D ROOM GEOMETRY INFERENCE FROM ROOM IMPULSE RESPONSES IN THE ABSENCE OF FIRST-ORDER ECHOES

Inmo Yeon and Jung-Woo Choi

School of Electrical Engineering, KAIST, Daejeon, South Korea

ABSTRACT

arXiv:2309.01513v3 [eess.AS] 1 May 2024

Room geometry is important prior information for implementing realistic 3D audio rendering. For this reason, various room geometry inference (RGI) methods have been developed by utilizing the time-of-arrival (TOA) or timedifference-of-arrival (TDOA) information in room impulse responses (RIRs). However, the conventional RGI technique poses several assumptions, such as convex room shapes, the number of walls known in priori, and the visibility of firstorder reflections. In this work, we introduce the RGI-Net which can estimate room geometries without the aforementioned assumptions. RGI-Net learns and exploits complex relationships between low-order and high-order reflections in RIRs and, thus, can estimate room shapes even when the shape is non-convex or first-order reflections are missing in the RIRs. RGI-Net includes the evaluation network that separately evaluates the presence probability of walls, so the geometry inference is possible without prior knowledge of the number of walls.

Index Terms— Deep neural network, room geometry inference, room impulse response

1. INTRODUCTION

Sound propagation in a room is affected by various physical phenomena involved with room geometries, such as specular and diffuse reflection, diffraction, and scattering. Therefore, knowing the room geometry can improve the performance of many acoustic problems including source localization [1], dereverberation [2], and source separation [3].

Sound propagation altered by room geometry is captured in room impulse responses (RIRs) in the form of various features. One of the representative features is the time-of-arrival (TOA) identifiable from the propagation delay of its distinct peaks. Therefore, a lot of room geometry inference (RGI) studies have utilized TOA information [4–9]. In particular, Antonacci *et al.* [4] localized 2D reflectors by converting a set of TOAs into ellipses. Two focal points of an ellipse correspond to a sound source and microphone, and the common tangent line across multiple ellipses can represent the room boundary. Baba et al. [8] extended ellipse-based method using stack-line detection in stacked RIRs. Common reflection lines were translated into real- and image-microphone positions, which determine room boundary. Lovedee-Turner and Murphy [9] demonstrated that the RGI of complex rooms, e.g., non-convex rooms, is possible based on RIRs acquired at multiple positions. They estimated all candidate walls and then filtered the estimated walls using a three-step validation process: path validation, line-of-sight (LOS) boundary validation, and closed geometry validation. The remaining walls constitute the final room geometry. However, the microphone array must be placed in a restricted area to secure the LOS condition for all the walls, and the acquired RIRs must include first-order reflections from the walls. Despite their success in estimating complex-shaped rooms, positioning sound sources at multiple locations makes it less practical.

Most previous studies assume that first-order reflections from every wall are visible. For rooms with complex shapes, however, first-order reflection visibility cannot be ensured in one measurement with a compact microphone array. The fundamental remedy might be to utilize high-order reflections and analyze the complex relationship between lowand high-order reflections. Therefore, recent studies have demonstrated the potential of deep neural networks (DNNs) for high-level feature extraction from RIR [10-15]. Yu and Kleijn [10], Poschadel et al. [11], and Tuna et al. [12] designed a DNN to extract the complex relationship between the temporal peaks of an RIR and estimated the geometrical parameters of a room. However, these DNN-based RGI studies have a limitation in that they cannot handle changes in the number of walls caused by various room types, as they have focused only on shoebox rooms. In our previous study [13], we attempted to address this limitation. However, the study only considered the LOS condition where all walls are visible from the audio device. Moreover, a spherical microphone array with 32 microphone capsules was used as the audio device, which makes the approach less practical.

In this study, we propose a DNN-based RGI model, RGI-Net, that can infer geometries of various rooms. The proposed model has two major contributions compared to con-

This study was supported by the National Research Foundation of Korea (NRF) Grant funded by the Ministry of Science and ICT (MSIT) of Korea (No. 1711091575) and BK21 FOUR program through the NRF funded by the Ministry of Education of Korea.



Fig. 1. Overview of the RGI-Net architecture. M, N, and W_0 denote the number of channels and temporal length of RIRs, and the maximum number of walls, respectively.

ventional RGI techniques. First, RGI-Net is designed to infer room geometry without prior knowledge of the number of walls. Second, RGI-Net is capable of inferring the room geometries, even when they do not satisfy the LOS conditions. The exploitation of high-order reflections is demonstrated by the visualization of temporal activation maps.

2. PROBLEM STATEMENT

The RGI problem can be defined as identifying W walls that compose a room based on the measured RIRs. In 3D space, each wall is described as a plane, which can be expressed as a set (\mathcal{A}_w) of points $(\mathbf{r} = [x, y, z, 1]^{\mathsf{T}})$ in homogeneous coordinates, satisfying the equation of a plane.

$$\mathcal{A}_w = \{ \mathbf{r} \in \mathbb{R}^4 \mid \mathbf{r}^\mathsf{T} \mathbf{a}_w = 0 \},\tag{1}$$

where the vector $\mathbf{a}_w = [a_{w1}, a_{w2}, a_{w3}, a_{w4}]^{\mathsf{T}}$ includes wall parameters characterizing the *w*th wall ($w = \{1, \dots, W\}$). The objective of RGI can be accomplished by determining \mathbf{a}_w constituting a room. Hereafter, we describe the architecture of RGI-Net to estimate wall parameters without prior information on the number of walls (*W*).

3. PROPOSED METHOD

3.1. RGI-Net Architecture

The proposed network comprises three sub-networks: a feature extractor, a wall parameter estimator, and an evaluation network. The feature extractor extracts appropriate features related to room geometries from multichannel RIRs. The *M*channel RIRs $\mathbf{g} \in \mathbb{R}^{M \times N}$ of N = 1024 in length are processed by the convolutional layer of kernel size 9 and stride 2 and fed into the feature extractor. As shown in Fig. 1, the ResNet [16] used as a feature extractor consists of four main blocks. As the signal passes through 1D convolution layers, the number of channels increases while the length of the feature map decreases. The convolution layers extract interchannel and temporal features through the multichannel kernel of size 5 and stride 1, except for the first layer of blocks 2, 3, and 4, where stride is 2. Each convolutional layer is followed by layer-norm [17] and rectified linear unit (ReLU) activation.

The wall parameter estimator is the combination of the 1×1 convolution and global average pooling (GAP) layers, which mixes and summarizes the extracted features, respectively, to obtain a set of wall parameter estimations $(\hat{\mathbf{a}}_w)$. Irrespective of the number of existing walls (W), the estimator is designed to generate W_0 wall parameter candidates $\hat{\mathbf{A}}_c = [\hat{\mathbf{a}}_1, \cdots, \hat{\mathbf{a}}_{W_0}]^{\mathsf{T}} \in \mathbb{R}^{W_0 \times 4}$. A well-trained wall parameter estimator would generate near-zero vectors ($\|\hat{\mathbf{a}}_w\|_2 \approx 0$) for nonexistent walls. However, to promote the detection of fake wall parameters, we additionally incorporate the evaluation network that evaluates and outputs the confidence of estimated parameters. In this sub-network, the presence probability $\hat{\mathbf{p}} = [\hat{p}_1, \cdots, \hat{p}_{W_0}]^\mathsf{T} \in \mathbb{R}^{W_0}$ of W_0 wall candidates is generated through the sigmoid function by considering both features of the feature extractor and wall parameter estimator. During training, the final wall parameters are estimated by multiplying the output of the wall parameter estimator with the wall presence probability obtained from the evaluation network ($\hat{\mathbf{A}} = \text{Diag}(\hat{\mathbf{p}})\hat{\mathbf{A}}_c$). However, during inference, the binary decision of true walls is made by hard-thresholding $\hat{\mathbf{p}}$ with a threshold 0.9, which is determined by considering the true-positive rate (TPR) and false-positive rate (FPR).

3.2. Loss Function

In all the experiments conducted, we set $W_0 \geq W$, and ground truth (GT) wall parameters and presence probabilities for nonexistent walls were initialized with zeroes. As the loss function for measuring the similarity between GT and estimated wall, angular loss between two flattened parameter vectors $\hat{\mathbf{h}} = \text{flatten}(\hat{\mathbf{A}})$ and $\mathbf{h} = \text{flatten}(\mathbf{A}) \in \mathbb{R}^{4W_0}$ was employed. That is,

$$L_{ang} = 1 - \cos^2 \theta$$
, where $\cos \theta = \frac{\mathbf{h} \cdot \mathbf{h}}{\|\hat{\mathbf{h}}\|_2 \|\mathbf{h}\|_2}$. (2)

Room type	Total		Shoebox		Pentagonal		Hexagonal		L-LOS		L-NLOS	
Number of RIRs	500		100		100		100		100		100	
Background noise level	Low	High	Low	High	Low	High	Low	High	Low	High	Low	High
ACC_W (%)	99.95	99.72	100	100	99.88	99.38	99.88	99.75	100	100	100	99.50
(ROC-AUC, %)	(99.99)	(99.98)										
Δd (m)	0.10	0.16	0.07	0.11	0.08	0.14	0.08	0.14	0.11	0.15	0.16	0.28
$\Delta \theta$ (degrees)	1.89	3.33	1.68	1.95	2.10	3.69	2.46	3.62	1.39	2.61	1.83	4.76

Table 1. Performance of RGI-Net on different room geometries at low- and high-noise levels



Fig. 2. Top view of rooms reconstructed from estimated wall parameters. The black dot (left) displays the position of a compact audio device. The black dashed lines and blue solid lines (right) correspond to reconstructed walls from the GT and inferred wall parameters, respectively.

Along with the angular loss, we used a decision loss L_d involved with the wall presence probability. The decision loss is defined as the binary cross entropy (BCE) between the GT and estimated probabilities: p_w and \hat{p}_w . To cope with the order mismatch in the GT and estimated walls, the permutation invariant training technique [18] was employed during training. For training, the Adam [19] optimizer and cosine annealing learning rate scheduler [20] were used with the maximum learning rate of $1e^{-3}$.

4. EXPERIMENTAL RESULTS AND ANALYSIS

4.1. Dataset

Although various measured RIRs have been released, their microphone-speaker configurations are not compatible with the compact audio device considered in this study. To train the model using RIRs obtainable from a compact audio system, we constructed an RIR dataset simulated using a circular microphone array with six omnidirectional microphones arranged on a circle of 0.05 m radius and a single loudspeaker centered in the array. The device was randomly positioned between [1, 2] m from the floor and within 70% space of a given floorplan. In the simulated rooms, the floor and ceil-



Fig. 3. Activation maps of multichannel RIRs displaying the use of high-order reflections for geometry inference. (a) convex pentagonal room and (b) non-convex L-NLOS room.

ing were parallel to each other and perpendicular to the other walls. Four different room types were considered: shoebox, pentagonal, hexagonal, and L-type rooms. Unlike the other types, L-type rooms can be categorized into L-LOS and L-NLOS (non-line-of-sight) types, depending on whether the device can capture LOS from all walls or not. The rooms were horizontally rotated within the range of $[0, 360]^{\circ}$ to reflect possible angular rotations of the device.

The RIRs were simulated by 'Pyroomacoustics' [21] using the image source method (ISM) at a sampling rate of 8 kHz. The absorption coefficient of each room was randomly selected within [0.1, 0.3]. The distance between the loudspeaker and microphones was always kept constant, so we trimmed out the direct part and silence region corresponding to the initial propagation delay from RIRs. Two datasets with low- and high-noise levels were constructed by adding white Gaussian noise to RIRs. In the high-noise level dataset, the noise level was sufficiently high to mask the peaks from third- or higher-order reflections. The resultant train dataset contains 600k RIRs, including 1k validation data.

 Table 2. Performance comparison to different RGI methods.

Method	Shoebox			Con	vex	Non-convex		
Metric	Ours	[8]	[9]	[12]	Ours	[9]	Ours	[9]
Δd (m)	0.07	0.08	0.05	0.10	0.08	0.04	0.13	0.15
$\Delta \theta$ (degree)	1.68	2.49	8.59	2.58	2.08	5.30	1.61	5.59

4.2. Evaluation Metrics

The performance of the proposed model was verified using three types of evaluation metrics: accuracy of wall presence estimation (ACC_W), distance error (Δd), and dihedral angle $(\Delta \theta)$. The ACC_W is defined as the number of correctly estimated walls normalized by the total number of walls. Since there is a hard-thresholding operation during inference, ACC_W can vary according to the threshold value. To achieve the threshold-independent evaluation of the wall presence probability, we also employed the area under the curve of the receiver operating characteristic (ROC–AUC) [22]. The Δd indicates the difference between the shortest distances from the device to the GT and estimated wall [6, 8, 9, 12], while the $\Delta \theta$ represents the angle between the normals of the GT and inferred walls [8, 9, 12]. These errors were calculated only for the walls that satisfy $AND(\hat{p}_w, p_w) = 1$ to avoid the error calculation for phantom walls.

4.3. Experimental Results

The RGI results on two different noise levels are listed in Table 1. The overall result shows that only the existence of 2 and 11 walls out of 4k candidate walls was misclassified in the low- and high-noise datasets, respectively. The average errors are approximately 10 cm and 1.9° for the low-noise dataset. RGI-Net shows good performance for most room types, but the most significant error variation between lowand high-noise levels is observed in L-NLOS rooms. Fig. 2 depicts the comparison between GT and inferred rooms based on the high-noise dataset. The left part of each result shows the location of the audio device (black dot), which was set as the origin of coordinates during inference. These results show that most of the inferred walls (blue solid lines) are very close to the GT walls (black dashed lines), while the invisible wall shown in Fig. 2(d) exhibits a more significant error than the other walls in the L-NLOS room. This is because the strong background noise masks high-order reflections that are small in magnitude but crucial in estimating the invisible walls in the L-NLOS rooms. This indirectly indicates that RGI-Net utilizes higher-order reflections when some low-order reflections are missing.

To further verify that RGI-Net can exploit high-order reflections, we generate an activation map using gradient information flowing into the last convolutional layer [23]. In the simple convex pentagonal room (Fig. 3(a)), the activation map of RGI-Net emphasizes early reflections within the traveling distance of 7 m (20 ms), indicating that low-order re-

 Table 3. Accuracy and robustness of the proposed method against noises.

0			
Model	Model trained with	Model trained with	Model trained with
Metric	clean RIRs	low-noise RIRs	high-noise RIRs
$ACC_W(\%)$	$99.96 \rightarrow 95.07$	$99.95 \rightarrow 99.45$	99.72 → 99.80
(ROC-AUC, %)	$(99.99 \rightarrow 94.91)$	$(99.99 \rightarrow 99.94)$	(99.98 → 99.98)
Δd (m)	0.10 ightarrow 0.41	0.10 ightarrow 0.17	0.16 ightarrow 0.17
$\Delta \theta$ (degree)	1.82 ightarrow 7.26	$1.89 \rightarrow \ 4.04$	3.33 → 3.47
		•	

flections are dominantly utilized. In the non-convex L-NLOS room (Fig. 3(b)), in contrast, the high-order reflections up to 21 m (60 ms) have strong activation. These results visually demonstrate that RGI-Net actively exploits high-order reflections to secure reliability when low-order reflections cannot be seen from the device due to occlusion by other walls.

Next, we compare the proposed model with different RGI techniques. Table 2 describes the performance comparison with two conventional [8,9] and one DNN-based [12] methods. Although direct comparison is not possible due to the differences in their data and conditions, the errors of the proposed method shown in Table 2 are in a similar range to those of the conventional and DNN-based techniques under lownoise conditions. More importantly, the proposed model can estimate non-convex rooms without relocation of the audio device to secure the LOS condition, and without prior knowledge of the number of walls.

To check the generalizability of the model, we tested the model using RIRs simulated by a different modeling technique. Unlike ISM used for the training data, we simulated test data using ray-tracing with a scattering coefficient of 0.1. The test was conducted without fine-tuning, and three different models trained on clean, low-noise, and high-noise ISM datasets were tested and compared. Table 3 summarizes the performance variation of three models against the ray-tracing dataset. The model trained on the high-noise dataset exhibits the smallest difference, whereas the model trained with clean RIRs exhibits significantly reduced performances in all metrics. Accordingly, exposure to noise during training helps secure robustness against the different simulation methods.

5. CONCLUSION

We proposed RGI-Net estimating geometries of complex and non-convex rooms without prior information about the number of walls. This ability was gained by training the model to simultaneously estimate the wall presence probability and geometric parameters of walls. To this end, wall parameter loss and decision loss were defined and used for the model training, which resulted in sufficiently small distance and angular errors even for the RIRs from L-NLOS rooms contaminated by high-level noises. RGI-Net utilizes high-order reflections when first-order reflections cannot be measured from the audio device, which was demonstrated through the visualization of temporal activation maps on RIRs of L-NLOS rooms.

6. REFERENCES

- F. Ribeiro, D. Ba, C. Zhang, and D. Florêncio, "Turning enemies into friends: Using reflections to improve sound source localization," in *Proc. IEEE Int. Conf. Multimedia Expo.*, Suntec City, Singapore, 2010, pp. 731–736.
- [2] Y. Peled and B. Rafaely, "Method for dereverberation and noise reduction using spherical microphone arrays," in *Proc. IEEE Int. Conf. Acoust. Speech Signal Process.*, Dallas, TX, USA, 2010, pp. 113–116.
- [3] I. Dokmanić, R. Scheibler, and M. Vetterli, "Raking the cocktail party," *IEEE J. Sel. Top. Signal Process.*, vol. 9, no. 5, pp. 825–836, 2015.
- [4] F. Antonacci, J. Filos, M.RP. Thomas, E.AP. Habets, A. Sarti, P.A. Naylor, and S. Tubaro, "Inference of room geometry from acoustic impulse responses," *IEEE Trans. Audio, Speech, Language Process.*, vol. 20, no. 10, pp. 2683–2695, 2012.
- [5] I. Dokmanić, R. Parhizkar, A. Walther, Y.M. Lu, and M. Vetterli, "Acoustic echoes reveal room shape," *Proc. Natl. Acad. Sci. U.S.A.*, vol. 110, no. 30, pp. 12186– 12191, 2013.
- [6] E. Nastasia, F. Antonacci, A. Sarti, and S. Tubaro, "Localization of planar acoustic reflectors through emission of controlled stimuli," in *Proc. Eur. Signal Process. Conf.*, Barcelona, Spain, 2011, pp. 156–160.
- [7] L. Remaggi, P.JB. Jackson, P. Coleman, and W. Wang, "Acoustic reflector localization: Novel image source reversion and direct localization methods," *IEEE/ACM Trans. Audio, Speech, Language Process.*, vol. 25, no. 2, pp. 296–309, 2016.
- [8] Y. El Baba, A. Walther, and E.AP. Habets, "3d room geometry inference based on room impulse response stacks," *IEEE/ACM Trans. Audio, Speech, Language Process.*, vol. 26, no. 5, pp. 857–872, 2017.
- [9] M. Lovedee-Turner and D. Murphy, "Threedimensional reflector localisation and room geometry estimation using a spherical microphone array," J. Acoust. Soc. Am., vol. 146, no. 5, pp. 3339–3352, 2019.
- [10] W. Yu and W.B. Kleijn, "Room acoustical parameter estimation from room impulse responses using deep neural networks," *IEEE/ACM Trans. Audio, Speech, Language Process.*, vol. 29, pp. 436–447, 2020.
- [11] N. Poschadel, R. Hupke, S. Preihs, and J. Peissig, "Room geometry estimation from higher-order ambisonics signals using convolutional recurrent neural networks," in *Proc. Audio Eng. Soc. Convention 150*, Virtual, 2021.

- [12] C. Tuna, A. Akat, H.N. Bicer, A. Walther, and E.AP. Habets, "Data-driven 3d room geometry inference with a linear loudspeaker array and a single microphone," in *Proc. Eur. Acoust. Assoc. (Forum Acousticum 2023)*, Torino, Italy, 2023.
- [13] I. Yeon and JW. Choi, "3d room geometry inference from multichannel room impulse response using deep neural network," in *Proc. Int. Congr. Acoust.*, Gyeongju, South Korea, 2022.
- [14] A. Luo, Y. Du, M. Tarr, J. Tenenbaum, A. Torralba, and C. Gan, "Learning neural acoustic fields," *Adv. Neural Inf. Process. Syst.*, vol. 35, pp. 3165–3177, 2022.
- [15] S. Purushwalkam, S.V.A. Gari, V.K. Ithapu, C. Schissler, P. Robinson, A. Gupta, and K. Grauman, "Audio-visual floorplan reconstruction," in *Proc. IEEE Int. Conf. Comput. Vis.*, Virtual, 2021, pp. 1183–1192.
- [16] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit.*, Las Vegas, NV, USA, 2016, pp. 770–778.
- [17] J.L. Ba, J.R. Kiros, and G.E. Hinton, "Layer normalization," arXiv:1607.06450, 2016.
- [18] D. Yu, M. Kolbæk, ZH. Tan, and J. Jensen, "Permutation invariant training of deep models for speakerindependent multi-talker speech separation," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process.*, New Orleans, LA, USA, 2017, pp. 241–245.
- [19] D.P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *Proc. Int. Conf. Learn. Repr.*, San Diego, CA, USA, 2015.
- [20] I. Loshchilov and F. Hutter, "Sgdr: Stochastic gradient descent with warm restarts," in *Proc. Int. Conf. Learn. Repr.*, Toulon, France, 2017.
- [21] R. Scheibler, E. Bezzam, and I. Dokmanić, "Pyroomacoustics: A python package for audio room simulation and array processing algorithms," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process.*, Calgary, AB, Canada, 2018, IEEE, pp. 351–355.
- [22] J. Huang and C.X. Ling, "Using auc and accuracy in evaluating learning algorithms," *IEEE Transactions on knowledge and Data Engineering*, vol. 17, no. 3, pp. 299–310, 2005.
- [23] R.R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, "Grad-cam: Visual explanations from deep networks via gradient-based localization," in *Proc. IEEE Int. Conf. Comput. Vis.*, Venice, Italy, 2017, pp. 618–626.