A Tight Lower Bound for 3-Coloring Grids in the Online-LOCAL Model

Yi-Jun Chang^{*}

Gopinath Mishra[†]

Mingyang Yang[§] Yu-Cheng Yeh[¶]

Hung Thuan Nguyen[‡]

Abstract

Recently, Akbari, Eslami, Lievonen, Melnyk, Särkijärvi, and Suomela (ICALP 2023) studied the locality of graph problems in distributed, sequential, dynamic, and online settings from a unified point of view. They designed a novel $O(\log n)$ -locality deterministic algorithm for proper 3-coloring bipartite graphs in the Online-LOCAL model. In this work, we establish the optimality of the algorithm by showing a *tight* deterministic $\Omega(\log n)$ locality lower bound, which holds even on grids. To complement this result, we have the following additional results:

- 1. We show a higher and tight $\Omega(\sqrt{n})$ lower bound for 3-coloring toroidal and cylindrical grids.
- 2. Considering the generalization of 3-coloring bipartite graphs to (k + 1)-coloring k-partite graphs, we show that the problem also has $O(\log n)$ locality when the input is a k-partite graph that admits a *locally inferable unique coloring*. This special class of k-partite graphs covers several fundamental graph classes such as k-trees and triangular grids. Moreover, for this special class of graphs, we show a tight $\Omega(\log n)$ locality lower bound.
- 3. For general k-partite graphs with $k \geq 3$, we prove that the problem of (2k 2)coloring k-partite graphs exhibits a locality of $\Omega(n)$ in the Online-LOCAL model, matching the round complexity of the same problem in the LOCAL model recently shown by Coiteux-Roy, d'Amore, Gajjala, Kuhn, Le Gall, Lievonen, Modanese, Renou, Schmid, and Suomela (STOC 2024). Consequently, the problem of (k + 1)-coloring k-partite graphs admits a locality lower bound of $\Omega(n)$ when $k \geq 3$, contrasting sharply with the $\Theta(\log n)$ locality for the case of k = 2.

^{*}National University of Singapore. Email: cyijun@nus.edu.sg

[†]National University of Singapore. Email: gopinath@nus.edu.sg

[‡]National University of Singapore. Email: hung@u.nus.edu

[§]National University of Singapore. Email: e0589912@u.nus.edu

[¶]National University of Singapore. Email: yu-cheng@comp.nus.edu.sg

Contents

1	Introduction			
	1.1	Technical Overview	5	
		1.1.1 Lower Bound for 3-Coloring Bipartite Graphs	5	
		1.1.2 Lower Bound for $(2k-2)$ -Coloring k-Partite Graphs	7	
		1.1.3 Coloring Graphs with Locally Inferable Unique Colorings	8	
	1.2	Roadmap	9	
2	Preliminaries			
	2.1	Grids	9	
	2.2	Models	10	
3	Har	rdness of 3-Coloring in Grids	10	
	3.1	Properties of 3-Coloring in Grids	10	
	3.2	Hardness of 3-Coloring in Simple Grids	13	
	3.3	Hardness of 3-Coloring in Toroidal and Cylindrical Grids	16	
4	Har	rdness of $(2k-2)$ -Coloring of k-Partite Graphs	17	
	4.1	Properties of the Gadgets	19	
	4.2	Properties of G^* and the Lower Bound Proof $\ldots \ldots \ldots$	20	
5	Coloring Graphs with Locally Inferable Unique Colorings 21			
	5.1	Upper Bound	21	
		5.1.1 Previous Approach	21	
		5.1.2 Our Algorithm	22	
	5.2	Lower Bound	27	
		5.2.1 Locally Inferable Unique Coloring	28	
		5.2.2 Locality Lower Bound	30	

1 Introduction

We focus on the *locality* of graph problems, which has been studied in a variety of models. Throughout the paper, we only consider the *deterministic* setting.

- **Distributed setting:** In the classical LOCAL model [Lin92; Pel00] of distributed computing, an algorithm with locality T processes the nodes of a graph simultaneously in parallel, in a way that each node determines its output by examining its neighborhood with a radius of T. Intuitively, an algorithm with locality T in the LOCAL model can be run on a distributed network in T synchronous communication rounds.
- Sequential setting: In the SLOCAL model [GKM17], an algorithm with locality T processes the nodes in a sequential order that is selected by an adversary. The output of a node may depend on its T-radius neighborhood and the outputs of the previously processed nodes. For instance, the well-known greedy coloring algorithm solves the (degree + 1)-list coloring problem with locality 1 in SLOCAL.
- **Dynamic setting:** There have been several papers studying local algorithms in the dynamic setting [AOS⁺18; BM19; BCH⁺18; DKK13; GK18; IL93; NS15], where an adversary constructs the graph *dynamically*, adding or removing nodes and edges sequentially. Following each modification, an algorithm with locality T is limited to adjusting the solution within the T-radius neighborhood of the point of change. Recently, Akbari et al. [AEL⁺23] formalized this setting by defining the two models Dynamic-LOCAL and Dynamic-LOCAL[±] to capture the incremental dynamic setting and the fully dynamic setting, respectively.

Ghaffari, Kuhn, and Maus [GKM17] studied the connections between LOCAL and SLOCAL. They developed a method of simulating an arbitrary SLOCAL algorithm in the LOCAL model using *network decompositions*. Combining this method with the deterministic polylogarithmic-round network decomposition of Rozhoň and Ghaffari [RG20], one can infer that the class of graph problems solvable with polylogarithmic locality deterministically is *identical* in LOCAL and SLOCAL.

Very recently, Akbari et al. $[AEL^+23]$ studied the locality of graph problems in distributed, sequential, and dynamic settings from a *unified* point of view. They considered a new model Online-LOCAL, which is a variant of SLOCAL that has a *global memory*. Among all the models {LOCAL, SLOCAL, Dynamic-LOCAL, Dynamic-LOCAL[±], Online-LOCAL}, the Online-LOCAL model is the *strongest* one: any algorithm in any of these models can be simulated in Online-LOCAL model with the same asymptotic locality. The LOCAL model is the *weakest* model in the sense that any LOCAL algorithm can be simulated in any of the above models with the same asymptotic locality. Therefore, all the mentioned models are sandwiched between the LOCAL and Online-LOCAL models. Consequently, if one can match a locality lower bound in Online-LOCAL with a locality upper bound in LOCAL, then it immediately implies a tight locality bound in all of the models.

Akbari et al. [AEL⁺23] obtained such a tight locality bound for a wide range of problems. For all *locally checkable labeling* problems in paths, cycles, and rooted regular trees, they have nearly the same locality in all of the models:

 $LOCAL \approx SLOCAL \approx Dynamic-LOCAL^{\pm} \approx Dynamic-LOCAL \approx Online-LOCAL$.

Coloring bipartite graphs in Online-LOCAL. While the above result suggests that these models can be quite similar, Akbari et al. [AEL⁺23] demonstrated an *exponential* separation between the LOCAL and Online-LOCAL models. They designed a novel $O(\log n)$ -locality algorithm for proper 3-coloring bipartite graphs in the Online-LOCAL model. In contrast, the same problem is known to have locality $\Omega(\sqrt{n})$ in the LOCAL model [BHK⁺17]. Their work left open the following question.

"Is it possible to find a 3-coloring in bipartite graphs in the Online-LOCAL model with locality $o(\log n)$?"

In this work, we resolve the question by demonstrating a *tight* $\Omega(\log n)$ locality lower bound in the Online-LOCAL which holds even on grids, which are bipartite graphs.

Theorem 1. In the Online-LOCAL model, the locality of 3-coloring a $(\sqrt{n} \times \sqrt{n})$ grid is $\Omega(\log n)$.

Combining the above result with the $O(\log n)$ upper bound by Akbari et al. [AEL+23], a tight bound is obtained.

Corollary 1.1. In the Online-LOCAL model, the locality of 3-coloring bipartite graphs is $\Theta(\log n)$.

To establish Theorem 1, a main technical barrier that we overcome is that in Online-LOCAL, we cannot rely on an *indistinguishability* argument due to the presence of global memory. Most of the existing LOCAL lower bound proofs rely on such kind of an argument. In particular, the known $\Omega(\sqrt{n})$ lower bound for 3-coloring grids in the LOCAL model [BHK⁺17] works by first proving the lower bound on *toroidal* grids and then using an indistinguishability argument to extend the lower bound to grids. The lower bound argument in [BHK⁺17] heavily depends on the assumption that the underlying graph is a toroidal grid with an *odd* number of columns, which is *not* bipartite.

The presence of a global memory in Online-LOCAL allows the possibility for a graph problem to have different localities in grids and toroidal grids. Indeed, in this work, we show a much higher $\Omega(\sqrt{n})$ lower bound for 3-coloring on toroidal grids in the Online-LOCAL model. The lower bound does not contradict the $O(\log n)$ -locality algorithm of [AEL⁺23] because toroidal grids are not bipartite in general.

Theorem 2. In the Online-LOCAL model, the locality of 3-coloring $(\sqrt{n} \times \sqrt{n})$ toroidal and cylindrical grids is $\Omega(\sqrt{n})$.

Combining the above Online-LOCAL lower bound with the trivial $O(\sqrt{n})$ locality upper bound in the LOCAL model, we establish that $\Theta(\sqrt{n})$ is a *tight* locality bound for 3-coloring toroidal and cylindrical grids in all the models discussed above, as they are sandwiched between LOCAL and Online-LOCAL.

Corollary 1.2. The locality of 3-coloring $(\sqrt{n} \times \sqrt{n})$ toroidal and cylindrical grids is $\Theta(\sqrt{n})$ in all the models {LOCAL, SLOCAL, Dynamic-LOCAL, Dynamic-LOCAL, Oline-LOCAL}.

Interestingly, our results yield two alternative proofs for the $\Omega(\sqrt{n})$ locality lower bound for 3coloring grids in LOCAL [BHK⁺17], which we briefly explain as follows. By an indistinguishability argument, the $\Omega(\sqrt{n})$ locality lower bound in Corollary 1.2 on toroidal and cylindrical grids in LOCAL automatically implies the same lower bound on grids in LOCAL. Alternatively, the $\Omega(\log n)$ lower bound of Theorem 1 in Online-LOCAL implies the same lower bound in LOCAL, and we can automatically improve such a lower bound to $\Omega(\sqrt{n})$ by the known $\omega(\log^* n) - o(\sqrt{n})$ complexity gap on grids in LOCAL [CKP19; CP19]. **Generalization:** (k + 1)-coloring k-partite graphs in Online-LOCAL. Next, we consider a natural generalization of the 3-coloring problem in bipartite graphs to the task of (k + 1)-coloring of k-partite graphs for any constant $k \ge 2$ within the Online-LOCAL model. Given Corollary 1.1, a pertinent question arises:

• Is the locality of (k + 1)-coloring k-partite graphs in Online-LOCAL $\Theta(\log n)$ for all k?

Interestingly, for $k \ge 3$, we can establish a lower bound of $\Omega(n)$. More specifically, we present a *much stronger* result demonstrating an $\Omega(n)$ lower bound for (2k-2)-coloring.

Theorem 3. Let $k \ge 2$ be a constant. The locality of (2k-2)-coloring a k-partite graph is $\Omega(n)$ in the Online-LOCAL model.

Observe that $k + 1 \leq 2k - 2$ for $k \geq 3$, so we have the following corollary.

Corollary 1.3. Let $k \ge 3$ be a constant. The locality of (k + 1)-coloring a k-partite graph is $\Omega(n)$ in the Online-LOCAL model.

Recall that for the case of k = 2, the locality (k+1)-coloring a k-partite graph is already known to be $\Theta(\log n)$ by Corollary 1.1.

Related work. In the LOCAL model, the same lower bound of $\Omega(n)$ for (2k-2)-coloring k-partite graphs has been very recently established in [CdG⁺24]. More generally, they showed that the round complexity of the problem of c-coloring k-partite graphs is $\Theta(n^{1/\alpha})$ in LOCAL, where $\alpha = \lfloor \frac{c-1}{k-1} \rfloor$ and the notation $\Theta(\cdot)$ hides polylogarithmic factors. Notably, this bound is polynomial in n for any constants k and c.

For the case of (c, k) = (3, 2), there is a huge gap between the complexities of 3-coloring bipartite graphs in LOCAL ($\Theta(\sqrt{n})$, [CdG⁺24]) and Online-LOCAL ($\Theta(\log n)$, Corollary 1.1). On the other hand, for $k \ge 3$ and $c \le 2k - 2$, Theorem 3 says that the locality of *c*-coloring *k*-partite graphs is $\Omega(n)$ in Online-LOCAL – a match with the round complexity of the same problem in LOCAL.

Improved upper bounds for special graph classes. For the problem of (k + 1)-coloring of k-partite graphs in Online-LOCAL, the locality is $\Theta(\log n)$ for k = 2 (Corollary 1.1) and is $\Omega(n)$ for $k \ge 3$ (Corollary 1.3). A plausible explanation for this notable shift in the locality bound when transitioning from k = 2 to $k \ge 3$ is as follows: While the bipartition (i.e., 2-coloring) of a (connected) bipartite graph is unique, a k-partite graph might not admit a unique k-coloring in general. Intuitively, this means that for $k \ge 3$, the colorings of two graph fragments computed by an Online-LOCAL algorithm may be completely incompatible, requiring more adjustments to combine them, thus leading to a locality of $\Omega(n)$.

We show that it is possible to break the $\Omega(n)$ locality lower bound of Theorem 3 if the underlying k-partite graph admits a unique k-coloring satisfying the following desirable property: For each graph fragment seen by an Online-LOCAL algorithm, the unique k-coloring restricted to that fragment can be inferred correctly, up to a permutation of the k colors. As we will later see, examples of such graphs include all (connected) bipartite graphs, triangular grids, and k-trees.

Let $\ell \in \mathbb{N}$ be a non-negative integer. Let G be a k-partite graph. Let G' = (V', E') be a connected subgraph of G. Define $\mathcal{C}^*(G', \ell)$ as the set of all proper k-colorings of the subgraph of G induced by the ℓ -radius neighborhood $\mathcal{B}(V', \ell)$ of V'. Define $\mathcal{C}(G', \ell)$ as the set of all proper k-colorings of G' resulting from restricting some coloring $c \in \mathcal{C}^*(G', \ell)$ to the domain V'. We say that

two k-colorings c and c' are identical up to a permutation if there exists a permutation $\phi: [k] \to [k]$ such that $c' = \phi \circ c$.

Definition 1.4 (Locally inferable unique colorings). We say that a k-partite graph G has a locally inferable unique k-coloring with radius ℓ if all colorings in $\mathcal{C}(G', \ell)$ are identical up to a permutation for any connected subgraph G' of G.

To put it another way, G admits a locally inferable unique k-coloring with radius ℓ if the kcolor partition of G is unique and can be inferred locally in the following way: For any connected subgraph G' of G, the unique k-color partition restricted to G' can be inferred by inspecting its ℓ -radius neighborhood. Since the bipartition of a bipartite graph is unique, every bipartite graph has a locally inferable unique k-coloring with radius $\ell = 0$. We show that triangular grids and k-trees also admit locally inferable unique colorings with $\ell \in O(1)$.

Triangular grids: The triangular grid G = (V, E) of side length d is defined as follows.

- $V = \{(x, y) \in \mathbb{N}^2 : 0 \le x + y \le d\}.$
- For any two nodes (x, y) and (x', y') in V, add an edge between them to E if |x x'| + |y y'| = 1 or $x x' = y y' \in \{-1, 1\}$.

Consider a connected subgraph G' = (V', E') of a triangular grid G. See Figure 1 for an illustration. For any node $u \in V'$, there is a triangle Δ_u containing u in the 1-radius neighborhood of V' in G. Observe that for any two nodes u and v in V', they are connected by a sequence of triangles $(\Delta_u = \Delta_1, \Delta_2, \ldots, \Delta_t = \Delta_v)$ in the 1-radius neighborhood of V' in G: For each $i \in [t-1]$, Δ_i and Δ_{i+1} shares an edge. If the nodes of Δ_i and Δ_{i+1} are $\{a, b, c\}$ and $\{b, c, d\}$, respectively, then the color of a and d must be identical under any 3-coloring. In particular, fixing the coloring of Δ_u uniquely determines the color of v. Therefore, for any given 3-coloring of the 1-radius neighborhood of V' in G, its restriction to V' must be unique up to a permutation. In other words, G admits a locally inferable unique 3-coloring with radius $\ell = 1$.

k-trees: The graphs that can be constructed as follows are called *k*-trees: Start with a (k+1)-clique, and then iteratively add nodes such that each newly added node v is adjacent to exactly kexisting nodes that form a *k*-clique. The construction of a *k*-tree *G* naturally yields a tree *H* so that each node $h \in V(H)$ corresponds to a (k+1)-clique of *G* and two nodes of *H* are adjacent if their corresponding cliques share *k* nodes. Consider a connected subgraph G' = (V', E') of a *k*-tree *G*. Similar to the case of triangular grids, by querying the 1-radius neighborhood of V' in *G*, we learn all the (k+1)-cliques containing at least one node in V' and their adjacency relations in *H*. Therefore, *k*-trees admit a locally inferable unique (k+1)-coloring with radius $\ell = 1$, as fixing the color assignment of any one of these (k + 1)-cliques fixes the color of all other nodes in *G'*.

For notational simplicity, from now on, we write $\mathcal{L}_{k,\ell}$ to denote the set of all k-partite graphs having a locally inferable unique k-coloring with radius ℓ . We show that a (k + 1)-coloring for any graph in $\mathcal{L}_{k,\ell}$ with $k \in O(1)$ and $\ell \in O(1)$ can be computed with $O(\log n)$ locality in the Online-LOCAL model.

Theorem 4. Let $k \ge 2$ be any constant. There is an Online-LOCAL algorithm with locality $O(\log n)$ that (k + 1)-colors any graph in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$.



Figure 1: The unique tripartition of a triangular grid restricted to a connected subgraph.

The following corollary is an immediate consequence of Theorem 4.

Corollary 1.5. The locality of 3-coloring triangular grids and (k+2)-coloring k-trees with $k \in O(1)$ is $O(\log n)$ in the Online-LOCAL model.

We complement Theorem 4 with a matching lower bound by extending the lower bound of Theorem 1 from k = 2 to higher values of k.

Theorem 5. Let $k \ge 2$ be any constant. For any Online-LOCAL algorithm that (k + 1)-colors any graph in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$, its locality must be $\Omega(\log n)$.

Combining Theorems 4 and 5, we obtain a tight bound for (k+1)-coloring for $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$.

Corollary 1.6. For any constant $k \ge 2$, in the Online-LOCAL model, the locality of (k+1)-coloring graphs in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$ is $\Theta(\log n)$.

Related models. Subsequent to the initial publication of this paper, Akbari et al. $[ACd^+24]$ studied the *randomized* variant of the Online-LOCAL model, extending our $\Omega(\log n)$ lower bound to the randomized setting. In addition to the Online-LOCAL model, researchers have studied other hybrids of shared-memory and message-passing models, including the *message-and-memory* (m&m) model $[ABC^+18]$ and the *computing-with-the-cloud* (CWC) model [AGP24].

1.1 Technical Overview

We give an overview of the proofs of Theorems 1 to 5.

1.1.1 Lower Bound for 3-Coloring Bipartite Graphs

We start by reviewing the $\Omega(\sqrt{n})$ locality lower bound for 3-coloring grids in LOCAL [BHK⁺17]. First of all, by an indistinguishability argument, they can focus on toroidal grids and not grids. Without loss of generality, they assumed that the coloring has a special property that any node colored with 3 is adjacent to a node colored with 1 and a node colored with 2. They showed that for any proper 3-coloring of a toroidal grid satisfying the above condition, it is possible to orient the diagonals between any two nodes colored with 3 in such a way that yields an Eulerian graph over the set of all nodes colored with 3. They made a key observation that the difference between the number of times a directed edge in the Eulerian graph passes a row in the upward direction and in the downward direction is *invariant* of the choice of the row. Let $s(\ell)$ denote this value, where ℓ is the number of nodes in a row. They showed that when ℓ is odd, $s(\ell)$ must be an odd number within the range $[-\ell/2, \ell/2]$. Based on this property, they obtained the desired lower bound by a reduction to the following problem on an *n*-cycle, which requires $\Omega(n)$ rounds to solve: Each node outputs a number in such a way that all the numbers sum up to exactly q, where q is any given odd integer in the range [-n/2, n/2].

The above lower bound proof does *not* apply to Online-LOCAL because it highly depends on the assumption that the underlying graph is a toroidal grid, which is fine in the LOCAL model due to an indistinguishability argument. This is not possible for Online-LOCAL due to the presence of a global memory. To extend the lower bound to Online-LOCAL, new ideas are required.

Our Online-LOCAL lower bound starts from the following informal observation. The notion of $s(\ell)$ can be extended beyond rows. Informally, for any directed path or directed cycle, we may define its s-value as the difference between the number of times a directed edge in the Eulerian graph passes it in the rightward direction and the leftward direction. Similarly, it is possible to argue that if two directed paths or two directed cycles are *homotopic* to each other, then their s-values must be identical. Moreover, this observation still makes sense even if the underlying graph is a grid and not a toroidal grid, although the directed graph defined on the set of all nodes colored with 3 might not be Eulerian in that case.

For the case of grids, one can observe that the s-value of any directed cycle must be zero. This gives rise to the following proof idea in the Online-LOCAL model. Suppose we have an adversary strategy that can force an algorithm to create a directed path in a row on the grid that has an s-value of at least t. In that case, such an algorithm must have locality $\Omega(t)$, since otherwise using such a directed path construction, the adversary can force a cycle to have an s-value that is nonzero, which is a contradiction.

A technical difficulty in realizing the above proof idea is that in the informal definition of the *s*-value of a directed path or directed cycle suggested above, the *s*-value not only depends on the colors on the path or cycle under consideration but also depends on the colors of all nodes adjacent to the path or cycle. Moreover, there are subtle issues about how we deal with an intersection that occurs at the endpoints of a path. This makes the informal definition of *s*-value inconvenient to use, especially because we have to consider partial coloring to prove lower bounds in the Online-LOCAL model.

To deal with the above issue, we develop the notion of b-value that depends only on the coloring of the considered path or cycle. The notion of b-value can be seen as a simplification of the notion of s-value that still enjoys all the nice properties of s-value that we need. It is noteworthy that our notion of b-value does not require the assumption that any node colored with 3 is adjacent to a node colored with 1 and a node colored with 2.

To realize the above proof idea, we demonstrate a recursive strategy that constructs a directed path with length at most $T \cdot c^k$ whose *b*-value is at least *k*, for some constant c > 0 and any given *T*-locality **Online-LOCAL** algorithm. By setting both *T* and *k* to be $\Theta(\log n)$ with a sufficiently small leading constant, the path length can be made smaller than \sqrt{n} , so we can fit the path in a $(\sqrt{n} \times \sqrt{n})$ grid. This gives us the desired $\Omega(\log n)$ locality lower bound. A key idea in the recursive construction is to utilize a property of *b*-value that whether it is even or odd is determined by the parity of the path length and the colors of the two endpoints.

To show the higher lower bound of $\Omega(\sqrt{n})$ in cylindrical and toroidal grids, we again utilize the

property that the *b*-value of each row is invariant of the choice of the row and is odd given that each row contains an odd number of nodes. Therefore, as an adversary, we may just ask the algorithm to produce a coloring of two rows, and then we set their directions in a way to force them to have different *b*-values.

1.1.2 Lower Bound for (2k-2)-Coloring k-Partite Graphs

To establish the $\Omega(n)$ lower bound for (2k - 2)-coloring k-partite graphs in the LOCAL model, [CdG⁺24] considered an instance $G^{\#}$ such that the chromatic number of $G^{\#}$ is 2k - 1, while the subgraphs induced by the o(n)-radius neighborhood of any node of $G^{\#}$ are k-partite. It is crucial to note that $G^{\#}$ lies outside the input family. Despite being outside the input family, the instance is locally solvable, signifying that the subgraph induced by the o(n)-neighborhood of any node can be colored with k colors. The lower bound in the LOCAL model is established through an indistinguishability argument by Linial [Lin92], which proves lower bounds by employing hard instances taken from outside the input family: To show a T-round LOCAL lower bound for c-coloring for G by this approach, one just needs to construct a graph $G^{\#}$ that cannot be c-colored and is indistinguishable to G by a T-round LOCAL algorithm.

The construction of the hard instance k-partite graph G^* , to establish the lower bound for (2k-2)-coloring k-partite graphs in the Online-LOCAL model, is inspired by the construction of $G^{\#}$. However, the application of Linial's technique, designed for LOCAL, is not straightforward in the Online-LOCAL model possibly due to the presence of global memory. Despite the inspiration of our hard instance being inspired from the hard instance in the LOCAL model, our arguments to establish the lower bound in the Online-LOCAL model are different, as sketched in the subsequent paragraphs, and accommodate the unique features of the Online-LOCAL setting, including the utilization of global memory.

In the construction of the hard instance graph G^* , we consider n/k^2 gadgets, each comprising k^2 nodes. The node set of a gadget is represented as elements in a $k \times k$ matrix. Two nodes in a gadget are connected by an edge if and only if they are neither in the same row nor the same column. Under a proper coloring of a gadget, the gadget is said to be *row-colorful (column-colorful)* if there exists a row (column) with all the k nodes being colored by distinct colors. We show that a gadget is exactly one out of row-colorful and column-colorful when we have a proper coloring of the gadget with 2k-2 colors. G^* is formed by assembling n/k^2 gadgets, connecting nodes in consecutive gadgets as follows: for any two consecutive gadgets, two nodes (one from each) are connected by an edge if and only if they are neither in the same row nor the same column. We prove that, in any proper coloring of G^* with 2k-2 colors, either all the gadgets are row-colorful or all of them are column-colorful.

The basis of our lower bound argument is as follows: if the locality of the algorithm in the Online-LOCAL model is o(n), then the adversary can ask the algorithm to color G^* in a specific order such that the first gadget is row-colorful and the last gadget is column-colorful. This scenario results in the impossibility of properly coloring some nodes, as all the gadgets must be either row-colorful or column-colorful.

In $[CdG^+24]$, the authors consider the problem of *c*-coloring *k*-partite graphs, where *c* and *k* are constants. This is a more general version than both 3-coloring bipartite graphs and (2k-2)-coloring *k*-partite graphs. Specifically, $[CdG^+24]$ establishes that the round complexity of this generalized problem is essentially $\tilde{\Theta}(n^{1/\alpha})$, where $\alpha = \lfloor \frac{c-1}{k-1} \rfloor$. We have discussed the extension of the hard instance construction for c = 2k - 2 (and thus $c \leq 2k - 2$) to demonstrate an $\Omega(n)$ lower bound

for (2k-2)-coloring k-partite graphs in the Online-LOCAL model. It is natural to consider the possibility of such an extension for all c and k. However, if such a general extension is possible for all c and k, we would have achieved $\Omega(\sqrt{n})$ lower bound on the locality of 3-coloring bipartite graphs in the Online-LOCAL model, which is impossible as the locality of 3-coloring bipartite graphs is $\Theta(\log n)$ due to Corollary 1.1. Resolving the locality of c-coloring k-partite graphs for all values of c and k in the Online-LOCAL model remains an intriguing open problem.

1.1.3 Coloring Graphs with Locally Inferable Unique Colorings

From the upper bound side, Akbari et al. [AEL⁺23] presented an $O(\log n)$ -locality Online-LOCAL algorithm of 3-coloring a bipartite graph. Their algorithm is based on a key observation that the bipartition for any (connected) bipartite graph G is unique, so there are exactly two different ways to 2-color G. In the subsequent discussion, we refer to these two possibilities as two parities.

The algorithm of Akbari et al. [AEL+23], in a nutshell, tries to 2-color the graph fragments seen by the Online-LOCAL algorithm using the colors in $\{1, 2\}$. A technical challenge arises when two graph fragments with different parities become connected, as their 2-coloring are incompatible with each other. The issue is resolved by *flipping* the parity of one graph fragment by adding a layer of the third color on the boundary. The flipping operation requires O(1) locality. By always flipping the graph fragment with a smaller size, it is guaranteed that at most $O(\log n)$ flipping operations are needed from the perspective of each node. Therefore, the total required locality is $O(\log n)$.

In this work, we extend their algorithm to (k + 1) coloring all k-partite graphs having a locally inferable unique coloring with radius $\ell \in O(1)$. For these k-partite graphs, there is a unique partition into k parts that can be inferred locally: Given a connected node set S, the partition restricted to S can be inferred by information within the ℓ -radius neighborhood of S. Therefore, we can assume that there is an oracle \mathcal{O} that returns such a k-partition for any graph fragment seen by the Online-LOCAL algorithm, as the cost of implementing such an oracle is just an extra $\ell \in O(1)$ locality. Our (k + 1) coloring algorithm is based on the generalization of the notion of parity into the assignment of the *indices* $\{1, 2, \ldots, k\}$ to the k parts in the partition, which is possible due to the oracle \mathcal{O} . Similar to the algorithm of Akbari et al. [AEL+23], we try to k-color the graph fragments seen by the Online-LOCAL algorithm using the colors in [k]. When two graph fragments with incompatible k-coloring become connected, we show that with O(1) locality, it is possible to unify their coloring by iteratively swapping the indices with the help of the extra color k + 1. As such, we can (k + 1)-color any graph in $\mathcal{L}_{k,\ell}$ for any constants k and ℓ with $O(\log n)$ locality.

Now, we discuss the idea behind $\Omega(\log n)$ lower bound on the locality of (k+1)-coloring k-partite graphs when the input graph is from $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$. Recall that Theorem 1 already establishes this result for the case of k = 2, as grids are bipartite graphs, which belong to $\mathcal{L}_{2,0}$. To extend the result to higher values of k, we construct a sequence of graphs (G_2, G_3, \ldots, G_k) recursively such that $G_k \in \mathcal{L}_{k,\ell}$ with $\ell \in O(1)$. For the base case, G_2 is a $(\sqrt{n} \times \sqrt{n})$ grid. For the inductive step, G_{i+1} is constructed from G_i by augmenting each node u in G_i with a new node u' that is connected to u and its (original) neighbors. We show that an $o(\log n)$ -locality algorithm that properly colors G_i with i + 1 colors can be obtained from an $o(\log n)$ -locality algorithm that properly colors G_{i+1} with i + 2 colors, so the $\Omega(\log n)$ lower bound for the case of k = 2 (Theorem 1) implies the same asymptotic lower bound for any constant $k \geq 2$.

1.2 Roadmap

In Section 2, we introduce essential graph terminology and define the computation models. In Section 3, we present our main lower bound results: an $\Omega(\log n)$ locality lower bound for 3-coloring in simple grids and a higher $\Omega(\sqrt{n})$ lower bound for toroidal and cylindrical grids (Theorems 1 and 2). In Section 4, we prove the $\Omega(n)$ locality lower bound for (2k - 2)-coloring of k-partite graphs (Theorem 3). In Section 5, we establish a tight $\Theta(\log n)$ bound for (k+1)-coloring in locally inferable unique coloring graphs (Theorems 4 and 5).

2 Preliminaries

Throughout this paper, the input graph G = (V, E) is simple, connected, undirected, and finite unless explicitly specified otherwise. We write n = |V| to denote the number of nodes in G. For a subset of nodes $U \subseteq V$ and a natural number T, we write $\mathcal{B}(U,T)$ to denote the set of all nodes within the T-radius neighborhood of any $v \in U$. If there is only one node v in U, we may write $\mathcal{B}(v,T)$ instead of $\mathcal{B}(U,T)$. We write G[U] to denote the subgraph of G induced by the set of nodes $U \subseteq V$. In particular, $G[\mathcal{B}(v,T)]$ is the subgraph of G induced by the T-radius neighborhood of v. For any graph H, we write V(H) and E(H) to denote its node set and edge set, respectively. For a subgraph $H \subseteq G$ and a node u, we write H - u to denote the induced subgraph $H[V(H) \setminus \{u\}]$. For $x \in \mathbb{N}$, we write [x] to denote $\{1, 2, \ldots, x\}$.

2.1 Grids

We investigate local algorithms in three types of grid topologies.

- Simple grids: A simple grid of dimension $(a \times b)$ is a grid with a rows and b columns. More formally, an $(a \times b)$ grid is defined by the set of nodes $\{(i, j) : i \in [a] \text{ and } j \in [b]\}$ such that two nodes (i, j) and (i', j') are adjacent if and only if |i i'| + |j j'| = 1. For each $i \in [a]$, the set of nodes $\{(i, j) : j \in [b]\}$ forms a row. For each $j \in [b]$, the set of nodes $\{(i, j) : i \in [a]\}$ forms a row and each column induce a path.
- **Cylindrical grids:** A cylindrical grid of dimension $(a \times b)$ is the result of adding the edges in $\{\{(i, 1), (i, b)\}: i \in [a]\}$ to an $(a \times b)$ grid. In other words, a cylindrical grid is the result of connecting the left border and the right border of a simple grid. In a cylindrical grid, each row induces a cycle and each column induces a path.
- **Toroidal grids:** A toroidal grid of dimension $(a \times b)$ is the result of adding the edges in $\{\{(i, 1), (i, b)\}: i \in [a]\}$ and $\{\{(1, j), (a, j)\}: j \in [b]\}$ to an $(a \times b)$ grid. In other words, a toroidal grid is the result of connecting the left and right borders and connecting the upper and lower borders of a simple grid. In a toroidal grid, each row and each column induce a cycle.

In Theorem 1, we consider simple grids of dimension $(\sqrt{n} \times \sqrt{n})$. In Theorem 2, we consider toroidal and cylindrical grids of dimension $(\sqrt{n} \times \sqrt{n})$. It is worth noting that toroidal grids and cylindrical grids with an odd number of columns are not bipartite graphs.

2.2 Models

We proceed to define two computation models: LOCAL and Online-LOCAL. In these models, the complexity of an algorithm is measured by its *locality*, which informally refers to the minimum number T such that the output of a node is determined by its T-radius neighborhood. Generally, the locality of an algorithm can be a function of the number n = |V| of nodes in the input graph G = (V, E). It is assumed that the algorithm knows the value of n. Throughout the paper, we only consider *deterministic* algorithms, so it does not matter whether the adversary is oblivious or adaptive in the following definitions. In both LOCAL and Online-LOCAL, the adversary assigns unique identifiers from the set $\{1, 2, \ldots, \text{poly}(n)\}$ to the nodes.

The LOCAL model. In an algorithm with locality T in the LOCAL model [Lin92; Pel00], each node independently determines its part of the output based on the information within its T-radius neighborhood. For example, for the proper k-coloring problem, each node $v \in V$ just needs to output its own color $c(v) \in [k]$ in such a way that no two adjacent nodes output the same color. The output of a node may depend on factors such as the graph structure, input labels, and unique identifiers.

There is an alternative way of defining the LOCAL model from the perspective of distributed computing by viewing the input graph G = (V, E) as a communication network, where each node $v \in V$ is a machine and each edge $e \in E$ is a communication link. The communication proceeds in synchronous rounds. In each round, each node can communicate with its neighbors by exchanging messages of unlimited size. The locality of an algorithm is the number of communication rounds.

The Online-LOCAL model. In an algorithm of locality T in the Online-LOCAL model [AEL⁺23], nodes are processed sequentially according to an adversarial input sequence $\sigma = (v_1, v_2, \ldots, v_n)$. Let $G_i = G\left[\bigcup_{j=1}^i \mathcal{B}(v_j, T)\right]$ denote the subgraph induced by the T-radius neighborhoods of the first i nodes in σ . When the adversary presents a node v_i , the algorithm must assign an output label to v_i based on the information from the subsequence (v_1, v_2, \ldots, v_i) and the induced subgraph G_i .

In the related SLOCAL model [GKM17], the assignment of the output label of v_i can only be based on $G[\mathcal{B}(v_i, T)]$ and the output labels that were already assigned to the nodes in $\mathcal{B}(v_i, T)$, so Online-LOCAL can be seen as a variant of SLOCAL that has a global memory.

3 Hardness of 3-Coloring in Grids

In this section, we establish our lower bound results for 3-coloring in a simple grid, as well as toroidal and cylindrical grids. In Section 3.1, we discuss some groundwork to prove the lower bounds presented in the subsequent sections. Moving on to Section 3.2, we prove Theorem 1, showing the $\Omega(\log n)$ locality lower bound for 3-coloring in a simple grid. Subsequently, in Section 3.3, we prove Theorem 2, establishing the $\Omega(\sqrt{n})$ locality lower bound for 3-coloring in toroidal and cylindrical grids.

3.1 Properties of 3-Coloring in Grids

In this section, we focus on analyzing the properties of proper 3-coloring and introducing the notion of b-value, which plays a critical role in the proof of Theorems 1 and 2. Although some of the

results in this section apply to general 3-partite graphs, they are particularly interesting when we restrict our focus to grid topologies. Throughout this section, we let $c: V \to \{1, 2, 3\}$ be any proper 3-coloring of any 3-partite graph G = (V, E).

Definition 3.1 (*a*-value). Let $\{u, v\} \in E$ be an edge in *G*. Define the *a*-value of (u, v) by

$$a(u,v) = \begin{cases} c(u) - c(v) & \text{if } c(u) \neq 3 \text{ and } c(v) \neq 3, \\ 0 & \text{otherwise.} \end{cases}$$

For any edge $\{u, v\} \in E$, note that $a(u, v) \in \{-1, 0, 1\}$. Moreover, the *a*-value of (u, v) is non-zero if and only if one of $\{u, v\}$ is colored with 1 and the other one is colored with 2. Observe that we always have a(u, v) + a(v, u) = 0 for any edge $\{u, v\} \in E$.

We define the *b*-value of a directed path P or a directed cycle C by the sum of a(u, v) over all directed edges (u, v) in P or C, respectively.

Definition 3.2 (*b*-value). Let *H* be a directed path or a directed cycle. Define the *b*-value of *H* by

$$b(H) = \sum_{(u,v)\in H} a(u,v).$$

For the special case of a zero-length directed path P, we define b(P) = 0, as it does not contain any directed edge.

We observe that b(C) = 0 for any 4-node directed cycle C. This observation is particularly relevant to grid topologies, as they consist of "cells" that are 4-node cycles.

Lemma 3.3 (Cancellation of the *a*-values within a cell). For any 4-node directed cycle C, b(C) = 0.

Proof. Let $C = \begin{array}{c} t & \leftarrow s \\ \downarrow & \uparrow \\ u & \rightarrow \end{array}$, so we have b(C) = a(u, v) + a(v, s) + a(s, t) + a(t, u). Since there are

only three colors, we have c(u) = c(s) or c(v) = c(t) or both. Without loss of generality, we assume c(u) = c(s), so

$$a(u, v) + a(v, s) = a(u, v) + a(v, u) = 0$$
 and $a(s, t) + a(t, u) = a(s, t) + a(t, s) = 0$,

implying that b(C) = a(u, v) + a(v, s) + a(s, t) + a(t, u) = 0.

We say that a cycle is *simple* if it does not have repeated nodes. As a consequence of Lemma 3.3, we show that b(C) = 0 for any simple directed cycle C in a grid.

Lemma 3.4 (b-value of a cycle). For any simple directed cycle C in a grid, b(C) = 0.

Proof. We can calculate $b(C) = \sum_{(u,v)\in C} a(u,v)$ alternatively by summing up the *b*-value of each cell that is inside the cycle, where each cell is seen as a 4-node directed cycle that has the same orientation as that of C, so b(C) = 0 by Lemma 3.3. The validity of the calculation is due to the cancellation of the *a*-values associated with the edges that are strictly inside C, as illustrated in Figure 2. For each directed edge (u, v) on C, a(u, v) appears exactly once in the calculation. For each edge $\{u, v\}$ that is inside C, both a(u, v) and a(v, u) appear exactly once in the calculation, so they cancel each other.



Figure 2: Cancellation of *a*-values.

For each node $u \in V$, we define

$$i(u) = \begin{cases} 1 & \text{if } c(u) = 3, \\ 0 & \text{otherwise.} \end{cases}$$

as the indicator variable for c(u) = 3. We show that the parity of the *b*-value of a directed path is uniquely determined by the colors of the two endpoints and the parity of the path length.

Lemma 3.5 (Parity of *b*-value). Let C be any directed cycle of length ℓ and let $P = (u, \ldots, v)$ be any directed path of length ℓ . We have

$$b(C) \equiv \ell \pmod{2}$$
 and $b(P) \equiv i(u) + i(v) + \ell \pmod{2}$.

Proof. We just need to focus on proving $b(P) \equiv i(u) + i(v) + \ell \pmod{2}$, as $b(C) \equiv \ell \pmod{2}$ follows from $b(P) \equiv i(u) + i(v) + \ell \pmod{2}$ by viewing C as a directed path that starts and ends at the same node u and observing that $i(u) + i(u) \pmod{2} = 0$ regardless of the color of u.

Base case. Suppose $\ell = 1$. We claim that $b(P) = a(u, v) \equiv i(u) + i(v) + \ell \pmod{2}$. To see this, we divide the analysis into two cases.

- If $c(u) \neq 3$ and $c(v) \neq 3$, then $a(u, v) \in \{-1, 1\}$, so $a(u, v) \equiv i(u) + i(v) + \ell \equiv 1 \pmod{2}$, as i(u) = i(v) = 0.
- If c(u) = 3 or c(v) = 3, then $0 = a(u, v) \equiv i(u) + i(v) + \ell \equiv 0 \pmod{2}$, as i(u) + i(v) = 1.

Summation. Consider the case where $\ell > 1$.

$$\begin{split} b(P) &= \sum_{(s,t)\in P} a(s,t) \\ &\equiv \sum_{(s,t)\in P} (i(s) + i(t) + 1) \pmod{2} \\ &\equiv -i(u) - i(v) + 2 \cdot \sum_{(s,t)\in P} (i(s) + i(t)) + \sum_{(s,t)\in P} 1 \pmod{2} \\ &\equiv i(u) + i(v) + \ell \pmod{2}. \end{split}$$
 (the base case)

We emphasize that the claim regarding b(C) in lemma 3.5 does *not* follow immediately from lemma 3.4, as lemma 3.4 only considers grids.

Before we continue, we briefly discuss the intuition behind our notion of *b*-value. This notion intuitively captures the level of difficulty in completing the coloring of the rest of the grid given a colored path. In a proper 3-coloring of a grid, the set of nodes with color 3 separates the remaining nodes into connected regions. In the subsequent discussion, a region refers to a connected set of nodes with colors 1 and 2.

Let us start by considering a directed path $3 \rightarrow 2 \rightarrow 1 \rightarrow 2 \rightarrow 1 \rightarrow 2 \rightarrow 3$ whose *b*-value is zero. Starting from the coloring of this path, it is easy to extend the partial coloring in a way that the region of nodes colored with 1 and 2 is enclosed by a cycle of nodes colored with 3, see Figure 3.



Figure 3: A directed path whose *b*-value is zero.

Consider a directed path $3 \rightarrow 2 \rightarrow 1 \rightarrow 2 \rightarrow 1 \rightarrow 3$ whose a *b*-value is 1. In this case, we cannot close the region with *one* cycle of nodes colored 3. The region of nodes colored with 1 and 2 must continue unless it closes with itself or reaches the boundary of the grid.

Consider any directed cycle C that contains the directed path $3 \rightarrow 2 \rightarrow 1 \rightarrow 2 \rightarrow 1 \rightarrow 3$ as a subpath. Observe that C must intersect with the region of nodes colored with 1 and 2 *again* via a directed path whose b-value is -1, as illustrated in Figure 4.

Intuitively, the *b*-value of a directed path counts the difference between the number of occurrences of $3 \rightarrow 2 \rightarrow \cdots$ (colors 1 and 2 appear alternatively) $\cdots \rightarrow 1 \rightarrow 3$ and the number of occurrences of $3 \rightarrow 1 \rightarrow \cdots$ (colors 1 and 2 appear alternatively) $\cdots \rightarrow 2 \rightarrow 3$. The above informal discussion suggests that each occurrence $3 \rightarrow 2 \rightarrow \cdots \rightarrow 1 \rightarrow 3$ has to be matched with an occurrence of $3 \rightarrow 1 \rightarrow \cdots \rightarrow 2 \rightarrow 3$. Therefore, if we can force an algorithm to create a directed path *P* with a large value of |b(P)|, then we may obtain a high locality lower bound for the algorithm.

3.2 Hardness of 3-Coloring in Simple Grids

In this section, we prove the main result of the paper, i.e., Theorem 1. Our proof uses the following properties of b-values in grids.

- The *b*-value of any directed cycle is *always zero* (Lemma 3.4).
- The parity of the *b*-value of any directed path is *solely determined* by the parity of the path length and the color of the two endpoints u and v (Lemma 3.5).



Figure 4: Intersection of a directed cycle and a region of nodes with colors 1 and 2.

To establish Theorem 1, we prove that any algorithm designed for 3-coloring grids, operating with a locality of $T(n) \in o(\log n)$, can be strategically countered by an adversary capable of forcing a directed cycle with a non-zero b-value. Throughout this section, let \mathcal{A} be any algorithm for 3coloring a $(\sqrt{n} \times \sqrt{n})$ grid G = (V, E) with a locality of $T(n) \in o(\log n)$. We analyze the coloring function $c: V \to \{1, 2, 3\}$ generated by algorithm \mathcal{A} .

The core strategy of our proof is to create a directed path with a substantial *b*-value, making it impossible for the algorithm to complete the coloring with a small locality. The interaction between the algorithm and the adversary in Online-LOCAL can be seen as a 2-player game as follows.

- The algorithm's task is to label each node v_i based on the current discovered region G_i and the sequence (v_1, v_2, \ldots, v_i) . The algorithm wins if the final coloring of G is proper.
- The adversary's task is to select the nodes v_i in the sequence $\sigma = (v_1, v_2, \ldots, v_n)$. Moreover, the adversary has the liberty to adjust how the current discovered region G_i fits into G as an induced subgraph. Informally, suppose G_i consists of several connected components. The adversary has the flexibility to adjust the *directions* of these components and the *distances* between these components, as the algorithm is unaware of the precise location of these components in G. The adversary wins if the final coloring of G is not proper.

Next, we show that there is an adversary strategy to construct a directed path with a large b-value within a row while keeping the discovered region small. Here we only allow our adversary strategy to select nodes within *one* row, so in the subsequent discussion, we measure the *length* of the current discovered region G_i by the distance between the two farthest nodes in G_i restricted to the row, where the distance is measured with respect to the row.

Lemma 3.6. Let k be a non-negative integer such that $5^{k+1} \cdot T(n) < \sqrt{n}$. There is an adversary strategy to construct a directed path with its b-value of at least k within a row while keeping the length of the discovered region at most $5^{k+1} \cdot T(n)$.

Proof. We prove the lemma by an induction on k.

Base case. For the case where k = 0, the adversary can just reveal any node v. We view node v as a directed path with a *b*-value of zero. The length of the discovered region is $2T(n) < 5^{k+1} \cdot T(n)$, as the algorithm has locality T(n).

Inductive step. Consider the case where $k \ge 1$. In the subsequent discussion, we write $P_{x,y}$ to denote the directed path starting from x and ending at y along the row. By the induction hypothesis, we construct two directed paths $P_{u,v}$ and $P_{s,t}$ with a b-value of at least k-1. The construction of both directed paths requires a discovered region of length at most $5^k \cdot T(n)$.

We now concatenate these two directed paths together into a directed path $P_{u,t}$ by concatenating the two discovered regions via a path of length $\ell \in \{2,3\}$ on the row. See Figure 5 for an illustration. After the concatenation, the length of the discovered region is at most $\ell + 2 \cdot 5^k \cdot T(n) \leq 5^{k+1} \cdot T(n)$. Here we use the fact that $T(n) \geq 1$, since 3-coloring cannot be solved with zero locality.

To finish the proof, we just need to select $\ell \in \{2, 3\}$ in such a way that we can find a directed path in the row using the nodes between u and t whose b-value is at least k. If the b-value of one of the paths $P_{u,v}$ and $P_{s,t}$ is already at least k, then we are done, so from now on we assume that their b-values are precisely k - 1.

By Lemma 3.5, the parity of the *b*-value of any directed path is *solely determined* by the parity of the path length and the color of the two endpoints. Therefore, we may select $\ell \in \{2, 3\}$ in such a way that the parity of the *b*-value of the path $P_{v,s}$ differs from k-1, i.e., $b(P_{v,s}) \not\equiv k-1 \pmod{2}$.

From now on, we write $h = b(P_{v,s})$, so we have $b(P_{u,t}) = 2(k-1) + h$. We claim that at least one of |2(k-1) + h| or |h| is greater than |k-1|. The claim holds true due to the inequality

$$|2(k-1) + h| + |h| = |2(k-1) + h| + |-h| \ge |2(k-1)| = 2 \cdot |k-1|$$

and the observation that the inequality becomes equality only when |h| = |k-1|, which is impossible because $h \neq k-1$. We conclude that the *b*-value of at least one of the directed paths $P_{v,s}$, $P_{s,v}$, $P_{u,t}$, and $P_{t,u}$ is at least k, as required.



Figure 5: Concatenating $P_{u,v}$ and $P_{s,t}$.

We are prepared to prove Theorem 1.

Theorem 1. In the Online-LOCAL model, the locality of 3-coloring a $(\sqrt{n} \times \sqrt{n})$ grid is $\Omega(\log n)$.

Proof. To prove the theorem, we just need to show that any algorithm \mathcal{A} with locality $T(n) \in o(\log n)$ for 3-coloring a $(\sqrt{n} \times \sqrt{n})$ grid is incorrect. As long as n is at least a sufficiently large constant, we may find an integer k to satisfy the two conditions: k > 4T(n) + 4 and $5^{k+1} \cdot T(n) < \sqrt{n}$.

In the subsequent discussion, if x and y are two nodes that belong to the same row or the same column, then we write $P_{x,y}$ to denote the directed path starting from x and ending at y along the row or the column.

In the $(\sqrt{n} \times \sqrt{n})$ grid, we apply the adversary strategy of Lemma 3.6 to force the algorithm \mathcal{A} to construct a directed path $P_{u,v}$ in a row R_1 starting from u and ending at v with $b(P_{u,v}) \ge k$. After that, we consider the row R_2 that is above the row R_1 by a distance of 2T(n) + 2. Let t be the node in R_2 that belongs to the same column as u. Let s be the node in R_2 that belongs to the same column as u. Let s be the node in R_2 that belongs to the same column as v. See Figure 6 for an illustration.

As the adversary, we ask the algorithm to color all the nodes in $P_{s,t}$. We may assume that $b(P_{s,t}) \ge 0$. In case $b(P_{s,t}) < 0$, we can simply reverse the direction of $P_{s,t}$. This is possible because the discovered region associated with $P_{s,t}$ is not connected to the discovered region associated with $P_{u,v}$ from the viewpoint of the algorithm, as the distance between R_1 and R_2 is at least 2T(n) + 2.

We let the algorithm finish the coloring of the remaining nodes arbitrarily. Now, consider the directed cycle C formed by concatenating the four directed paths $P_{u,v}$, $P_{v,s}$, $P_{s,t}$, and $P_{t,u}$. By its definition, the absolute value of the b-value of one path P is at most its length, so the b-value of both $P_{v,s}$ and $P_{t,u}$ is at least -(2T(n) + 2), so

$$b(C) = b(P_{u,v}) + b(P_{v,s}) + b(P_{s,t}) + b(P_{t,u}) \ge k - (2T(n) + 2) + 0 - (2T(n) + 2) > 0,$$

which is impossible due to Lemma 3.4, so the coloring produced by the algorithm is incorrect. \Box

We remark that if we consider a general $(a \times b)$ grid, then the above proof yields an $\Omega(\min\{\log \max\{a, b\}, \min\{a, b\}\})$ locality lower bound. To see this, without loss of generality, assume $b \ge a$, and observe that the proof above works so long as the locality T of the algorithm satisfies $T \in o(\log b)$ and $T \in o(a)$.



discovered region with length $< \sqrt{n}$

Figure 6: Construction of a directed cycle with non-zero *b*-value

3.3 Hardness of 3-Coloring in Toroidal and Cylindrical Grids

In this section, we prove Theorem 2.

Theorem 2. In the Online-LOCAL model, the locality of 3-coloring $(\sqrt{n} \times \sqrt{n})$ toroidal and cylindrical grids is $\Omega(\sqrt{n})$.

Proof. We start by discussing the properties of proper 3-coloring of toroidal and cylindrical grids. Consider any two directed cycles C_1 and C_2 corresponding to orienting two rows with *different directions*. Same as the proof of Lemma 3.4, we may calculate $b(C_1) + b(C_2)$ alternatively by summing up the *b*-value for the cells located between C_1 and C_2 , so we infer that

$$b(C_1) + b(C_2) = 0. (1)$$

Furthermore, if the number of columns is *odd*, then the lengths of the two directed cycles C_1 and C_2 are odd, so Lemma 3.5 implies that both $b(C_1)$ and $b(C_2)$ are odd numbers.

Consider an arbitrary algorithm \mathcal{A} designed for 3-coloring $(\sqrt{n} \times \sqrt{n})$ cylindrical or toroidal grids with locality $T(n) \in o(\sqrt{n})$. Let us choose a sufficiently large value of n such that \sqrt{n} is an odd number and $4T(n) + 4 \leq \sqrt{n}$. Therefore, we may select two rows such that their T(n)-radius neighborhoods induce *non-adjacent* cylindrical grids with 2T(n) + 1 rows and \sqrt{n} columns.

As the adversary, we instruct algorithm \mathcal{A} to color these two rows. From the perspective of the algorithm, it sees precisely two disjoint cylindrical grids with 2T(n) + 1 rows and \sqrt{n} columns. Furthermore, the algorithm is unaware of their positions and directions in the input graph. As the adversary, we have the liberty to choose their directions *after* the algorithm fixes the coloring of the two rows. Since the *b*-value of an odd-length directed cycle is odd, we can always select their directions to violate Equation (1). Hence the algorithm \mathcal{A} cannot correctly 3-color the graph. \Box

We remark that the $\Omega(\sqrt{n})$ locality lower bound in the proof above comes from the fact that the number of rows is \sqrt{n} . If we consider a general $(a \times b)$ toroidal or cylindrical grid, then the above proof yields an $\Omega(a)$ locality lower bound whenever the number of columns b is an odd number.

4 Hardness of (2k-2)-Coloring of k-Partite Graphs

In this section, we consider the problem of coloring a k-partite graph using 2k-2 colors and establish a lower bound of $\Omega(n)$ on the locality in the Online-LOCAL model, where $k \ge 2$ is a constant. Thus we prove Theorem 3. We introduce a specific type of gadget. Following that, we will proceed with constructing the hard instance graph using these gadgets to establish the lower bound.

Gadget definition. A gadget A(k) is represented as a graph with a set of nodes denoted by $[k] \times [k]$, where each node corresponds to an ordered pair (i, j). Two nodes, (i, j) and (i', j'), are connected by an edge if and only if $i \neq i'$ and $j \neq j'$. Furthermore, for any $i \in [k]$, the set of nodes $\{(i, j): j \in [k]\}$ defines the *i*-th row of the gadget A(k). Similarly, for $j \in [k]$, the set of nodes $\{(i, j): i \in [k]\}$ defines the *j*-th column of the gadget. Therefore, an edge exists between two nodes in a gadget if and only if they are neither in the same row nor the same column.

Construction of the hard instance graph G^* . G^* comprises of $n' = n/k^2$ gadgets denoted as $A_1, \ldots, A_{n'}$, where the node set of the ℓ -th gadget A_ℓ can be represented as $\{\ell\} \times [k] \times [k]$. Consequently, the node set of G^* is $[n'] \times [k] \times [k]$. The edge set of G^* is defined as follows.

Edges within the gadgets: For each $\ell \in [n']$, there is an edge between (ℓ, i, j) and (ℓ, i', j') if and only if $i \neq i'$ and $j \neq j'$.

Edges between consecutive gadgets: For each $\ell \in [n'-1]$, there is an edge between (ℓ, i, j) and $(\ell+1, i', j')$ if and only if $i \neq i'$ and $j \neq j'$.

Proposition 4.1. The graph G^* is k-partite.

Proof. We will demonstrate a proper coloring of G^* with a set of k colors $\{1, \ldots, k\}$. Recall the construction of G^* that consists of gadgets $A_1, \ldots, A_{n'}$. For any gadget, color all the nodes in the *i*-th row using color *i*, where $i \in [k]$. This coloring is proper due to the following reason: An edge between two nodes, either in the same gadget or in consecutive gadgets, can only exist if they are neither in the same row nor the same column.

We first sketch the high-level idea behind the lower bound proof. Given a proper coloring of a gadget, it is said to be row-colorful if it has a row where all nodes in the row are colored with distinct colors. Similarly, we can define a column-colorful gadget. We show (in Section 4.1) that, for a proper coloring of a gadget with 2k - 2 colors, the gadget is precisely one out of row-colorful and column-colorful. Furthermore, leveraging the above properties of the gadgets, we establish (in Section 4.2) a crucial property of the graph G^* with gadgets $A_1, \ldots, A_{n'}$: For any proper (2k - 2)coloring of G^* , all the gadgets are either row-colorful or all of them are column-colorful. To establish the lower bound, consider a scenario where the adversary asks the algorithm to first color the nodes in A_1 , followed by the nodes in $A_{n'}$, and then the remaining nodes. Regardless of how the algorithm, in the **Online-LOCAL** model with locality o(n), colors the nodes in A_1 and $A_{n'}$, we argue that the adversary can modify the input graph in a specific way. In particular, the modification results in an input graph that is isomorphic to G^* , consistent with the previously explored part of the graph, and crucially ensures that A_1 is row-colorful while $A_{n'}$ is column-colorful. However, this leads to a failure to color some nodes in the future, as either all the gadgets in the input graph are row-colorful or all of them are column-colorful.

Comparison with the lower bound proof in the LOCAL model. In $[CdG^+24]$, the authors showed that (2k-2)-coloring a k-partite graph requires $\Omega(n)$ rounds in the LOCAL model. Our hard instance G^* , designed to establish the lower bound in the Online-LOCAL model, is inspired by the hard instance in [CdG⁺24]. Specifically, their hard instance, denoted as $G^{\#}$, comprises G^{*} and two cliques with k nodes each, denoted as X and Y, as its subgraphs. Let the node sets in X and Y be $\{x_1, \ldots, x_k\}$ and $\{y_1, \ldots, y_k\}$, respectively. Furthermore, each x_i is connected to every node in the gadget A_1 that is not in the *i*-th row, and each y_i is connected to every node in the gadget $A_{n'}$ that is not in the *j*-th column. It is crucial to highlight that the chromatic number of $G^{\#}$ is 2k-1. However, the subgraph induced by the o(n) neighborhood of any node is k-partite. Note that $G^{\#}$ is a graph outside the input family. However, the instance is locally solvable, meaning the subgraph induced by the o(n)-radius neighborhood of any node can be colored with k colors. The lower bound in the LOCAL model can be established using an indistinguishability argument by Linial [Lin92], which proves lower bounds where the hard instance is taken from outside the input family. While the hard instance G^* in the Online-LOCAL model draws inspiration from the $G^{\#}$ hard instance developed for the LOCAL model, the application of Linial's technique, designed for LOCAL. is not straightforward in the Online-LOCAL model possibly due to the presence of global memory. Despite the inspiration from the LOCAL model, our arguments to establish the lower bound in the Online-LOCAL model are different and accommodate the unique features of the Online-LOCAL setting, including the utilization of global memory.

4.1 Properties of the Gadgets

In this section, we discuss some properties of gadgets, specifically establishing that a gadget is exactly one out of row-colorful and column-colorful in a proper coloring with 2k - 2 colors. We progress towards the proof by introducing the concept of "confining a color to some row/column" and discussing a related claim.

Definition 4.2 (Confinement of a color). Consider a proper coloring of a gadget. A color c is labeled as *confined* to a row (column) if there are at least two nodes within that row (column) colored with the same color c.

Claim 4.3. Consider a proper coloring of a gadget. The following statements hold.

- (i) A color can be confined to at most one row (column).
- (ii) Moreover, a color cannot be confined to both a row and a column.

Proof. To establish (i), let us assume that color c is confined to both the i_1 -th and i_2 -th rows. In this scenario, there exist four nodes (two in each row) colored with c, denoted as (i_1, j_1) , (i_1, j'_1) , (i_2, j_2) , and (i_2, j'_2) . Note that $i_1 \neq i_2$, $j_1 \neq j'_1$, and $j_2 \neq j'_2$. If there is an edge between (i_1, j_1) and (i_2, j_2) (i.e., $j_1 \neq j_2$), then both nodes cannot share the same color c. Alternatively, if $j_1 = j_2$ (implying $j_1 \neq j'_2$), there must be an edge between (i_1, j_1) and (i_2, j'_2) . Hence, coloring them with the same color is not feasible. This leads to a contradiction!

To establish (ii), let us assume that color c is confined to both the *i*-th row and *j*-th column. Let (i, j_1) and (i, j'_1) be nodes in the *i*-th row colored with color c. Additionally, there are two nodes in the *j*-th column colored with the same color. Note that, out of these two nodes in the *j*-th column, at least one must not be in the *i*-th row. Let this node be (i', j) with $i' \neq i$. If there is an edge between (i, j_1) and (i', j) (i.e., $j_1 \neq j$), both nodes cannot share the same color c. Alternatively, if $j_1 = j$ (implying $j'_1 \neq j$), there must be an edge between (i, j'_1) and (i', j). Hence, coloring them with the same color is not feasible. This leads to a contradiction!

Now, let us provide a formal definition of the concept of a gadget being row-colorful or columncolorful. Subsequently, in Claim 4.5, we will prove the desired property that each gadget is exactly one out of row-colorful and column-colorful.

Definition 4.4 (Row-colorful and column-colorful gadgets). Consider a proper coloring of a gadget. A row (column) of the gadget is *colorful* if all its k nodes have distinct colors. In other words, a row (column) is colorful if no color is confined to the row (column). A gadget is categorized as row-colorful (column-colorful) if it contains at least one colorful row (column).

Claim 4.5. Let us consider a proper coloring of gadget A with 2k - 2 colors. Then A is exactly one out of row-colorful and column-colorful.

Proof. We divide the proof into two parts as follows: (i) A is row-colorful or column-colorful, and (ii) A cannot simultaneously be row-colorful and column-colorful.

To establish (i), assume, by contradiction, that A is neither row-colorful nor column-colorful. This implies that for each row (column), a color is confined to that specific row (column). Applying Claim 4.3, we find 2k colors, each confined to some row or column. However, this scenario implies an impossibility as we have 2k - 2 colors.

For (ii), assume by contradiction that the *i*-th row of gadget A is colorful, and simultaneously, the *j*-th column of A is also colorful. Consider the set comprising (2k - 1) nodes, which are in the *i*-th row or the *j*-th column. Since we are using 2k - 2 colors to color gadget A, there must be two nodes from the set of (2k - 1) nodes colored with the same color. If these two nodes are in the *i*-th row, it implies that the *i*-th row is not colorful, leading to a contradiction. Similarly, these two nodes cannot be in the *j*-th column. The only possible scenario is that one of them is in the *i*-th row but not in the *j*-th column, and the other is in the *j*-th column but not in the *i*-th row. That is, these two nodes take the form (i, j_1) and (i_1, j) , satisfying $i \neq i_1$ and $j \neq j_1$. Due to the construction of gadget A, nodes (i, j_1) and (i_1, j) cannot be colored with the same color, as there is an edge between them.

4.2 Properties of G^* and the Lower Bound Proof

We first show that all gadgets in G^* are of the same category, either row-colorful or column-colorful. This, in turn, allows us to prove the desired lower bound on the locality of (2k - 2)-coloring for k-partite graphs in Theorem 3.

Lemma 4.6. Consider the graph G^* with gadgets $A_1, \ldots, A_{n'}$ and a proper coloring of G^* using 2k-2 colors. Then, either all the gadgets are row-colorful or all of them are column-colorful.

Proof. By Claim 4.5, each gadget A_i is exactly one out of row-colorful or column-colorful. Therefore, for any $\ell \in [n'-1]$, it is sufficient to demonstrate that either both A_ℓ and $A_{\ell+1}$ are row-colorful or both are column-colorful.

By contradiction, assume that A_{ℓ} is row-colorful and $A_{\ell+1}$ is column-colorful. Let $i \in [k]$ be such that the k nodes of the *i*-th row of A_{ℓ} are colored with distinct colors. Let C be the set of k colors used by the nodes in the *i*-th row of A_{ℓ} . By Claim 4.5, $A_{\ell+1}$ is not row-colorful. Thus, for each of the k rows of $A_{\ell+1}$, there exists a color confined to the row. Let c_j denote the color confined to the *j*-th row of $A_{\ell+1}$, where $j \in [k]$. In the following paragraph, we show that the colors confined to any of the k - 1 rows of $A_{\ell+1}$, excluding the *i*-th row of $A_{\ell+1}$, are distinct from the k colors utilized by the nodes in the *i*-th row of A_{ℓ} .

By contradiction, assume that c_j is in C for some $j \neq i$. Let (i, j_1) be the node in the *i*-th row of A_{ℓ} that is colored with color c_j . As c_j is confined to the *j*-th row of $A_{\ell+1}$, consider two nodes in it that are colored with color c_j . Let the two nodes be (j, j_2) and (j, j'_2) . Note that $j \neq i$ and $j_2 \neq j'_2$. If there is an edge between (i, j_1) and (j, j_2) (i.e., $j_1 \neq j_2$), both nodes cannot share the same color c_j . Alternatively, if $j_1 = j_2$ (implying $j_1 \neq j'_2$), there must be an edge between (i, j_1) and (j, j'_2) . Hence, coloring them with the same color is not feasible. This leads to a contradiction!

Recall that we are using 2k - 2 colors. Additionally, as previously argued, for each $j \neq i$, the color c_j is distinct from the k colors present in C. Therefore, there are at most k - 2 colors in the set $\{c_1, \ldots, c_k\} \setminus \{c_i\}$, implying the existence of two rows in $A_{\ell+1}$ where a specific color is confined to both of them. However, this is impossible due to Claim 4.3.

We are ready to prove the $\Omega(n)$ locality lower bound of (2k-2)-coloring for k-partite graphs.

Theorem 3. Let $k \ge 2$ be a constant. The locality of (2k-2)-coloring a k-partite graph is $\Omega(n)$ in the Online-LOCAL model.

Proof. Consider the graph G^* with gadgets $A_1, A_2, \ldots, A_{n'}$. As discussed in Proposition 4.1, G^* is k-partite. For our lower bound proof, we assume that the input graph provided to the algorithm is

isomorphic to G^* . Notably, the algorithm operates without any knowledge of the gadget information, as well as the row/column details of the nodes.

Assuming, by contradiction, the existence of an algorithm that properly colors the input graph with 2k-2 colors in the Online-LOCAL model with $T \in o(n) = o(n')$ locality. Note that $n \in \Theta(n')$ as k is a constant. Let the adversary ask the algorithm to color the nodes in gadget A_1 first, followed by the nodes in gadget $A_{n'}$, and then the remaining nodes. For each k, we select a sufficiently large n such that the T-radius neighborhood of nodes in gadget A_1 is non-adjacent to the T-radius neighborhood of nodes in gadget $A_{n'}$. Consequently, when the algorithm colors nodes in A_1 and $A_{n'}$, it lacks information about the other gadgets.

Without loss of generality, assume that when the algorithm colors the nodes in A_1 , A_1 is rowcolorful. Now, we discuss how the adversary transforms the input graph into one isomorphic to G^* , forcing gadget $A_{n'}$ to be column-colorful.

Upon coloring the nodes in $A_{n'}$, assume $A_{n'}$ is not column-colorful. By Claim 4.5, $A_{n'}$ is rowcolorful. Consider the set of gadgets in the *T*-radius neighborhood of the nodes in $A_{n'}$. The adversary alters the row/column information of all the nodes in these gadgets, making $A_{n'}$ column-colorful. Importantly, this modification does not affect the *T*-radius neighborhood of nodes in gadget A_1 . Additionally, the algorithm is oblivious to anything beyond the *T*-radius neighborhood of the nodes in A_1 or $A_{n'}$. Consequently, the remaining part of the graph (outside the *T*-radius neighborhood of the nodes in A_1 or $A_{n'}$) can be suitably modified to be isomorphic to G^* .

As the algorithm proceeds to color nodes outside the gadgets A_1 and $A_{n'}$, it fails to properly color certain nodes. This follows from the fact that either all the gadgets are row-colorful or all of them are column-colorful, as established in Lemma 4.6.

5 Coloring Graphs with Locally Inferable Unique Colorings

In this section, we prove Theorems 4 and 5: For $k \in O(1)$, the locality of (k + 1)-coloring k-partite graphs with locally inferable unique colorings in the Online-LOCAL model is $\Theta(\log n)$. The upper bound is shown in Section 5.1 and the lower bound is shown in Section 5.2.

5.1 Upper Bound

In this section, we present an Online-LOCAL algorithm with $O(\log n)$ locality for (k + 1)-coloring the graphs in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$.

5.1.1 Previous Approach

We first review the $O(\log n)$ -locality Online-LOCAL algorithm by Akbari et al. [AEL⁺23] that 3colors bipartite graphs. Consider the color set $\{1, 2, 3\}$. When a node u is revealed by the adversary, its T-radius neighborhood $\mathcal{B}(u, T)$ is seen by the algorithm, where $T \in O(\log n)$ is the locality of the Online-LOCAL algorithm. Following Akbari et al. [AEL⁺23], each connected component of the subgraph induced by the set of all nodes seen by the algorithm so far is called a group. How the algorithm of Akbari et al. [AEL⁺23] colors a newly revealed node u depends on the status of the nodes in $\mathcal{B}(u, T+1)$ right before u is revealed. The algorithm tries to 2-color the nodes using $\{1, 2\}$ in most cases and only uses color 3 in one exceptional case.

- 1. If all nodes in $\mathcal{B}(u, T+1)$ are unseen, then $\mathcal{B}(u, T)$ forms a new group and the algorithm colors u with 1. Observe that fixing the color of u determines a unique way to complete the coloring of $\mathcal{B}(u, T)$ using $\{1, 2\}$, so in this sense the parity of the group $\mathcal{B}(u, T)$ is fixed.
- 2. If some nodes in $\mathcal{B}(u, T+1)$ are seen and they are from the same group C, then $\mathcal{B}(u, T)$ is merged into C to form a larger group $C \cup \mathcal{B}(u, T)$. If u is still uncolored, then the algorithm assigns a color from $\{1, 2\}$ to u based on the parity of $\mathcal{B}(u, T)$, as this parity determines a unique way to complete the coloring of $C \cup \mathcal{B}(u, T)$ using $\{1, 2\}$.
- 3. If some nodes in $\mathcal{B}(u, T+1)$ are seen and they belong to multiple groups C_1, C_2, \ldots, C_t , then $\mathcal{B}(u, T)$ and these groups are merged into a group $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u, T)$. The algorithm first unifies the parities of these groups iteratively and then colors u according to the unified parity if u is still uncolored. The unification of the parities of two groups A and B is done as follows. If their parities are already consistent, then nothing needs to be done. If their parities are inconsistent, then the parity of one group, say A, is *flipped* by utilizing color 3 in three steps.
 - (a) For all uncolored neighbors of all nodes in A colored with 1, set their colors to be 2.
 - (b) For all uncolored neighbors of all nodes in A colored with 2, set their colors to be 3.
 - (c) For all uncolored neighbors of all nodes in A colored with 3, set their colors to be 1.

Intuitively, flipping the parity of a group is achieved by constructing a barrier using the third color, which requires a locality of 3. For the flipping operation to work correctly, all the nodes colored during the operation must be within the group under consideration. If we always flip the parity of the smaller-sized group when unifying the parities of two groups, then it is guaranteed that the total number of flips performed, from the perspective of a node, is at most $\log n$. Thus, setting the locality of the algorithm to be $T = 3 \log n$ is sufficient.

5.1.2 Our Algorithm

Let $k \ge 2$ be any constant. Consider any graph $G = (V, E) \in \mathcal{L}_{k,\ell}$ with $\ell \in O(1)$. To (k+1)-color G with locality $O(\log n)$ in Online-LOCAL, we follow the recipe of the bipartite case described above.

Oracle. The assumption that $G \in \mathcal{L}_{k,\ell}$ implies that G admits a *unique* k-coloring up to permutation. This can be seen by setting G' = G in Definition 1.4. Moreover, for any connected subset of nodes $C \subseteq V$ of G, ¹ this unique partition of V into k parts restricted to C can be inferred by the subgraph of G induced by $\mathcal{B}(C,\ell)$, as follows: Take any k-coloring of $G[\mathcal{B}(C,\ell)]$ and restrict the coloring to C. Definition 1.4 guarantees that the resulting partition of C is invariant of the choice of the k-coloring of $G[\mathcal{B}(C,\ell)]$, so the partition of C must be consistent with the unique k-coloring of G up to a permutation. Therefore, in the subsequent discussion, we may assume that our Online-LOCAL algorithm is equipped with an oracle \mathcal{O} such that for any connected subset of nodes $C \subseteq V$ seen by the algorithm, the oracle returns a partition $\mathcal{O}(C)$ of C into k parts consistent with the unique k-coloring of G up to a permutation. The oracle can be implemented with an extra locality of $\ell \in O(1)$.

¹A subset $C \subseteq V$ is said to be connected subset if the subgraph induced by C is connected.

Type. Recall that a group is a connected component of the subgraph induced by the set of nodes seen by the Online-LOCAL algorithm so far. While oracle \mathcal{O} allows each group C to locally infer the unique k-coloring of G restricted to C up to a permutation, different groups can still disagree on the assignment of the k colors [k] to the k parts of the k-partite graph G. Analogous to the parity for the bipartite case, we call each of the k! possible color assignments a *type*.

Algorithm. We are prepared to present our (k + 1)-coloring algorithm given the oracle \mathcal{O} . Set $T = 3(k - 1) \log n$ as the locality of our algorithm. Throughout the algorithm, each group C is associated with a type in such a way that the following induction hypothesis is maintained:

• For each colored node $v \in C$ that is adjacent to an uncolored node in G, the color of v is consistent with the type of C.

Consequently, the current partial coloring of C can be completed using the colors in [k] by adapting the color assignment given by the type for the remaining uncolored nodes in C.

Similar to the algorithm of Akbari et al. [AEL+23], how our algorithm colors a newly revealed node u depends on the status of the nodes in $\mathcal{B}(u, T+1)$ right before u is revealed. The algorithm tries to k-color the nodes using [k] in most cases and only uses color k + 1 in one exceptional case.

We illustrate our algorithm in Figures 7 to 10 by considering 4-coloring a triangular grid. The colors in the figures have the following meanings: Gray indicates "unseen," white indicates "seen," and the remaining colors indicate "seen and committed to a specific color."

1. If all nodes in $\mathcal{B}(u, T+1)$ are unseen, then $\mathcal{B}(u, T)$ forms a new group and the algorithm colors u with 1. We query the oracle to obtain the partition $\mathcal{O}(\mathcal{B}(u, T))$ and assign a type to the group $\mathcal{B}(u, T)$ such that the type is consistent with the color of u. See Figure 7 for an illustration.



Figure 7: In Case 1, node u in $\mathcal{B}(u,T)$ (the white part) receives color 1.

- 2. If some nodes in $\mathcal{B}(u, T+1)$ are seen and they are from the same group C, then $\mathcal{B}(u, T)$ is merged into C to form a larger group $C \cup \mathcal{B}(u, T)$. The type of $C \cup \mathcal{B}(u, T)$ is set to be the type of C. If u is still uncolored, then we query the oracle to obtain the partition $\mathcal{O}(C \cup \mathcal{B}(u, T))$ and assign a color from [k] to u based on the type of C. See Figure 8 for an illustration.
- 3. If some nodes in $\mathcal{B}(u, T+1)$ are seen and they belong to multiple groups C_1, C_2, \ldots, C_t , then $\mathcal{B}(u, T)$ and these groups are merged into a group $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u, T)$. We query the oracle to obtain the partition $\mathcal{O}(C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u, T))$, unify the types of these groups,



Figure 8: In Case 2, node u in $\mathcal{B}(u,T)$ (the orange part) is colored based on the type of group C.

and assign a color from [k] to u based on the unified type if u is still uncolored. The type of the new group $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u,T)$ is set to be the unified type.

The unification of the types of groups C_1, C_2, \ldots, C_t is done as follows. We reorder the groups so that $|C_1| \ge |C_2| \ge \cdots \ge |C_t|$, and then we *change* the type of each group $X \in \{C_2, \ldots, C_t\}$ to match the type of C_1 . In the subsequent discussion, let

$$\mathcal{O}(C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u, T)) = V_1 \cup V_2 \cup \cdots \cup V_k.$$

Therefore, from now on, we may write the type of a group $X \in \{C_2, \ldots, C_t\}$ as a permutation $\pi : [k] \to [k]$ of the set [k], where $\pi(i) = j$ specifies that the type assigns color j to part V_i .

Given any two distinct colors $i \in [k]$ and $j \in [k]$, Algorithm 1 allows us to swap two colors i and j in the type of X. This is done by fixing a certain coloring of the 3-radius neighborhood of the colored subset of X using colors from [k + 1]. See Figure 10 for an illustration of Algorithm 1.

Any permutation of [k] can be transformed into any other permutation of [k] by at most k-1 swaps, so we can change the type of X to match the type of C_1 by executing Algorithm 1 for at most k-1 times. See Figure 9 for an illustration: In this example, the type of one group is changed by swapping yellow and purple by Algorithm 1, where three layers of colored nodes are created to perform the swap: yellow \rightarrow orange, purple \rightarrow yellow, and orange \rightarrow purple.



Figure 9: In Case 3, node u in $\mathcal{B}(u,T)$ (the orange part) is colored based on the type of group $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u,T)$ after unifying the types of C_1, C_2, \ldots, C_t .

Locality of the algorithm. Similar to the bipartite case, for our (k + 1)-coloring algorithm to work correctly, all the nodes colored during each execution of Algorithm 1 must be within the group

under consideration so that all the nodes colored by our algorithm are within the seen region. We show that our choice of $T = 3(k-1)\log n$ as the locality of our algorithm is sufficient. From the algorithm description, whenever the type of a group $X \in \{C_2, \ldots, C_t\}$ is changed, X is merged into a group $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u, T)$ whose size is at least $|C_1| + |X| \ge 2|X|$, as $|C_1| \ge |C_2| \ge \cdots \ge |C_t|$. Therefore, from the perspective of a node, the total number of type changes is at most $\log n$, as the size of a group cannot exceed n. When the type of a group X is changed, Algorithm 1 is executed for at most k - 1 times, which induces at most 3(k - 1) layers of colored nodes. This means that choosing $T = 3(k-1)\log n \in O(\log n)$ ensures that all nodes colored by Algorithm 1 are within the group under consideration.

The overall locality for implementing our algorithm in the Online-LOCAL model is $T + \ell \in O(\log n)$, where $\ell \in O(1)$ is the cost of implementing the oracle \mathcal{O} . For the rest of the section, we prove Theorem 4 by showing that our algorithm outputs a proper coloring.

Algorithm 1: Swapping colors for a group			
Input: A group X, a permutation $\pi : [k] \to [k]$ representing the type of X, and two			
distinct colors $i_1, i_2 \in [k]$.			
Result: The two colors i_1 and i_2 are swapped in π .			
1 $X' \leftarrow$ The nodes of X committed to a color;			
2 change_index $(i_1, k+1);$			
3 change_index $(i_2, i_1);$			
4 change_index $(k+1,i_2);$			
5 Function change index (i, j)			
Input: A color $i \in [k+1]$ used in π and a color $j \in [k+1]$ not used in π .			
Result: Color <i>i</i> is replaced by color <i>j</i> in π .			
6 foreach $s \in [k]$ do			
7 if $\pi(s) = i$ then			
8 Commit each node of $(\mathcal{B}(X',1) \cap V_s) \setminus X'$ to color j ;			
9 $\pi(s) \leftarrow j;$			
10 else			
11 Commit each node of $(\mathcal{B}(X',1) \cap V_s) \setminus X'$ to color $\pi(s)$;			
12 end			
13 end			
14 $X' \leftarrow \mathcal{B}(X', 1);$			

Theorem 4. Let $k \ge 2$ be any constant. There is an Online-LOCAL algorithm with locality $O(\log n)$ that (k + 1)-colors any graph in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$.

Proof. Since we already know that our algorithm takes $O(\log n)$ locality in the Online-LOCAL model, we just need to verify that our algorithm outputs a (k + 1)-coloring correctly. To do so, we show that the following induction hypothesis is maintained throughout the algorithm for each group C.

• For each colored node $v \in C$ that is adjacent to an uncolored node in G, the color of v is consistent with the type of C.

Consequently, at any time step, the current partial coloring of C can be completed using the colors in [k] by adapting the color assignment given by the type for the remaining uncolored nodes in



Figure 10: Swapping colors 1 and 2.

C. Based on this, we verify that all the color assignments made by the algorithm do not induce a monochromatic edge. We check the three cases in the algorithm description.

- In Case 1, $\mathcal{B}(u,T)$ forms a new group, whose type is chosen to be consistent with the color 1 assigned to node u, so the induction hypothesis is maintained. Since u does not have any colored neighbor, the color assignment cannot induce a monochromatic edge.
- In Case 2, $\mathcal{B}(u,T)$ is merged into an existing group C to form a larger group $C \cup \mathcal{B}(u,T)$ that inherits the type of C. Since the color assigned u is chosen according to the type of $C \cup \mathcal{B}(u,T)$, the induction hypothesis is maintained and the color assignment does not induce a monochromatic edge.
- In Case 3, $\mathcal{B}(u,T)$ and the groups C_1, C_2, \ldots, C_t are merged into a new group $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u,T)$. Before the merge, we first change the type of each group $X \in \{C_2, \ldots, C_t\}$ to match the type of C_1 by iteratively running Algorithm 1, so the new group can inherit the type of C_1 . Similar to Case 2, since the color assigned u is chosen according to the type of

 $C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u, T)$, the induction hypothesis is maintained and the color assignment does not induce a monochromatic edge. Thus, we only need to check that Algorithm 1 works correctly. Following the algorithm description, consider

$$\mathcal{O}(C_1 \cup C_2 \cup \cdots \cup C_t \cup \mathcal{B}(u,T)) = V_1 \cup V_2 \cup \cdots \cup V_k,$$

so the type of $X \in \{C_2, \ldots, C_t\}$ can be written as a permutation π of the set [k], where $\pi(i) = j$ specifies that the type assigns color j to part V_i . Given any two distinct colors $i_1 \in [k]$ and $i_2 \in [k]$, Algorithm 1 swaps the two colors in the color assignment π in three steps: change_index $(i_1, k + 1)$, change_index (i_2, i_1) , and change_index $(k + 1, i_2)$. To prove the correctness of Algorithm 1, we just need to verify that change_index(i, j) correctly replaces color i with color j in π in the following sense.

- 1. The induction hypothesis is maintained: At the end of change_index(i, j), for each colored node $v \in X$ that is adjacent to an uncolored node in G, the color of v is consistent with the color assignment π' that is the result of replacing i with j in π .
- 2. Algorithm 1 does not induce monochromatic edges.

Let X' be the set of nodes in X that have been colored at the beginning of change_index(i, j). For each $s \in [k]$, each node v in $(\mathcal{B}(X', 1) \cap V_s) \setminus X'$ is colored with j if $\pi(s) = i$ and $\pi(s)$ otherwise. Since the color assignment is consistent with π' , Item 1 holds. For the case of $\pi(s) \neq i$, by the induction hypothesis, coloring v with $\pi(s)$ does not induce a monochromatic edge. For the case of $\pi(s) = i$, coloring v with j also does not induce a monochromatic edge because color j is not used in π , so the induction hypothesis guarantees that v does not have a neighbor that is colored with j. Therefore, Item 2 holds.

5.2 Lower Bound

In this section, we prove that (k + 1)-coloring of the graphs in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$ requires locality $\Omega(\log n)$ in the Online-LOCAL model, thereby proving Theorem 5. Recall that $\mathcal{L}_{k,\ell}$ is the class of k-partite graphs that admit locally inferable unique colorings with radius ℓ (Definition 1.4). For k = 2, the claim follows from Theorem 1, as $(\sqrt{n} \times \sqrt{n})$ grid belongs to $\mathcal{L}_{2,0}$.

Construction of hard instance graphs $\{G_k\}$. Given a parameter n such that \sqrt{n} is an integer, we construct a sequence of graphs G_2, G_3, \ldots such that $G_k \in \mathcal{L}_{k,\ell}$ and (k+1)-coloring of the graphs in $\mathcal{L}_{k,\ell}$ requires locality $\Omega(\log n)$ in the Online-LOCAL model.

Base case: For k = 2, let G_2 be the $(\sqrt{n} \times \sqrt{n})$ simple grid. Define $H_2 = V(G_2)$.

Inductive step: For $k \ge 2$, G_{k+1} is constructed from G_k as follows: For each node u in G_k , create a new node u^* that is adjacent to u and all the neighbors of u in G_k . In the subsequent discussion, we call u^* the *duplicate* of u in G_{k+1} . Define H_{k+1} as the set of the new nodes created in the construction of G_{k+1} from G_k . In other words, H_{k+1} is the set of all nodes in G_{k+1} that do not belong to G_k .

Observe that the nodes of G_{k+1} are partitioned into k layers: $V(G_{k+1}) = H_2 \cup \cdots \cup H_{k+1}$. We say that a node v is in layer i if $v \in H_i$. We make the following additional observations.

Observation 5.1. For any $k \ge 2$, the number of nodes in G_k is $n_k = 2^{k-2}n$.

Proof. The number of nodes in G_2 is n. From the construction, the number of nodes in G_{k+1} is exactly twice that of G_k .

Observation 5.2. G_k is a k-partite graph.

Proof. A proper k-coloring of G_k can be obtained as follows. We can properly 2-color H_2 using colors 1 and 2, as H_2 induces a grid. For each layer number $i \in \{3, \ldots, k\}$, we color all nodes in H_i with color i. The coloring is proper because H_i is an independent set for each $i \in \{3, \ldots, k\}$. \Box

5.2.1 Locally Inferable Unique Coloring

We first show that G_k admits a locally inferable unique coloring. Consider any node $v \in H_i$ in layer i of G_k , where $i \in \{3, \ldots, k\}$. Since $i \geq 3$, there exists a node $u \in H_2 \cup \cdots \cup H_{i-1}$ such that $v = u^*$ is the duplicate of u in the construction of G_i . We write $\pi(v) = u$ to denote such a node u. By iteratively applying the function π to v, we eventually obtain a node w in H_2 . We write $\pi_{\diamond}(v) = w$ to denote such a node w. Intuitively, $\pi(v)$ is the immediate ancestor of v, and $\pi_{\diamond}(v)$ is the ancestor of v in the base layer H_2 . For each node $v \in H_2$, we define $\pi_{\diamond}(v) = v$.

Claim 5.3. For each $v \in V(G_k)$, there exists a k-clique that contains both v and $\pi_{\diamond}(v)$.

Proof. We prove the claim by an induction on k. For the base case of k = 2, any edge incident to $v = \pi_{\diamond}(v)$ is a desired k-clique. For the inductive step, suppose the claim is true for k - 1. Consider any $v \in V(G_k)$. There are two cases.

- Suppose $v \in H_k$. By the induction hypothesis, $\pi(v)$ and $\pi_{\diamond}(v)$ are contained in a (k-1)-clique K of G_{k-1} . Since v is adjacent to all neighbors of $\pi(v)$ in G_k , $K \cup \{v\}$ is a desired k-clique.
- Suppose $v \in H_i$ for some $i \in \{2, \ldots, k-1\}$. By the induction hypothesis, v and $\pi_{\diamond}(v)$ are contained in a (k-1)-clique K of G_{k-1} . Observe that the duplicate v^* of v in H_k is adjacent to every node of K. Thus, $K \cup \{v^*\}$ is a desired k-clique.

Claim 5.4. For each edge $\{u, v\}$ in G_k , the two nodes $\pi_{\diamond}(u)$ and $\pi_{\diamond}(v)$ are adjacent.

Proof. Let $u \in H_{\ell}$ and $v \in H_{\ell'}$. We prove the claim by induction on $\ell + \ell'$. For the base case, when $\ell = \ell' = 2$, $u = \pi_{\diamond}(u)$ is adjacent to $v = \pi_{\diamond}(v)$. Now, consider the inductive step. Since H_3, H_4, \ldots are all independent sets, we must have $\ell \neq \ell'$ unless $\ell = \ell' = 2$. Therefore, without loss of generality, we may assume $\ell < \ell'$. Observe that $\pi(v)$ must be adjacent to u because v is adjacent to u and v is the duplicate of $\pi(v)$. By the induction hypothesis applied to u and $\pi(v)$, we infer that $\pi_{\diamond}(u)$ and $\pi_{\diamond}(\pi(v)) = \pi_{\diamond}(v)$ are adjacent.

Let $t \geq 2$. Given two t-cliques K and K', we write $K \leftrightarrow K'$ if they share at least t-1 nodes. We write $K \stackrel{*}{\leftrightarrow} K'$ if there exists a sequence of t-cliques $(K = K_1, \ldots, K_s = K')$ such that $K_1 \leftrightarrow K_2 \leftrightarrow \cdots \leftrightarrow K_{s-1} \leftrightarrow K_s$.

Claim 5.5. Let $\{u, v\}$ be any edge in G_k such that $u \in H_2$ and $v \in H_2$. For any two k-cliques K and K' such that $u \in K$ and $v \in K'$, $K \stackrel{*}{\leftrightarrow} K'$ in the subgraph of G_k induced by $\mathcal{B}(\{u, v\}, k-1)$.

Proof. We prove the claim by induction on k. For the base case of k = 2, the claim holds because $K \leftrightarrow \{u, v\} \leftrightarrow K'$ in the 1-radius neighborhood of $\{u, v\}$. For the inductive step, suppose the claim holds for k - 1. Observe that any k-clique of G_k contains exactly two nodes from H_2 and exactly one node from H_i for each $i \in \{3, \ldots, k\}$, since H_2 is triangle-free and H_i is an independent set for each $i \in \{3, \ldots, k\}$. Therefore, $K_{\bullet} = K \setminus H_k$ and $K'_{\bullet} = K' \setminus H_k$ are two (k - 1)-cliques in G_{k-1} .

If $K_{\bullet} = K'_{\bullet}$, then we already have $K \leftrightarrow K'$, so from now on we assume $K_{\bullet} \neq K'_{\bullet}$. By the induction hypothesis, there exists a sequence of distinct (k-1)-cliques $(K_{\bullet} = K_1, K_2, \ldots, K_t = K'_{\bullet})$ in the subgraph of G_{k-1} induced by $\mathcal{B}(\{u, v\}, k-2)$ such that $K_1 \leftrightarrow K_2 \leftrightarrow \cdots \leftrightarrow K_{t-1} \leftrightarrow K_t$.

Now, we focus on the two (k-1)-cliques K_i and K_{i+1} for any $i \in [t-1]$.

- Consider the (k-2)-clique $\kappa = K_i \cap K_{i+1}$.
- Let u_1 be the unique node in $K_i \setminus \kappa$.
- Let $v_1 \in H_k$ be the duplicate of u_1 in the construction of G_k from G_{k-1} (i.e., $\pi(v_1) = u_1$).
- Let u_2 be the unique node in $K_{i+1} \setminus \kappa$.
- Let $v_2 \in H_k$ be the duplicate of u_2 in the construction of G_k from G_{k-1} (i.e., $\pi(v_2) = u_2$).
- Select $w \in H_k$ to be the duplicate of any node in κ .

Observe that v_1 is adjacent to u_1 and all nodes in κ , v_2 is adjacent to u_2 and all nodes in κ , and w is adjacent to u_1 , u_2 , and all nodes in κ . Now, consider the following four k-cliques (see Figure 11):

$$Q_{i,1} = Q_a = \kappa \cup \{v_1, u_1\}, \qquad Q_b = \kappa \cup \{u_1, w\}, Q_c = \kappa \cup \{w, u_2\}, \qquad Q_{i,2} = Q_d = \kappa \cup \{u_2, v_2\}.$$

We have

$$Q_{i,1} = Q_a \leftrightarrow Q_b \leftrightarrow Q_c \leftrightarrow Q_d = Q_{i,2},$$

and these k-cliques have the following properties.

- $Q_{i,1}$ is the union of K_i and the duplicate of a node in K_i .
- $Q_{i,2}$ is the union of K_{i+1} and the duplicate of a node in K_{i+1} .
- All the nodes in Q_a , Q_b , Q_c , and Q_d are confined to $\mathcal{B}(\{u, v\}, k-1)$.

By concatenating K, the sequence of k-cliques $Q_{i,1} = Q_a \leftrightarrow Q_b \leftrightarrow Q_c \leftrightarrow Q_d = Q_{i,2}$ from i = 1 to i = t - 1, and K' into a sequence, we obtain that

$$K \leftrightarrow Q_{1,1} \stackrel{*}{\leftrightarrow} Q_{1,2} \leftrightarrow Q_{2,1} \stackrel{*}{\leftrightarrow} Q_{2,2} \leftrightarrow \cdots \leftrightarrow Q_{t-1,1} \stackrel{*}{\leftrightarrow} Q_{t-1,2} \leftrightarrow K',$$

and all of the k-cliques in the sequence are confined to $\mathcal{B}(\{u, v\}, k-1)$.

We are ready to show that G_k admits a locally inferable unique coloring.

Lemma 5.6. For any constant $k \geq 2$, $G_k \in \mathcal{L}_{k,\ell}$ with $\ell \in O(1)$.



Figure 11: The k-cliques Q_a , Q_b , Q_c , and Q_d .

Proof. Set $\ell = k \in O(1)$. Given a connected subgraph G' = (V', E') of G_k , we show that all k-colorings of the ℓ -radius neighborhood of V' in G_k restricting to V' yield the same k-coloring of V' up to permutation. Consider any proper k-coloring of the ℓ -radius neighborhood of V' in G_k , and let u and v be two arbitrary nodes in G'. We will find a k-clique K with $u \in K$ such that the color of v is uniquely determined given the coloring of K.

Since G' is connected, there exists a u-v path $(u = w_1, w_2, \ldots, w_t = v)$ in G'. By Claim 5.3, there exists a k-clique K_i in G_k such that $\{w_i, \pi_{\diamond}(w_i)\} \subseteq K_i$ for each $i \in [t]$. By Claim 5.4, $\pi_{\diamond}(w_i)$ and $\pi_{\diamond}(w_{i+1})$ are adjacent in G_k for each $i \in [t-1]$. By Claim 5.5, we have

$$K_1 \stackrel{*}{\leftrightarrow} K_2 \stackrel{*}{\leftrightarrow} \cdots \stackrel{*}{\leftrightarrow} K_{t-1} \stackrel{*}{\leftrightarrow} K_t$$

in the subgraph of G_k induced by the (k-1)-radius neighborhood of $\{\pi_{\diamond}(w_1), \pi_{\diamond}(w_2), \ldots, \pi_{\diamond}(w_t)\}$, which is within the k-radius neighborhood of the u-v path $(u = w_1, w_2, \ldots, w_t = v)$.

For any two k-cliques Q and Q' such that $Q \leftrightarrow Q'$, fixing the k-coloring of Q uniquely determines the k-coloring of Q'. Thus, fixing the coloring of the first clique K_1 , which contains u, uniquely determines the coloring of the last clique K_t , which contains v.

5.2.2 Locality Lower Bound

Next, we establish a lower bound on the locality of (k + 1)-coloring G_k .

Lemma 5.7. Let $k \ge 2$. In the Online-LOCAL model, the locality of (k + 1)-coloring G_k is $\Omega\left(\log \frac{n_k}{2k-2}\right)$, where n_k is the number of nodes in G_k .

Proof. We prove the lemma by an induction on k. For the base case of k = 2, G_2 is the $(\sqrt{n} \times \sqrt{n})$ simple grid, so the lower bound $\Omega\left(\log \frac{n_k}{2^{k-2}}\right) = \Omega(\log n)$ immediately follows from Theorem 1.

For the inductive step, suppose the lower bound $\Omega\left(\log \frac{n_k}{2^{k-2}}\right)$ has been established for G_k . To prove the lemma by contradiction, suppose there exists an algorithm \mathcal{A} that can properly color G_{k+1} using colors in [k+2] and with locality $T \in o\left(\log \frac{n_{k+1}}{2^{k-1}}\right)$.

Using \mathcal{A} as a black box, we demonstrate an algorithm \mathcal{A}' to properly color the nodes in G_k with colors in [k + 1], as follows. When a node u in G_k is revealed by the adversary, we first ask the

algorithm \mathcal{A} to color the same node u in G_{k+1} . Let $c \in [k+2]$ be the color chosen for u in G_{k+1} . If $c \in [k+1]$, then we color node u in G_k with c. If c = k+2, then we ask the algorithm \mathcal{A} to color its duplicate u^* in G_{k+1} and color node u in G_k with the same color c' used by u^* . Observe that $c' \in [k+1]$, as u in G_{k+1} has already been colored c = k+2 by \mathcal{A} . Therefore, \mathcal{A}' only uses colors from [k+1].

We show that \mathcal{A}' is correct. Suppose \mathcal{A}' produces a monochromatic edge $\{u, v\}$ in G_k . Let c be the color used by both u and v. By the algorithm description, we know that the colors of u and v in G_{k+1} given by \mathcal{A} must come from $\{c, k+2\}$. By the correctness of \mathcal{A} , $\{u, v\}$ cannot be monochromatic in the coloring of G_{k+1} by \mathcal{A} . Therefore, without loss of generality, we may assume that u is colored c and v is colored k+2 in G_{k+1} by \mathcal{A} . By the algorithm description, the duplicate v^* of v must be colored c in G_{k+1} by \mathcal{A} , so $\{u, v^*\}$ is a monochromatic edge, contradicting the correctness of \mathcal{A} . Therefore, \mathcal{A}' outputs a proper (k+1)-coloring of G_k .

The locality of algorithm \mathcal{A}' is the same as that of algorithm \mathcal{A} , which is $T \in o\left(\log \frac{n_{k+1}}{2^{k-1}}\right) = o\left(\log \frac{n_k}{2^{k-2}}\right)$, due to Observation 5.1, contradicting the induction hypothesis, so we have the desired locality lower bound $\Omega\left(\log \frac{n_{k+1}}{2^{k-1}}\right)$ for G_{k+1} .

We are ready to prove Theorem 5.

Theorem 5. Let $k \ge 2$ be any constant. For any Online-LOCAL algorithm that (k + 1)-colors any graph in $\mathcal{L}_{k,\ell}$ with $\ell \in O(1)$, its locality must be $\Omega(\log n)$.

Proof. By Lemma 5.6, $G_k \in \mathcal{L}_{k,\ell}$ with $\ell \in O(1)$. Hence the theorem follows from Lemma 5.7 along with the assumption that k is a constant.

References

- [ABC⁺18] Marcos K Aguilera, Naama Ben-David, Irina Calciu, Rachid Guerraoui, Erez Petrank, and Sam Toueg. Passing messages while sharing memory. In *Proceedings of the 2018 ACM symposium on principles of distributed computing (PODC)*, pages 51–60, 2018.
- [ACd⁺24] Amirreza Akbari, Xavier Coiteux-Roy, Francesco d'Amore, François Le Gall, Henrik Lievonen, Darya Melnyk, Augusto Modanese, Shreyas Pai, Marc-Olivier Renou, Václav Rozhoň, and Jukka Suomela. Online locality meets distributed quantum computing. arXiv preprint arXiv:2403.01903, 2024.
- [AEL⁺23] Amirreza Akbari, Navid Eslami, Henrik Lievonen, Darya Melnyk, Joona Särkijärvi, and Jukka Suomela. Locality in Online, Dynamic, Sequential, and Distributed Graph Algorithms. In Kousha Etessami, Uriel Feige, and Gabriele Puppis, editors, 50th International Colloquium on Automata, Languages, and Programming (ICALP 2023), volume 261 of Leibniz International Proceedings in Informatics (LIPIcs), 10:1–10:20, Dagstuhl, Germany. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2023. ISBN: 978-3-95977-278-5. DOI: 10.4230/LIPIcs.ICALP.2023.10.
- [AGP24] Yehuda Afek, Gal Giladi, and Boaz Patt-Shamir. Distributed computing with the cloud. Distributed Computing, 37:1–18, 2024.

- [AOS⁺18] Sepehr Assadi, Krzysztof Onak, Baruch Schieber, and Shay Solomon. Fully dynamic maximal independent set with sublinear update time. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, STOC 2018, pages 815–826, Los Angeles, CA, USA. Association for Computing Machinery, 2018. ISBN: 9781450355599. DOI: 10.1145/3188745.3188922. URL: https://doi.org/10.1145/3188745.3188922.
- [BCH⁺18] Sayan Bhattacharya, Deeparnab Chakrabarty, Monika Henzinger, and Danupon Nanongkai. Dynamic algorithms for graph coloring. In Proceedings of the Twenty-Ninth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '18, pages 1– 20, New Orleans, Louisiana. Society for Industrial and Applied Mathematics, 2018. ISBN: 9781611975031.
- [BHK⁺17] Sebastian Brandt, Juho Hirvonen, Janne H. Korhonen, Tuomo Lempiäinen, Patric R.J. Östergård, Christopher Purcell, Joel Rybicki, Jukka Suomela, and Przemysław Uznański. Lcl problems on grids. In *Proceedings of the ACM Symposium on Principles* of Distributed Computing, PODC '17, pages 101–110, Washington, DC, USA. Association for Computing Machinery, 2017. ISBN: 9781450349925. DOI: 10.1145/3087801. 3087833. URL: https://doi.org/10.1145/3087801.3087833.
- [BM19] Leonid Barenboim and Tzalik Maimon. Fully dynamic graph algorithms inspired by distributed computing: deterministic maximal matching and edge coloring in sublinear update-time. Journal of Experimental Algorithmics (JEA), 24:1–24, 2019.
- [CdG⁺24] Xavier Coiteux-Roy, Francesco d'Amore, Rishikesh Gajjala, Fabian Kuhn, François Le Gall, Henrik Lievonen, Augusto Modanese, Marc-Olivier Renou, Gustav Schmid, and Jukka Suomela. No distributed quantum advantage for approximate graph coloring. In Proceedings of the 56th Annual ACM SIGACT Symposium on Theory of Computing (STOC), 2024.
- [CKP19] Yi-Jun Chang, Tsvi Kopelowitz, and Seth Pettie. An exponential separation between randomized and deterministic complexity in the local model. SIAM Journal on Computing, 48(1):122–143, 2019.
- [CP19] Yi-Jun Chang and Seth Pettie. A time hierarchy theorem for the local model. *SIAM Journal on Computing*, 48(1):33–69, 2019.
- [DKK13] Stefan Dobrev, Rastislav Královič, and Richard Královič. Independent set with advice: the impact of graph knowledge. In Thomas Erlebach and Giuseppe Persiano, editors, *Approximation and Online Algorithms*, pages 2–15, Berlin, Heidelberg. Springer Berlin Heidelberg, 2013. ISBN: 978-3-642-38016-7.
- [GK18] Manoj Gupta and Shahbaz Khan. Simple dynamic algorithms for maximal independent set and other problems. *arXiv preprint arXiv:1804.01823*, 2018.
- [GKM17] Mohsen Ghaffari, Fabian Kuhn, and Yannic Maus. On the complexity of local distributed graph problems. In *Proceedings of the 49th Annual ACM SIGACT Sympo*sium on Theory of Computing, STOC 2017, pages 784–797, Montreal, Canada. Association for Computing Machinery, 2017. ISBN: 9781450345286. DOI: 10.1145/3055399. 3055471. URL: https://doi.org/10.1145/3055399.3055471.
- [IL93] Zoran Ivković and Errol L Lloyd. Fully dynamic maintenance of vertex cover. In International Workshop on Graph-Theoretic Concepts in Computer Science (WG), pages 99– 111. Springer, 1993.

- [Lin92] Nathan Linial. Locality in distributed graph algorithms. SIAM Journal on computing, 21(1):193–201, 1992.
- [NS15] Ofer Neiman and Shay Solomon. Simple deterministic algorithms for fully dynamic maximal matching. ACM Transactions on Algorithms (TALG), 12(1):1–15, 2015.
- [Pel00] David Peleg. Distributed computing: a locality-sensitive approach. SIAM, 2000.
- [RG20] Václav Rozhoň and Mohsen Ghaffari. Polylogarithmic-time deterministic network decomposition and distributed derandomization. In Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing (STOC), pages 350–363, 2020.