Modeling Linear and Non-linear Layers: An MILP Approach Towards Finding Differential and Impossible Differential Propagations

Debranjan Pal, Vishal Pankaj Chandratreya, Abhijit Das, and Dipanwita Roy Chowdhury

Crypto Research Lab, Indian Institute of Technology Kharagpur, India debranjanpal@iitkgp.ac.in, vpaijc@kgpian.iitkgp.ac.in {abhij,drc}@cse.iitkgp.ac.in

Abstract. Symmetric key cryptography stands as a fundamental cornerstone in ensuring security within contemporary electronic communication frameworks. The cryptanalysis of classical symmetric key ciphers involves traditional methods and techniques aimed at breaking or analyzing these cryptographic systems. In the evaluation of new ciphers, the resistance against linear and differential cryptanalysis is commonly a key design criterion. The wide trail design technique for block ciphers facilitates the demonstration of security against linear and differential cryptanalysis. Assessing the scheme's security against differential attacks often involves determining the minimum number of active SBoxes for all rounds of a cipher. The propagation characteristics of a cryptographic component, such as an SBox, can be expressed using Boolean functions. Mixed Integer Linear Programming (MILP) proves to be a valuable technique for solving Boolean functions. We formulate a set of inequalities to model a Boolean function, which is subsequently solved by an MILP solver. To efficiently model a Boolean function and select a minimal set of inequalities, two key challenges must be addressed. We propose algorithms to address the second challenge, aiming to find more optimized linear and non-linear components. Our approaches are applied to modeling SBoxes (up to six bits) and EXOR operations with any number of inputs. Additionally, we introduce an MILP-based automatic tool for exploring differential and impossible differential propagations within a cipher. The tool is successfully applied to five lightweight block ciphers: Lilliput, GIFT64, SKINNY64, Klein, and MIBS.

Keywords: Symmetric key · Block cipher · SBox · MILP · Differential cryptanalysis · Impossible differential cryptanalysis.

1 Introduction

Differential cryptanalysis [10] and linear cryptanalysis [28] stand out as the primary techniques in the world of symmetric-key cryptography analysis. Differential cryptanalysis unveils the transformation of input differences in plaintext into

output differences in ciphertext for block ciphers. In contrast, linear cryptanalysis expresses the probabilistic linear relationships among plaintext, ciphertext, and key. When scrutinizing a cipher's robustness, especially in the context of key-recovery attacks or distinguishers, the deviation of an ideal cipher from a random one becomes a pivotal feature for differential and linear cryptanalysis.

In the realm of new ciphers, it's common practice to prioritize resistance against linear and differential cryptanalysis during the cipher analysis process. The wide trail design technique [16] for block ciphers is instrumental in proving security against these cryptanalysis methods. Evaluating the security of a scheme against differential attacks often involves determining the minimum number of active SBoxes within the cipher. While this task has garnered significant attention, the manual and computational effort required for its execution remains substantial. Enter MILP, a powerful optimization tool that deals with integral variables and offers an efficient approach to tackle complex problems.

To address the challenge of finding the minimum number of active SBoxes, attackers employ MILP to define potential differential propagation patterns in a round function. The subsequent execution of an MILP solver in parallel provides the minimal number of active SBoxes for the specified propagation patterns. Establishing a lower bound for the quantity of active SBoxes in differential and linear cryptanalysis allows for the calculation of an upper bound for the likelihood of the best characteristic. The maximum differential probability (MDP) of the SBoxes plays a crucial role in this process, enabling the accurate calculation of the overall differential probability by summing up the probabilities of all matching characteristics.

The propagation characteristic of cryptographic components, such as SBoxes, is often expressed through Boolean functions. Modeling these functions using the MILP method involves computing a set of inequalities and determining solutions that precisely correspond to supporting the Boolean function. Researchers grapple with the challenge of efficiently modeling Boolean functions by creating a minimal set of possible inequalities. Various techniques proposed by researchers, including those in references [29,39,38,37,13,31,25], aim to address these challenges.

While MILP models are frequently employed in cryptanalysis, the quest for the most effective comprehensive model continues. Researchers emphasize the need to build and thoroughly investigate different proposed models, considering the variety of possible inequalities involved. The optimization of MILP models hinges on observing a reduction in the number of inequalities, as even a singleunit decrease holds significance in the broader context of computing resources and timing requirements for MILP solvers in full-round ciphers.

The key emphasis for differential and impossible differential cryptanalysis lies in identifying difference propagations through a cipher path. Consequently, there is a notable focus among cryptographers on developing automatic search algorithms [27,32,40,24,26,33] tailored for the identification of these characteristics and approximations. In literature, limited efficient tools are available by an attacker who can choose distinguishable customizable parameters like primitive components of a round function or a designer can verify during construction. Also, different search options are needed for choosing input and output differences during the attack.

1.1 Related Work

Mouha et al. [29] were the first to articulate the challenge of determining the minimum number of active SBoxes amenable to MILP modeling for evaluating word-oriented ciphers. However, there exist ciphers that do not adhere to the word-oriented paradigm, such as PRESENT, which employs a 4-bit SBox and subsequently redistributes four bits from one SBox to four distinct SBoxes using bit-permutation.

Sun et al. [39] devised a method to simulate all potential differential propagations bit by bit, even within the SBox, enabling the application of MILP to such structures. They leveraged MILP-based techniques to evaluate the security of block ciphers against related-key differential attacks. These methods are predominantly employed to search for single-key or related-key differential characteristics on PRESENT80, LBlock, SIMON48, DESL, and PRESENT128. Sun et al. [39] detail various approaches for modeling the differential characteristics of an SBox using linear inequalities.

In one approach, inequalities are derived based on specific conditional differential characteristics of an SBox. Another method involves extracting inequalities from the H-representation of the convex hull for all potential differential patterns of the SBox. To select a specific number of inequalities from the convex hull, they devised a greedy algorithm for the latter technique. They advocate for an automated method to assess the security of bit-oriented block ciphers against differential attacks, proposing numerous strategies to establish tighter security bounds using these inequalities in conjunction with MILP methodology.

Sun et al. [38] further explore the examination of differential and linear characteristics across various block ciphers using mixed-integer linear programming (MILP). They stress that a concise set of linear inequalities can effectively characterize the differential behavior of each SBox. In constructing MILP models for a variety of ciphers, Sun et al. [38] define feasible regions that accurately encapsulate all valid differential and linear properties. They assert that any subset of $\{0,1\}^n \subset \mathbb{R}^n$ can be precisely delineated through linear inequalities. They introduce a method that can discern all specified features of differential and linear properties by refining Sun et al.'s heuristic approach [39] for identifying such characteristics into a precise one based on these MILP models. Mouha's technique [29] proves unsuitable for SPN ciphers containing diffusion layers with bitwise permutations, known as S-bP structures. This issue arises from the challenge of reconciling the diffusion effect computed concurrently by the non-linear substitution layers and bitwise permutation layers. Additionally, the MILP constraints presented by Mouha lack adequacy in modeling the differential propagation of a linear diffusion layer derived from almost-MDS or non-MDS matrices. To automatically establish a lower constraint on the number of active SBoxes for block ciphers with S-bP structures, Sun et al. [37] expanded upon Mouha et

al.'s method [29] and proposed a novel strategy grounded in mixed-integer linear programming (MILP). They successfully applied this technique to PRESENT-80.

Matsui [27] introduced an automated search tool utilizing the branch-andbound search algorithm, initially applied to DES for uncovering both differential characteristics and linear approximations. To automate the quest for such characteristics in ARX ciphers, Kai Fu et al. [18] developed a MILP model. By presuming independent inputs for modular addition and independent rounds, they leveraged the differential and linear properties of modular addition. Their exploration extended to identifying differential properties and linear approximations of the Speck cipher using the novel MILP model. The differential characteristics they identified for Speck64, Speck96, and Speck128 span one, three, and five rounds, respectively, compared to prior best differential characteristics. Moreover, the differential characteristic for Speck48 exhibits greater viability. Cui et al. [15] introduced an innovative automatic method for searching impossible differential trails in ciphers containing SBoxes, accounting for the differential and linear features of non-linear components, such as SBoxes themselves. They expanded the tool's functionality to include modulo addition and applied it to ARX ciphers. For HIGHT, SHACAL-2, LEA, and LBlock, the tool improves upon the current best outcomes. A new SBox modeling approach capable of addressing the likelihood of differential characteristics and reflecting a condensed version of the Differential Distribution Table (DDT) of large SBoxes was presented by Ahmed Abdelkhalek et al. [2]. They increased the number of rounds necessary to resist simple differential distinguishers by one round after evaluating the upper bound on SKINNY-128's differential features. Additionally, the upper bound on differential features for two AES-round based constructions was examined. Coming to the automatic searching of impossible differential propagations, J Kim et al. [24] introduced the U method, which expresses these differential propagations as matrix operations. Subsequently, Y Luo et al. [26] addressed some of the U method's limitations with their UID method. For a period, encryption scheme designers widely adopted the UID method for security assessments. In a broader context, generalizing impossible differential cryptanalysis as the quest for impossible differential characteristics, S Wu and M Wang [40] introduced an automated matrix-based approach. This approach bridges the gap between manual searches conducted via ad hoc techniques and the UID method. Furthermore, Y Sasaki and Y Todo [32] developed an automated tool based on MILP techniques to assess a cipher's security. This tool takes inputs, including the number 'r' representing rounds and a system of linear inequalities describing the cipher's non-linear and linear layers. In turn, it generates a system of linear inequalities representing 'r' rounds of the cipher. Additional constraints can be applied to search for either a differential characteristic (that minimizes the number of active SBoxes in input and output differences) or impossible differential characteristics (that occur with zero probability in input and output differences).

1.2 Our Contribution

In this paper, we introduce models for valid differential trail propagation through the linear and non-linear layers¹. Applying these primitive components we designed an MILP based tool for searching differential and impossible differential propagation's through a cipher path.

 Modeling linear and non-linear layer We propose two new algorithms for modeling non-linear layer and a novel XOR model for linear layer.

Greedy random-tiebreaker algorithm We introduce a novel algorithm that selects randomly from the outcomes of the greedy algorithm. Our approach enhances the threshold for the minimum number of inequalities applicable to 4-bit SBoxes of MIBS, LBlock, and Serpent compared to the current greedy algorithm [39].

Subset addition approach We propose a subset-addition-based algorithm that generates new inequalities derived from the outcomes of the H-representation of the convex hull. By incorporating k-subset inequalities to create new inequalities, we eliminate more improbable propagations. Subsequently, we replace a subset of old inequalities with the new ones, resulting in enhancements over existing algorithms designed for 4-bit SBoxes like Minalpher, LBlock, Serpent, Prince, and Rectangle. Moreover, the subset addition algorithm is effective for 5- and 6-bit SBoxes.

For 5-bit SBoxes such as ASCON and SC2000, we refine the boundary of inequalities. In the case of 6-bit SBoxes like APN and SC2000, we reduce the number of inequalities compared to existing results. Furthermore, we significantly improve the time required to find the minimum set of inequalities compared to the approach proposed by Boura and Coggia [13].

New XOR model We investigated a brief depiction of the linear layer, mostly utilising XOR gates. Notably, our model performs better than competing models in terms of computational efficiency while still achieving a simplified form.

- Automatic differential and impossible differential searching tool We created a tool that, when given the round function specification for an SPN block cipher, generates a MILP model for a user-specified number of rounds. The model is then solved to discover a differential characteristic that minimises the amount of active SBoxes. It also searches impossible differential characteristics corresponding to impossible transitions from the input to the output.

1.3 Organization of the paper

The organization of the paper is as follows. Section 2 explains the background of our work. We describe the greedy random tiebreaker algorithm and its results in Section 3.1. In Section 3.3, we present the subset addition approach and the

¹ A preliminary version of this paper is presented in CANS 2023 [30]

corresponding implementation process with the results. A description of modeling linear layer along with a new XOR model is provided in Section 4. Section 5 presents the automatic tool for finding differential and impossible differential propagations. Section 6 concludes the papaer.

2 Background

In this section we describe about the MILP modeling of the word oriented and the bit oriented block ciphers.

2.1 Modeling word oriented block ciphers

In Mouha et al.'s approach, word level variations propagating through a block cipher are represented as binary variables, which are subject to restrictions imposed by the word-oriented operations, XOR, nonlinear transformation and linear transformation with a predefined branch number. Let a string P consisting of n words $P = \{P_0, P_1, \ldots, P_{n-1}\}$. We can define the difference vector $D = \{D_0, D_1, \ldots, D_{n-1}\}$ corresponding to P as follows,

$$D_i = \begin{cases} 0, & \text{if } P_i = 0. \\ 1, & \text{otherwise.} \end{cases}$$
(1)

Now taking the words of difference vector D as input or output we formalize the objective functions and the constraints of the MILP model.

Objective Function Set up the objective function to be the sum of all variables representing the input words of the Sboxes. Obviously, this objective function corresponds to the number of active Sboxes, and can be minimized to determine its lower bound. Suppose a binary variable S_j represents the inputs of the SBox's used in the encryption function, then the objective function is,

$$minimize \sum_{j} S_{j} \tag{2}$$

Defining Constraints

- XOR Operation Consider an XOR gate with inputs u_1 and v_1 in one instance, and u_2 and v_2 in another. Let the corresponding outputs be y_1, y_2 and the input differences be,

Suppose the output difference be $y = u \oplus v$, where $u_1, u_2, u, v_1, v_2, v, y_1, y_2, y \in F_2^w$ (w is the word size). The following constraints will make sure that when u, v, and y are not all zero, then there are at least two of them are nonzero:

$$\begin{cases} u+v+y \ge 2d, \\ d \ge u, \\ d \ge v, \\ d \ge y \end{cases}$$
(3)

where d is a dummy variable taking values from $\{0, 1\}$. If each one of u, v, and y represents one bit, we should also add the inequality $u + v + y \leq 2$.

- Linear Transformations Let u_{i_k} and v_{j_k} , $k \in 0, 1, \ldots, m-1$, be binary variables denoting the word-level input and output differences of the linear transformation L respectively. Since for nonzero input differences, there are totally at least B_L nonzero w-bit words in the input and output differences, we include the following constraints:

$$\sum_{k=0}^{m-1} (u_{i_k} + v_{j_k}) \ge B_L d_L \tag{4}$$

Here $d_L \ge u_{ik}$, $k \in \{0, \ldots, m-1\}$ and $d_L \ge v_{ik}$, $k \in \{0, \ldots, m-1\}$ where d_L is a dummy variable taking values in 0, 1 and B_L is the branch number of the linear transformation.

 Non-zero SBox In order to prevent the trivial solution, where the minimal number of active S-boxes is zero, an additional linear equation is introduced to guarantee that at least one SBox is active.

Security evaluation Solve the MILP model using any MILP optimizer, and the optimized solution, say N, is the minimum number of the active Sboxes. The probability of the best differential characteristic is upper bounded by ϵ^N , where ϵ is the maximum differential probability (MDP) of a single SBox.

Example The number of active SBox'es for AES are provided in Table 1. The MDP of AES SBox is 2^{-6} . So, the upper bound of the differential characteristics for eight rounds of AES is 2^{-300} .

Table 1: Minin	nu	ım	ı r	num	ibe	r of	f ac	tiv	e S	Bo	xes	for	· Al	\mathbf{ES}
Rounds	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Active SBoxes	1	5	9	25	26	30	34	50	51	55	59	75	76	80

2.2 Framework for Bit Oriented Ciphers

Bit-oriented ciphers require mainly two types of constraints, constraints imposed by XOR operations (same as word oriented ciphers) and constraints for modeling the SBox's.

- Bit level representations A new binary variable x_i is required for every input and output bit-level difference.

$$x_i = \begin{cases} 0 \text{ if the bit difference is zero} \\ 1 \text{ if the bit difference is one} \end{cases}$$

Introduce another new binary variable S_j for every inputs of the SBox's used in the encryption function and the key-schedule procedure.

$$S_{j} = \begin{cases} 1 & \text{if the input word of the SBox is nonzero} \\ 0 & \text{if the input word of the SBox is zero} \end{cases}$$

- Constraints for SBox Operations Suppose an $q \times r$ SBox denoted by S_t and the bit-level input and output differences are $(x_{i_0}, x_{i_1}, \ldots, x_{i_{q-1}})$ and $(y_{j_0}, y_{j_1}, \ldots, y_{j_{r-1}})$. Here we want to maintain

$$S_t = \begin{cases} 1 \text{ iff at least one of } x_{i_0}, x_{i_1}, \dots, x_{i_{q-1}} \text{ is active} \\ 0 \text{ iff all are zero} \end{cases}$$

Equivalently, add the following set of inequalities,

$$\begin{cases} x_{i_0} + x_{i_1} + \ldots + x_{i_{q-1}} - S_t \ge 0\\ S_t - x_{i_k} \ge 0,\\ \text{where } k \in \{0, \ldots (q-1)\} \end{cases}$$
(5)

For bijective Sbox's nonzero input differences must results non zero output differences and the opposite is also true,

$$\begin{cases} qy_{j_0} + qy_{j_1} + \ldots + qy_{j_{(r-1)}} - (x_{i_0} + x_{i_1} + \ldots + x_{i_{q-1}}) \ge 0\\ rx_{i_0} + rx_{i_1} + \ldots + rx_{i_{q-1}} - (y_{j_0} + y_{j_1} + \ldots + y_{j_{(r-1)}}) \ge 0 \end{cases}$$
(6)

The hamming weight of (q + r) bit word $x_{i_0} \dots x_{i_{q-1}} y_{j_0} \dots y_{j_{r-1}}$ is lower bounded by branch number B_s of the SBox for non-zero input difference $x_{i_0} \dots x_{i_{q-1}}$ and d_s is a dummy variable.

$$\begin{cases} \sum_{k=0}^{q-1} x_{i_k} + \sum_{t=0}^{r-1} y_{j_t} \ge B_s d_s \\ d_s \ge x_{i_k}, \\ d_s \ge y_{i_k} \end{cases}$$
(7)

where d_s is a dummy variable taking values in $\{0, 1\}$ and B_s is the branch number of the linear transformation.

- Updated objective function The new objective function is,

$$f = Minimize \sum_{j} S_j \tag{8}$$

The purpose is to find the lower bound of the number of active SBox's.

In this section we describe the earlier used methods and algorithms for modeling SBoxes using inequalities.

2.3 Representation of SBox using inequalities

An SBox S can be represented as $S : \mathbb{F}_2^n \to \mathbb{F}_2^n$. We can symbolize any operation on an SBox as $x \to y$ with $x, y \in \mathbb{F}_2^n$. Let $(x_0, \ldots, x_{n-1}, y_0, \ldots, y_{n-1}) \in \mathbb{R}^{2n}$ be a 2*n*-dimensional vector, where \mathbb{R} is the real number field, and for an SBox the input-output differential pattern is denoted using a point $(x_0, \ldots, x_{n-1}, y_0, \ldots, y_{n-1})$.

H-representation of the convex hull The convex hull of a set P comprising distance points in \mathbb{R}^n represents the smallest convex set that encompasses P. We determine the H-representation of the convex hull encompassing all possible input-output differential patterns of the SBox by computing the Differential Distribution Table (DDT) and utilizing SageMath [1] to compute the H-representation.

The H-representation furnishes w linear inequalities, expressed as:

$$A\begin{bmatrix} x_0\\ \vdots\\ x_{n-1}\\ y_0\\ \vdots\\ y_{n-1}\end{bmatrix} \le b$$

where A represents a $w \times 2n$ matrix and both A and b comprise solely integer values. Each linear inequality invalidates specific points associated with impossible differential propagations. Moreover, the H-representation includes redundant inequalities linked to the MILP-based differential trail search due to the confinement of feasible points to $\{0,1\}^{2n}$ rather than \mathbb{R}^{2n} . Consequently, numerous extra linear inequalities impede the efficiency of the MILP solver. Researchers employ various techniques to eliminate these redundant inequalities.

Conditional differential characteristics modeling The logical condition that $(x_0, \ldots, x_{m-1}) = (\delta_0, \ldots, \delta_{m-1}) \in \{0, 1\}^m \subseteq \mathbb{Z}^m$ implies $y = \delta \in \{0, 1\} \subseteq \mathbb{Z}$ can be modeled by using the following linear inequality,

$$\sum_{i=0}^{m-1} (-1)^{\delta_i} x_i + (-1)^{\delta+1} y - \delta + \sum_{i=0}^{m-1} \delta_i \ge 0$$
(9)

Algorithm 1 Greedy Based Approach [39]

Input:

HI: Inequalities in the H-Representation of the convex hull of an SBox. *ID*: The set of all impossible differential patterns of an SBox Output: *RI*: Set of inequalities that generates a stricter feasible region after maximizing the removed impossible differential patterns. 1: $l \leftarrow \phi, RI \leftarrow \phi$ 2: while $ID \neq \phi$ do $l \leftarrow$ The inequality in HI which maximizes the number of removed im-3: possible differential patterns from ID. 4: $ID \leftarrow ID - \{\text{Removed impossible differential patterns using } l\}$ $HI \leftarrow HI - \{1\}$ 5: $RI \leftarrow RI \cup \{1\}$ 6: 7: end while 8: return Rl

Example Let (x_0, x_1, x_2, x_3) and (y_0, y_1, y_2, y_3) be MILP variables for the input and output differences of a 4-bit SBox. Let $(1010) \rightarrow (0111)$ be an impossible propagation in the DDT corresponding to the SBox. That is, the input difference (1010) is not propagating to (0111). The linear inequality which eliminates the impossible point (1001, 0111) is, $-x_0 + x_1 - x_2 + x_3 + y_0 - y_1 - y_2 - y_3 + 4 \ge 0$. Corresponding to an SBox, if in a DDT there occur *n* impossible paths, then at most *n* linear inequalities are needed to model the DDT correctly. But one can reduce the value of *n* by merging one or more available inequalities and therefore generating new inequalities. For example if we consider two impossible propagations $(1010) \rightarrow (0111)$ and $(1010) \rightarrow (0110)$, then the linear inequality: $-x_0 + x_1 - x_2 + x_3 + y_0 - y_1 - y_2 + y_3 \ge -3$ eliminates both the impossible points together.

2.4 Choosing the best inequalities from the convex hull

Utilizing an MILP model does not assure the creation of a valid differential path. Our objective is to minimize the number of active SBoxes across a wider region, ensuring that the optimal value remains equal to or less than the minimum number of active SBoxes. Therefore, we aim to identify linear inequalities capable of trimming the MILP model while preserving the validity of the region's differential characteristics. Various algorithms have been proposed by researchers to diminish the number of inequalities in an SBox representation.

Greedy Algorithm Based Modeling [39] The discrete points within the H-Representation (convex hull) yield numerous inequalities. An effective strategy involves identifying the most advantageous valid inequalities, which optimize the

Algorithm 2	Modeling b	oy selecting rε	andom set of	inequalities	13
T					

Inputs: P: Input set corresponding to the possible transitions in an SBox. k: The number of inequalities to be added together. Output: RI: Set of inequalities that generates more stricter feasible region after maximizing the removed impossible differential patterns. 1: $H \leftarrow ConvHull(P)$ 2: $RI \leftarrow H$ 3: for all $p \in P$ do Choose k inequalities such that p belongs to the hyperplanes of 4: Q_1, Q_2, \ldots, Q_k $Q_{new} = Q_1 + \ldots + Q_k$ 5:if Q_{new} removes new impossible transitions 6: $RI \leftarrow RI \cup \{Q_{new}\}$ 7: 8: end if 9: end for 10: return RI

elimination of infeasible differential patterns within the convex hull's feasible region. Algorithm 1 elucidates the greedy approach proposed by Sun et al.

Modeling by selecting random set of inequalities [13] A larger collection of newly generated inequalities (resulting from the random addition of kinequalities) tends to be ineffective, as they are likely to encompass the entire space $\{0, 1\}^m$. When k hyperplanes of the H-representation converge at a vertex within the cube $\{0, 1\}^m$, aggregating corresponding inequalities may yield a novel inequality Q_{new} . However, the hyperplane represented by Q_{new} must intersect the cube at least once. In such instances, Q_{new} potentially invalidates a distinct set of infeasible points within the H-representation compared to the previous inequalities. Algorithm 2 outlines the complete procedure.

MILP-based reduction algorithm Sasaki and Todo[31] introduce a methodology that formulates a minimization problem, subsequently solved using a standard MILP solver to obtain a condensed set of inequalities. Initially, they identify all impossible differential points derived from the DDT of an SBox and derive impossible patterns based on these points. Then, for each impossible pattern, they determine which subset of inequalities renders the pattern invalid. Subsequently, they establish a constraint: every impossible pattern must be invalidated by at least one inequality within the feasible region. They construct an MILP problem aimed at minimizing the overall set of inequalities while adhering to the constraints, which they solve to obtain the minimized set of inequalities. Algorithm 3 delineates the entire process in a systematic manner.

Algorithm 3 MILP based reduction [31]

Inputs:

IDP: Impossible differential patterns corresponding to the impossible transitions from the DDT of an SBox.

P: Input set corresponding to the possible transitions in an SBox Output:

 I_{SR} : Set of inequalities that generates more stricter feasible region after maximizing the removed impossible differential patterns.

- 1: $\mathbf{H} \leftarrow ConvHull(P)$
- $2: RI \leftarrow H$
- 3: Create a table *PIT* of size $|RI| \times |IDP|$ where $PIT_{i,j} = 1$ if inequality RI_i removes pattern IDP_j , else set $PIT_{i,j} = 0$
- 4: Set m = |RI|
- 5: Generate *m* binary variables such that c_1, c_2, \ldots, c_m such that $c_i = 1$ means inequality *i* is included in the solution space else $c_i = 0$.
- 6: $constraintSet \leftarrow \phi$
- 7: for each $point \in IDP$ do
- 8: $constraintSet \leftarrow constraintSet \cup \{Construct a constraint c_k, \dots, c_l \ge 1$ such that p is removed by at least one inequality applying table $PIT\} \triangleright$ Generate constraints
- 9: **end for**
- 10: Create an objective function $\sum_{i=1}^{m} c_i$ with constraints *constraintSet* and solve to get best inequalities (I_{SR}) that generate a stricter feasible region after maximizing the removed impossible differential patterns.
- 11: return I_{SR}



Fig. 1: Variation of the output of the greedy algorithm because of a random tiebreaker

Algorithm 4 Randomly select inequalities from greedy set (Greedy Random-Tiebreaker)

Input:

 H_{Rep} : Inequalities in the H-Representation of the convex hull of an SBox. I_D : The set of all impossible differential paths of an SBox

Output:

 I_{SR} : Set of n-best inequalities that generates more stricter feasible region after maximizing the removed impossible differential paths.

1: $I_M \leftarrow \phi, I_{SR} \leftarrow \phi$

2: while $I_D \neq \phi$ do

- 3: $I_M \leftarrow$ The inequalities in H_{Rep} which maximizes the number of removed impossible differential paths from I_D .
- 4: $I_D \leftarrow I_D \{\text{Removed impossible differential paths using } I_M \}$
- 5: **if** $Degree(I_M) > 1$ **then** \triangleright Returns the number of elements in a set 6: $Rand_I \leftarrow ChooseRandomInequality(I_M) \qquad \triangleright$ Chooses randomly an element from a set
- 7: end if
- 8: $H_{Rep} \leftarrow H_{Rep} Rand_I$
- 9: $I_{SR} \leftarrow I_{SR} \cup Rand_I$
- 10: end while
- 11: return I_{SR}

Algorithm 5 Generates a minimal subset of inequalities eliminating all impossible differential paths (Subset Addition)

Input:

 H_{Rep} : Inequalities in the H-Representation of the convex hull of an SBox. I_P : The set of all possible differential paths of an SBox

 I_D : The set of all impossible differential paths of an SBox Output:

 I_{SR} : Set of n-best inequalities that generates more stricter feasible region after maximizing the removed impossible differential paths.

1:
$$I_{SR} \leftarrow H_{Rep}$$

2: for $p \in I_P$ do

3: $I_H \leftarrow \text{all hyperplanes in } H_{Rep}$ which the point p lies on

- 4: **for** $\{h_1, h_2, ..., h_k\} \in P_{Set}(I_H)$ **do**
- 5: $h \leftarrow h_1 + h_2 + \ldots + h_k$

6: **if** *h* is a good hyperplane (If satisfies condition of Type 1 or Type 2) **then**

 $I_{SR} \leftarrow I_{SR} \cup \{h\}$

- 8: end if
- 9: end for

10: **end for**

7:

11: **return** the smallest subset of I_{SR} removing all paths in I_D .



Fig. 2: Separating Type 1 and Type 2 inequalities in convex hull

3 Modeling Non-linear Primitives: Our Approach

3.1 Filtering Inequalities by Greedy Random-Tiebreaker

We employ the original greedy algorithm proposed by S Sun et al. [39] in our approach. Our method closely aligns with the original greedy algorithm, with the key distinction being that when multiple inequalities share the same rank, we opt for a random selection among them.

We posit that the introduction of a random tiebreaker could yield varying numbers of inequalities across multiple runs. To substantiate this claim, we illustrate it with an example of the set cover problem, which is homomorphic to the task of minimizing the MILP model of an SBox. Consider the set $S = \{1, 2, 3, 4, 5, 6, 7\}$ and its subsets $\{\{1, 2\}, \{1, 2, 3\}, \{2, 3, 5\}, \{4, 5\}, \{6\}, \{6, 7\}\}$ designed to find a cover of S. Two distinct greedy approaches yield covers of sizes three ($\{\{1, 2, 3\}, \{4, 5\}, \{6, 7\}\}$) and four ($\{\{2, 3, 5\}, \{4, 5\}, \{6, 7\}, \{1, 2\}\}$) (refer to Figure 1).

During numerous iterations of the greedy random-tiebreaker approach, we identify the most effective (reduced) set of inequalities capable of invalidating all impossible differential patterns. Consequently, the random tiebreaker augments the efficiency of the greedy algorithm. Table 2 presents a comparative evaluation of the reduced number of inequalities across various 4-bit SBoxes.

The overarching methodology is encapsulated in Algorithm 4. Let H_{Rep} denote the set of inequalities generated from the SageMath method *inequality_generator()*, representing the H-representation of the convex hull of an SBox. Assume I_D represents the set of all impossible differential points selected from the difference distribution table (DDT) of an SBox. Let I_M store the hyperplanes in H_{Rep} that

eliminate the maximum number of paths from I_D . If I_M comprises more than one element, we randomly select an inequality from I_M using the *ChooseRandomInequality* method and store it in I_{SR} . The optimal set of inequalities is retained in I_{SR} , and the entire process is iterated multiple times to derive the optimal set of inequalities.

3.2 Implementations and results

We executed Algorithm 4 using SageMath on a desktop computer equipped with an Intel Core i5-6500 4C/4T CPU running Manjaro Linux Sikaris 22.0.0 Xfce Edition 64-bit. During implementation, we employed a flag to randomize the list of inequalities.

Applications on 4-bit SBoxes We conducted our greedy random-tiebreaker algorithm on a comprehensive set of 4-bit SBoxes commonly used in ciphers. Here, we outline the comparison between our findings and the best-known results to date in terms of the minimum number of inequalities. The initial section of Table 2 presents the outcomes for 4-bit SBoxes across 14 distinct ciphers. Our results exhibit variability; for instance, in the case of MIBS [23], we obtained 24 inequalities, three fewer than those achieved by Sun et al. [39]. Conversely, for Prince [12], our results match the existing findings, while for four other ciphers, our results are comparable. The third segment of Table 2 illustrates the outcomes for all the SBoxes within Serpent [9]. Among the existing results for the eight SBoxes, we observe improvements for four of them (S3, S4, S5, S7), while the results remain consistent for S2. However, for the remaining three (S0, S1, S6), we experience a marginal loss, with at most a difference of two inequalities.

In the second section of Table 2, concerning LBlock [41], our results surpass those of Sun et al. [39] across all SBoxes. Additionally, the reduced set of 24 inequalities for MIBS [23] is detailed in Section 3.4.

3.3 Filtering Inequalities by Subset Addition

The primary drawback of the greedy algorithm lies in its inability to guarantee an optimal solution for minimization problems. To address this limitation, we employed the Gurobi Optimizer [20], following the methodology outlined by Sasaki and Todo [31], to identify optimal solutions and successfully replicated their results. It's important to note that the solutions obtained using this approach represent optimal subsets of the H-representation rather than globally optimal solutions. In an attempt to overcome this, we explore the technique proposed by Boura and Coggia [13].

Boura and Coggia's algorithm focuses on generating a larger initial set of inequalities, making it easier to identify a smaller, more optimal subset. They achieve this by creating new inequalities through the addition of k-size subsets of existing inequalities, each representing the hyperplanes on which possible differential paths may lie. These newly generated inequalities are then evaluated

Table 2: Minimum number of inequalities for 4-bit SBoxes (Random Greedy-Tiebreaker)

Cipher	SageMath [1]	Sun et al. [39]	Random Greedy (Our Approach)
GIFT	237	-	22
KLEIN	311	22	22
Lilliput	324	-	26
MIBS	378	27	24
Midori S0	239	-	25
Midori S1	367	-	24
Minalpher	338	-	25
Piccolo	202	23	24
PRESENT	327	22	22
PRIDE	194	-	22
PRINCE	300	26	26
RECTANGLE	267	-	23
SKINNY	202	-	24
TWINE	324	23	25
LBlock S0	205	28	25
LBlock S1	205	27	25
LBlock S2	205	27	25
LBlock S2	205	27	26
LBlock S4	205	28	25
LBlock S5	205	20	25
LBlock S6	205	27	26
LBlock S7	205	27	20
LBlock S8	205	21	25
LBlock S0	205	20	20
Sorport S0	410	21	29
Serpent S0	410	23	24
Serpent S1	409	24	25
Serpent S2	306	2.0	20
Serpent S3	390	26	23
Serpent 54	226	20	24
Serpent S5	200	20	23
Serpent S0	470	22	21
Serpent S7	264	50	21
Serpent So	257	-	25
Serpent S9	307	-	24
Serpent S10	309	-	21
Serpent S11	399	-	21
Serpent 512	300	-	24
Serpent S13	308	-	24
Serpent S14	308	-	20
Serpent S15	308 265	-	23 25
Serpent 516	000 202	-	20
Serpent S17	093 960	-	01 07
Serpent 518	008 200	-	21
Serpent 519	098 951	-	23
Serpent S20	301	-	24
Serpent S21	447	-	20
Serpent S22	405	-	25
Serpent S23	328	-	24
Serpent S24	357	-	24
Serpent S25	366	-	22
Serpent S26	368	-	23
Serpent S27	523	-	24
Serpent S28	278	-	23
Serpent S29	394	-	24
Serpent S30	394	-	23
Serpent S31	357	-	27

based on their ability to eliminate a fresh set of impossible differential paths. However, this approach may be sluggish as it involves comparing lists of impossible differential paths removed by individual inequalities with those removed by the new inequality.

In light of this potential inefficiency, we propose an alternative algorithm that deviates from the approach outlined in [13]. The core concept involves adding k inequalities that represent the hyperplanes corresponding to a potential differential path $(h_1 \text{ through } h_k)$, thereby creating a novel inequality.

$$h = \sum_{i=1}^{k} h_i$$

and keep it only if it is good. We propose that h is good if,

- **Type 1** New inequality h removes more impossible differential paths than the inequality in $h_1, h_2, h_3, \ldots, h_k$ which removes the fewest; or
- **Type 2** New inequality h invalidates at least as many impossible differential paths as the inequality in $h_1, h_2, h_3, \ldots, h_k$ which removes the most.

Algorithm 5 delineates the overall process. Eventually, we determine an optimal subset using the Gurobi Optimizer. It is important to note that, unlike in [13], we do not consider which impossible differential paths are eliminated by h. Instead, we only assess the number of paths it removes. Figure 2 showcases examples of the two types of hyperplanes. These examples are purely illustrative, as the differential paths are situated on the vertices of the unit hypercube. $(h_1 + h_2)$ represents type 2, eliminating 12 impossible differential paths, whereas h_1 eliminates 12 and h_2 removes 10. Conversely, $h'_1 + h'_2$ belongs to type 1, removing 14 paths, while h'_1 eliminates 16 and h'_2 removes 10 paths respectively.

Multithreading and Filtration Each iteration of the loop, commencing at line 4 in Algorithm 5, is designed to run independently of others. Consequently, the algorithm is amenable to implementation in a multithreaded fashion utilizing a thread pool. Whenever a thread becomes available, it selects the next iteration of the loop and initiates its execution. Through this process, we observed that one particular thread consistently requires a noticeably longer time compared to others, regardless of the cipher under analysis.

This discrepancy arises because the potential differential path associated with the origin, denoted as [0, 0, 0, 0, 0, 0, 0], seems to intersect significantly more hyperplanes than any other path. However, it does not generate any new inequalities that contribute to the eventual optimal subset. Consequently, the thread assigned to process this specific path spends the longest duration performing non-useful tasks, rendering it apparent that this path can be disregarded from the outset.

Implementation and Results We implemented Algorithm 5 in C++ on a desktop computer equipped with an Intel Core i5-6500 4C/4T CPU running

Cipher	Sasaki and Todo [31]	Boura and Coggia [13]	Subset Addition $(k = 2)$ (Our approach)	Subset Addition $(k = 3)$ (Our approach)
CIDT	1000 [01]	17	(Our approach)	
GIFT	-	17	17	17
KLEIN	21	19	19	19
Lilliput	23	19	20	19
MIBS	23	20	20	20
Midori S0	21	16	17	16
Midori S1	22	20	20	20
Minalpher	22	19	19	18
Piccolo	21	16	16	16
PRESENT	21	17	17	17
PRIDE	-	16	17	17
PRINCE	22	19	19	18
RECTANGLE	21	17	17	16
SKINNY	21	16	16	16
TWINE	23	19	20	19
LBlock S0	24	17	17	16
LBlock S1	24	17	17	16
LBlock S2	24	17	17	16
LBlock S3	24	17	17	16
LBlock S4	24	17	17	16
LBlock S5	24	17	17	16
LBlock S6	24	17	17	16
LBlock S7	24	17	17	16
LBlock S8	24	17	17	16
LBlock S9	24	17	17	16
Serpent S0	21	17	18	17
Serpent St	21	17	10	18
Serpent S2	21	18	18	17
Serpent S2	21	20	16	14
Serpent S4	21	10	10	10
Serpent S5	23	10	15	17
Serpent S6	25	17	16	16
Serpent S0	21	20	10	16
Serpent S7	21	20	10	10
Serpent S0	-	-	10	10
Serpent S10	-	-	10	16
Serpent S10	-	-	11	10
Serpent SII	-	-	10	10
Serpent 512	-	-	18	10
Serpent S13	-	-	18	18
Serpent 514	-	-	18	10
Serpent S15	-	-	18	18
Serpent S16	-	-	17	10
Serpent S17	-	-	19	19
Serpent S18	-	-	18	18
Serpent S19	-	-	18	17
Serpent S20	-	-	19	19
Serpent S21	-	-	18	17
Serpent S22	-	-	17	16
Serpent S23	-	-	19	19
Serpent S24	-	-	18	17
Serpent S25	-	-	17	16
Serpent S26	-	-	18	18
Serpent S27	-	-	17	16
Serpent S28	-	-	17	17
Serpent S29	-	-	17	17
Serpent S30	-	-	17	17
Serpent S31	-	-	18	17

Table 3: Minimum number of inequalities for 4-bit SBoxes (Subset Addition)

Manjaro Linux Sikaris 22.0.0 Xfce Edition 64-bit. Subsequently, we extended the program to incorporate the Gurobi Optimizer for identifying the optimal subset of inequalities. Users are provided with the option to choose (by defining a macro during compilation) between good hyperplanes of types 1 and 2. Our experiments indicate that selecting type 1 is either superior to or on par with selecting type 2.

Application to 4-bit SBoxes Algorithm 5 has been effectively applied to most 4-bit SBoxes. Among the 14 4-bit SBoxes listed in the first section of Table 3, we observe improved results for Prince [12], Minalpher [35], and Rectangle [43] when setting k = 3. However, the results remain consistent with existing ones for 10 SBoxes. Only for PRIDE [3], do we note an additional minimum number of inequalities.

For all ten LBlock [41] SBoxes, the inequality count decreases to 16 from 17 [13]. The outcomes for LBlock are detailed in the second section of Table 3 for both k = 2 and k = 3 settings.

The third section of Table 3 illustrates the results for 32 Serpent [9] SBoxes. Comparing with the existing results of eight Serpent SBoxes (S0 to S7), we improve the results for five (S2, S3, S5, S6, S7). However, for two SBoxes (S0, S4), the results remain unchanged, while for S2, we observe a decrease. For the remaining 24 SBoxes, we present new results. The inequalities for Serpent S3 are detailed in Section 3.4.

Application to 5- and 6-bit SBoxes We applied Algorithm 5 to ASCON [17] and SC2000 [36], which utilize 5-bit SBoxes. In this scenario, by setting k = 3, we observed improved results. For 6-bit SBoxes of APN [14] and SC2000 with k = 2, we surpassed the existing boundary set by Boura and Coggia [13]. However, for the 5-bit SBox of FIDES [11], we obtained one additional inequality compared to the existing boundary. The results for 5 and 6-bit SBoxes are presented in Table 4, alongside existing results, for comparison.

Reducing running time over Boura and Coggia [13] technique As previously noted, given that each impossible differential path is handled independently, parallel processing can be utilized to decrease the overall running time. In this approach, a worker thread can independently process a distinct possible differential path at a time.

To implement multithreading, we utilized the C++ POSIX Threads API, encapsulated within the thread library. In Table 5, we present the runtime data of our algorithm (Algorithm 5) for several SBoxes. We report the average running times for LBlock S0 through S9 and Serpent S0 through S7. Generally, it seems that larger values of k tend to result in smaller subsets of inequalities. However, we were unable to confirm this hypothesis definitively. While in our experiments, k = 3 typically produced smaller subsets than k = 2, testing with k = 4 posed challenges. For Lilliput [8], MIBS [23], and Serpent S3, the outputs did not

			1		
SBox	SBox Size	SageMath [1]	Boura and Coggia [13]	Subset Addition k = 2 (Our approach)	Subset Addition k = 3 (Our approach)
ASCON		2415	32	31	31
FIDES	5	910	61	64	62
SC2000		908	64	65	63
APN		5481	167	163	
FIDES	6	7403	180	184	_
SC2000]	11920	214	189	

Table 4: Minimum number of Inequalities for 5- and 6-bit SBoxes

improve with k = 4, but the memory requirement soared to around 10 GiB. Consequently, we couldn't test other ciphers due to these limitations.

Boura and Coggia [13] reported that their algorithm implementation took a few minutes for k = 2, while for k = 3, it required a few hours. They haven't provided precise estimates of running times for different SBoxes using their approach. While we attempted to replicate their results, the runtime on our system exceeded our expectations. Nonetheless, we compare our algorithm for k = 2 and k = 3 with that of Boura and Coggia [13], and our results are detailed in Table 5. Our implementation is faster by two orders of magnitude and yields comparable results. We achieved significantly better running times after implementing all the optimizations mentioned earlier in our program.

SBoy	Required Time for A	Algorithm 5 (in sec)
SDOX	No. of Inequality, $k = 2$	No. of Inequality, $\mathbf{k} = 3$
Klein	0.16	2.5
LBlock S*	0.19	2.2
MIBS	1.9	4.5
Piccolo	0.15	2.0
PRESENT	0.28	3.9
PRINCE	0.17	4.8
Serpent S*	0.49	8.3
TWINE	0.16	3.4

Table 5: Approximate running time of Subset Addition Algorithm

3.4 Sample Reduced Inequalities

Applying random greedy tiebreaker algorithm 4 for MIBS [23], the reduced 24 inequalities are as follows,

$$-1x3 - 2x2 - 2x1 - 1x0 + 4y3 + 5y2 + 5y1 + 5y0 >= 0$$

+	5x3	+	4x2	+	4x1	+	3x0	-	1y3	-	2y2	+	1y1	-	2y0	>=	0
-	2x3	+	2x2	+	4x1	+	1x0	+	ЗуЗ	+	1y2	-	3y1	-	3y0	>=	-4
-	1x3	-	4x2	+	3x1	+	2x0	-	1y3	-	3y2	+	4y1	+	2y0	>=	-5
-	2x3	+	1x2	-	3x1	-	1x0	-	1y3	-	3y2	-	2y1	-	2y0	>=	-11
-	1x3	-	2x2	-	4x1	+	4x0	-	4y3	+	2y2	+	1y1	-	3y0	>=	-10
+	2x3	-	1x2	+	3x1	+	1x0	-	2y3	+	2y2	-	3y1	+	1y0	>=	-3
+	1x3	+	2x2	-	4x1	+	2x0	+	ЗуЗ	+	1y2	+	2y1	+	4y0	>=	0
+	1x3	+	3x2	-	2x1	-	3x0	+	1y3	+	3y2	+	2y1	-	1y0	>=	-3
+	2x3	-	1x2	-	2x1	-	2x0	-	1y3	-	1y2	-	2y1	+	0y0	>=	-7
+	0x3	+	2x2	+	2x1	-	1x0	+	1y3	+	1y2	-	1y1	+	1y0	>=	0
-	3x3	-	3x2	+	1x1	-	2x0	+	1y3	-	2y2	+	1y1	+	2y0	>=	-7
+	2x3	-	1x2	+	2x1	-	1x0	+	1y3	+	1y2	+	2y1	-	1y0	>=	-1
+	1x3	-	2x2	-	2x1	+	2x0	+	1y3	+	1y2	-	1y1	-	2y0	>=	-5
-	1x3	+	2x2	-	1x1	+	1x0	+	2y3	-	2y2	+	1y1	-	1y0	>=	-3
-	1x3	+	1x2	+	0x1	-	1x0	-	1y3	-	1y2	+	0y1	+	1y0	>=	-3
+	1x3	-	2x2	-	1x1	-	1x0	+	1y3	-	2y2	-	2y1	+	1y0	>=	-6
+	2x3	-	1x2	+	0x1	-	2x0	-	2y3	+	2y2	-	1y1	+	1y0	>=	-4
-	1x3	-	1x2	+	1x1	-	1x0	-	1y3	+	0y2	-	1y1	-	1y0	>=	-5
-	1x3	+	1x2	-	1x1	+	2x0	+	1y3	+	2y2	-	1y1	+	2y0	>=	-1
+	2x3	+	1x2	+	2x1	+	3x0	-	2y3	-	1y2	-	1y1	+	2y0	>=	-1
-	3x3	-	2x2	+	1x1	+	3x0	-	1y3	+	1y2	+	2y1	+	3y0	>=	-3
+	1x3	-	1x2	-	2x1	-	2x0	-	1y3	-	1y2	-	1y1	-	1y0	>=	-7
-	1x3	+	1x2	+	0x1	-	1x0	-	1y3	+	1y2	+	1y1	-	1y0	>=	-3

Applying subset addition algorithm 5 for Serpent S3 the inequalities are as follows,

Applying subset addition algorithm 5 for ASCON SBox the 31 inequalities are as follows,

-	9x5	+	8x4	+	6x3	+	11x2	-	6x1	+	4y5	-	5y4	-	ЗуЗ	-	1y2	+	3y1	>=	12
-	1x5	+	5x4	+	8x3	+	7x2	-	3x1	+	8y5	+	7y4	-	2y3	+	1y2	-	2y1	>=	0
+	1x5	+	2x4	+	4x3	+	2x2	-	2x1	-	4y5	-	3y4	-	2y3	+	0y2	-	4y1	>=	11
+	5x5	+	11x4	+	4x3	+	11x2	+	6x1	-	3y5	+	2y4	-	1y3	+	0y2	-	7y1	>=	0
+	5x5	+	7x4	-	6x3	+	3x2	-	3x1	+	6y5	-	1y4	-	1y3	+	4y2	+	1y1	>=	4
-	1x5	+	7x4	+	7x3	+	9x2	-	3x1	+	9y5	-	3y4	-	2y3	-	1y2	+	9y1	>=	0
-	1x5	-	2x4	+	0x3	+	2x2	-	1x1	-	3y5	-	3y4	+	2y3	+	1y2	+	2y1	>=	7
-	1x5	+	7x4	+	9x3	+	8x2	-	3x1	-	3y5	+	9y4	-	2y3	-	1y2	+	10y1	>=	0
-	2x5	+	5x4	+	2x3	-	5x2	-	3x1	-	2y5	+	0y4	+	0y3	-	1y2	-	3y1	>=	11
+	1x5	-	2x4	+	0x3	-	1x2	+	2x1	+	0y5	+	1y4	+	2y3	-	2y2	-	2y1	>=	5
+	2x5	-	1x4	+	0x3	+	1x2	+	2x1	+	0y5	+	0y4	-	2y3	+	2y2	-	1y1	>=	2
+	3x5	+	2x4	+	0x3	-	3x2	+	1x1	-	2y5	+	0y4	-	1y3	-	2y2	+	3y1	>=	5
+	3x5	+	5x4	+	4x3	-	4x2	+	2x1	+	3y5	+	0y4	-	1y3	-	1y2	+	3y1	>=	0
-	2x5	+	0x4	-	1x3	-	2x2	-	2x1	+	1y5	+	1y4	+	ЗуЗ	+	3y2	+	0y1	>=	4
+	2x5	-	3x4	+	3x3	-	3x2	-	2x1	+	0y5	+	0y4	+	1y3	+	3y2	+	1y1	>=	5
+	2x5	+	2x4	-	2x3	-	2x2	-	1x1	+	0y5	+	0y4	+	0y3	+	2y2	+	1y1	>=	3
+	1x5	-	4x4	-	4x3	+	3x2	+	2x1	+	2y5	+	2y4	-	1y3	-	1y2	+	2y1	>=	6
-	1x5	-	3x4	-	12x3	+	10x2	+	4x1	-	9y5	+	8y4	-	5y3	+	1y2	-	7y1	>=	25
-	3x5	-	1x4	-	6x3	+	6x2	-	1x1	-	5y5	-	5y4	-	ЗуЗ	+	2y2	+	7y1	>=	17
+	0x5	+	3x4	-	2x3	+	3x2	+	2x1	-	1y5	-	1y4	+	2y3	+	0y2	-	1y1	>=	2
-	1x5	+	4x4	-	2x3	+	10x2	-	6x1	+	5y5	+	5y4	+	4y3	-	1y2	+	6y1	>=	0
-	2x5	+	2x4	-	2x3	-	2x2	+	1x1	+	2y5	+	0y4	+	0y3	+	0y2	-	1y1	>=	5
+	6x5	-	5x4	-	6x3	-	2x2	+	3x1	-	1y5	-	6y4	+	0y3	-	3y2	+	1y1	>=	17
+	2x5	-	2x4	-	2x3	-	3x2	-	2x1	+	0y5	+	3y4	+	1y3	+	1y2	+	1y1	>=	6
-	2x5	-	1x4	-	1x3	-	3x2	-	3x1	+	0y5	-	1y4	-	2y3	-	2y2	+	0y1	>=	12
+	0x5	-	2x4	-	1x3	+	2x2	+	0x1	+	2y5	-	2y4	+	1y3	+	0y2	-	2y1	>=	5
+	0x5	-	2x4	+	3x3	+	4x2	+	3x1	-	1y5	+	1y4	+	4y3	+	0y2	-	1y1	>=	0
-	2x5	-	2x4	+	2x3	-	1x2	+	1x1	+	0y5	-	2y4	+	1y3	+	2y2	-	2y1	>=	7
-	2x5	-	1x4	+	2x3	-	2x2	+	2x1	+	1y5	-	2y4	+	0y3	-	2y2	+	2y1	>=	7
-	3x5	-	3x4	-	1x3	-	1x2	-	2x1	+	0y5	+	2y4	-	4y3	-	4y2	-	3y1	>=	17
_	2x5	_	2x4	_	1x3	_	2x2	+	2x1	+	0v5	+	2v4	+	0v3	+	1v2	+	1v1	>=	5

4 Modeling Linear Primitives

The XOR modeling approach (see Equation 3) proposed by Mouha et al. [29] does not accurately model an XOR gate. For example, the solution u = 1, v = 1, y = 1, d = 1 implies that if $u_1 \oplus v_1 = y_1$ then $\overline{u_1} \oplus \overline{v_1} = \overline{y_1}$ where the overline denotes complementation. However, the last statement is clearly false.

A more robust model for XOR gates, which overcomes the limitations of the previous approach, was introduced by Jun Yin et al. [42] based on the research of Yu Sasaki and Yosuke Todo [31]. This improved model, formalized by M. B. Ilter and A. A. Selçuk [22], dispenses with the use of dummy variables and offers a more accurate representation of XOR gates. The fundamental idea behind this model is to treat an n-input XOR gate as a transformation, similar to an SBox.

By computing the convex hull of potential differential paths and applying [31]'s MILP technique to find an optimal subset, this approach allows for a thorough analysis of XOR gates. For instance, the case of n = 4 is illustrated in Table 6 of the reference.

Tab	le 6:	DDT	of	a	four	-input	XOR	gate
-----	-------	-----	----	---	------	--------	-----	------

	02	1_{2}	
016	16	0	
1116	0	16	
216	0	16	
316	16	0	
416	0	16	
516	16	0	
616	16	0	
716	0	16	
816	0	16	
916	16	0	
A ₁₆	16	0	
B ₁₆	0	16	
C ₁₆	16	0	
D ₁₆	0	16	
E16	0	16	
F ₁₆	16	0	

As before, row indices indicate input differences, and column indices indicate output differences.

 $\{(0, 0, 0, 0, 0), (0, 0, 0, 1, 1), (0, 0, 1, 0, 1), \dots, (1, 1, 1, 1, 0)\}$

after which, the inequalities are found just like in the case of the non-linear layer (as described in the previous section). According to [22], an XOR gate with n input bits requires 2^n inequalities to model accurately.

4.1 An Example of 3-input XOR modeling

Let $D = A \oplus B \oplus C$ where $A, B, C, D \in \mathbb{F}_2$. We write the possible points corresponding to (A, B, C, D) for transitions as follows,

 $\{(0,0,0,0),(0,0,1,1),(0,1,1,0),(1,1,0,0),(1,0,1,0),(0,1,0,1),(0,1,1,0),(1,1,1,1)\}$

A polyhedron with an H-representation has a set of given valid points in its representation. Among 16 constraints, some of which are redundant are derived by computing the H-representation of these valid points. The goal is to avoid all impossible transitions like

 $\{(0,0,0,1),(0,0,1,0),(0,1,0,0),(1,0,0,0),(1,1,1,0),(1,1,0,1),(1,0,1,1),(0,1,1,1)\}$

Now find the fewest equations feasible to represent the 2-input XOR operation. The reduction approach developed by Sasaki and Todo [33] is used for this procedure. The eight constraints (see Table 7) are derived for the 3-input XOR model after guaranteeing that all impossible points are eliminated.

Impossible Transition	Inequality
(0, 0, 0, 1)	$A + B + C - D \ge 0$
(0,0,1,0)	$A + B - C + D \ge 0$
(0, 1, 0, 0)	$A - B + C + D \ge 0$
(1,0,0,0)	$-A + B + C + D \ge 0$
(1, 1, 1, 0)	$-A - B - C + D \ge -2$
(1, 1, 0, 1)	$-A - B + C - D \ge -2$
(1,0,1,1)	$-A + B - C - D \ge -2$
(0, 1, 1, 1)	$A - B - C - D \ge -2$

Table 7: Inequalities corresponding to impossible transitions

4.2 Representation of MixColumn Layer

For MixColumn matrix (MDS or MDS-like), we convert it to its primitive representation. For example in the case of Midori, convert the MixColumn matrix of midori into the following 16×16 binary matrix M,

	0000 1000 1000 1000
	0000 0100 0100 0100
	0000 0010 0010 0010
	0000 0001 0001 0001
	1000 0000 1000 1000
	0100 0000 0100 0100
	0010 0000 0010 0010
	0001 0000 0001 0001
M =	
	1000 1000 0000 1000
	1000 1000 1000 0000
	0100 0100 0100 0000
	0010 0010 0010 0000
	0001 0001 0001 0000
	L .

Now for the MixColumn operation of Midori64 we apply, $M \times X = Y$, where M is the (16×16) binary MixColumn matrix. X and Y is the (16×1) matrices, representing one column of input state and output state respectively. Hence, each output bit of Midori's MixColumn can be written as a form of three input XOR. The valid propagation can be modeled by removing eight impossible transitions for each bit. Hence, all the valid propagation patterns can be modeled with $64 \times 8 = 512$ inequalities. The number of inequalities depends on the hamming weight(HW) of any row of a MixColumn matrix. For each bit result with n variables 2^{n-1} inequalities are required.

4.3 Difference between SBox and XOR Modeling

We briefly describe the DDT of Liliput SBox, presented in Table 8 and the DDT of a four input XOR gate (see Table 6) to highlight significant distinctions between a conventional SBox and an XOR gate. These distinctions extend beyond the well-known fact that SBox'es execute non-linear transformations while XOR gates carry out linear transformations.

-																
	016	1 ₁₆	216	3 ₁₆	416	5 ₁₆	6 ₁₆	716	816	916	A_{16}	B ₁₆	C ₁₆	D ₁₆	E ₁₆	F_{16}
016	16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
116	0	2	0	0	0	0	2	0	0	2	2	2	4	0	0	2
216	0	0	0	2	2	0	2	2	0	4	0	2	0	2	0	0
316	0	2	0	0	0	2	2	2	2	0	0	0	0	2	0	4
416	0	0	0	2	0	2	0	0	0	0	2	4	0	2	2	2
516	0	4	2	2	0	2	0	2	0	2	2	0	0	0	0	0
616	0	0	2	0	0	0	4	2	0	0	2	0	2	2	2	0
716	0	0	0	2	2	2	2	0	2	0	4	0	2	0	0	0
816	0	2	2	4	2	0	2	0	0	0	0	0	0	0	2	2
916	0	0	0	2	0	0	0	2	4	2	0	0	2	0	2	2
A_{16}	0	0	2	0	2	0	0	4	2	0	2	2	0	0	0	2
B ₁₆	0	2	0	0	2	2	0	2	0	0	0	2	2	0	4	0
C ₁₆	0	2	0	0	2	0	0	0	2	2	2	0	0	4	2	0
D ₁₆	0	2	4	2	0	0	0	0	2	0	0	2	2	2	0	0
E ₁₆	0	0	2	0	4	2	0	0	0	2	0	0	2	2	0	2
F ₁₆	0	0	2	0	0	4	2	0	2	2	0	2	0	0	2	0

Table 8: DDT of the SBox of Lilliput

- Output Size SBox outputs are typically multi-bit, meaning that an invertible SBox with an n-bit input will produce n-bit outputs. In contrast, XOR gate outputs are single-bit, where an n-bit input is reduced to a single bit.
- **Bijectivity** In most cases, SBox'es are designed to be bijective, ensuring a one-to-one and invertible relationship between input and output to prevent any loss of information. Conversely, XOR gates exhibit a many-to-one relationship, making them inherently non-bijective.

- 26 D Pal et al.
 - Difference Propagation Referencing Table 8, it becomes evident that SBox differences exhibit a one-to-many relationship, wherein a single input difference can map to multiple output differences. Conversely, as depicted in Table 6, XOR gate differences demonstrate a many-to-one relationship, indicating that several input differences can lead to the same output difference.
 - Output Difference Predictability These observations naturally stem from the earlier points. Understanding the input difference of an SBox does not uniquely determine the corresponding output difference. In contrast, when it comes to an XOR gate, knowledge of the input difference directly determines the corresponding output difference.

The final observations hold substantial importance. The relationship between input and output differences in an XOR gate exhibits the characteristics of a well-defined function. Leveraging this insight, it becomes possible to create an efficient model for the linear layer.

4.4 New XOR modeling

MILP involves the optimization of linear constraints within a problem containing a mix of both integral and non-integral variables. However, when applied in the realm of differential cryptanalysis, it's important to note that all variables are artificially constrained to be binary integers, essentially transforming the problems into ILP, or Integer Linear Programming, problems.

In contrast, MILP solvers are engineered to be highly versatile, capable of handling a wide range of variable types, including non-integral, integral non-binary, and binary variables. Hence, for an *n*-input XOR gate:

$$u_0 = u_1 \oplus u_2 \oplus u_3 \oplus \cdots \oplus a_n$$

we propose the following constraint,

$$y_0 + y_1 + y_2 + y_3 + \dots + y_n = 2d \tag{10}$$

Here, y_0 through y_n are binary variables; y_i represents the difference corresponding to u_i and u_i . We introduce d, a dummy integral variable, to capture the behaviour of the XOR gate. In general, Equation 10 conveys the concept that differences can be introduced in an even number of bits. In simpler terms, the parity (odd or even) of the input difference vector must align with that of the output difference.

In Equation 10 the range of values e can take as,

$$0 \le e \le \left\lfloor \frac{n+1}{2} \right\rfloor \tag{11}$$

Since the selection of values for the variables on the left-hand side of Equation 10 completely determines e, we omit to specify these constraints. Correctness of this model is trivial: it only admits solutions corresponding to non-zero cells in the

		Output I	Difference
		0	1
	0	2^n	0
I	1	0	2^n
n	2	0	2^n
p	3	2^n	0
u	4	0	2^n
t	5	2^n	0
	6	2^n	0
D	7	0	2^n
li	8	0	2^n
f	9	2^n	0
f	10	2^n	0
e	11	0	2^n
r	12	2^n	0
e	13	0	2^n
n	14	0	2^n
c	15	2^n	0
e	:		:
	$2^{n} - 1$	$\int 2^n n \text{ is even}$	$\int 0 n \text{ is even}$
	2 -1	0 n is odd	2^n <i>n</i> is odd

Table 9: DDT of an n-input XOR gate

Table 10: Comparison of n-input XOR gate models

Number	Number	of	Number	of	
of inputs	New varial	oles	New constraints		
or inputs	Sasaki et al.	Ours	Sasaki et al.	Ours	
2	0	1	4	1	
3	0	1	8	1	
4	0	1	16	1	
5	0	1	32	1	
6	0	1	64	1	
7	0	1	128	1	

DDT of an *n*-input XOR gate (see Table 9). We also compare the weight of this model with the previous one in Table 10. Ours always introduces only one more variable and constraint, irrespective of the size of the XOR gate.

It is worth noting that Yu Sasaki and Yosuke Todo [34] made a passing reference to modelling large XOR gates in this manner (but with the bounds, as in Equation 11) without formally laying out the concept and defining why it would work, as we have done here.

4.5 Implementation and results

As a stress test, we use the above two models to simulate 3200 *n*-input XOR gates constructed such that from a 16-bit input $(u_{(0,0)}u_{(0,1)}u_{(0,2)}\ldots u_{(0,15)})$ a 16-bit output can be produced $(u_{(200,0)}u_{(200,1)}u_{(200,2)}\cdots u_{(200,15)})$ according to the following relation,

$$u_{(r+1,i)} = \bigoplus_{j=i}^{i+n} u_{(r,j \text{ mod } 16)}, \forall i \in \{0, 1, 2, \cdots, 15\}$$

where $r \in \{0, 1, 2, \dots, 199\}$. We solve each model a total of 16 times (once for each input and output nibble pair constrained to have non-zero differences).

Number of	Solving Tim	ie (sec)
Inputs	Sasaki et al	Ours
2	3.40	1.45
3	3.18	1.42
4	21.89	1.54
5	49.84	1.34
6	91.43	1.73
7	252.15	1.67

Table 11: Performance of *n*-input XOR gate models

The total time taken to solve the models is shown in Table 11. We perform this experiment on a machine with a 32C/32T Intel Xeon Gold 6130 CPU running 64-bit CentOS Linux 7 (Core) using the Python API of Gurobi Optimizer[20].

5 MILP-Aieded Autometic Search for Differential and Impossible Differential Propagations

Differential cryptanalysis is one of the most fundamental cryptanalysis techniques. Identifying distinct differential trails is the first and most crucial step in the method. The concern of cryptographers has been on the automatic search methods for differentiating properties. In order to build an automatic search algorithm for differential cryptanalysis, MILP has been explicitly used. The goal of the MILP problem is to optimize an objective function while taking into account specific constraints. It belongs to a class of optimization problems derived from linear programming.

Impossible differential cryptanalysis is rooted in a miss-in-the-middle attack strategy, where an input difference is propagates forward through the cipher's rounds while an output difference is propagated backward. At an intermediate round, discrepancies arise between the transformed input and output differences.

We introduce MILP-based solutions for valid differential trail propagation through the linear and non-linear layers. Applying these primitive components we designed a tool for searching differential and impossible differential propagation's through a cipher path. We created a tool that generates a MILP model for a user-specified number of rounds when the round function is given for an SPN block cipher. The model is then solved to discover a differential characteristic that minimises the amount of active SBoxes. It also searches impossible differential characteristics corresponding to impossible transitions from the input to the output. Our tool have following distinguishable properties,

- Customizable linear layer The user can change the linear layer components. It is possible to test a cipher by replacing a new linear layer.
- Customizable non-linear layer One can apply an arbitrary SBox to any cipher and check its differential propagations.
- Granularity option in searching an input/output difference During searching of impossible differential propagations the user have various options to provide the input/output differences.
- Faster operations Due to choosing optimized primitive linear and components in every rounds the searching operations are fast.

For verification we applied the tool to Lilliput, GIFT64, SKINNY64, Klein and MIBS. The results for impossible differential propagations are tabulted in Table 12.

5.1 Autometic search

With the well-established MILP models for all three layers in place, it becomes feasible to combine them in various ways to accurately represent any cryptographic cipher. We introduce Algorithm 6, which outlines an automated procedure for exploring differential and impossible differential propagations. To accurately represent SBox'es and PBoxes, it is essential to provide their specifications. This necessitates the establishment of a grammar for expressing these specifications. In the pursuit of efficient cryptanalysis, it is imperative that this grammar remains as straightforward as possible.

Additionally, a mechanism should be incorporated to enable users to specify whether they intend to discover a differential characteristic, characterized by the fewest active SBoxes, or impossible differential characteristics, denoting pairs of

	I I I I I I I I I I I I I I I I I I I			
Cipher	Source	Rounds	Count	Execution Time
Lilliput	Our	9	217	27 mins
Limput	Sasaki and Todo [32]	9	217	-
	Our	5	7200	4 sec
GIFT64	Our	6	768	45 sec
	Banik et al. [5]	6	-	-
SKINNV64	Our	11	2700	21 sec
5111111104	Beierle et al. [7]	11	-	-
Kloin	Our	4	40	45 mins
I I I I I I I I I I I I I I I I I I I	Han et al. [21]	4	-	-
MIBS	Our	8	6	2 hours 12 mins
	Bay et al. [6]	8	-	-

Table 12: List of impossible differential characteristics

input and output differences that occur with a zero probability. The users can fine-tune the granularity of the search for impossible differential characteristics, with three distinct levels available.

- fuzzy searches for impossible differential characteristics in which the input and output word differences take some non-zero values.
- equal searches for impossible differential characteristics in which the input and output word differences are equal.
- **targeted** performs a brute-force search for impossible differential characteristics over all combinations of input and output word differences.

If the granularity is not specified, it searches for a differential characteristic instead. Algorithm 7 describes the automatic tool, which first select the attack type and then chooses the corresponding granularity. Now the tool generates the objective function and associate the MILP constraints.

Rounds	Active SBoxes	Input Difference	Output Difference
1	0	460A442EE0000000	E0000000AEC1A4A8
2	1	EEEEEEFE0000000	00000000E0000000
3	2	8E0000000000080	0000800080002000
4	3	000000000000000000000000000000000000000	A0000000A6A8AAAA
5	5	3A33333830000000	90008000199ED099
6	9	D4EBBB24B9000F00	0000800089001F00
7	12	0200C0000E080EAE	3333915E000010C3
8	15	826EA0020000800	0000200200D06B00

Table 13: Differential characteristics of Lilliput

Algorithm 6 Produce an MILP model for a user-specified number of rounds of a cipher

Inputs: File F containing the specification of the round function of a cipher,
number of rounds n .
function GenerateCipherModel (F, n)
repeat
$n \leftarrow n-1$
for $block \in F$ do
if $block = SBox$ then
write inequalities modelling the non-linear layer
else if $block = XOR$ then
write inequalities modelling the linear layer
else if $block = PBox$ then
write equalities modelling the permutation layer
end if
end for
until $n > 0$
end function

Algorithm 7 Searching for a differential/impossible differential path
<i>Inputs</i> : The attack type and the MILP constraints.
function AutoSearchModel(attack_type, Constraints)
$\mathbf{if} \ \mathrm{attack_type} = \mathtt{differential} \ \mathbf{then}$
Set the objective function
Add the model constraints
Solve the MILP model
$else \ if \ attack_type = impossible_differential \ then$
Keep the objective function as blank
$\mathbf{if} \ \mathbf{block} = \mathbf{fuzzy} \ \mathbf{then}$
Initialize the input and output difference as any fixed non-zero value
Add the model constraints
Solve the MILP model
else if $block = equal then$
Initialize the input and output difference as equal non-zero value
Add the model constraints
Solve the MILP model
else if $block = targeted then$
Take all possible values for input and output differences
Add the model constraints
Solve the MILP model
end if
end if
end function

Input Difference	Output Difference
0000000*00000000	000000000000000000000000000000000000000
000000*000000000	*000000000000000
000000*000000000	000000000000000000
0000002000000000	000000000000200
000000300000000	000000000000300
000000800000000	008000000000800
0000009000000000	000000000000000000000000000000000000000
000000E000000000	0000000000000E00
000000F00000000	0000000000000F00
000000*000000000	000000000000000000
00000*0000000000	*000000000000000
00000*000000000	000000000000000000000000000000000000000
00000*0000000000	000000000000000000000000000000000000000
00000*0000000000	000000000000000000000000000000000000000
0000*00000000000	*000000000000000
0000*00000000000	0000000000000000000
0000700000000000	0000000000000700
0000E00000000000	0000000000000E00
0000*00000000000	000000000000000000000000000000000000000
000*00000000000000000000000000000000000	00000000000000000
000100000000000000	000000000000000000000000000000000000000
000100000000000000000000000000000000000	0000000000000050
000200000000000000000000000000000000000	0000000000000020
000300000000000000000000000000000000000	0000000000000030
000400000000000000000000000000000000000	00000000000000040
000500000000000000000000000000000000000	000000000000000000000000000000000000000
000600000000000000000000000000000000000	000000000000000000000000000000000000000
	000000000000000000000000000000000000000
000000000000000000000000000000000000000	080000000000000000000000000000000000000
000900000000000000000000000000000000000	000000000000000000000000000000000000000
000000000000000000000000000000000000000	0A00000000000000000
000800000000000000000000000000000000000	00000000000000000000000000000000000000
000E00000000000000000000000000000000000	000000000000000E0
000000000000000000000000000000000000000	000000000000000000000000000000000000000
000000000000000000000000000000000000000	000000000000000000000000000000000000000

Table 14: Impossible differential characteristics of Lilliput $\left(r=9\right)$

Rounds	Active SBoxes	Input Difference	Output Difference
1	1	F0000000000000000	4000200010008000
2	2	000000000000000000000000000000000000000	2000100000000000
3	3	00000000000000000000000000000000000000	0000200010000000
4	5	00000000000000000000000000000000000000	040002000000880
5	7	000000000000000000F7	0008004000000010
6	10	000000000000100B	1000080040020201
7	13	000009000000B0F	0024201000018008
8	16	0000000000000010C	080000002000001
9	18	0000000000000070C	0008000100020004

 Table 15: Differential characteristics of Gift64

5.2 Implementation and results

We implemented Algorithm 6 in Python on a machine with a 32C/32T Intel Xeon Gold 6130 CPU running 64-bit CentOS Linux 7 (Core). To solve the MILP models generated, we used the Python API of Gurobi Optimizer[20]. We analysed Lilliput[8], Gift64[5], Skinny64[7], Midori64[4] and Klein[19].

5.3 Lilliput

For differential characteristics of liliput up to eight rounds the counts of active SBox'es obtained through this tool is tabulated in Table 13). The results align with the results reported by Yu Sasaki and Yosuke Todo [34]. Through a **tar-geted** search lasting 20 minutes, we identified 217 impossible differentials for nine rounds of Lilliput, all meticulously documented in Table 14. (Please note that an asterisk (*) denotes any non-zero nibble value). Remarkably, this count precisely matches the findings reported by Sasaki and Y. Todo [32]. It is worth noting, however, that their search was not exhaustive and took approximately an hour to complete.

5.4 Gift64

Our tool successfully determined the number of active SBox'es in Gift64 upto nine rounds, and the outcomes are consistent with the findings reported by the Gift64 [5] authors. Additionally, as a demonstration of the tool's capabilities, we conducted **fuzzy** impossible differential cryptanalysis on a five-round Gift64 variant. The results, encompassing 7200 characteristics, are meticulously presented in Table 16. (In this representation, an asterisk (*) signifies any non-zero nibble value, while a hyphen (-) denotes any independently chosen non-zero nibble value.)

1	
Input Difference	Output Difference
00000000000000000	0000000000-00000
*000000000000000	0000000-000000000
0000000000000000000	000000000000000000000000000000000000000
000000000000000000	000000000000000000000000000000000000000
000000000000000000	00-000000000000000000000000000000000000
000000000000000000000000000000000000000	0000000-000000000
000000000000000000000000000000000000000	00-000000000000000000000000000000000000
000000000000000000000000000000000000000	000000000000000000
000000000000000000000000000000000000000	00000-000000000
000000000000000000000000000000000000000	000000000000000000000000000000000000000
000000000000000000000000000000000000000	000000000000000000
000000000000000000000000000000000000000	000000000000000000000
000000000000000000000000000000000000000	0-00000000000000000
0000000*0000000	00000-000000000
0000000*0000000	0-00000000000000000
0000000*00000000	0000000-0000000
0000000*00000000	0000-0000000000
000000*000000000	0000000000000000000000
0000000*000000000	0000000-0000000
000000*00000000000000000000000000000000	0000000000000000000000
000000*00000000000000000000000000000000	-00000000000000000
0000*0000000000000000000000000000000000	0000-00000000000
0000*0000000000000000000000000000000000	-00000000000000000
000*00000000000000000000000000000000000	00000000000000000000000
000*00000000000000000000000000000000000	0000000-00000000
00*000000000000000000000000000000000000	-0000000000000000
00*000000000000000000000000000000000000	00000000000000000000000
0*0000000000000000	-0000000000000000
0*000000000000000	000-00000000000000000000000000000000000
*000000000000000	0000000-00000000
*00000000000000	000-000000000000

Table 16: Impossible differential characteristics of Gift64 (r = 5)

Table 17: Differential characteristics of Skinny64

Rounds	Active SBoxes	Input Difference	Output Difference
1	1	000000000000000000	0002000000020002
2	2	000000A000000000	0004000400000004
3	5	1000000700100000	0020000000200020
4	8	9000000E00700000	0010010000100011
5	12	000100000003000	0414041000044414
6	16	00260400D0000000	0222022000022222
7	27	060204004800B005	C0060440C046C402

abie 10. imp	obbible amoreneial of		
	Input Difference	Output Difference	
	000*00000000000000	0000000-00000000	
	000*00000000000000000000000000000000000	000000-000000000	
	000*00000000000000000000000000000000000	0000-00000000000	
	00*00000000000000000	0000000-00000000	
	00*0000000000000000	000000-000000000	
	00*00000000000000000	00000-0000000000	
	0*0000000000000000	000000-000000000	
	0*0000000000000000	00000-0000000000	
	0*0000000000000000	0000-00000000000	
	*000000000000000	0000000-00000000	
	*000000000000000	00000-0000000000	
	*000000000000000	0000-00000000000	

Table 18: Impossible differential characteristics of Skinny64 (r = 11)

Table 19: Differential characteristics of Midori64

Rounds	Active SBoxes	Input Difference	Output Difference
1	1	0000000000000000D	0AAA000000000000000
2	4	0100000000000010	4440000044040000
3	7	0000000140000100	0000101188800888
4	16	0101011001110011	1011110100001110
5	23	000001000010000E	1011444022020302
6	32	0106000B00142004	4404202244400000
7	40	000000000080002	000051418C4C0000

Table 20: Differential characteristics of Klein

Rounds	Active SBoxes	Input Difference	Output Difference
1	1	0000000000000000	0DDED30D00000000
2	5	80800000000000808	D50D07D202060404
3	8	0505000000000005	0505DADF03DEDD05
4	15	020D000000000000	01D8D90103020100
5	17	0000000000000000000000000	C0B8783000000000

5.5 Skinny64

Table 17 presents the count of active SBox'es for Skinny64 [7] up to seven rounds as determined by our tool. It's worth noting that the authors reported 26 active SBox'es for a seven-round Skinny64, whereas our tool identified 27 active SBox'es. The difference can likely be attributed to the authors' utilization of N. Mouha's SBox modeling [29], as opposed to employing the more stringent models.

Furthermore, we showcase a collection of 2700 impossible differential characteristics obtained through a fuzzy search in Table 18. (In this representation, an asterisk (*) signifies any non-zero nibble value, while a hyphen (-) denotes any independently chosen non-zero nibble value.)

5.6 Midori64

Regarding Midori64 [4], we have documented the minimum counts of active SBox'es in Table 19. Specifically, for six and seven rounds of Midori64, our analysis yielded 32 and 40 active SBox'es, respectively. In contrast, the authors Midori64 [4] reported counts of 30 and 35 active SBox'es for the same rounds. It's important to note that the authors derived their counts not through the MILP method but by pursuing optimal permutations of the rows in which the cipher state is organized. Our counts for fewer rounds align with those of the authors. Furthermore, following a fuzzy search, our tool can not identify any impossible differentials for eight rounds or more.

5.7 Klein

Due to the intricate nature of Klein [19], stemming partly from the linear layer that involves matrix multiplication with elements interpreted as polynomials in \mathbb{F}_2^8 (modeled according to the approach outlined by B. Ilter and A. A. Selçuk [22]), we were able to ascertain the count of minimally active SBox'es in Klein only for a limited number of rounds, as reflected in Table 20. Similarly, owing to the same complexities, we have provided **equal** impossible differentials for four rounds of Klein in Table 21. The total count of impossible differential characteristics discovered in this context is 40.

6 Conclusion

In this paper, we present two innovative techniques for identifying the minimum set of inequalities to model the differential propagations of an SBox. The algorithms we propose for modeling the Difference Distribution Table (DDT) of an SBox demonstrate superior efficiency compared to existing methods. Recognizing that a greedy algorithm is only complete with the incorporation of a tiebreaker, we have developed a new version of the greedy approach employing a random tiebreaker. The results of the greedy random tiebreaker surpass those

37

input Difference	Output Difference	
000000000000000000000000000000000000000	00000080000000	
000000000000B00	0000000В0000000	
000000000000000000000000000000000000000	800000000000000000000000000000000000000	
000000000003000	000003000000000	
0000000000007000	000000000000000000000000000000000000000	
0000000000008000	800000000000000000	
0000000000008000	0000080000000000	
0000000000009000	000900000000000000000000000000000000000	
00000000000000000000000000000000000000	000B000000000000	
000000000000E000	000E000000000000	
0000000008000000	0008000000000000000	
0000000008000000	000080000000000000000000000000000000000	
000000000В000000	000B000000000000	
000000030000000	03000000000000000	
0000000070000000	0000000000070000	
000000080000000	0000800000000000000	
000000080000000	080000000000000000000000000000000000000	
0000000090000000	0000000900000000	
00000000В0000000	0000000В0000000	
00000000E0000000	0000000E00000000	
0000080000000000	00000080000000	
0000080000000000	800000000000000000000000000000000000000	
00000B0000000000	000000000000000B	
0000300000000000	000000000000300	
0000700000000000	0000000700000000	
000080000000000000000000000000000000000	00800000000000800	
0000800000000000000	0000000800000000	
000090000000000000000000000000000000000	0000000000090000	
0000B00000000000	00000000000000000000000000000000000000	
0000E00000000000	00000000000E0000	
080000000000000000000000000000000000000	0008000000008000	
080000000000000000000000000000000000000	000080000000000000000000000000000000000	
0B000000000000000000000000000000000000	00000000000B0000	
300000000000000000000000000000000000000	000000003000000	
700000000000000000000000000000000000000	0007000000000000	
800000000000000000000000000000000000000	00000080000000	
8000000000000000	000000000000000000000000000000000000000	
90000000000000000	00000000000000000	
B0000000000000000	000000000000000B	
E0000000000000000000000000000000000000	0000000000000000000E	

Table 21: Impossible differential characteristics of Klein (r = 4)Input DifferenceOutput Difference

of the original greedy method for certain SBoxes. The subset addition algorithm proves effective in modeling SBoxes up to 6 bits, providing better or nearly identical outcomes for most SBoxes. Additionally, we have enhanced the execution time required to identify minimized inequalities compared to previous implementations. We have explored a concise representation of the linear layer, primarily utilizing XOR gates. This approach harnesses the capacity of MILP solvers to handle not only binary variables but also non-binary integral variables. Notably, this model not only achieves a streamlined form but also outperforms alternative models in terms of computational efficiency.

Furthermore, we have developed, implemented, and demonstrated the functionality of a tool that can interpret this specification and autonomously embark on the quest for a differential characteristic (i.e., the minimum count of differentially active SBox'es) or impossible differential characteristics (i.e., pairs of input and output differences with a probability of zero) for any given number of rounds within a block cipher.

References

- 1. The sage developers. sagemath, the sage mathematics software system (version 9.0) (2020), https://www.sagemath.org.
- Abdelkhalek, A., Sasaki, Y., Todo, Y., Tolba, M., Youssef, A.M.: MILP modeling for (large) s-boxes to optimize probability of differential characteristics. IACR Trans. Symmetric Cryptol. 2017(4), 99–129 (2017), https://doi.org/10.13154/ tosc.v2017.i4.99-129
- Albrecht, M.R., Driessen, B., Kavun, E.B., Leander, G., Paar, C., Yalçin, T.: Block ciphers - focus on the linear layer (feat. PRIDE). In: Garay, J.A., Gennaro, R. (eds.) Advances in Cryptology - CRYPTO 2014 - 34th Annual Cryptology Conference, Santa Barbara, CA, USA, August 17-21, 2014, Proceedings, Part I. Lecture Notes in Computer Science, vol. 8616, pp. 57–76. Springer (2014), https://doi.org/10. 1007/978-3-662-44371-2_4
- Banik, S., Bogdanov, A., Isobe, T., Shibutani, K., Hiwatari, H., Akishita, T., Regazzoni, F.: Midori: A block cipher for low energy. In: Advances in Cryptology – ASIACRYPT 2015. pp. 411–436 (2015)
- Banik, S., Pandey, S.K., Peyrin, T., Sasaki, Y., Sim, S.M., Todo, Y.: GIFT: A small present - towards reaching the limit of lightweight encryption. In: Fischer, W., Homma, N. (eds.) Cryptographic Hardware and Embedded Systems - CHES 2017 - 19th International Conference, Taipei, Taiwan, September 25-28, 2017, Proceedings. Lecture Notes in Computer Science, vol. 10529, pp. 321–345 (2017), https://doi.org/10.1007/978-3-319-66787-4_16
- Bay, A., Jr., J.N., Vaudenay, S.: Cryptanalysis of reduced-round MIBS block cipher. In: Heng, S., Wright, R.N., Goi, B. (eds.) Cryptology and Network Security -9th International Conference, CANS 2010, Kuala Lumpur, Malaysia, December 12-14, 2010. Proceedings. Lecture Notes in Computer Science, vol. 6467, pp. 1– 19. Springer (2010). https://doi.org/10.1007/978-3-642-17619-7_1, https:// doi.org/10.1007/978-3-642-17619-7_1
- Beierle, C., Jean, J., Kölbl, S., Leander, G., Moradi, A., Peyrin, T., Sasaki, Y., Sasdrich, P., Sim, S.M.: The skinny family of block ciphers and its low-latency variant mantis. In: Advances in Cryptology – CRYPTO 2016. pp. 123–153 (2016)

- Berger, T.P., Francq, J., Minier, M., Thomas, G.: Extended generalized feistel networks using matrix representation to propose a new lightweight block cipher: Lilliput. IEEE Trans. Computers 65(7), 2074–2089 (2016). https://doi.org/10. 1109/TC.2015.2468218, https://doi.org/10.1109/TC.2015.2468218
- Biham, E., Anderson, R.J., Knudsen, L.R.: Serpent: A new block cipher proposal. In: Vaudenay, S. (ed.) Fast Software Encryption, 5th International Workshop, FSE '98, Paris, France, March 23-25, 1998, Proceedings. Lecture Notes in Computer Science, vol. 1372, pp. 222–238. Springer (1998)
- Biham, E., Shamir, A.: Differential Cryptanalysis of the Data Encryption Standard. Springer-Verlag, Berlin, Heidelberg (1993)
- Bilgin, B., Bogdanov, A., Knezevic, M., Mendel, F., Wang, Q.: Fides: Lightweight authenticated cipher with side-channel resistance for constrained hardware. In: Bertoni, G., Coron, J. (eds.) Cryptographic Hardware and Embedded Systems -CHES 2013 - 15th International Workshop, Santa Barbara, CA, USA, August 20-23, 2013. Proceedings. Lecture Notes in Computer Science, vol. 8086, pp. 142–158. Springer (2013)
- Borghoff, J., Canteaut, A., Güneysu, T., Kavun, E.B., Knezevic, M., Knudsen, L.R., Leander, G., Nikov, V., Paar, C., Rechberger, C., Rombouts, P., Thomsen, S.S., Yalçin, T.: PRINCE - A low-latency block cipher for pervasive computing applications (full version). IACR Cryptol. ePrint Arch. p. 529 (2012)
- Boura, C., Coggia, D.: Efficient MILP modelings for sboxes and linear layers of SPN ciphers. IACR Trans. Symmetric Cryptol. 2020(3), 327–361 (2020), https: //doi.org/10.13154/tosc.v2020.i3.327-361
- Browning, K., Dillon, J., McQuistan, M., Wolfe., A.: App permutation in dimension six. In: Postproceedings of the 9th International Conference on Finite Fields and Their Applications (2010)
- Cui, T., Jia, K., Fu, K., Chen, S., Wang, M.: New automatic search tool for impossible differentials and zero-correlation linear approximations. IACR Cryptol. ePrint Arch. p. 689 (2016), http://eprint.iacr.org/2016/689
- Daemen, J., Rijmen, V.: The wide trail design strategy. In: Honary, B. (ed.) Cryptography and Coding, 8th IMA International Conference, Cirencester, UK, December 17-19, 2001, Proceedings. Lecture Notes in Computer Science, vol. 2260, pp. 222–238. Springer (2001)
- Dobraunig, C., Eichlseder, M., Mendel, F., Schläffer, M.: Ascon v1.2: Lightweight authenticated encryption and hashing. J. Cryptol. 34(3), 33 (2021), https://doi. org/10.1007/s00145-021-09398-9
- Fu, K., Wang, M., Guo, Y., Sun, S., Hu, L.: Milp-based automatic search algorithms for differential and linear trails for speck. In: Peyrin, T. (ed.) Fast Software Encryption - 23rd International Conference, FSE 2016, Bochum, Germany, March 20-23, 2016, Revised Selected Papers. Lecture Notes in Computer Science, vol. 9783, pp. 268-288. Springer (2016), https://doi.org/10.1007/978-3-662-52993-5_14
- Gong, Z., Nikova, S., Law, Y.W.: Klein: A new family of lightweight block ciphers. In: RFID. Security and Privacy. pp. 1–18 (2012)
- 20. Gurobi Optimization LLC.: Gurobi optimizer reference manual. 9.5.2 (2022), https://www.gurobi.com/, https://www.gurobi.com/
- Han, G., Zhang, W., Zhao, H.: An upper bound of the longest impossible differentials of several block ciphers. KSII Trans. Internet Inf. Syst. 13(1), 435–451 (2019). https://doi.org/10.3837/TIIS.2019.01.024, https://doi.org/10.3837/tiis.2019.01.024

- 40 D Pal et al.
- Ilter, M.B., Selçuk, A.A.: A new milp model for matrix multiplications with applications to klein and prince. In: Proceedings of the 18th International Conference on Security and Cryptography, SECRYPT 2021. pp. 420–427 (2021)
- Izadi, M., Sadeghiyan, B., Sadeghian, S.S., Khanooki, H.A.: MIBS: A new lightweight block cipher. In: Garay, J.A., Miyaji, A., Otsuka, A. (eds.) Cryptology and Network Security, 8th International Conference, CANS 2009, Kanazawa, Japan, December 12-14, 2009. Proceedings. Lecture Notes in Computer Science, vol. 5888, pp. 334–348. Springer (2009)
- Kim, J., Hong, S., Sung, J., Lee, S., Lim, J., Sung, S.: Impossible differential cryptanalysis for block cipher structures. In: Progress in Cryptology – INDOCRYPT 2003. pp. 82–96 (2003)
- Li, T., Sun, Y.: Superball: A new approach for MILP modelings of boolean functions. IACR Trans. Symmetric Cryptol. 2022(3), 341–367 (2022)
- Luo, Y., Wu, Z., Lai, X., Gong, G.: A unified method for finding impossible differentials of block cipher structures. Cryptology ePrint Archive, Paper 2009/627 (2009)
- Matsui, M.: On correlation between the order of s-boxes and the strength of DES. In: Santis, A.D. (ed.) Advances in Cryptology - EUROCRYPT '94, Workshop on the Theory and Application of Cryptographic Techniques, Perugia, Italy, May 9-12, 1994, Proceedings. Lecture Notes in Computer Science, vol. 950, pp. 366– 375. Springer (1994). https://doi.org/10.1007/BFb0053451, https://doi.org/ 10.1007/BFb0053451
- Matsui, M., Yamagishi, A.: A new method for known plaintext attack of FEAL cipher. In: Rueppel, R.A. (ed.) Advances in Cryptology EUROCRYPT '92, Workshop on the Theory and Application of of Cryptographic Techniques, Balaton-füred, Hungary, May 24-28, 1992, Proceedings. Lecture Notes in Computer Science, vol. 658, pp. 81–91. Springer (1992), https://doi.org/10.1007/3-540-47555-9_7
- Mouha, N., Wang, Q., Gu, D., Preneel, B.: Differential and linear cryptanalysis using mixed-integer linear programming. In: Wu, C., Yung, M., Lin, D. (eds.) Information Security and Cryptology - 7th International Conference, Inscrypt 2011, Beijing, China, November 30 - December 3, 2011. Revised Selected Papers. Lecture Notes in Computer Science, vol. 7537, pp. 57–76. Springer (2011), https://doi. org/10.1007/978-3-642-34704-7_5
- Pal, D., Chandratreya, V.P., Chowdhury, D.R.: New techniques for modeling sboxes: An MILP approach. In: Deng, J., Kolesnikov, V., Schwarzmann, A.A. (eds.) Cryptology and Network Security - 22nd International Conference, CANS 2023, Augusta, GA, USA, October 31 - November 2, 2023, Proceedings. Lecture Notes in Computer Science, vol. 14342, pp. 318-340. Springer (2023). https://doi.org/10.1007/978-981-99-7563-1_15, https://doi.org/10.1007/ 978-981-99-7563-1_15
- 31. Sasaki, Y., Todo, Y.: New algorithm for modeling s-box in MILP based differential and division trail search. In: Farshim, P., Simion, E. (eds.) Innovative Security Solutions for Information Technology and Communications - 10th International Conference, SecITC 2017, Bucharest, Romania, June 8-9, 2017, Revised Selected Papers. Lecture Notes in Computer Science, vol. 10543, pp. 150–165. Springer (2017), https://doi.org/10.1007/978-3-319-69284-5_11
- Sasaki, Y., Todo, Y.: New impossible differential search tool from design and cryptanalysis aspects. In: Advances in Cryptology – EUROCRYPT 2017. pp. 185–215 (2017)

- 33. Sasaki, Y., Todo, Y.: New impossible differential search tool from design and cryptanalysis aspects - revealing structural properties of several ciphers. In: Coron, J., Nielsen, J.B. (eds.) Advances in Cryptology - EUROCRYPT 2017 - 36th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Paris, France, April 30 - May 4, 2017, Proceedings, Part III. Lecture Notes in Computer Science, vol. 10212, pp. 185–215 (2017), https: //doi.org/10.1007/978-3-319-56617-7_7
- Sasaki, Y., Todo, Y.: Tight bounds of differentially and linearly active s-boxes and division property of lilliput. IEEE Transactions on Computers 67(5), 717–732 (2018)
- 35. Sasaki, Y., Todo, Y., Aoki, K., Naito, Y., Sugawara, T., Murakami, Y., Matsui, M., Hirose, S.: Minalpher. In: Directions in Authenticated Ciphers (DIAC 2014). pp. 23-24 (2014), https://info.isl.ntt.co.jp/crypt/minalpher/files/ minalpher-diac2014.pdf
- 36. Shimoyama, T., Yanami, H., Yokoyama, K., Takenaka, M., Itoh, K., Yajima, J., Torii, N., Tanaka, H.: The block cipher SC2000. In: Matsui, M. (ed.) Fast Software Encryption, 8th International Workshop, FSE 2001 Yokohama, Japan, April 2-4, 2001, Revised Papers. Lecture Notes in Computer Science, vol. 2355, pp. 312–327. Springer (2001), https://doi.org/10.1007/3-540-45473-X_26
- 37. Sun, S., Hu, L., Song, L., Xie, Y., Wang, P.: Automatic security evaluation of block ciphers with s-bp structures against related-key differential attacks. In: Lin, D., Xu, S., Yung, M. (eds.) Information Security and Cryptology 9th International Conference, Inscrypt 2013, Guangzhou, China, November 27-30, 2013, Revised Selected Papers. Lecture Notes in Computer Science, vol. 8567, pp. 39–51. Springer (2013), https://doi.org/10.1007/978-3-319-12087-4_3
- 38. Sun, S., Hu, L., Wang, M., Wang, P., Qiao, K., Ma, X., Shi, D., Song, L., Fu, K.: Towards finding the best characteristics of some bit-oriented block ciphers and automatic enumeration of (related-key) differential and linear characteristics with predefined properties. Cryptology ePrint Archive, Paper 2014/747 (2014), https://eprint.iacr.org/2014/747
- 39. Sun, S., Hu, L., Wang, P., Qiao, K., Ma, X., Song, L.: Automatic security evaluation and (related-key) differential characteristic search: Application to simon, present, lblock, DES(L) and other bit-oriented block ciphers. In: Sarkar, P., Iwata, T. (eds.) Advances in Cryptology ASIACRYPT 2014 20th International Conference on the Theory and Application of Cryptology and Information Security, Kaoshiung, Taiwan, R.O.C., December 7-11, 2014. Proceedings, Part I. Lecture Notes in Computer Science, vol. 8873, pp. 158–178. Springer (2014)
- Wu, S., Wang, M.: Automatic search of truncated impossible differentials for wordoriented block ciphers. In: Progress in Cryptology – INDOCRYPT 2012. pp. 283– 302 (2012)
- Wu, W., Zhang, L.: Lblock: A lightweight block cipher. In: López, J., Tsudik, G. (eds.) Applied Cryptography and Network Security 9th International Conference, ACNS 2011, Nerja, Spain, June 7-10, 2011. Proceedings. Lecture Notes in Computer Science, vol. 6715, pp. 327–344 (2011)
- 42. Yin, J., Ma, C., Lyu, L., Song, J., Zeng, G., Ma, C., Wei, F.: Improved cryptanalysis of an ISO standard lightweight block cipher with refined MILP modelling. In: Chen, X., Lin, D., Yung, M. (eds.) Information Security and Cryptology - 13th International Conference, Inscrypt 2017, Xi'an, China, November 3-5, 2017, Revised Selected Papers. Lecture Notes in Computer Science, vol. 10726, pp. 404–426 (2017), https://doi.org/10.1007/978-3-319-75160-3_24

- 42 D Pal et al.
- 43. Zhang, W., Bao, Z., Lin, D., Rijmen, V., Yang, B., Verbauwhede, I.: RECTANGLE: A bit-slice ultra-lightweight block cipher suitable for multiple platforms. IACR Cryptol. ePrint Arch. p. 84 (2014)