A semantic loss for ontology classification

Simon Flügel^{1[0000-0003-3754-9016]}, Martin Glauer^{1[0000-0001-6772-1943]}, Till Mossakowski^{1[0000-0002-8938-5204]}, and Fabian Neuhaus^{1[0000-0002-1058-3102]}

Otto von Guericke University Magdeburg, Germany {sfluegel, martin.glauer, till.mossakowski, fneuhaus}@ovgu.de

Abstract. Deep learning models are often unaware of the inherent constraints of the task they are applied to. However, many downstream tasks require logical consistency. For ontology classification tasks, such constraints include subsumption and disjointness relations between classes. In order to increase the consistency of deep learning models, we propose a semantic loss that combines label-based loss with terms penalising subsumption- or disjointness-violations. Our evaluation on the ChEBI ontology shows that the semantic loss is able to decrease the number of consistency violations by several orders of magnitude without decreasing the classification performance. In addition, we use the semantic loss for unsupervised learning. We show that this can further improve consistency on data from a distribution outside the scope of the supervised training.

Keywords: Semantic loss · ontology classification · ChEBI

1 Introduction

Deep learning models have been successfully applied to a wide range of classification tasks over the past years, often replacing hand-crafted features with end-to-end feature learning [7,3]. This approach is based on the assumption that all the knowledge required to solve a specific classification task is available in the data used. These systems are often built for a specific use case. In the case of a classification problem, emphasis is placed on the correct classification of the input data and the success of a system is measured in its ability to correctly perform this task. However, this approach disregards that there are often domain-specific logical constraints between different classification targets.

These logical constraints can be of great importance, as applications, especially those leading to further development, are often based on the assumption that inputs are logically consistent. Imagine a system consisting of two components in an autonomous vehicle. The first component recognises and labels objects using a deep learning model. Based on this output, a rule-based system built by experts determines the direction of travel. A contradictory classification of the first system, e.g. a traffic light as both red and green, or a road user as a pedestrian and as a car, can have fatal consequences, as the control system may not cover such a scenario.

It is therefore important to prime systems towards logical consistency. Learning concepts by example is not optimally suited to adhere to domain-specific constraints out of to box. Instead, reliance is placed on the fact that the corresponding constraints are represented in the data and that the model can approximate them accordingly during training. However, this approach has significant disadvantages. Firstly, it assumes that there is a sufficiently large amount of data so that the corresponding constraints are well represented. Secondly, the system is deprived of important information that is readily available in the domain. Thirdly, it creates an additional, implicit learning task that is not adequately represented by the loss function.

For many research domains, ontologies exist that define important concepts and their relations via logical constraints [20,4,2]. Ontologies therefore provide a necessary logical axiomatisation that can be used to check the consistency of models and to prime them for consistency. For instance, the subsumption relation A is-a B requires that every entity classified as A is also classified as B. Usually, this knowledge is not explicitly given to machine learning models trained on concepts from an ontology. Instead, it can only be derived implicitly from seeing a large enough number of A samples that are also B samples.

The aim of this paper is to integrate symbolic knowledge from ontologies into the learning process of a machine learning model. To this end, in Section 3, we present a *semantic loss* that extends regular loss functions by additional terms that ensure the model's coherence with ontological constraints. In Section 4, we introduce a classification task on the ChEBI ontology and appropriate evaluation metrics. These are used in Section 5, where we evaluate different semantic loss variants. The results are discussed in Section 6 and a conclusion is drawn in Section 7.

2 Related Work

A well-studied field within Machine Learning are hierarchical multi-label classification tasks, in which labels are structured in a hierarchy, similar the subsumption relations in an ontology. However, it is usually assumed that each class only has one superclass which allows the assigning of hierarchy levels. Many models use these levels directly in their architecture [27,5]. In ontologies such as ChEBI, many classes have multiple superclasses, which makes the assignment of hierarchy levels non-trivial. In addition, ontologies include different kinds of logical relations between classes, such as disjointness or parthood relations. Therefore, our tasks requires a more general approach towards ensuring logical consistency.

Among the approaches that have integrated logical constraints into neural networks, one of the earliest have been "Knowledge-Based Artificial Neural Networks" (KBANN, [26]), which attempted to directly represent formulae in propositional logic within the network structure. During training, the system is able to adapt these structures to better fit the training data. This allows the priming of a learning system with prior knowledge.

The training process of neural networks is usually based on a form of gradient descent. Consequently, in order to allow answers as truth values $\{0, 1\}$, one must allow arbitrary predictions from [0, 1] in order to remain differentiable. This naturally leads to an interpretation of these values as values from a manyvalued logic such as fuzzy logic or probabilistic logic. Indeed, there have been many approaches that aim to combine fuzzy systems and neural networks [22,30]. These systems are particularly useful when training data is limited. In a recent work [16,19], we applied an ontology-based neuro-fuzzy controller. The approach in this paper is inspired by this work, in which we also apply a semantic penalty system to ensure logically sound rules.

DeepProbLog [23] follows a probabilistic interpretation of prediction values. This approach is based on the probabilistic logic programming framework ProbLog [9]. ProbLog allows the expression of Prolog-like inference rules with additional uncertainty annotations, e.g. 0.3::P(X) := Q(X), R(X). The formulation of these rules does, however, require extensive expert knowledge or data in order to derive the appropriate annotations. DeepProbLog extends this framework by allowing uncertainty annotations to be derived from a neural network. Logic Tensor Networks (LTNs,[1]) train neural predicates to maximise satisfiability of a background theory, which is a form of semantic loss.

Neural networks are, in particular during training, prone to making mistakes that may result in logically inconsistent predictions. An image recognition system may, for example, classify the same picture as a cat and a dog. In combination with logic approaches, these mistakes may cause severe side effects for other systems that expect consistent input [11]. In most classical logics, once an inconsistency has been derived, any statement is entailed. This strong effect of inconsistencies is not desirable in applications that must allow for some level of inconsistency - in particular if human input is used. If a person makes an inconsistent statement in their tax form, a possible neuro-symbolic tax system should not be able to infer that Elvis is the king of Sweden or other arbitrary facts from that - the inconsistency should be kept local. Logical Neural Networks (LNNs, [25]) allow for some local inconsistencies in their reasoning process. This kind of network is designed to directly represent the structure of a logical theory with upper and lower bounds instead of truth values. During inference, these systems also use a semantic penalty term that trains the system to avoid logical inconsistencies.

Xu et al. propose a more general definition of a semantic loss for arbitrary logical sentences [29]. Neural network outputs in a multi-class classification task are interpreted as probabilities, leading to a probability that can be assigned to each state in which a given logical sentence is either satisfied or not. The loss function is then defined as the negative logarithm of the sum of probabilities for each variable assignment satisfying the sentence φ in question:

$$L_{Xu}(\varphi, p) \propto -\log \sum_{x \models \varphi} \prod_{x \models X_i} p_i \prod_{i: x \models \neg X_i} (1 - p_i)$$
(1)

Models in this loss definition are binary. Therefore, a given model satisfies $A \sqsubseteq B$ if and only if $x \models \neg A$ or $x \models B$. For an implication $A \sqsubseteq B$ and a prediction vector p, the loss is calculated as

$$L_{Xu}(A \sqsubseteq B, p) \propto -\log \sum_{\substack{x \models A \sqsubseteq B}} \prod_{\substack{x \models X_i}} p_i \prod_{\substack{i:x \models \neg X_i}} (1-p_i)$$

= $-\log((1-p_a) \cdot (1-p_b) + (1-p_a) \cdot p_b + p_a \cdot p_b)$ (2)
= $-\log(p_a \cdot p_b - p_a + 1)$
= $-\log(1-p_a \cdot (1-p_b))$

The loss definition of Xu et al. is similar to the one used in this work, although we derive our loss from fuzzy logic instead of probabilistic. When using the product t-norm, our loss for an implication is defined as

$$L_{prod}(A \sqsubseteq B, p) = p_a \cdot (1 - p_b) \tag{3}$$

The additional negative logarithm is introduced by Xu et al. to achieve a closer correspondence to cross-entropy loss functions, while we use the result of the logical evaluation directly. For comparison, we include the semantic loss defined by Xu et al. in our evaluation in Section 5.

3 Semantic loss

Predictions made by a neural network may contradict a logical theory that underlies the predicted labels. In this work, we aim to incentivise a model to produce logically more consistent predictions by adding an additional term to its loss function. While many types of ontology axioms exist, here, we focus on two types that are widely used and domain independent: subsumption relations, i.e., $A \sqsubseteq B$, and disjointness, i.e., $C \sqcap D \equiv \bot$. While these axioms are usually interpreted in binary semantics, we need differentiable terms that can be used for training a neural network. We achieve differentiability by applying a fuzzylogic interpretation [17] to our output values. Let $h_c : x \to [0, 1]$ be a fuzzy membership function for a given class c and T a fuzzy t-norm. Our semantic loss term for implications is then defined as

$$L_T(A \sqsubseteq B, x) := \hat{h}(\neg (A \to B), x) = \hat{h}(A \land \neg B, x) = T(h_A(x), 1 - h_B(x)).$$
(4)

This assumes that the fuzzy negation used is a strong negation N(x) = 1 - x. Accordingly, the semantic loss term for disjointness is defined as

$$L_T(C \sqcap D \equiv \bot, x) := \hat{h}(\neg \neg (C \land D), x) = \hat{h}(C \land D, x) = T(h_C(x), h_D(x)).$$
(5)

Intuitively, the semantic loss can be interpreted as the degree to which a given prediction violates an ontological constraint.

In Section 5, we evaluate loss functions derived from two commonly used t-norms, the product t-norm $T_{prod}(a,b) = a \cdot b$ and the Łukasiewicz t-norm $T_{luka}(a,b) = \max(a+b-1,0).$

Let **x** be a vector of length *m* of sample vectors, **y** the vector of *m* corresponding label vectors and $\hat{\mathbf{y}} = [h_A(x)]_{A \in O}$ the vector of predicted labels. Based on the loss terms given in Eqs 4 and 5, we define our loss function as follows:

$$L_{T}(\mathbf{x}, \mathbf{y}) = L_{base}(\mathbf{y}, \hat{\mathbf{y}}) + \frac{w_{impl}}{m} \sum_{i=1}^{m} \sum_{A \sqsubseteq B} T((\hat{y}_{i})_{A}, 1 - (\hat{y}_{i})_{B}) + \frac{w_{disj}}{m} \sum_{i=1}^{m} \sum_{C \sqcap D \equiv \bot} T((\hat{y}_{i})_{C}, (\hat{y}_{i})_{D})$$

$$(6)$$

The L_{base} term refers to the supervised loss used to train the model on the classification task. The weights w_{impl} and w_{disj} are intended to adjust the importance of the semantic loss terms in relation to the base loss and to compensate for the different prevalences of the axiom types in the ontology. In general, we expect the number of subsumption and disjointness relations in an ontology to vary based on the hierarchy depth and number of disjointness axioms available. Therefore, these weights have to be adjusted based on the task at hand.

3.1 Balanced implication loss

The loss terms for implication face an imbalance issue: Since the classes on the left-hand side of each implication are subclasses of the right-hand side classes, they necessarily have fewer members in the ontology and therefore fewer labels in a given dataset. Since we include transitive subsumption relations as well, the difference may be drastic, with some left-hand side classes representing only a small fraction of the right-hand side class. Therefore, in case of violations, it might be relatively inexpensive for the model to disregard classes further down in the hierarchy entirely. This strategy results in a low number of implication violations, since such classes appear mostly on the left-hand side of implications, and a low supervised loss, due to the lack of positive samples.

However, this behaviour is clearly not in our interest. To counter-balance this effect, the *balanced implication loss* has a lower gradient for the left-hand class and a higher gradient for the right-hand class instead of applying the same gradient to both classes. Practically, this is achieved with two additional parameters k > 1 and $\epsilon > 0$:

$$L_T^B(A \sqsubseteq B, x; k, \epsilon) = T(\frac{((h_A(x) + \epsilon)^{1/k} - \epsilon^{1/k})}{((1 + \epsilon)^{1/k} - \epsilon^{1/k})}, (1 - h_B(x))^k)$$
(7)

 ϵ is a small constant that is added to $h_A(x)$ to avoid an infinite gradient at $h_A(x) = 0$. The additional ϵ -terms adjust the loss so that $L_T^B = 0$ if $h_A(x) = 0$ and $L_T^B = 1$ if $h_A(x) = 1$ and $h_B(x) = 0$. In our evaluation, we will use $\epsilon = 0.01$. The parameter k modifies the loss term such that, in the maximal violation case of $h_A(x) = 1$ and $h_B(x) = 0$, the gradient is larger for h_B than for h_A . For instance, for the product T-norm, $\frac{\partial L_{prod}^B}{\partial h_A(x)}\Big|_1 = \frac{1}{k}$ and $\frac{\partial L_{prod}^B}{\partial h_B(x)}\Big|_0 = -k$.

The regular implication loss can be seen as a specialised version of this balanced implication loss where $k = \epsilon = 0$.

4 Experimental setup

We evaluate the semantic loss for a classification task in the ChEBI ontology. This task has been studied in our previous work and a deep learning-based approach for the ChEBI classification task has been developed [18,12,13]. In all evaluations, we train an ELECTRA model [6] for a hierarchical multi-label classification task in which ChEBI classes act as labels and molecules as instances. For a detailed description of the approach, we refer to [14]. Here, we just provide an overview. The source code for our implementation is available on GitHub¹.

¹ https://github.com/ChEB-AI/python-chebai

4.1 Datasets

Our setup draws data from two sources. Labelled data is taken from the ChEBI ontology [10,20], while additional unlabelled data is sourced from the PubChem database [21]. All datasets are available on Kaggle ².

In all datasets, we use the SMILES (Simplified Molecular Input Line Entry System) [28], a common string representation for chemical structures. It encodes molecules as sequences in which characters represent atoms and bonds, with additional notation for branches, rings and stereoisomerism.

For the labelled data, we use version 231 of ChEBI, which contains 185 thousand SMILES-annotated classes. Out of these classes, we form the ChEBI₁₀₀ dataset by attaching all superclasses as labels which have at least 100 SMILESannotated subclasses. The transitive closure of subsumption relations between the labels is used for the semantic loss. Disjointness axioms for ChEBI are provided by an additional ontology module ³. Here as well, we take the transitive closure of all disjointness relations between label-classes. In total, this provides us with 997 labels, 19,308 implication loss terms and 31,416 disjointness loss terms.

From PubChem, we have sourced two distinct datasets. The first is used during training while the second one, *PubChem Hazardous*, is only used in the evaluation. The Hazardous dataset includes SMILES strings for chemicals that are annotated with a class from the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) [24]. The GHS covers different kinds of health, physical and environmental hazards and has been developed by the United Nations as a standard for labelling hazardous chemicals and providing related safety instructions. From this, we have removed all SMILES strings that also appear in the labelled dataset. In our evaluation, we use this dataset to test model performance for a data distribution outside the learning distribution.

For the training dataset, we have randomly selected 1 million SMILES strings from PubChem. This set has been split into groups of 10,000. From each group, we have selected the 2,000 SMILES strings with the lowest similarity score, resulting in 200,000 instances. The similarity score used is the sum of pairwise Tanimoto similarities between the RDKit fingerprints of a given SMILES string and all other SMILES strings in the group. This way, we ensure with limited computational expense that our dataset covers a broad range of chemicals.

The training set is used for two tasks: Firstly, a pretraining step prior to the training on the $ChEBI_{100}$ dataset which is shared by all models in our evaluation. And secondly, a semi-supervised training, in which we train a model simultaneously on labelled and unlabelled data. In our evaluation, we will compare semi-supervised training to training on only labelled data.

4.2 Loss function

In order to apply the semantic loss function from Eq. 6, we need to choose a classification loss L_{base} and assign the weights w_{impl} and w_{disj} .

² https://www.kaggle.com/datasets/sfluegel/chebai-semantic-loss

³ https://ftp.ebi.ac.uk/pub/databases/chebi/ontology/chebi-disjoints.owl

For the classification loss, we have chosen a weighted binary cross-entropy loss:

$$L_{base}(\mathbf{x}, \mathbf{y}) = \frac{1}{m} \sum_{i=1}^{m} \sum_{c \in C} w_c y_c \cdot \log h_c(x) + (1 - y_c) \cdot \log(1 - h_c(x))$$
(8)

Here, w_c is a weight assigned to positive entries based on the class c. These weights are used to increase the importance of classes with fewer members in an imbalanced dataset. We apply the scheme introduced by [8] with $\beta = 0.99$ and normalize the weights:

$$w_{c} = \frac{w_{c}' \cdot |C|}{\sum_{c' \in C} w_{c'}'} \text{ where } w_{c}' = \frac{1 - \beta}{1 - \beta^{|c|}}$$
(9)

For the semantic loss terms, although the number of disjointness terms (31,416) is larger than the number of implication terms (19,308), we have chosen the weights $w_{impl} = 0.01$ and $w_{disj} = 100$. This is motivated by preliminary experiments in which the implication loss was larger than the disjointness loss by several orders of magnitude.

4.3 Violation metrics

In order to quantify the consistency of model predictions with the ontology, we introduce a notion of true positives (TPs) and false negatives (FNs) for consistency violations. In this context, all pairs of $ChEBI_{100}$ -labels are considered as violation-labels. These labels are positive if an explicit subsumption / disjointness relation between both classes exists in ChEBI. Individual predictions are converted into truth values according to a threshold of 0.5 and the resulting truth values are compared against the label-pairs.

Given a sample x, we define the number of TPs as

$$\#TP_{impl}(x) = |\{(A,B) : A \sqsubseteq B \land h_A(x) > 0.5 \land h_B(x) > 0.5\}|$$
(10)

and the number of FNs as

$$\#FN_{impl}(x) = |\{(A,B) : A \sqsubseteq B \land h_A(x) > 0.5 \land h_B(x) \le 0.5\}|.$$
(11)

For disjointness, the definition is analogous:

$$\#TP_{disj}(x) = |\{(C, D) : C \sqcap D \equiv \bot \land h_C(x) > 0.5 \land h_D(x) \le 0.5\}|$$
(12)

$$\#FN_{disj}(x) = |\{(C,D) : C \sqcap D \equiv \bot \land h_C(x) > 0.5 \land h_D(x) > 0.5\}|.$$
(13)

This definition does not take the cases $h_A(x) \leq 0.5$ or $h_C(x) \leq 0.5$ into account which could be considered as true positives as well since they do not contradict the ontology axioms. However, since these cases do not require an active prediction, we consider them as "consistent by default" and as less relevant for our evaluation. Note that, although disjointness axioms are symmetric, this non-symmetric metric requires that we consider both "directions" of the axiom:

Vocabulary size	$1,\!400$
Hidden size	256
# attention heads	8
# hidden layers	6
# max. epochs	200
learning rate	$1e^{-3}$
Optimizer	Adamax
w_{impl}	0.01
w_{disj}	100
β	0.99

Table 1: Hyperparameters used during training

If $C \sqcap D \equiv \bot$, $h_C(x) \leq 0.5$ and $h_D(x) > 0.5$, we do not count (C, D) as a true positive, but instead count (D, C). This also means that $\#FN_{disj}(x)$ will necessarily be even since for every false negative (C, D), there is another false negative (D, C).

Given the numbers of TPs and FNs, we use the false negative rate (FNR), defined as

$$FNR_t(x) = \frac{\#FN_t(x)}{\#FN_t(x) + \#TP_t(x)},$$
(14)

in our evaluation, t being either *impl* or *disj*.

5 Results

We evaluate four configurations of the semantic loss, one using the Łukasiewicz T-norm $T_{Luka}(x, y) = \max(0, a + b - 1)$ and three using the product T-norm $T_{prod}(x, y) = x \cdot y$. For the product T-norm, we include, besides the "standard" variant, one which uses the balanced implication loss L^B described in Section 3.1 with k = 2 and the semi-supervised variant trained on a mixed ChEBI₁₀₀ and PubChem dataset (see Section 4.1). For comparison, we also include a configuration using the semantic loss described by Xu et al. [29] and a baseline configuration trained without semantic loss.

We have conducted a pretraining run on our PubChem dataset and subsequently, 3 fine-tuning runs for each variant. In the following, we will only report averages for the 3 runs, the results for individual runs can be found in Appendix A.

The hyperparameters shared by all models are given in Table 1.We have split the ChEBI₁₀₀ dataset into a training, validation and test set with a 340/9/51 ratio. The evaluation has been conducted on the test set using the models with the highest micro-F1 score from each training run.

Table 2 and Figure 1a show the false negative rate (FNR) for implication and disjointness violations on the ChEBI₁₀₀ and the PubChem Hazardous datasets. It can be seen that all models outperform the baseline by a margin of about two orders of magnitude. In absolute terms, this corresponds to 13×10^3 false

	$ChEBI_{100}$	PubChem Hazardous
baseline	0.0031 ± 0.0002	0.0067 ± 0.005
T_{Luka}	${\bf 2.09\times 10^{-5}\pm 3.3\times 10^{-6}}$	$1.49 \times 10^{-5} \pm 2.6 \times 10^{-5}$
T_{prod}	$3.18 \times 10^{-5} \pm 1.2 \times 10^{-5}$	$5.54 \times 10^{-5} \pm 4.6 \times 10^{-5}$
T_{prod} (k=2)	$3.74 \times 10^{-5} \pm 1.5 \times 10^{-5}$	$7.29 \times 10^{-5} \pm 8.8 \times 10^{-5}$
T_{prod} (mixed data)	$5.91 \times 10^{-5} \pm 3.2 \times 10^{-5}$	$1.05 imes 10^{-5} \pm 9.8 imes 10^{-6}$
Xu et al.	$3.62 \times 10^{-5} \pm 1.2 \times 10^{-5}$	$3.93 \times 10^{-5} \pm 2.8 \times 10^{-5}$

Table 2: Average FNR for binary implication violations on the $ChEBI_{100}$ and PubChem Hazardous datasets. The FNR has been calculated separately for each run before averaging. In addition, the table shows the standard deviation between the runs.





 $ChEBI_{100}$ (left) and PubChem Hazardous gregated on the micro- (left) and macrodatasets. The standard deviation is indi- level. The black bars indicate the standard cated by black dashes along each bar.

(a) FNR for implication violations on the (b) F1-scores on the ChEBI₁₀₀ dataset, agdeviation between the 3 runs.

negatives for the baseline and between 81 FNs (for T_{Luka}) and 247 FNs (T_{prod}) with mixed data) for the semantic loss models. The number of true positives is similar for all models (between 3.85×10^6 and 4.29×10^6).

For the Łukasiewicz t-norm models, we observe the lowest FNR on $ChEBI_{100}$. The models trained with a product t-norm based loss and the semantic loss of Xu et al. have slightly higher FNRs on ChEBI₁₀₀. Regarding the PubChem Hazardous dataset, it is remarkable that, while most models have a smiliar or slightly higher FNR compared to ChEBI₁₀₀, the models trained with additional PubChem data perform significantly better on PubChem Hazardous.

Regarding the disjointness violations, we have not observed any violations for any model except the baseline models. There, we have averages of 171 FNs on ChEBI₁₀₀ and 4 FNs on PubChem Hazardous. While these numbers are far below the numbers of TPs $(1.07 \times 10^7 \text{ for ChEBI}_{100} \text{ and } 1.12 \times 10^8 \text{ for PubChem}$ Hazardous), they show that the semantic loss had a consistency-improving effect. For all semantic loss variants, the models were able to produce inconsistency-free results regarding disjointness.

In addition, we also evaluated the predictive performance of all configurations. As can be seen in Table 3 and Figure 1b, the F1-score for the models

	Micro-F1	Macro-F1
baseline	0.913 ± 0.004	0.653 ± 0.02
T_{Luka}	0.869 ± 0.003	0.395 ± 0.02
T_{prod}	0.907 ± 0.0003	0.593 ± 0.009
T_{prod} (k=2)	0.913 ± 0.004	0.643 ± 0.04
T_{prod} (mixed data)	0.898 ± 0.002	0.501 ± 0.03
Xu et al.	0.906 ± 0.002	0.579 ± 0.02

Table 3: F1-scores calculated on labelled data. The micro-F1 aggregates predictions over all classes before calculation the score, while the macro-F1 is the average of the class-wise scores.

that were trained with semantic loss, with exception of the balanced version, is slightly lower than for the baseline models. This is particularly true for the models that were trained on mixed data or with the Łukasiewicz loss.

The lower performance of the Łukasiewicz models is linked to an unsuccessful training. While the performance of all other models continuously increased during training and converged to the level reported here near the end of allotted 200 epochs, for all 3 Łukasiewicz models, the performance started to drop at approximately 50 epochs into the training. Further analysis suggests that the drop during training has been caused by exploding gradients. Here, we report the results for the best-performing models near the 50 epoch-mark. At that point, the performance of the other semantic loss models was similar to the Łukasiewicz models.

6 Discussion

Our results indicate that the introduction of a semantic loss during training increases the overall logical consistency of predictions significantly. However, since the number of consistency violations is relatively low even for the baseline model, one might consider an a posteriori processing step that transforms the model output into consistent predictions (e.g., by setting all but the highest output value to 0 for disjointness axioms). This can be expected lead to little or no loss in predictive performance since most predictions are already non-violating and some corrections might even turn wrong predictions into correct ones. However, we have only considered the unprocessed predictions in our evaluation. We justify this by the intended use cases: A model trained on the classification task may further be used in downstream tasks (e.g., prediction of chemical properties [15]). Those require that the model has actually learned the ontology's structure. This can only be achieved by giving the model direct feedback during training (as we did with the semantic loss) instead of superficially correcting the results.

For most semantic loss variants, their increase of consistency comes to the detriment of the actual predictive quality. This result seems contradictory at first, as one would assume more consistent results to be better overall.

One possible explanation lies in the imbalanced character of ontology-based datasets. The hierarchical relations between labels create a dataset in which a



Fig. 2: Value of the semantic loss variants L_{prod} , L_{luka} , L_{Xu} and L_{prod}^B with k = 2 for a subsumption relation $A \sqsubseteq B$ with different values of $h_A(x)$ and $h_B(x)$. L_{Xu} has been cut off at $L_{Xu} = 1$ since $\lim_{p_a \to 0, p_b \to 1} L_{Xu}(A \sqsubseteq B, p) = \infty$

significant imbalance is inevitable and cannot be overcome by sampling procedures in any significant way. A class will always have less members than its parents as long as there is an ontological distinction between them that is also represented in the dataset. Consequently, classes that reside further down in the hierarchy are often significantly smaller than those higher up. For ChEBI in particular, more specialised classes also require the model to learn relatively complex patterns from a limited amount of samples. The corresponding labels receive a relatively small training signal that is then counteracted by the additional loss due to violations. This may render the model unable to learn some smaller classes.

This is supported by the differences between micro- and macro-F1. For all models, the macro-F1 is far lower than the micro-F1. This means that many small classes that contribute little to the micro-F1, but receive a stronger weighting in the macro-F1, perform badly. For the semantic loss variants, with the exception of the balanced semantic loss, this gap widens (from 26% for the baseline to 31% for T_{prod} or 47% for T_{luka}). This shows that, when the predictive performance decreases, it mostly affects classes with fewer members.

However, a general tendency to make less predictions cannot be observed. While all models make a similar amount of predictions on the $ChEBI_{100}$ dataset, the semantic loss models make more predictions on average for the PubChem dataset (9.4 with product loss, 8.1 for the baseline). This shows that the lower F1-score in the final models is not due to a generally more "cautious" behaviour. Instead, only some classes may get left out while additional (consistent, but wrong) predictions are made for other classes. Also, the lower performance may be attributed to differences in the learning process, e.g., a less explorative model behaviour or a slower convergence.

In addition, the results confirm our hypothesis regarding the balanced semantic loss. Without losing consistency compared to the unbalanced variant, it is able to reach a predictive performance similar to the baseline. Recall that the main difference between the balanced and unbalanced semantic loss is the gradient in cases where for a subsumption relation $A \sqsubseteq B$, the model predicts $h_A(x)$ close to 1 and $h_B(x)$ close to 0 (cf. Figure 2). There, without the balancing, both classes get the same gradient. With balancing, the gradient is stronger for $h_B(x)$ than for $h_A(x)$ (in our experiment, by a factor of approximately 4).

The balanced semantic loss has been successful in pushing the model towards more consistent predictions without pushing it towards predictions that contradict the labels of the classification task.

The results also indicate that the inclusion of unlabelled data into the training process does hedge the system against inconsistencies on unseen data. This result can be particularly useful in scenarios in which the distribution of features in the dataset is limited. Deep learning systems are prone to suffer from outof-distribution errors, e.g., unpredictable behaviour on data that has not been sampled from the same distribution as the training data. Lifting this limitation is often not easy because additional labelling is required. The semi-supervised training method presented here can help to alleviate this problem.

7 Conclusion

In this work, we have introduced a semantic loss function for the task of ontology classification. Our semantic loss is based on a fuzzy logic interpretation of the ontology subsumption and disjointness relations. To counteract the loss function's tendency to disincentivise predictions of low-level ontology classes, we have proposed a balanced semantic loss variant as well. In our evaluation, we have compared different versions of our semantic loss (based on either the Łukasiewicz t-norm or the product t-norm) to a baseline model and the semantic loss function proposed by [29]. We have shown that all semantic loss variants were able to reduce the number of consistency violations by approximately two orders of magnitude.

Regarding performance on the classification task, we have seen greater differences between the loss functions. Most variants have both a slightly lower microand a significantly macro-F1 than the baseline (especially the Łukasiewicz-based variant). This indicates that especially the predictive performance of small classes is affected by the semantic loss. Only the balanced semantic loss was able to perform on a par with our baseline.

In addition, we have used the semantic loss for an additional training task on unlabelled data. This allows us to generalise beyond the original data distribution used for supervised training. Our evaluation on the Hazardous subset of PubChem shows that this form of training can further improve the consistency of predictions for out-of-distribution data.

Future work will include an improved normalisation to avoid performance issues like we reported for the Łukasiewicz semantic loss. Also, it is possible to extend our approach to other types of ontology axioms, e.g., parthood relations. Finally, it would be interesting to incorporate our finding of a balanced implication loss into more general frameworks like LTNs or LNNs.

Acknowledgements

This work has been funded by the Deutsche Forschungsgesellschaft (DFG, German Research Foundation) - 522907718.

A Result for individual runs

In Section 5, we have presented results as the average and standard deviation out of 3 runs for every configuration.

	Dataset	$\operatorname{Run1}$	$\operatorname{Run2}$	Run3
Baseline	$ChEBI_{100}$	0.0034	0.0031	0.0029
	Hazardous	0.0066	0.012	0.0015
T_{Luka}	$ChEBI_{100}$	2.32×10^{-5}	$1.72\times \mathbf{10^{-5}}$	2.23×10^{-5}
	Hazardous	4.45×10^{-5}	0	1.79×10^{-7}
T_{prod}	$ChEBI_{100}$	$1.94\times\mathbf{10^{-5}}$	3.36×10^{-5}	4.24×10^{-5}
	Hazardous	6.26×10^{-5}	$5.72\times\mathbf{10^{-6}}$	9.78×10^{-5}
T_{prod} (k=2)	$ChEBI_{100}$	$2.41\times\mathbf{10^{-5}}$	3.46×10^{-5}	5.35×10^{-5}
	Hazardous	$2.22\times \mathbf{10^{-5}}$	0.00017	2.25×10^{-5}
Xu et al.	$ChEBI_{100}$	4.44×10^{-5}	$2.30\times\mathbf{10^{-5}}$	4.12×10^{-5}
	Hazardous	$6.68\times\mathbf{10^{-6}}$	5.58×10^{-5}	5.56×10^{-5}
T_{prod} (mixed data)	$ChEBI_{100}$	4.78×10^{-5}	$3.46\times\mathbf{10^{-5}}$	9.48×10^{-5}
- · · · ·	Hazardous	$2.98 imes 10^{-7}$	1.98×10^{-5}	1.14×10^{-5}

Table 4: FNRs for implication violations on the ${\rm ChEBI}_{100}$ and PubChem datasets.

	Aggregation	Run1	Run2	Run3
Baseline	micro	0.909	0.915	0.915
	macro	0.625	0.669	0.665
T_{Luka}	micro	0.870	0.866	0.873
	macro	0.399	0.369	0.415
T_{prod}	micro	0.907	$\boldsymbol{0.907}$	0.907
	macro	0.584	$\boldsymbol{0.600}$	0.597
T_{prod} (k=2)	micro	0.915	$\boldsymbol{0.916}$	0.908
	macro	0.661	$\boldsymbol{0.666}$	0.601
Xu et al.	micro	0.904	$\boldsymbol{0.908}$	0.905
	macro	0.570	0.597	0.569
T_{prod} (mixed data)	micro	0.895	0.899	0.899
	macro	0.471	0.502	0.529
11 5 171 .	.1 .	1		. •

Table 5: F1-scores with micro and macro aggregation.

Tables 4 and 5 show the FNR and and F1-scores for the individual runs. For the FNR, it can be observed that the results vary significantly between runs, especially on the Hazardous datasets. This is likely due to the small scale we are considering: On the ChEBI₁₀₀, a FNR of 2.5×10^{-5} roughly corresponds to about 100 observed false negatives over the whole test set. I.e., out of 19 thousand samples, each of which had 19 thousand subsumption relations that could have resulted in a false negative, only 100 actually are false negatives. Therefore, slight changes in the predictive performance can have a significant impact on the false negative rate.

The F1-scores are more stable overall, with a range of less than one percent for the micro aggregation and up to six percent for the macro aggregation.

References

- Badreddine, S., d'Avila Garcez, A.S., Serafini, L., Spranger, M.: Logic tensor networks. Artif. Intell. 303, 103649 (2022). https://doi.org/10.1016/J.ARTINT. 2021.103649, https://doi.org/10.1016/j.artint.2021.103649
- Bayerlein, B., Schilling, M., Birkholz, H., Jung, M., Waitelonis, J., M\u00e4dler, L., Sack, H.: Pmd core ontology: Achieving semantic interoperability in materials science. Materials & Design 237, 112603 (2024)
- Bojarski, M., Del Testa, D., Dworakowski, D., Firner, B., Flepp, B., Goyal, P., Jackel, L.D., Monfort, M., Muller, U., Zhang, J., et al.: End to end learning for self-driving cars. arXiv preprint arXiv:1604.07316 (2016)
- Booshehri, M., Emele, L., Flügel, S., Förster, H., Frey, J., Frey, U., Glauer, M., Hastings, J., Hofmann, C., Hoyer-Klick, C., et al.: Introducing the open energy ontology: Enhancing data interpretation and interfacing in energy systems analysis. Energy and AI 5, 100074 (2021)
- Cerri, R., Barros, R.C., De Carvalho, A.C.: Hierarchical multi-label classification using local neural networks. Journal of Computer and System Sciences 80(1), 39– 56 (2014)
- Clark, K., Luong, M.T., Le, Q.V., Manning, C.D.: Electra: Pre-training text encoders as discriminators rather than generators. arXiv preprint arXiv:2003.10555 (2020)
- Collobert, R., Weston, J., Bottou, L., Karlen, M., Kavukcuoglu, K., Kuksa, P.: Natural language processing (almost) from scratch. Journal of machine learning research 12, 2493–2537 (2011)
- Cui, Y., Jia, M., Lin, T.Y., Song, Y., Belongie, S.: Class-balanced loss based on effective number of samples. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 9268–9277 (2019)
- De Raedt, L., Kimmig, A., Toivonen, H.: Problog: A probabilistic prolog and its application in link discovery. In: IJCAI 2007, Proceedings of the 20th international joint conference on artificial intelligence. pp. 2462–2467. IJCAI-INT JOINT CONF ARTIF INTELL (2007)
- Degtyarenko, K., de Matos, P., Ennis, M., Hastings, J., Zbinden, M., McNaught, A., Alcántara, R., Darsow, M., Guedj, M., Ashburner, M.: ChEBI: a database and ontology for chemical entities of biological interest. Nucleic Acids Research 36(Database issue), D344–D350 (Jan 2008). https://doi.org/10.1093/nar/ gkm791, http://dx.doi.org/10.1093/nar/gkm791, publisher: European Bioinformatics Institute, Wellcome Trust Genome Campus, Hinxton, Cambridge, UK.
- Giunchiglia, E., Stoian, M.C., Khan, S., Cuzzolin, F., Lukasiewicz, T.: Road-r: The autonomous driving dataset with logical requirements. Machine Learning 112(9), 3261–3291 (2023)
- Glauer, M., Memariani, A., Neuhaus, F., Mossakowski, T., Hastings, J.: Interpretable ontology extension in chemistry. Semantic Web **Preprint**(Preprint), 1–22 (2023)
- Glauer, M., Neuhaus, F., Mossakowski, T., Memariani, A., Hastings, J., Hitzler, P., Sarker, M., Eberhart, A.: Neuro-symbolic semantic learning for chemistry. Compendium of Neurosymbolic Artificial Intelligence. Frontiers in Artificial Intelligence and Applications pp. 460–484 (2023)

- Glauer, M., Neuhaus, F., Flügel, S., Wosny, M., Mossakowski, T., Memariani, A., Schwerdt, J., Hastings, J.: Chebifier: Automating semantic classification in ChEBI to accelerate data-driven discovery. Digital Discovery p. to appear (2024)
- Glauer, M., Neuhaus, F., Mossakowski, T., Hastings, J.: Ontology pre-training for poison prediction. In: German Conference on Artificial Intelligence (Künstliche Intelligenz). pp. 31–45. Springer (2023)
- Glauer, M., West, R., Michie, S., Hastings, J.: Esc-rules: Explainable, semantically constrained rule sets. arXiv preprint arXiv:2208.12523 (2022)
- Hájek, P.: Metamathematics of fuzzy logic, vol. 4. Springer Science & Business Media (2013)
- Hastings, J., Glauer, M., Memariani, A., Neuhaus, F., Mossakowski, T.: Learning chemistry: exploring the suitability of machine learning for the task of structurebased chemical ontology classification. Journal of Cheminformatics 13, 1–20 (2021)
- Hastings, J., Glauer, M., West, R., Thomas, J., Wright, A.J., Michie, S.: Predicting outcomes of smoking cessation interventions in novel scenarios using ontologyinformed, interpretable machine learning. Wellcome Open Research 8(503), 503 (2023)
- Hastings, J., Owen, G., Dekker, A., Ennis, M., Kale, N., Muthukrishnan, V., Turner, S., Swainston, N., Mendes, P., Steinbeck, C.: ChEBI in 2016: Improved services and an expanding collection of metabolites. Nucleic Acids Research 44(D1), D1214–D1219 (Jan 2016). https://doi.org/10.1093/nar/gkv1031
- Kim, S., Chen, J., Cheng, T., Gindulyte, A., He, J., He, S., Li, Q., Shoemaker, B.A., Thiessen, P.A., Yu, B., et al.: Pubchem 2023 update. Nucleic acids research 51(D1), D1373–D1380 (2023)
- Kruse, R., Nauck, D.: Neuro-fuzzy systems. In: Computational Intelligence: Soft Computing and Fuzzy-Neuro Integration with Applications. pp. 230–259. Springer (1998)
- Manhaeve, R., Dumancic, S., Kimmig, A., Demeester, T., De Raedt, L.: Deepproblog: Neural probabilistic logic programming. Advances in neural information processing systems **31** (2018)
- 24. Nations, U.: Globally harmonized system of classification and labelling of chemicals, rev. 10. Tech. rep., United Nations (2023)
- Riegel, R., Gray, A., Luus, F., Khan, N., Makondo, N., Akhalwaya, I.Y., Qian, H., Fagin, R., Barahona, F., Sharma, U., et al.: Logical neural networks. arXiv preprint arXiv:2006.13155 (2020)
- Towell, G.G., Shavlik, J.W.: Knowledge-based artificial neural networks. Artificial intelligence 70(1-2), 119–165 (1994)
- Wehrmann, J., Cerri, R., Barros, R.: Hierarchical multi-label classification networks. In: International conference on machine learning. pp. 5075–5084. PMLR (2018)
- Weininger, D.: Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules. Journal of chemical information and computer sciences 28(1), 31–36 (1988)
- Xu, J., Zhang, Z., Friedman, T., Liang, Y., Broeck, G.: A semantic loss function for deep learning with symbolic knowledge. In: International conference on machine learning. pp. 5502–5511. PMLR (2018)
- Zhang, D., Bai, X.L., Cai, K.Y.: Extended neuro-fuzzy models of multilayer perceptrons. Fuzzy sets and systems 142(2), 221–242 (2004)