QIANYU YU, The Hong Kong University of Science and Technology (Guangzhou), China GIULIANO LOSA, Stellar Development Foundation, USA

XUECHAO WANG, The Hong Kong University of Science and Technology (Guangzhou), China

This paper presents TetraBFT, a novel unauthenticated Byzantine fault tolerant protocol for solving consensus in partial synchrony, eliminating the need for public key cryptography and ensuring resilience against computationally unbounded adversaries.

TetraBFT has several compelling features: it necessitates only constant local storage, has optimal communication complexity, satisfies optimistic responsiveness — allowing the protocol to operate at actual network speeds under ideal conditions — and can achieve consensus in just 5 message delays, which outperforms all known unauthenticated protocols achieving the other properties listed. We validate the correctness of TetraBFT through rigorous security analysis and formal verification.

Furthermore, we extend TetraBFT into a multi-shot, chained consensus protocol, making a pioneering effort in applying pipelining techniques to unauthenticated protocols. This positions TetraBFT as a practical and deployable solution for blockchain systems aiming for high efficiency.

CCS Concepts: • Theory of Computation → Distributed Algorithms.

Additional Key Words and Phrases: Consensus, Blockchain, BFT

#### **1** INTRODUCTION

Byzantine fault tolerant (BFT) consensus protocols are the foundation of permissionless blockchain systems like Bitcoin, Ethereum, and Cosmos. These three systems are each an example of the three types of permissionless blockchains in the hierarchy of Roughgarden and Lewis-Pye [23]: fully permissionless (Bitcoin), dynamically available (Ethereum), and quasi-permissionless (Cosmos).

While quasi-permissionless systems make the strongest assumptions about their participants — assuming that their list is known and that a large fraction of them (e.g. two thirds) are available and honest — those assumptions allow using partially-synchronous BFT consensus protocols in the vein of the seminal PBFT protocol [13]. This is advantageous, because PBFT-style protocols have been honed by at least 3 decades of research and achieve significantly better performance and lower resource consumption than fully-permissionless protocols and, unlike current dynamically-available protocols, they remain safe during asynchrony.

There are two main categories of PBFT-style protocols: protocols relying on authenticated messages, often called authenticated protocols, and protocols relying only on authenticated channels, often called unauthenticated or information-theoretic protocols. The key difference is that, with authenticated messages, a node  $n_1$  can easily prove to a node  $n_2$  that a third node  $n_3$  sent a given message ( $n_1$  just forwards  $n_3$ 's authenticated message to  $n_2$ , which can check the authenticity of the message). However, with only authenticated channels, there is no straightforward way for  $n_2$  to verify a claim by  $n_1$  that  $n_3$  sent a given message — it could easily be a lie.

Authenticated messages make it fundamentally easier to devise efficient protocols. For example, in synchronous systems, with signatures we can solve consensus regardless of the number of failures using the Dolev-Strong algorithm [16]; without signatures, we must assume that less that a

For correspondence on the paper, please contact Xuechao Wang at xuechaowang@hkust-gz.edu.cn.

Authors' Contact Information: Qianyu Yu, qyu100@connect.hkust-gz.edu.cn, The Hong Kong University of Science and Technology (Guangzhou), China; Giuliano Losa, giuliano@stellar.org, Stellar Development Foundation, USA; Xuechao Wang, xuechaowang@hkust-gz.edu.cn, The Hong Kong University of Science and Technology (Guangzhou), China.

third of the nodes are faulty [29]. Recent results of Abraham et al.[1, 2] also show that Byzantine reliable broadcast is solvable with a good-case latency of 2 message delays in the authenticated model with  $3f+1 \le n$  (where *n* is the number of nodes and *f* the number of Byzantine nodes among them), but it takes at least 3 message delays in the unauthenticated model when  $3f + 1 \le n < 4f$ . Perhaps for this reason, authenticated protocols have attracted considerable research attention and have seen wide adoption by quasi-permissionless blockchain systems (Cosmos, Sui, Aptos, Solana, etc.). Example protocols include Tendermint [8], Hotstuff [32] and its variants [20, 27], and Jolteon [19], etc.

In contrast, unauthenticated BFT consensus protocols [3, 6, 25] have been much less studied. However, they offer compelling advantages:

- (1) Unauthenticated BFT protocols avoid computationally expensive cryptographic operations, like public-key cryptography, and are therefore advantageous in resource-constrained environments. This includes protocols which must be executed by smart contracts, e.g. trustless cross-chain synchronization protocols like TrustBoost [30] and the Interchain timestamping protocol [31]. In those settings, public-key cryptography would be prohibitively expensive.
- (2) Instead of mandating global trust assumptions (such as 1/2 of the mining power being honest in Bitcoin, or 1/2 of the weighted stakers being honest in Ethereum), some blockchains allow participants to make unilateral, heterogeneous trust assumptions. For example, one participant might assume 1/2 of a set A of participants is honest, while another participant assumes 2/3 of another set  $B \neq A$  is honest. Examples include Ripple[5] and Stellar's Federated Byzantine Agreement model (FBA) [25]. In this setting, authenticated messages are of limited use because forwarding the set of messages that caused one node  $n_1$  to take some action will not necessarily convince another node  $n_2$  to take the same action if  $n_2$ 's trust assumptions are different from  $n_1$ . For example, well-known techniques based on disseminating quorum certificates do not work anymore in this setting. This rules out every authenticated protocol that we know of. However, with a few tweaks, unauthenticated protocols work in this heterogeneous setting.
- (3) Finally, rehashing Abraham and Stern [3], by avoiding message authentication, unauthenticated protocol implementations have a smaller attack surface and rely on minimal cryptographic assumptions, making them more "future-proof".

In this paper, we are interested in unauthenticated, partially-synchronous BFT consensus protocols that have optimal resilience (i.e. requiring only  $n \ge 3f + 1$  nodes), that are optimisticallyresponsive [28], that use only constant local storage space, and that have an optimal communication complexity of  $O(n^2)$  bits [15], where each node sends and receives a linear number of bits. This combination of features is almost a requirement in practice:

- Optimal resilience means we maximize the fault-tolerance budget given a fixed system size. This is crucial in the extremely adversarial environments faced by permissionless systems.
- Once the network becomes synchronous, optimistically responsive protocols make progress as fast as messages are received; instead, their non-responsive counterparts [4, 24] must wait for fixed-duration timeouts to recover from asynchrony. In practice, non-responsiveness can cause large performance hiccups, leading to backlogs of work that are hard to clear out.
- In a blockchain setting, where the system is expected to never stop and potentially reach very large scale (e.g. Ethereum currently has hundreds of thousands of validators), we cannot tolerate storage requirements that keep growing forever or a communication complexity higher than linear per node.

Before this work, there were only 3 known optimally-resilient, optimistically-responsive, partiallysynchronous unauthenticated BFT consensus protocols: two versions of PBFT [11, 12] (a version

requiring unbounded storage and a constant-storage version) and Information-Theoretic HotStuff (IT-HS) [3]. While the unbounded-storage, unauthenticated PBFT version obviously fails our bounded-storage requirement, its constant-storage counterpart fails the linear-communication requirement: it uses a complex view-change protocol in which each nodes sends a worst-case quadratic number of bits, for a worst-case cubic total complexity. Only IT-HS achieves all our desiderata (using both constant storage and linear per-node worst-case communication). However, IT-HS has a whooping good-case latency of 6 message delays. Roughly speaking, good-case latency is the latency of the protocol when the network is synchronous and the system is not under attack. It is important to minimize it because this will be the latency in the common case in practice.

It is not known whether IT-HS's good-case latency of 6 message delays can be improved without incurring non-constant space usage (either in messages or local persistent state). Thus, the first question that we ask in this paper is the following:

What is the minimum good-case latency achievable in partially-synchronous, optimallyresilient, constant-space, quadratic-communication, optimistically-responsive unauthenticated BFT consensus?

We make significant progress towards an answer by presenting TetraBFT, an unauthenticated, partially synchronous BFT consensus algorithm that has optimal resilience ( $n \ge 3f+1$ ), is optimisticallyresponsive, uses constant-size storage, has worst-case quadrati communication, and has a good-case latency of 5 message delays. This shows that IT-HS's 6 message delays is not optimal, but we do not know whether 5 is the lower bound.

We provide detailed proofs establishing both the safety and liveness of TetraBFT, but we also formally specify TetraBFT using the TLA+ language [22] and we mechanically verify its safety property using the Apalache model-checker [21]. We are able to exhaustively check that TetraBFT is safe in all possible executions with 4 nodes, among which one is Byzantine, 3 different proposed values, and a maximum of 5 views. This gives us extremely high confidence in the safety of TetraBFT.

While unauthenticated BFT protocols satisfying the desiderata above are a first step towards practical protocols, the next step in practice is to boost throughput using pipelining. However, the very brief sketch in [3] notwithstanding, there are no known pipelined unauthenticated BFT consensus protocols. The next question we ask is therefore:

#### Can unauthenticated BFT consensus protocols be made practical using pipelining?

We answer positively by extending TetraBFT for pipelined multi-shot consensus (also known as state machine replication (SMR)), enabling nodes to efficiently reach consensus on a sequence of blocks and thus construct a blockchain. Using pipelining, TetraBFT is able to commit one new block every message delay in the good case, and thus, in theory, it achieves a maximal throughput of 5 times the throughput that would be achieved by simply repeating instances of single-shot TetraBFT. Pipelined TetraBFT is also conceptually simple, using only 2 message types in the good case (proposals and votes), and uses its view-change protocol only to recover from a malicious leader or from asynchrony. This is a significant improvement over the pipelined version of IT-HS (briefly sketched in Section 3.2 of [3]), which mandates the transmission of suggest/proof messages (used during view change in the single-shot IT-HS) alongside vote messages regardless of the scenario. To the best of our knowledge, this work is the first to offer a comprehensive description and analysis of pipelining in the unauthenticated setting.

Single-shot TetraBFT, described in Section 3, follows the classic blueprint for partially-synchronous consensus first proposed by Dwork, Lynch, and Stockmeyer [17]. The protocol executes a sequence of views, where each view has a unique leader that proposes a value, followed by a voting phase after which either a decision is made or nodes timeout and start a view-change protocol. In the view-change protocol, nodes gather information about what happened in previous views and

determine which values are safe — meaning values that cannot possibly contradict any decision that was or will ever be made in a previous view — to propose and vote for in the new view.

Our main contributions are summarized below.

- We propose TetraBFT, a novel partial synchronous unauthenticated BFT consensus algorithm with bounded persistent storage, optimistic responsiveness, and reduced latency, improving efficiency by shortening consensus phases.
- (2) We conduct a comprehensive security analysis and a formal verification of TetraBFT, affirming the correctness of the protocol and its established security properties.
- (3) We extend TetraBFT into a multi-shot, pipelined consensus algorithm, making the first detailed exploration of pipelining within the unauthenticated context.

#### 1.1 Protocol Overview

We consider a message-passing system consisting of *n* nodes running TetraBFT. Among the *n* nodes, *f* exhibiting Byzantine faults are considered malicious, while the remaining n - f nodes are well-behaved. We assume 3f < n. Well-behaved nodes follow the protocol faithfully while malicious nodes may arbitrarily deviate from the protocol. We define any group of n - f or more nodes as a *quorum*, and any group of f + 1 or more nodes as a *blocking set*.

TetraBFT executes a sequence of views, each of which is pre-assigned a unique leader (e.g. chosen round-robin). Each view consists of 7 phases leading to a possible decision: suggest/proof, proposal, vote-1, vote-2, vote-3, vote-4 and view-change. Initially, at view 0, suggest /proof messages are not required as all the values are determined safe. In the good case, no view-change message is sent, allowing a decision to be reached in 5 phases.

The protocol is segmented into four key components:

1. **Proposal.** A well-behaved leader determines the safety of a value based on the suggest messages from a quorum of nodes before proposing. Only values determined safe are proposed. A suggest message is composed of the historical information about vote-2 and vote-3 messages.

2. **Voting.** Mirroring the leader's process, well-behaved nodes determine the safety of a proposed value through a quorum of proof messages, which carry historical information about vote-1 and vote-4 messages. A node casts vote-1 only for values determined safe. A node votes through the voting sequence—vote-1, vote-2, vote-3, to vote-4—sequentially, sending each subsequent vote only after receiving a quorum of messages for the preceding vote type. The name TetraBFT comes from the fact that there are 4 voting phases in the protocol.

3. Deciding. A node decides a value val upon receiving a quorum of vote-4 messages for val.

4. View change. A node sends a view-change message for the next view when its current view does not produce a decision by a fixed time after the view started (nodes use timers for this). A node also issues a view-change message for a new view v upon receiving f + 1 messages from that view, provided it hasn't already sent a message for v or a higher view. A transition to the new view occurs once n - f view-change messages are received. Nodes keep checking view-change messages throughout all views.

In a nutshell, TetraBFT guarantees safety by ensuring the well-behaved nodes only ever vote for safe values, i.e. values that cannot possibly contradict a decision in a previous view. Liveness is more subtle, and the key is that the leader determines whether a value *val* is safe at a view when the vote-2 messages of a blocking set show that *val* is safe, and follower nodes determine that *val* is safe when the vote-1 messages of a blocking set show that *val* is safe. Thus, any value determined safe by a leader is also determined safe by all other well-behaved nodes.

#### 1.2 Related Work

Table 1 compares TetraBFT to other partially-synchronous, unauthenticated BFT protocols in terms of responsiveness (where "responsive" in the table means optimistically responsive [28]), good-case latency, latency with view-change, and size of storage and messages. Good-case latency means the latency of the protocol in message delays when the network is synchronous from the start and the leader of the first view is well-behaved. Latency with view-change is the latency of a view, in message delays, starting with a view-change.

We justify latencies as follows. IT-HS (blog version) [4] has a latency of 4 phases in the good case: propose, echo, accept, lock, and a suggest message is sent in the view-change scenario. The Byzantine consensus protocol in Li et al. [24] has a latency of 6 in both cases, attributable to the employment of two instances of Byzantine reliable broadcast, each consisting of three phases. IT-HS [3] experiences a latency involving 6 phases in the good case: propose, echo, key-1, key-2, key-3, and lock. Additionally, proof/suggest, request, and abort messages become necessary in the view-change case. PBFT [11, 12] demonstrates a latency of 3 phases in the good case: pre-prepare, prepare, commit. The view-change case necessitates an extra four messages: request, view-change, view-change-ack, and new-view.

	Responsiveness	Good-case	Latency with	Storage/
		latency	view-change	Communicated bits
IT-HS (blog version) [4]	non-responsive	4	5	$O(1)/O(n^2)$
IT-HS [3]	responsive	6	9	$O(1)/O(n^2)$
PBFT (bounded) [11]	responsive	3	7	$O(1)/O(n^3)$
PBFT (unbounded) [11, 12]	responsive	3	7	unbounded/unbounded
SCP [25]	not applicable <sup>1</sup>	6	$4^{2}$	$O(1)/O(n^2)$
Li et al. [24]	non-responsive	6	6	unbounded/unbounded
TetraBFT	responsive	5	7	$O(1)/O(n^2)$

Table 1. Characteristics of the partially-synchronous, unauthenticated BFT consensus protocols known to the authors, as well as two protocols (SCP and the protocol of Li et al.) for heterogeneous-trust systems. "Responsive" means optimistically responsive. Latencies are expressed in message delays.

As we can see in Table 1, unresponsive protocols have better latency. However, non-responsiveness is problematic in practice. Optimistically responsive means that, once the network becomes synchronous with actual delay  $\delta$ , all well-behaved parties decide in time proportional to  $\delta$  (at most  $7\delta$  in TetraBFT) instead of proportional to the worst-case latency  $\Delta$  in the non-responsive case; this is typically due to the leader having to wait for a fixed duration at the beginning of a new view in order to collect enough information in order to make a proposal that will be accepted by the other nodes. In practice, one usually makes conservative assumptions about message delay, such that it is likely for  $\delta$  to be much smaller than  $\Delta$ . In this case, an unresponsive protocols will take significantly longer to change views. This is a practical problem because, in multi-shot consensus, a long view-change will cause an accumulating backlog of work that may be hard to recover from.

PBFT, IT-HS, and TetraBFT are optimistically responsive. PBFT achieves better latency, but even its constant-storage version [11] still sends messages of size linear in the number of nodes. This is not practical in large systems. For example, Ethereum has hundreds of thousands of validators as of early 2024.

<sup>&</sup>lt;sup>1</sup>SCP does not guarantee termination unless Byzantine nodes are all eventually evicted.

<sup>&</sup>lt;sup>2</sup>In SCP, views after the first take fewer phases but have weaker liveness guarantees than the first view.

Like TetraBFT, IT-HS is optimistically responsive, uses constant storage, and has an optimal communication complexity of  $O(n^2)$  bits per view. The main advantage of TetraBFT over IT-HS is that TetraBFT reduces good-case latency by one message-delay. TetraBFT achieves this feat by ensuring that, upon view change, well-behaved nodes collect enough information to never send a message containing an unsafe value. Instead, IT-HS relies on locks for safety, but locks are in some sense imperfect: even though an unsafe value cannot make it to the "key-1" phase of IT-HS because a quorum will have a lock for a different value, some well-behaved nodes may still echo unsafe values because they are not locked. Thus, even if f + 1 nodes echo the same value *val*, it does not prove that *val* is safe, and this property is only achieved at the "key-1" phase of IT-HS. In contrast, in TetraBFT, well-behaved nodes never send a message containing an unsafe value. Thus we do not need the equivalent of IT-HS's echo phase, and that is how TetraBFT achieves 5 phases instead of 6.

To the best of our knowledge, the brief sketch in [3] notwithstanding, this work is the first to offer a comprehensive description and analysis of pipelining in the unauthenticated setting. Abraham and Stern [3] briefly discuss pipelining IT-HS, but do not give much detail. Moreover, their suggested protocol seems to mandate the transmission of suggest/proof messages (used during view change in the single-shot IT-HS) alongside vote messages regardless of the scenario, while multi-shot TetraBFT sends only proposals and votes in the good case.

The Stellar Consensus Protocol (SCP) [25] and the protocols of Li et al. [24] are not strictly speaking unauthenticated protocols. While they are partially-synchronous BFT consensus protocols, they are presented in two heterogeneous trust models: the federated Byzantine agreement (FBA) model for SCP, and the heterogeneous quorum system model for Li et al. In these models, nodes are allowed to make their own failure assumptions, resulting in different nodes having different sets of quorums. Variants of heterogeneous models include asymmetric quorum systems [9], subjective quorum systems [18], personal Byzantine quorum systems [26], and permissionless quorum systems [10]. In these models, because nodes may not agree on what is a quorum, authenticated messages and quorum certificates — as used in one form or another in all partially-synchronous, authenticated BFT consensus protocols known to the authors — do not work. Thus, for the main aspects of BFT consensus protocols, those heterogeneous models look unauthenticated, and SCP and the protocol of Li et al. indeed are easily transferable to the unauthenticated setting. An implementation of SCP, called stellar-core, has been in use in the Stellar network since 2015.

An interesting observation is that this also works the other way, from the unauthenticated setting to the heterogeneous setting: TetraBFT could be adapted to work in an heterogeneous setting like the FBA model. The main difficulty in open heterogeneous settings like FBA is assigning a unique leader to each view. This is because, without global agreement on a list of participants, we cannot use a round-robin strategy. Instead, SCP uses a synchronous sub-protocol, called the nomination protocol [25], whose principles could be applied to TetraBFT to obtain simulate a unique leader.

# 2 MODEL AND PRELIMINARY DEFINITIONS

We assume the classic setting with n > 3f nodes among which f are Byzantines. Each node has a local timer (used for timeouts) ticking at the same rate and we assume that local computation is instantaneous. However, the network is only partially synchronous [17]. This means that the network is initially asynchronous but becomes synchronous after an unknown global stabilization time, noted GST. Before GST, there is no guarantee of message delivery and messages sent before GST may be permanently lost. Note that with constant storage, we must allow the loss of messages during asynchrony, as preventing this would necessitate unbounded buffers. However, every message sent after GST is guaranteed to be delivered within a known bound  $\Delta$ .

We are interested in protocols solving first the consensus problem, and then its multi-shot variant total-order broadcast (TOB, also called atomic broadcast). In the problem of consensus, each node

starts with an initial input value, with the goal being for all nodes to agree on a single output value. A distributed algorithm solving consensus should guarantee the usual properties:

DEFINITION 1 (CONSENSUS).

- Termination. Every well-behaved node eventually decides a value.
- Agreement. No two well-behaved nodes decide different values.
- Validity. If all nodes are well-behaved and they all have the same input value val, then every well-behaved node that decides a value decides the value val.

In contrast to consensus, multi-shot consensus enables nodes to reach consensus on an unlimited series of values *val*1, *val*2, *val*3, . . . Each value is assigned with a *slot* number, indicating its position in the series. In the context of a blockchain, these values, essentially data blocks containing *transactions*, are linked sequentially via hash pointers, collectively forming a *chain*. When a node outputs a block or an entire chain, we say that the block or the chain is *finalized* by the node. Multi-shot consensus satisfies consistency and liveness, as defined in [14]:

Definition 2 (Multi-shot Consensus).

- **Consistency**. If two chains are finalized by two well-behaved nodes, then one chain must be a prefix of, or equal to, the other.
- *Liveness*. If some well-behaved node receives a transaction txn, txn will eventually be included in all well-behaved nodes' finalized chains.

# **3 BASIC TETRABFT**

In this section, we present the Basic TetraBFT protocol that solves the problem of consensus as defined in Definition 1. We first delve into the message types used in the protocol, detailing the structure and the purpose of each message type. Following this, we present a comprehensive operational description of the protocol, focusing on the evolution of a view. Finally, we provide two helper algorithms designed to assist nodes in efficiently determining safe values.

# 3.1 Messages

We outline the message types that a node can send in Basic TetraBFT. We denote a view by *v* and a value by *val*. A leader node sends proposal messages and non-leader nodes can send 4 types of vote messages, suggest/proof messages and view-change messages. The suggest/proof messages, incorporating historical records of previously sent vote messages, facilitate leaders and nodes in determining safe values. Besides, view-change messages enable nodes to transition to a new view. In a more formal structure:

- Only sent by the leader:
  - proposal message: formatted as (proposal, *v*, *val*).
- Sent by all nodes:
  - vote-i message:  $\langle vote-i, v, val \rangle$ , where i = 1,2,3,4.
  - suggest message: (suggest, (vote-2, v, val), (prev-vote
    - -2, v, val', (vote-3, v, val), where
      - \* highest vote-2 message (vote-2, *v*, *val*): the highest vote-2 message in the view number that the node has sent;
      - \* second-highest vote-2 message (prev-vote-2, v, val'): the highest vote-2 message in the view number that the node has sent for a different value from the highest vote-2 message;
      - \* highest vote-3 message (vote-3, *v*, *val*): the highest vote-3 message in the view number that the node has sent.

- proof message: (proof, (vote-1, v, val), (prev-vote-1, v,

val', (vote-4, v, val), which follows the same struture as the suggest message, but uses vote-4 instead of vote-3 and vote-1 instead of vote-2.

- view-change message:  $\langle view-change, v \rangle$ .

Throughout the views, a node needs only to store the highest vote-1 and vote-2, vote-3 and vote-4 messages it sent, along with the second highest vote-1 and vote-2 messages that carry a different value from their respective highest messages. Thus, similar to IT-HS, TetraBFT requires only a constant amount of persistent storage.

#### 3.2 Evolution of a View

Our protocol operates on a view-based manner, with each view having a unique and pre-determined leader. Every node begins at view 0, equipped with an initial value. In any view, should the leader determine that arbitrary values (including its initial value) are safe in step 2, it will propose its initial value by default. A view *v* proceeds as follows:

- (1) Upon starting the view, each node sets its timer to a timeout of  $9\Delta$ , ensuring sufficient time for deciding when the leader of current view is well-behaved. If v = 0, the node proceeds directly to step 2; otherwise, if v > 0, the node undertakes the following steps:
  - (a) it broadcasts a proof message for the current view and
  - (b) it sends a suggest message to the leader of the current view.
- (2) When the leader has determined that a value *val* is safe to propose in the current view according to Rule 1, it broadcasts a proposal message for the current view and for *val*. A well-behaved leader broadcasts only one proposal message in a view.
- (3) When a node determines that the leader's proposal is safe in the current view according to Rule 3, it broadcasts a vote-1 message for the current view and the leader's proposal. A well-behaved node broadcasts only one vote-1 message in a view.
- (4) A node that receives a quorum of vote-1 messages for the current view and for the same value *val* sends a vote-2 message for the current view and for *val*.
- (5) A node that receives a quorum of vote-2 messages for the current view and for the same value *val* sends a vote-3 message for the current view and for *val*.
- (6) A node that receives a quorum of vote-3 messages for the current view and for the same value *val* sends a vote-4 message for the current view and for *val*.
- (7) A node that receives a quorum of vote-4 messages for the current view and for the same value *val* decides *val*.

Upon observing the timer expiration, a node broadcasts a view-

change message for the next view. On receiving f + 1 view-change messages for a view v', a node sends a view-change message for view v' if it has not sent a view-change message for view v' or any higher view. On receiving n - f view-change messages for a view, a node changes to the view. Nodes keep checking view-change messages regardless of the current view.

We justify the timeout value of  $9\Delta$ , assuming the network is synchronous with a maximum delay of  $\Delta$  (i.e., after GST). Let us consider a well-behaved node that receives n - f view-change messages at time t, including at least f + 1 from well-behaved nodes. Due to the network delay, other well-behaved nodes might receive these f + 1 view-change messages at time  $t + \Delta$  and subsequently echo a view-change message. Hence, all well-behaved nodes should receive n - f view-change messages by time  $t + 2\Delta$ . This indicates a maximum difference of  $2\Delta$  in the view change time across well-behaved nodes. An additional  $6\Delta$  is necessary for processing suggest/proof messages, a proposal message, and four vote messages. Thus, summing these intervals, we opt for a timeout of  $9\Delta$  to slightly overshoot the cumulative  $8\Delta$ , adding a safety margin.

The following are the rules applied in steps 2 and 3. Rule 1 applies when a well-behaved leader determines a value safe based on suggest messages from a quorum of nodes. If  $v \neq 0$ , the quorum must meet specific criteria, including the existence of a blocking set within the quorum all claiming in their suggest messages that the value is safe according to Rule 2. Note that "claim" is distinguished from "determine" used previously. Rule 3 is invoked when a well-behaved node determines a leader's proposal safe, mirroring Rule 1 but with notable distinctions: it relies on proof messages instead of suggest message, employs vote-4 in place of vote-3, and vote-1 instead of vote-2. Additionally, Rule 3 Item 2(b)iii incorporates an extra condition involving two blocking sets of nodes, which corresponds to a special scenario where any value can be determined safe. In Section 4, we will proof safety and liveness properties based on these rules. Specifically, we will justify the rationale behind Rule 1 and demonstrate how Rule 3 can be logically derived from Rule 1.

RULE 1. All values are safe in view 0. If  $v \neq 0$ , a leader determines that the value val is safe to propose in view v when the following holds:

- (1) A quorum q has sent suggest messages in view v, and
- (2) According to what is reported in suggest messages, either
  - (a) no member of q sent any vote-3 before view v, or
  - (b) there is a view v' < v such that
    - (i) no member of q sent any vote-3 messages for a view strictly higher than v', and
    - (ii) any member of q that sent a vote-3 message in view v' did so with value val, and
    - (iii) there is a blocking set b (e.g. f + 1 nodes) that all claim in their suggest messages that val is safe at v' (see Rule 2).

Rule 2. We say that a node claims that val is safe in v' in a suggest message when either

- (1) v' is 0,
- (2) the node's highest vote-2 message, as reported in the suggest message, was sent at view  $v'' \ge v'$  and for value val, or
- (3) the second highest view for which the node sent a vote-2 message, as reported in the suggest message, is a view  $v'' \ge v'$ .

RULE 3. A node that receives a proposal from the leader of the current view determines that the value val is safe to propose in view v when:

- (1) A quorum q has sent proof messages in view v, and
- (2) According to what is reported in proof messages, either
  - (a) no member of q sent any vote-4 before view v, or
  - (b) there is a view v' < v such that
    - (i) no member of q sent any vote-4 messages for a view strictly higher than v', and
    - (ii) any member of q that sent a vote-4 message in view v' did so with value val, and
    - (iii) (A) there is a blocking set b (e.g. f + 1 nodes) that all claim in their proof messages that val is safe at v' (as described in Rule 4), or
      - (B) there is a value val, a view  $\tilde{v}$ , and blocking set  $\tilde{b}$  that all claim in their proof messages that  $\widetilde{val}$  is safe at  $\tilde{v}$  where  $v' \leq \tilde{v} < v$ , and there is a value  $\widetilde{val}'$ , a view  $\tilde{v}'$ , and blocking set  $\tilde{b}'$  that all claim in their proof messages that  $\widetilde{val}' \neq \widetilde{val}$  is safe at  $\tilde{v}'$  where  $\tilde{v} < \tilde{v}' < v$ .

Rule 4. We say that a node claims that val is safe in v' in a proof message when either

- (1) v' is 0,
- (2) the node's highest vote-1 message, as reported in the proof message, was sent at view  $v'' \ge v'$ and for value val, or

(3) the second highest view for which the node sent a vote-1 message, as reported in the proof message, is a view  $v'' \ge v'$ .

#### 3.3 Helper Algorithms

In this section, we introduce two helper algorithms that assist nodes in efficiently determining safe values according to Rule 1 and Rule 3 respectively. In Section 4.1, we will prove the existence of a safe proposal according to Rule 1: upon receiving suggest messages from a quorum that includes all well-behaved nodes, a well-behaved leader is able to determine a value to be safe (see Lemma 2). However, it is important to note that a leader does not know whether the suggest messages it receives are from well-behaved nodes or not. Therefore, the leader should carefully select a quorum from at most n suggest messages to determine a safe value. This process necessitates an efficient algorithm, which we present as Algorithm 4 for Rule 1. Similarly, for Rule 3, we introduce Algorithm 5, which allows nodes to efficiently identify a quorum from at most n proof messages to determine the safety of a leader's proposal. Algorithm 1 illustrates a function utilized in both Algorithm 4 and Algorithm 5 describing the contents of Rule 2 and Rule 4. Rule 2 and Rule 4 can be found in Appendix A.

**Algorithm 1** node\_claim\_safe(*suggest/proof*, *v'*, *val*)

```
    if suggest then vote ← suggest.vote2, prev_vote ← suggest.prev_vote2
    if proof then vote ← proof.vote1, prev_vote ← proof.prev_vote1
    if v' = 0 then
    return true
    else if vote.view ≥ v' and vote.val = val then
    return true
    else if prev_vote.view ≥ v' then
    return true
    else
    return true
```

The key point of Algorithm 4 lies in tracing back from view v - 1 to find the view v' as specified in Rule 1, where v denotes the current view. A notable optimization to reduce the algorithm's complexity lies in skipping a view if it lacks sufficient vote-2 and prev-vote-2 (see line 19 in Algorithm 4), as Rule 1 Item 2(b)iii is not satisfied. The overall computational complexity of Algorithm 4 is  $O(v \times m \times n)$ , where m = O(n) is the number of possible values derived from vote-3 and prev-vote-2 messages, and n is the total number of nodes.

The logic in lines 11-19 of Algorithm 5 is similar to Algorithm 4, but is simplified as the value is given. For verifying Rule 3 Item 2(b)iiiB, the goal is to identify two blocking sets that claim two different values val and val' safe, at views  $\tilde{v}$  and  $\tilde{v}'$ , satisfying  $v' \leq \tilde{v} < \tilde{v}' < v$ . Although it involves identifying three specific views, v',  $\tilde{v}$  and  $\tilde{v}'$ , the process only backtracks from view v - 1once, which is crucial for complexity reduction. We first verify if the number of nodes claiming a value safe (using Algorithm 1) meets the size of a blocking set. If so, we record the (*view*, *val*) pair, representing the possible blocking sets. We then verify every possible combination of these pairs to ensure that the two blocking sets are within the same quorum, thereby satisfying Rule 3 Item 2(b)ii. Upon determining  $\tilde{v}$  and  $\tilde{v}'$ , it is critical to note that for identifying v', verifying whether  $v' = \tilde{v}$ meets Rule 3 Item 2(b)i and Item 2(b)ii suffices. This is because if no quorum member sent any vote-4 messages for a view strictly higher than v' (Rule 3 Item 2(b)i), this condition remains valid



Fig. 1. Liveness lemmas logical framework.

for smaller value of v', thus also reducing the computational complexity. The algorithm maintains an overall complexity of  $O(v \times m \times n)$ , the same as Algorithm 4.

# 4 SECURITY ANALYSIS

In this section, we prove that Basic TetraBFT solves the problem of consensus as defined in Definition 1. We first prove some useful lemmas on liveness and safety. The proof for liveness is the most interesting, and it follows the logic illustrated in Fig. 1. Our first objective is to prove the existence of a safe value, showing that a leader is capable of determining a value as safe upon receiving suggest messages from a quorum containing all well-behaved nodes. We then proceed to demonstrate that once a well-behaved node has received proof messages from each of the other well-behaved nodes, it determines the leader's proposal safe. Finally, we show that when all well-behaved nodes determine the leader's proposal safe, a decision is consequently made.

The proof of safety is divided into two main components: within-view safety and cross-view safety. We first prove that well-behaved nodes cannot make conflicting decisions within the same view. Regarding cross-view safety, we show that after a value is decided by any well-behaved node, all well-behaved nodes will not send vote-1 messages for a different value in future views, thus preventing any possibility of conflicting decisions.

Building on liveness and safety arguments, we finally present the main theorem. TetraBFT guarantees agreement, validity and termination in partial synchrony.

#### 4.1 Liveness Argument

The argument concerning liveness is predicated on the assumption that view *v* is led by a wellbehaved leader and the network is synchronous (i.e. the view starts after GST). The first lemma establishes that when a well-behaved node sends a vote-1 or a vote-2 message for a value *val*, it means that the node claims *val* is safe in all preceding views, and this assertion is maintained in all subsequent views. This lemma illustrates a property that the set of safe values claimed by a well-behaved node shrinks as views advance, yet the claim holds in later views. We prove the first statement of the lemma by considering two cases: whether the value of the highest vote-1 message in later views matches *val* or not. By mapping these two cases to Rule 4 Item 2 and Rule 4 Item 3 respectively, the statement is proved. Similarly, by altering vote-1 message to vote-2 message and proof message to suggest message and using Rule 2 Item 2 and Rule 2 Item 3, the second statement is also validated.

LEMMA 1. If a well-behaved node sends a vote-1 message for value val in view v, it will claim val is safe at any view  $\leq v$  in its proof message in views greater than v. Similarly, if a well-behaved node sends a vote-2 message for value val in view v, it will claim val is safe at any view  $\leq v$  in its suggest message in views greater than v.

**PROOF.** We prove the lemma for the case of the proof message and the same logic can be applied to the suggest message. Our aim is to demonstrate that if a well-behaved node, denoted as i, sends a vote-1 message for value val in view v, then in its proof message in views greater than v, it will

claim *val* is safe at any view v' with  $v' \le v$ . Suppose *i* sends a vote-1 message for value *val* in view *v*. In *i*'s proof message in a view greater than *v*, the highest vote-1 message was sent in a view v'' with  $v'' \ge v \ge v'$  for some value *val*'. If *val'* = *val*, then the highest vote-1 message was sent at a view  $v'' \ge v'$  and for value *val*, satisfying Rule 4 Item 2. If *val'*  $\ne val$ , then the second highest view for which *i* sent a vote-1 message (for a different value from the highest vote-1) was at a view  $\ge v'$ , satisfying Rule 4 Item 3. Combining these two cases, we have that node *i* claims in its proof message in views greater than *v* that *val* is safe at view v'. Similarly, by altering vote-1 message to vote-2 message and proof message to suggest message, using Rule 2 Item 2 and Rule 2 Item 3, the same line of reasoning substantiates the second statement. Thus, the lemma is proven.

The following lemma proves that a leader is able to determine a safe value once it receives suggest messages from a quorum containing all well-behaved nodes, while Algorithm 4 gives an efficient solution to find the safe value. We validate this lemma by analyzing Rule 1. The case corresponding to Rule 1 Item 2a is straightforward. Regarding Rule 1 Item 2b, we consider the last view v' where some node in the quorum sent vote-3 messages, as specified in Rule 1 Item 2(b)i. Building on this, the fulfillment of Rule 1 Item 2(b)ii can be easily inferred by the quorum-intersection property (i.e., the intersection of two quorums must contain at least one well-behaved node), and Rule 1 Item 2(b)ii is logically supported by Lemma 1.

LEMMA 2. Upon receiving suggest messages from a quorum containing all well-behaved nodes, a leader determines some value val that is safe.

PROOF. Suppose in a view  $v \neq 0$ , a well-behaved leader received suggest messages from a quorum q containing all well-behaved nodes. If no member of q sent any vote-3 messages before view v, then any value proposed by the leader is safe according to Rule 1 Item 2a. Now consider there is a view v' < v which is the last view in which some nodes in q sent vote-3 messages. Suppose a member of quorum q, node i, has sent a vote-3 message for value val in view v'. In this case, node i must have received vote-2 messages for value val in view v' from a quorum of nodes, within which a blocking set b of nodes are well-behaved. According to Lemma 1, we have that all nodes in the blocking set b claim in their suggest messages that val is safe at v'. In addition, since no member of b sent vote-2 message for any value  $val' \neq val$  in view v', then there was no quorum of nodes that sent vote-2 message for val' in v'. Thus, no member in q sent a vote-3 message for any value other than val in v'. Then, by Rule 1 Item 2b, the claim is proved.

The subsequent lemma outlines the implications arising when a well-behaved node claims a value safe in its suggest message. Specifically, it shows how Rule 3 derives from each item in Rule 2. The case for Rule 2 Item 1 is straightforward. By applying Lemma 1, we show that Rule 3 Item 2(b)ii and Rule 3 Item 2(b)iii directly relate to Rule 2 Item 2 and Rule 2 Item 3, respectively.

LEMMA 3. If a well-behaved node claims that val is safe at v' in its suggest message in view v > v',

- (1) then there is a blocking set b composed entirely of well-behaved nodes such that, in any proof message in views greater than or equal to v, every member of b claims that val is safe at v',
- (2) or there are two blocking sets  $\tilde{b}$  and  $\tilde{b}'$  both composed entirely of well-behaved nodes such that, in any proof message in views greater than or equal to v, every member of  $\tilde{b}$  claims that val is safe at  $\tilde{v}$  where  $v' \leq \tilde{v} < v$ , and every member of  $\tilde{b}'$  claims that val'  $\neq$  val is safe at  $\tilde{v}'$  where  $\tilde{v} < \tilde{v}' < v$ .

**PROOF.** Suppose a well-behaved node *i* claims value *val* is safe at view v' in its suggest message in view *v*. By Rule 2, there are three cases and we will discuss each one separately.

First (Rule 2 Item 1), if v' = 0, then Rule 4 Item 1 will trivially be true for every well-behaved node.

Second (Rule 2 Item 2), if node *i*'s highest vote-2 message was sent at view  $v'' \ge v'$  for value *val*, then it has received a quorum of vote-1 messages for value *val* in view v''. Since 3f < n, it can be inferred that there is a well-behaved blocking set *b* that has sent vote-1 messages in view v'' for value *val*. According to Lemma 1, it follows that every node in the blocking set *b* claims in its proof message in views greater than or equal to *v* that *val* is safe at view v', which proves the claim by satisfying the first consequent.

Third (Rule 2 Item 3), node *i*'s second highest vote-2 message was sent at view  $\tilde{v}$  with  $v' \leq \tilde{v} < v$  for value val, and its highest vote-2 message was sent at a view denoted as  $\tilde{v}'$ , with  $\tilde{v} < \tilde{v}' < v$  and for value  $val' \neq val$ . From *i*'s second highest vote-2 message, it can be deduced that in view  $\tilde{v}$  a quorum of nodes has sent vote-1 messages for value val, where a blocking set  $\tilde{b}$  of nodes are well-behaved. According to Lemma 1, it follows that in any proof message in views greater than or equal to v, every member of  $\tilde{b}$  claims that val is safe at  $\tilde{v}$ . Similarly, from *i*'s highest vote-2 message, in view  $\tilde{v}'$  a quorum of nodes sent vote-1 messages for value val', where a blocking set b' of nodes are well-behaved. As per Lemma 1, it holds that in any proof message in views greater than or equal to v, every member of  $\tilde{b}'$  claims that val' is safe at  $\tilde{v}'$ . Thus, the second consequent of Lemma 3 is satisfied and we can conclude the proof.

The following lemma shows that a well-behaved node will determine a well-behaved leader's proposal as safe. To prove this lemma, we demonstrate alignment between the cases outlined in Rule 1 and those in Rule 3. The cases corresponding to v = 0 and Rule 1 Item 2a are straightforward. As for the case corresponding to Rule 1 Item 2b, we establish a one-to-one mapping from Rule 1 Item 2(b)i, Item 2(b)ii, Item 2(b)iii to Rule 3 Item 2(b)i, Item 2(b)ii, Item 2(b)iii by quorum-intersection and Lemma 3.

#### LEMMA 4. A well-behaved node eventually determines that the leader's value val is safe.

**PROOF.** According to the rule that a well-behaved leader uses to propose a safe value (Rule 1), there are three cases.

First, if v = 0, then all well-behaved nodes trivially determine that the leader's value is safe.

Second (Item 2a), suppose that  $v \neq 0$  and that the leader proposes *val* because a quorum *q* reports not sending any vote-3 messages. Then, there is an entirely well-behaved blocking set *b* that never sent any vote-3 messages. Since vote-4 messages are sent in response to a quorum of vote-3 messages, and since a quorum and a blocking set must have a well-behaved node in common, we conclude that no well-behaved node ever sent a vote-4 message. Thus, once a well-behaved node *i* receives proof messages from all other well-behaved nodes, *i* concludes that the proposal is safe according to Rule 3 Item 2a.

Third (Item 2b), suppose that the view is not 0 and we have a quorum q and a view  $v^\prime < v$  such that:

- (1) no member of q sent any vote-3 messages for a view strictly higher than v', and
- (2) any member of q that sent a vote-3 message in view v' did so with value val, and
- (3) there is a blocking set b (e.g. f + 1 nodes) that all claim in their suggest messages that *val* is safe at v' (see Rule 2).

We make the following observations:

- a) By Item 1 above, no well-behaved node sent any vote-4 message in any view higher than v'; otherwise, a quorum would have sent the corresponding vote-3 messages and, by the quorum-intersection property, this contradicts Item 1.
- b) By Item 2 above, we can deduce any well-behaved node that sent a vote-4 message in view v' did so for value *val*. This can be proved by contradiction. Suppose there is a well-behaved

node sent a vote-4 message for value  $val' \neq val$  in view v'. In this case, it implies that a well-behaved blocking set b sent vote-3 message for value val' in view v'. According to Item 2 above, and using the quorum-intersection property, the quorum q with val intersect with blocking set b with val', and this intersection includes at least one well-behaved node. This situation leads to a contradiction.

c) By Item 3, there is a well-behaved node that claims that *val* is safe in v' in its suggest message. By Lemma 3, we conclude that there is a blocking set *b* composed entirely of well-behaved nodes that claim in their proof messages that *val* is safe at v', or there are two blocking sets  $\tilde{b}$  and  $\tilde{b}'$  both composed entirely of well-behaved nodes such that, every member of  $\tilde{b}$  claims in its proof message that val is safe at  $\tilde{v}$  where  $v' \leq \tilde{v} < v$ , and every member of  $\tilde{b}'$  claims in its proof message that  $val' \neq val$  is safe at  $\tilde{v}'$  where  $\tilde{v} < \tilde{v}' < v$ .

By Items a), b), and c) and Rule 3, we conclude that, once every well-behaved node has received a proof message from every other well-behaved node, every well-behaved node determines that the leader's proposal is safe.  $\hfill \Box$ 

The final lemma on liveness shows if the leader's proposal is determined safe by all the wellbehaved nodes, then the protocol will proceeds smoothly and a decision will be reached by all the well-behaved nodes.

LEMMA 5. If all well-behaved nodes determine that the leader's value is safe, then a decision is made by all well-behaved nodes.

**PROOF.** If all well-behaved nodes determine that the leader's value *val* is safe, they will broadcast vote-1 messages for *val*. Consequently, all the well-behaved nodes receive n - f vote-1 messages for *val* and broadcast vote-2 messages for *val*. Continuing in the same logic, all well-behaved nodes broadcast vote-3 and vote-4 messages for *val*. Upon receiving n - f vote-4 messages for *val*, a decision is made by all well-behaved nodes.

## 4.2 Safety Argument

The first two lemmas show that within a view, well-behaved nodes send vote messages for the same value and decide the same value. These lemmas follow directly from the evolution of a view as discussed in Section 3.2 and can primarily be proven through the quorum-intersection property.

LEMMA 6. If two well-behaved nodes send a vote message in view v, where vote can be one of {vote-2,vote-3,vote-4}, for values val and val' separately, then val = val'.

**PROOF.** Observe two well-behaved nodes *i* and *j* send a vote-2 message in view *v* for *val* and *val'* respectively. Then, node *i* received vote-1 messages in view *v* for *val* from a quorum of nodes  $q_1$ , and node *j* received vote-1 messages in view *v* for *val'* from a quorum of nodes  $q_2$ . Since there are only *n* nodes,  $q_1 \cap q_2$  must contain at least one well-behaved node. Therefore, *val = val'* as well-behaved nodes only send one vote-1 message in a view. By similar logic, the same result can be concluded for vote-3 and vote-4.

LEMMA 7. If a well-behaved node decides a value val in view v, then no well-behaved node decides other values in view v.

**PROOF.** In view v, if a well-behaved node decides value val, it must have first received vote-4 messages for value val from a quorum of nodes. By Lemma 6, all well-behaved nodes that send vote-4 messages in view v do so with the same value val. Well-behaved nodes only send vote-4 messages for a value val after receiving at least n - f vote-3 messages for the value val'. Since n - f > f, at least one of those messages must have been received from a well-behaved node,

and thus val' = val. By applying similar reasoning, every well-behaved node that sends a vote-1 message does so with value val'' = val. If two well-behaved nodes separately decide different values, it implies that two quorums of nodes must have sent vote-1 messages for two different values, leading to a contradiction.

In the following lemma, we demonstrate that if a value is decided in view v, then in later views, no well-behaved node determines a different value as safe. We approach the proof by contradiction, starting with the assumption that there exists a scenario where a different value is determined safe (in accordance with Rule 3), focusing on the first view where this occurs. Then we compare view v with the view appeared in the Rule 3 Item 2(b)i (denoted as v''), leading to three cases. It becomes straightforward to check that cases where v'' < v and v'' = v result in contradictions due to the quorum-intersection property. Then we discuss the case where v'' > v, examining Item 2(b)iiiA and Item 2(b)iiiB. For Item 2(b)iiiA, we verify the cases outlined in Rule 4 and find that, under the assumption that this is the first view a different value is determined safe, they either do not exist or lead to contradictions. In the case of Item 2(b)iiiB, we establish that it is impossible for the two blocking sets to meet any of the four possible combinations of Rule 4 Item 3 and Rule 4 Item 2 by the logic of views and values. Additionally, it is straightforward to verify that Rule 4 Item 1 cannot hold.

LEMMA 8. If a well-behaved node decides a value val in view v, then no well-behaved node sends a vote-1 message for a different value val' of any later view v' > v.

**PROOF.** Assume by contradiction that a well-behaved node *i* decides value *val* in view *v*, and let v' > v be the first view in which some well-behaved node (denoted as *j*) sends vote-1 message for a value other than *val* (denoted as *val'*). Before sending vote-1, node *j* receives a quorum q' of proof messages in view *v'*, and determines the proposal from the leader for value *val'* is safe. As node *i* decides value *val* in view *v*, there must be a quorum *q* that has sent vote-4 messages in view *v*. Then we discuss cases of Rule 3 Item 2a and Rule 3 Item 2b individually.

- 1. Since  $q \cap q'$  must contain one well-behaved node who has sent vote-4 in view v, the case of Rule 3 Item 2a is impossible.
- 2. Now consider Rule 3 Item 2b, and there is a view v'' < v' satisfies conditions in Rule 3 Item 2b. In this case, we discuss three cases separately: v'' < v, v'' = v, and v'' > v.
  - a) When v'' < v, a quorum q sends vote-4 messages in view v. Two quorums q and q' intersect at least one well-behaved node, who has sent a vote-4 message in view v > v'', contradicting Rule 3 Item 2(b)i.
  - b) When v'' = v, again by quorum intersection, there must exists at least one well-behaved node in q' that has sent a vote-4 message for value val in view v'' = v; however, any member of q' should not have sent vote-4 message for any value other than val' according to Rule 3 Item 2(b)ii. This is a contradiction.
  - c) When v'' > v, if Rule 3 Item 2(b)iiiA is satisfied, there is a blocking set *b* where all members claim in their proof messages that *val'* is safe at v''. Notably, *b* must contain at least one well-behaved node, which we denote as *k*. Subsequently, we examine each condition in Rule 4 for *k*.
    - i. Since v'' > v, then  $v'' \neq 0$ , making it impossible for Rule 4 Item 1 to hold.
    - ii. As for the circumstance of Rule 4 Item 2, if val' is claimed safe at v'' in k's proof message, there is a view v''' with  $v'' \le v''' < v'$  where k sends a vote-1 message for value val'. However, v' is the first view where some node sends vote-1 for val'. Thus, this situation is nonexistent.

- d) When v'' > v, if Rule 3 Item 2(b)iiiB is satisfied, there is a blocking set  $\tilde{b}$  where all members claim in their proof messages that val is safe at  $\tilde{v}$  where  $v'' \leq \tilde{v} < v'$ , and there is a blocking set  $\tilde{b}'$  where all members claim in their proof messages that  $val' \neq val$  is safe at  $\tilde{v}'$  where  $\tilde{v} < \tilde{v}' < v'$ . Notably,  $\tilde{b}$  must contain at least one well-behaved node, denoted as *m*, and similarly,  $\tilde{b}'$  must contain at least one well-behaved node, denoted as *m'*. We discuss the scenarios involving combinations of Rule 4 for *m* and *m'*.
  - i. Since v'' > v, then  $v'' \neq 0$ , making it impossible for Rule 4 Item 1 to hold for either *m* and *m'*.
  - ii. Next, we examine the scenario in which either of *m* or *m'* satisfies Rule 4 Item 3. Without loss of generality, we assume *m* satisfies Rule 4 Item 3. Accordingly, *m* sends a vote-1 message for value  $\overline{val}$  in view  $\overline{v}$  and a vote-1 message for  $\overline{val'} \neq \overline{val}$  in view  $\overline{v}'$ , where  $\overline{v} \leq \overline{v} < \overline{v'} < v'$ . Since *v'* is the first view wherein a vote-1 message for a value different from *val* is sent, we deduce that  $\overline{val} = \overline{val'} = val$ . Thus, this situation does not exist. Likewise, the same holds true for node *m'*. Therefore, either *m* or *m'* satisfies Rule 4 Item 3.
  - iii. Then, only one case remains, that is, both *m* and *m'* follows Rule 4 Item 2. Accordingly, since val is claimed safe at  $\tilde{v}$  in *m*'s proof message, there is a view  $\bar{v}$  with  $\tilde{v} \leq \hat{v} < v'$  where *m* sends a vote-1 message for value val. Since *v'* is the first view where some node sends vote-1 for a value different from *val*. Then, we can deduce that val = val. Similarly, we have val' = val. However, this contradicts the premise of  $val \neq val'$ . Consequently, this situation is nonexistent.

Thus, in no circumstances does node *j* decide that leader's proposal for value *val'* safe. Therefore, it never sends a vote-1 message for a value *val'* in view v' > v, which concludes the claim.  $\Box$ 

#### 4.3 Main Theorem

Building on these arguments, we now present the main theorem.

THEOREM 1. TetraBFT guarantees agreement, validity and termination in partial synchrony. Specifically, it guarantees agreement and validity even in periods of asynchrony, while termination is assured after GST.

PROOF. The proof for each property is provided separately.

**Termination.** By Lemma 2, Lemma 4 and Lemma 5, we conclude that a decision is reached by all well-behaved nodes.

**Agreement.** We consider two scenarios involving well-behaved nodes *i* and *j* deciding value *val* and *val'*  $\neq$  *val* respectively. If *i* and *j* decide value in the same view, Lemma 7 implies that *val* = *val'*, as a contradiction would arise otherwise. Now, suppose *i* decides *val j* in view *v* and *j* decides value *val'*  $\neq$  *val* in a later view v' > v. According to Lemma 8, no well-behaved node would send a vote-1 message with value different from *val* in view *v'* or subsequent views. Similarly, no well-behaved node would send a vote-2 message for a different value *val'* in any v' > v. That is because, to do so, it must have first received n - f vote-1 messages for value *val'*. For the same reasons, no well-behaved node sends vote-3 or vote-4 messages for a value *val'*  $\neq$  *val* and ultimately decides it in view v'. Based on these analyses, it's evident that once a value *val* is decided

by a well-behaved node, no other well-behaved node can decide a different value  $val' \neq val$  at any stage of the protocol.

**Validity.** Assume that all nodes are well-behaved and that they have the same input value *val*. Consider a well-behaved leader proposes the initial value *val*, and each well-behaved node sends vote messages do so for value *val* in the previous views. Consequently, by assumption, the initial value *val* is determined safe. Then vote-1 message sent by well-behaved nodes will be for *val*. If a node sends a vote-2 messages for a different value *val'*, it must have first received n - f vote-1 messages for *val'*. However, since all vote-1 messages from well-behaved nodes are for *val*, it logically follows that *val'* = *val*. Subsequently, if a node sends vote-3 messages for a value *val'*, it must have received n - f vote-2 messages for value *val'*. However, since two quorums intersect at least one behave node, it is impossible that a quorum of nodes send vote-2 for *val* and a quorum of nodes send vote-2 for a value *val'*  $\neq$  *val*, given that some well-behaved node has sent a vote-2 message for *val*. Similarly, if a node sends vote-4 and decides a value, that value cannot be any value other than *val*.

#### 5 FORMAL VERIFICATION

To gain one more degree of confidence in TetraBFT, we formalize the single-shot protocol of Section 3 in TLA+ [22] and we use the Apalache model-checker [21] to formally verify that the agreement property holds in all possible executions of a system with 4 nodes, including one Byzantine node, that try to agree on a value among 3 different values and execute 5 views.

Since every view consists of 4 voting phases, including Byzantine behavior, the size of the state-space to explore, even within those seemingly small bounds, is staggeringly large. In our experiments, explicitly exploring even a small fraction of this state-space was out of reach with explicit state exploration using the TLC model-checker [22]. Checking the agreement property by unrolling the transition relation, which is the default mode with the Apalache model-checker, is also unrealistic because, given our model of the protocol, Apalache would need to unroll a complex transition relation at least 5 \* 4 \* 4 = 80 times (5 views times 4 voting phases times 4 nodes) to reach the end of view 5. In our experiments, verifying the agreement property when the transition relation is unfolded only 10 times already takes too long.

Instead, to perform the verification, we provide the Apalache model-checker with a candidate inductive invariant *Inv* implying the agreement property, and we ask Apalache to verify that the invariant is inductive. This involves checking that *Inv* holds in the initial state and checking that if *Inv* holds in an arbitrary state and the system takes one single step, then *Inv* holds again in the new state. For a symbolic model-checker like Apalache, this is much easier than unrolling the transition relation, and Apalache successfully verifies that the invariant is inductive in about three hours on a consumer desktop machine. The formal specification appears in full in Appendix B.

# 6 MULTI-SHOT TETRABFT

In this section, we extend Basic TetraBFT, which enables nodes to reach consensus on a single value, to Multi-shot TetraBFT. This extension allows nodes to achieve consensus on a sequence of blocks, thereby forming a blockchain. We first demonstrate the protocol in the good case. Subsequently, building on the protocol for the ideal case, we explore scenarios involving timeouts, thereby necessitating the incorporation of a view-change mechanism.

# 6.1 Multi-Shot TetraBFT in the Good Case

In the Multi-shot TetraBFT, blocks are indexed by slot numbers. A pre-determined leader in each slot appends its block to that of the previous slot. Upon receiving the block  $b_i$  for slot i, each node ensures that 1) a block  $b_{i-1}$  for slot i - 1 has received a quorum of votes; 2)  $b_i$  extends  $b_{i-1}$ .

Once both conditions are satisfied, a well-behaved node then broadcasts a vote message for  $b_i$ . Simultaneously, upon receiving block  $b_i$  and confirming both conditions, a well-behaved leader for slot i + 1 proposes a new block extending  $b_i$ . This proposal can effectively serve as an implicit vote to save one message per slot. A block is *notarized* on receiving votes from a quorum of nodes. The first block in a chain of four notarized blocks with consecutive slot numbers is finalized, as well as its entire prefix in the chain.

In Fig. 2, we give an example to illustrate the protocol under the good case (with well-behaved leaders and synchrony). Starting with view 0 of slot *s*, a well-behaved leader proposes a block with value *val*<sub>1</sub>. On receiving *val*<sub>1</sub>, a well-behaved leader proposes a block with value *val*<sub>2</sub>. At the same time, each well-behaved node determines *val*<sub>1</sub> safe (as the view number is 0), and broadcasts a vote message (vote, *slot* – *s*, *view* – 0, *value* – *val*<sub>1</sub>), which represents vote-1 for *val*<sub>1</sub>. In slot *s* + 1, upon determining *val*<sub>2</sub> safe and notarizing the block for slot *s* (i.e., receiving a quorum of vote messages for it), each well-behaved node broadcasts a vote message (vote, *slot* – *s* + 1, *view* – 0, *value* – *val*<sub>2</sub>). This vote represents vote-1 for *val*<sub>2</sub> and vote-2 for *val*<sub>1</sub>. Simultaneously, a well-behaved leader proposes a block with value *val*<sub>3</sub>. In slot *s* + 2, after determining *val*<sub>3</sub> safe and receiving a quorum of vote message for *val*<sub>2</sub> of slot *s* + 1, a well-behaved node broadcasts a vote -1 for *val*<sub>3</sub>, vote-2 for *val*<sub>2</sub> and vote-3 for *val*<sub>1</sub>. The process in slot *s* + 3 mirrors that of slot *s* + 2, hence its explanation is omitted here. After nodes receiving a quorum of vote messages (vote, *slot* – *s* + 3, *view* – 0, *value* – *val*<sub>4</sub>), the block for slot *s* + 3 is notarized and the block for slot *s* is finalized.



Fig. 2. Example of Multi-shot TetraBFT in the good case.

## 6.2 View Change in Multi-Shot TetraBFT

The preceding section presents an ideal scenario where a block is successfully finalized in view 0. In this section, we illustrate the protocol's operation in instances requiring a view change due to aborted blocks (refer to Algorithm 2 and 3). Upon receiving a proposal message for the slot s - 1, a well-behaved node starts the slot s and sets the view timer. Should the 9 $\Delta$  timeout elapse without block finalization, the node broadcasts a view-change message for the next view, indicating the lowest slot number of the aborted blocks. Note that if a block is aborted, all subsequent blocks are aborted as well; however, the number of aborted blocks is limited by the protocol's finality latency, specifically to 5. On receiving f + 1 view-change messages for view v and slot s, a node broadcasts a view-change message for view v and slot s, a node changes to view v for all slots numbered no less than s and resets the corresponding timers. Nodes keep

monitoring view-change messages regardless of the current view. Upon view change, a node sends suggest/proof messages for all aborted slots. On receiving the suggest messages, a well-behaved leader of view v and slot s proposes a new block with a safe value. Subsequently, the protocol mirrors the good case, with the distinction that proposals and votes for safe values are informed by suggest/proof messages and guided by Rule 1 and Rule 3 in views other than 0.



Fig. 3. Example of Multi-shot TetraBFT with failed blocks.

We also provide an example illustrating a block failure leading to a view change (refer to Fig. 3). Starting with view 0 of slot 1, a view timer  $t_1$  starts. A well-behaved leader proposes a block with value  $val_1$ , and subsequently nodes vote for  $val_1$  and start a view timer  $t_2$  for slot 2. Concurrently, a well-behaved leader for slot 2 proposes a block with value  $val_2$ . Upon receiving a quorum of vote messages (vote, slot - 1, view - 0,  $value - val_1$ ), a well-behaved node votes for  $val_2$ . However, if a well-behaved node fails to receive a quorum of vote messages for  $val_2$  by the time  $t_1$  expires, it results in aborting the block for slot 1, consequently, the block for slot 2. In response, the node broadcasts a view-change message (view-change, slot - 1, view - 1). When a node receives n - fview-change messages for view 1, it changes to view 1 and resets the view timer  $t_1$ . It then sends two proof messages (vote-1, slot-1, view-0,  $value-val_1$ ), (vote-1, slot-2, view-0,  $value-val_2$ ) and one suggest message (vote-2, slot - 1, view - 0,  $value - val_1$ ) (notably, although vote messages do not explicitly indicate the phase, this information is preserved in the local memory). Upon receiving enough suggest messages, a well-behaved leader for view 1 and slot 1 proposes a new block with a safe value *val*'<sub>1</sub>, adhering to Rule 1. On receiving the proposal message with *val*'<sub>1</sub>, a well-behaved node resets the view timer  $t_2$  and advances to view 1 of slot 2. On determining  $val'_1$  safe according to Rule 3, a well-behaved node broadcasts a vote message (vote, slot - 1, view - 1,  $value - val'_1$ ). Simultaneously, a well-behaved leader for view 1 and slot 2 proposes a block with a safe value val', following Rule 1. After determining  $val'_2$  safe and receiving a quorum of vote messages for  $val'_1$ , a well-behaved node broadcasts a vote message (vote, slot - 2, view - 1,  $value - val'_2$ ). The process for slot 3 mirrors that for slot 2, and is thus not detailed further. As no block for slot 4 was proposed previously, it defaults to starting from view 0. Slot 4 and subsequent slots proceed as in the good case described earlier. If a quorum of vote messages for slot 4 is received before the expiration of timer  $t_1$ , the block for slot 4 is notarized and the block for slot 1 is finalized.

#### 6.3 Security Analysis for Multi-shot TetraBFT

THEOREM 2. Multi-shot TetraBFT guarantees consistency and liveness.

## **Algorithm 2** *view\_change(v, s)*

#### Code for node *i*:

1:	$proposed_v \leftarrow v + 1$
2:	while true do
3:	<b>upon</b> receiving $f + 1$ (view-change, $slot - s'$ , $view - v'$ ) messages <b>do</b>
4:	if $v' > proposed_v$ then
5:	$proposed_v \leftarrow v'$
6:	broadcast a <pre>\view-change, slot - s', view - proposed_v</pre> message
7:	<b>upon</b> receiving $n - f$ (view-change, $slot - s''$ , $view - v''$ ) messages <b>do</b>
8:	$v \leftarrow v''$
9:	$s \leftarrow s''$
10:	abort blocks for $s, s + 1,$ (view timers $t_s, t_{s+1},$ are invalid)
11:	broadcast a suggest and a proof message for block $s, s + 1, \ldots$

#### Algorithm 3 Multi-shot TetraBFT

С	ode for node <i>i</i> :			
1: $v \leftarrow 0, s \leftarrow 1$				
2: while true do				
3:	continually <b>run</b> <i>view_change</i> ( <i>v</i> , <i>s</i> ) in the background			
4:	a view timer t <sub>s</sub> starts // a new slot s begins			
5:	continually <b>run</b> lines 6-8 in the background			
6:	for $t_{s_k} \in (t_{s-3}, t_{s-2}, t_{s-1})$ do			
7:	at time $t_{s_k} + 9\Delta$ do			
8:	broadcast a $\langle view-change, slot - s_k, view - v_{s_k} + 1 \rangle$ message			
9:	if block s is not proposed before then			
10:	$v \leftarrow 0$			
11:	if $s = 1$ and node $i =$ leader then			
12:	propose block s with a safe value val according to Rule 1			
13:	if node $i \neq$ leader and determines block s's value val safe according to Rule 3 then			
14:	broadcast a (vote, $slot - s$ , $view - v$ , $value - val$ ) message			
15:	if node <i>i</i> = leader <b>then</b>			
16:	propose block $s + 1$ with a safe value <i>val'</i> according to Rule 1			
17:	<b>upon</b> receiving $n - f$ (vote, <i>slot</i> – <i>s</i> , <i>view</i> – <i>v</i> , <i>value</i> – <i>val</i> ) messages <b>do</b>			
18:	notarize block s with value val			
19:	if blocks $s - 3$ , $s - 2$ , $s - 1$ , $s$ are notarized <b>then</b>			
20:	finalize block $s - 3$			
21:	$s \leftarrow s + 1$			

**PROOF.** In the Multi-shot TetraBFT protocol, every vote serves multiple purposes: it acts as a proposal for the current block *s*, and simultaneously as vote-1 for block s - 1, vote-2 for block s - 2, vote-3 for block s - 3, and vote-4 for block s - 4. Each vote is sent only after receiving a quorum from the preceding vote. In a view-change case, if a node receives n - f view-change messages for a view and slot, it changes to the new view for that block. This scenario necessitates the sending of suggest/proof messages as well. In the Multi-shot TetraBFT protocol, the structure

of voting and the process for view change are consistent with basic TetraBFT, allowing us to apply the properties of basic TetraBFT to validate Multi-shot TetraBFT.

**Consistency.** Assuming two chains are finalized by two well-behaved nodes, and if one chain is neither a prefix of the other nor identical, this situation leads to the finalization of two distinct blocks within the same slot. However, according to the agreement property of the basic TetraBFT, no two well-behaved nodes can decide different values. This scenario presents a contradiction to the agreement property of basic TetraBFT.

**Liveness.** We consider after GST that all messages are guaranteed to be delivered. Consider a scenario where a well-behaved node receives a sequence of proposals (transactions) from well-behaved leaders. Consequently, all well-behaved nodes will receive these proposals from the leaders. Leveraging the validity and termination properties of the basic TetraBFT protocol, each well-behaved node will make a decision on each proposal. In the good case, every proposal is decided and notarized as a block. In the view-change case, after  $5\Delta$  time ( $2\Delta$  for view change and  $3\Delta$  for suggest/proof message, proposal message, and a vote message), a new block gets notarized. Given that every sequence of four consecutive blocks gets notarized, the first block is finalized. Therefore, as long as there are blocks that have been notarized, it follows that the transactions received can also be finalized.

# 7 CONCLUSION AND FUTURE WORK

In this paper, we have improved upon the state-of-the-art in optimally-resilient, optimistically responsive, partially-synchronous unauthenticated BFT consensus protocols, deploying new algorithmic principles to propose TetraBFT, which achieves better latency than IT-HS [3] while guaranteeing constant storage and linear communicated bits per node per view.

Moreover, we have proposed a pipelined version of TetraBFT which, at least in theory, multiplies the throughput of TetraBFT by a factor of 5, and we have conducted the first detailed analysis of a pipelined protocol in the unauthenticated setting.

Taking stock, we asked in the introduction what is the minimum good-case latency achievable for optimistic responsiveness with constant space. TetraBFT shows that the latency of 6 message delays achieved by IT-HS is not optimal, as it achieves 5. However, whether 5 is the lower bound remains an open question. Anecdotal evidence could point towards a lower bound of 5, as a recent investigation of the connected-consensus problem [7] (a generalization of adopt-commit and graded agreement), which is solvable asynchronously, also arrived at an unauthenticated BFT protocol with 5 phases.

In future work, it would also be interesting to implement multi-shot Tetra BFT and conduct a practical evaluation, in particular in the context of heterogeneous trust systems such as the XRP Ledger or the Stellar network, where TetraBFT has the potential to offer better guarantees than currently deployed protocols, and in the context of trustless cross-chain synchronization protocols executed by smart contracts.

#### ACKNOWLEDGMENTS

This work is supported in part by a gift from Stellar Development Foundation and by the Guangzhou-HKUST(GZ) Joint Funding Program (No. 2024A03J0630).

#### REFERENCES

 Ittai Abraham, Kartik Nayak, Ling Ren, and Zhuolun Xiang. 2021. Good-case Latency of Byzantine Broadcast: a Complete Categorization. In *Proceedings of the 2021 ACM Symposium on Principles of Distributed Computing (PODC'21)*. Association for Computing Machinery, New York, NY, USA, 331–341. https://doi.org/10.1145/3465084.3467899

- [2] Ittai Abraham, Ling Ren, and Zhuolun Xiang. 2022. Good-Case and Bad-Case Latency of Unauthenticated Byzantine Broadcast: A Complete Categorization. In DROPS-IDN/v2/document/10.4230/LIPIcs.OPODIS.2021.5. Schloss-Dagstuhl – Leibniz Zentrum für Informatik. https://doi.org/10.4230/LIPIcs.OPODIS.2021.5
- [3] Ittai Abraham and Gilad Stern. 2020. Information theoretic hotstuff. arXiv preprint arXiv:2009.12828 (2020).
- [4] Ittai Abraham and Gilad Stern. 2021. Information Theoretic HotStuff (IT-HS): Part One. https://decentralizedthoughts. github.io/2021-09-20-information-theoretic-hotstuff-it-hs-part-one/.
- [5] Ignacio Amores-Sesar, Christian Cachin, and Jovana Mićić. 2020. Security analysis of ripple consensus. arXiv preprint arXiv:2011.14816 (2020).
- [6] Hagit Attiya and Jennifer L Welch. 2023. Multi-valued connected consensus: A new perspective on crusader agreement and adopt-commit. arXiv preprint arXiv:2308.04646 (2023).
- [7] Hagit Attiya and Jennifer L. Welch. 2023. Multi-Valued Connected Consensus: A New Perspective on Crusader Agreement and Adopt-Commit. https://doi.org/10.48550/arXiv.2308.04646 arXiv:2308.04646 [cs].
- [8] Ethan Buchman. 2016. Tendermint: Byzantine fault tolerance in the age of blockchains. Ph. D. Dissertation. University of Guelph.
- [9] Christian Cachin. 2021. Asymmetric distributed trust. In International Conference on Distributed Computing and Networking 2021. 3–3.
- [10] Christian Cachin, Giuliano Losa, and Luca Zanolini. 2023. Quorum Systems in Permissionless Networks. In 26th International Conference on Principles of Distributed Systems (OPODIS 2022) (Leibniz International Proceedings in Informatics (LIPIcs), Vol. 253), Eshcar Hillel, Roberto Palmieri, and Etienne Rivière (Eds.). Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl, Germany, 17:1–17:22. https://doi.org/10.4230/LIPIcs.OPODIS.2022.17 ISSN: 1868-8969.
- [11] Miguel Castro. 2001. Practical Byzantine Fault Tolerance. Ph.D. MIT.
- [12] Miguel Castro and Barbara Liskov. 2002. Practical byzantine fault tolerance and proactive recovery. ACM Transactions on Computer Systems (TOCS) 20, 4 (2002), 398–461.
- [13] Miguel Castro, Barbara Liskov, et al. 1999. Practical byzantine fault tolerance. In OsDI, Vol. 99. 173-186.
- [14] Benjamin Y Chan and Elaine Shi. 2020. Streamlet: Textbook streamlined blockchains. In Proceedings of the 2nd ACM Conference on Advances in Financial Technologies. 1–11.
- [15] Danny Dolev and Rüdiger Reischuk. 1985. Bounds on Information Exchange for Byzantine Agreement. J. ACM 32, 1 (Jan. 1985), 191–204. https://doi.org/10.1145/2455.214112
- [16] D. Dolev and H. R. Strong. [n. d.]. Authenticated Algorithms for Byzantine Agreement. 12, 4 ([n. d.]), 656–666. https://doi.org/10.1137/0212045 Publisher: Society for Industrial and Applied Mathematics.
- [17] Cynthia Dwork, Nancy Lynch, and Larry Stockmeyer. 1988. Consensus in the presence of partial synchrony. Journal of the ACM (JACM) 35, 2 (1988), 288–323.
- [18] Álvaro García-Pérez and Alexey Gotsman. 2018. Federated Byzantine Quorum Systems. In 22nd International Conference on Principles of Distributed Systems (OPODIS 2018). Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik.
- [19] Rati Gelashvili, Lefteris Kokoris-Kogias, Alberto Sonnino, Alexander Spiegelman, and Zhuolun Xiang. 2022. Jolteon and ditto: Network-adaptive efficient consensus with asynchronous fallback. In *International Conference on Financial Cryptography and Data Security*. Springer, 296–315.
- [20] Mohammad M Jalalzai, Jianyu Niu, Chen Feng, and Fangyu Gai. 2023. Fast-hotstuff: A fast and robust bft protocol for blockchains. *IEEE Transactions on Dependable and Secure Computing* (2023).
- [21] Igor Konnov, Jure Kukovec, and Thanh-Hai Tran. 2019. TLA+ model checking made symbolic. Proceedings of the ACM on Programming Languages 3, OOPSLA (Oct. 2019), 123:1–123:30. https://doi.org/10.1145/3360549
- [22] Leslie Lamport. 2002. Specifying Systems: The TLA+ Language and Tools for Hardware and Software Engineers. Addison-Wesley Longman Publishing Co., Inc., USA.
- [23] Andrew Lewis-Pye and Tim Roughgarden. 2023. Permissionless Consensus. https://doi.org/10.48550/arXiv.2304.14701 arXiv:2304.14701 [cs].
- [24] Xiao Li, Eric Chan, and Mohsen Lesani. 2023. Quorum subsumption for heterogeneous quorum systems. In 37th International Symposium on Distributed Computing (DISC 2023). Schloss-Dagstuhl-Leibniz Zentrum für Informatik.
- [25] Marta Lokhava, Giuliano Losa, David Mazières, Graydon Hoare, Nicolas Barry, Eli Gafni, Jonathan Jove, Rafał Malinowsky, and Jed McCaleb. 2019. Fast and secure global payments with stellar. In Proceedings of the 27th ACM Symposium on Operating Systems Principles. 80–96.
- [26] Giuliano Losa, Eli Gafni, and David Mazières. 2019. Stellar Consensus by Instantiation. In 33rd International Symposium on Distributed Computing (DISC 2019) (Leibniz International Proceedings in Informatics (LIPIcs), Vol. 146), Jukka Suomela (Ed.). Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, Dagstuhl, Germany, 27:1–27:15. https://doi.org/10.4230/ LIPIcs.DISC.2019.27 tex.ids= losaStellarConsensusInstantiation2019a ISSN: 1868-8969.
- [27] Dahlia Malkhi and Kartik Nayak. 2023. HotStuff-2: Optimal Two-Phase Responsive BFT. *Cryptology ePrint Archive* (2023).

23

- [28] Rafael Pass and Elaine Shi. 2018. Thunderella: Blockchains with Optimistic Instant Confirmation. In Advances in Cryptology – EUROCRYPT 2018 (Lecture Notes in Computer Science), Jesper Buus Nielsen and Vincent Rijmen (Eds.). Springer International Publishing, Cham, 3–33. https://doi.org/10.1007/978-3-319-78375-8\_1
- [29] M. Pease, R. Shostak, and L. Lamport. [n. d.]. Reaching Agreement in the Presence of Faults. 27, 2 ([n. d.]), 228–234. https://doi.org/10.1145/322186.322188
- [30] Peiyao Sheng, Xuechao Wang, Sreeram Kannan, Kartik Nayak, and Pramod Viswanath. 2023. TrustBoost: Boosting Trust among Interoperable Blockchains. In Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security. 1571–1584.
- [31] Ertem Nusret Tas, Runchao Han, David Tse, and Mingchao Yu. 2023. Interchain timestamping for mesh security. In Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security. 1585–1599.
- [32] Maofan Yin, Dahlia Malkhi, Michael K Reiter, Guy Golan Gueta, and Ittai Abraham. 2019. HotStuff: BFT consensus with linearity and responsiveness. In Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing. 347–356.

#### APPENDIX

# A HELPER ALGORITHMS

#### Algorithm 4 A leader determines value val safe in view v

Input: suggest messages({suggest[vote2[view, val], prev\_vote2[view, val]], vote3[view, val]}), v 1: vote3 val\_set  $\leftarrow \emptyset$ , vote2 val\_set  $\leftarrow \emptyset$ 2:  $val \leftarrow val_{init}$ , count\_no\_vote3  $\leftarrow 0$ 3: vote2 view val dict  $\leftarrow$  {}, prev vote2 view val dict  $\leftarrow$  {} // vote2\_view\_val\_dict : {view : (cnt, vote2\_inner\_val\_set)} prev vote2 view val dict : {view, cnt} 4: for all suggest  $\in$  suggest messages do **if** suggest.vote $3 = \emptyset$  **then** ▶ Rule 1 Item 2a 5:  $count\_no\_vote3 \leftarrow count\_no\_vote3 + 1$ 6: if  $count_no_vote3 \ge n - f$  then 7: return val 8: **else if** *suggest.vote3.val* ∉ *vote3\_val\_set* **then** 9: add suggest.vote3.val to vote3\_val\_set 10: **if**  $suggest.vote2 \neq \emptyset$  and  $suggest.prev_vote2 = \emptyset$  **then** 11:  $vote2\_view\_val\_dict[suggest.vote2.view] \leftarrow \{cnt \leftarrow cnt + 1 \text{ if } suggest.vote2.view}$ 12: exists in the dict else 1, add *suggest.vote2.val* to *vote2\_inner\_val\_set*} if suggest.prev vote  $2 \neq \emptyset$  then 13: prev vote2 view val dict[suggest.prev vote2.view]  $\leftarrow$  {cnt  $\leftarrow$  cnt + 1 14: if *suggest.prev vote2.view* exists in the dict else 1} 15: **for**  $v' \leftarrow v - 1, v - 2, ..., 0$  **do** ▶ Rule 1 Item 2b quorum num  $\leftarrow 0$ , blocking num  $\leftarrow 0$ 16:  $vote2\_view\_ge\_v'\_cnt \leftarrow \sum vote2\_view\_val\_dict[view][cnt] if view \ge v'$ 17:  $prev_vote2_view_ge_v'_cnt \leftarrow \sum prev_vote2_view_val_dict[view][cnt] if view \ge v'$ 18: if  $vote2\_view\_ge\_v'\_cnt + prev\_vote2\_view\_ge\_v'\_cnt < f + 1$  then 19: continue 20. else 21.  $vote2 val\_set \leftarrow vote2 val\_set \cup vote2\_view\_val\_dict[v'][vote2\_inner\_val\_set]$ 22. for all  $val \in vote2 \ val\_set \cup vote3 \ val\_set$  do 23. for all  $suggest \in suggest$  messages do 24. **if** suggest.vote3.view < v' **or** (suggest.vote3.view = v' **and** 25: suggest.vote3.val = val) then  $quorum\_num \leftarrow quorum\_num + 1$ 26: 27: **if** node\_claim\_safe(suggest, v', val) = true **then** 28:  $blocking_num \leftarrow blocking_num + 1$ **if**  $quorum_num \ge n - f$  **and**  $blocking_num \ge f + 1$  **then** 29: return val 30: 31: return val

Algorithm 5 A node determines value *val* safe in view *v* 

Input: proof messages({proof[vote1[view, val], prev vote1[view, val]], vote4[view, val]}), v, val 1: count no vote4  $\leftarrow 0$ 2: val view dict = {} // val view dict = {(view, val) : proof message inner set} 3: vote1 val set  $\leftarrow \emptyset$ 4: for all  $proof \in proof$  messages do ▶ Rule 3 Item 2a **if** *proof*.*vote* $4 = \emptyset$  **then** 5: count no vote4  $\leftarrow$  count no vote4 + 1 6: if count no vote  $4 \ge n - f$  then 7: return true 8: **if** *proof*.*vote*  $1 \neq \emptyset$  and *proof*.*prev vote*  $1 = \emptyset$  **then** 9: add proof.vote1.val to vote1 val set 10: 11: for  $v' \leftarrow v - 1, \ldots, 0$  do ▶ Rule 3 Item 2(b)iiiA quorum\_num  $\leftarrow 0$ , blocking\_num  $\leftarrow 0$ 12: for all  $proof \in proof$  messages do 13: if proof.vote4.view < v' or (proof.vote4.view = v' and proof.vote4.val = val) then 14:  $quorum\_num \leftarrow quorum\_num + 1$ 15: **if**  $node_claim_safe(proof, v', val) = true$  **then** 16:  $blocking_num \leftarrow blocking_num + 1$ 17: **if** quorum\_num  $\ge n - f$  **and** blocking\_num  $\ge f + 1$  **then** 18: return true 19: 20: for view  $\leftarrow v - 1, \ldots, 0$  do ▶ Rule 3 Item 2(b)iiiB for all  $val \in vote1_val_set$  do 21: node claim safe cnt  $\leftarrow 0$ , proof inner set  $\leftarrow \emptyset$ 22: for all  $proof \in proof$  messages do 23: **if** node\_claim\_safe(proof, view, val) = true **then** 24: 25: node claim safe  $cnt \leftarrow node$  claim safe cnt + 1add val to proof\_inner\_set 26: **if**  $node\_claim\_safe\_cnt \ge f + 1$  **then** 27:  $val\_view\_dict[(view, val)] \leftarrow \{proof\_inner\_set\}$ 28: for all {(view', val') : proof\_inner\_set'} in val\_view\_dict 29: if (view' > view and  $val' \neq val)$  do  $quorum\_num \leftarrow 0, proof\_quorum\_set \leftarrow \emptyset$ 30: for all *proof*  $\in$  proof messages do 31: // it is sufficient to check if Rule 3 Items 2(b)i and 2(b)ii hold only when v' = view**if** proof.vote4.view < view 32: **or** (*proof.vote4.view* = *view* **and** *proof.vote4.val* = *val*) **then**  $quorum\_num \leftarrow quorum\_num + 1$ 33: add proof to proof quorum set 34: if quorum\_num  $\geq n - f$  and 35:  $|proof\_inner\_set \cap proof\_quorum\_set| \ge f + 1$  and  $|proof\_inner\_set' \cap proof\_quorum\_set| \ge f + 1$  then return true 36: 37: return false

#### — module Voting -1 1 This is a high-level specification of TetraBFT. There is no explicit network or messages at this level of 2 abstraction However, we do model Byzantine failures. **EXTENDS** Integers 3 CONSTANTS V the set of values to decide on *P* the set of processes (typically 3f+1 nodes) Quorum the set of quorums (typically, sets of 2f+1 nodes out of 3f+1) Blocking the set of blocking sets (typically, sets of f+1 nodes out of 3f+1) $B \;$ the set of malicious nodes (typically f nodes) View the set of views 10 Each view consists of 4 phases: 11 Phase $\stackrel{\Delta}{=} 1 \dots 4$ 12 A vote is cast in a phase of a view and for a value: 13 $Vote \stackrel{\Delta}{=} [view : View, phase : Phase, value : V]$ 14 NotAVote $\triangleq$ [view $\mapsto$ -1, phase $\mapsto$ 1, value $\mapsto$ choose val $\in$ V : true] 15 Whether vote vt is maximal in S 16 $Maximal(vt, S) \triangleq$ 17 Λ $vt \in S$ 18 $\forall vt2 \in S: vt2.view \leq vt.view$ Λ 19 A maximal element in the set S, if such exists, and otherwise the default value provided: 20 $Max(S, default) \triangleq$ 21 IF $\exists e \in S : Maximal(e, S)$ 22 Then choose $e \in S$ : Maximal(e, S)23 else default 24 We now specify the behaviors of the algorithm: 25 VARIABLES votes, view 26 $vars \stackrel{\Delta}{=} \langle view, votes \rangle$ 27 $TupeOK \triangleq$ 28 $\wedge \quad \textit{votes} \, \in \, [P \rightarrow \texttt{subset Vote}]$ 29 Λ $view \in [P \rightarrow View]$ 30 decided $\triangleq$ {val $\in$ V : $\exists Q \in Quorum, v \in View : \forall p \in Q \setminus B$ : 31 $[view \mapsto v, phase \mapsto 4, value \mapsto val] \in votes[p]\}$ 32 largest vote of p in phase 'phase' before view v 33 $HighestVote(p, phase, v) \triangleq$ 34 LET $vts \stackrel{\Delta}{=} \{vt \in votes[p] : vt.phase = phase \land vt.view < v\}$ IN 35 Max(vts, NotAVote) 36

#### В FORMAL SPECIFICATION OF TETRABFT IN TLA+

```
second largest vote (for a value different from the highest vote) of p in phase 'phase' before view v
37
    SecondHighestVote(p, phase, v) \stackrel{\Delta}{=}
38
         LET largest \triangleq Highest Vote(p, phase, v)
39
               vts \stackrel{\Delta}{=} \{vt \in votes[p] : vt.phase = phase \land vt.view < v \land vt.value \neq largest.value\}
         IN Max(vts, NotAVote)
41
      'v' is safe in view 'v2' according to the votes of process 'p' in phase 'phase' before view v:
42
    ClaimsSafeAt(val, v, v2, p, phase) \triangleq
43
          \vee v2 = 0
44
          \vee LET mv \stackrel{\Delta}{=} Highest Vote(p, 1, v)IN Highest vote of p in phase 1 before view v
45
                \land v2 \leq mv.view
46
                \land mv.value = v
47
          \lor v2 \leq SecondHighestVote(p, 1, v).view
48
      Whether value val is safe to vote for/propose in view v by process p
      In case of a vote, we'll use phaseA=4 and phaseB=1
50
51
      In case of a proposal, we'll use phaseA=3 and phaseB=2
    ShowsSafeAt(val, v, p, phaseA, phaseB) \stackrel{\Delta}{=}
52
          \vee v = 0
53
          \lor \exists Q \in Quorum :
54
               \land \forall \ q \ \in \ Q: view[q] \geq v \ \text{ every member of } \mathsf{Q} \text{ is in view at least } \mathsf{v}
55
                    members of Q never voted in phaseA before v:
56
                    \lor \forall q \in Q : HighestVote(q, phaseA, v).view = -1
57
                     or:
58
                    \lor \exists v2 \in View:
59
                         \wedge \, 0 < v2 \wedge v2 < v
60
                          no member of Q voted in phaseA in view v2 or later, and
61
                          all members of Q that voted in v2 voted for v:
62
                         \wedge \forall q \in Q: Let hvq \triangleq HighestVote(q, phaseA, v)IN
63
                              \wedge hvg.view < v2
64
                              \land hvq.view = v2 \Rightarrow hvq.value = v
65
                         \land val must be safe at v2
66
                              \forall \exists S \in Blocking : \forall q \in S : ClaimsSafeAt(val, v, v2, q, phaseB)
67
                              \lor \exists S1, S2 \in Blocking : \exists v1, v2 \in V : \exists v3, v4 \in View :
68
                                   \wedge \, v1 \neq v2
69
                                   \wedge v2 < v3 \wedge v3 < v4 \wedge v4 < v
70
                                   \land \forall q \in S1: ClaimsSafeAt(v1, v, v3, q, phaseB)
71
                                   \land \forall q \in S2 : ClaimsSafeAt(v2, v, v4, q, phaseB)
72
    Init \stackrel{\Delta}{=} The initial state
73
          \land votes = [p \in P \mapsto \{\}]
74
          \land view = [p \in P \mapsto 0]
75
      Next we specify the actions that can be taken:
76
    DoVote(p, val, v, phase) \triangleq
77
           never voted before in this view and phase:
78
```

 $\land \forall w \in V : [view \mapsto v, phase \mapsto phase, value \mapsto w] \notin votes[p]$ 79 cast the vote: 80  $\land votes' = [votes \text{ except } ! [p] = @ \cup \{[view \mapsto v, phase \mapsto phase, value \mapsto val]\}]$ 81  $\wedge$  unchanged  $\langle view \rangle$ 82  $Vote1(p, val, v) \triangleq$ 83  $\wedge v = view[p]$ 84  $\wedge$  ShowsSafeAt(val, v, p, 4, 1) 85  $\wedge$  Do Vote(p, val, v, 1)86 whether val has been voted for by a quorum of p in phase 'phase' of view 'v': 87  $Accepted(p, val, v, phase) \stackrel{\Delta}{=} \exists Q \in Quorum :$ 88  $\land p \in Q$ 89  $\land \forall q \in Q : [view \mapsto v, phase \mapsto phase, value \mapsto val] \in votes[q]$ 90  $Vote2(p, val, v) \stackrel{\Delta}{=}$ 91  $\wedge v = view[p]$ 92  $\wedge$  Accepted (p, val, v, 1)93  $\wedge$  DoVote(p, val, v, 2) 94  $Vote3(p, val, v) \stackrel{\Delta}{=}$ 95  $\wedge v = view[p]$ 96  $\wedge$  Accepted (p, val, v, 2)97  $\wedge$  DoVote(p, val, v, 3) 98  $Vote4(p, val, v) \triangleq$ 99  $\wedge v = view[p]$ 100  $\wedge$  Accepted (p, val, v, 3)101  $\wedge$  DoVote(p, val, v, 4)102  $StartView(p, v) \triangleq$ 103  $\wedge view[p] < v$ 104  $\land view' = [view \text{ except } ! [p] = v]$ 105  $\wedge$  unchanged  $\langle votes \rangle$ 106 This models malicious behavior 107 ByzantineHavoc  $\triangleq$ 108  $\exists new\_votes \in [P \rightarrow subset Vote]:$ 109  $\exists new\_view \in [P \rightarrow View]:$ 110  $\land votes' = [p \in P \mapsto if p \in B \text{ then } new\_votes[p] \text{ else } votes[p]]$ 111  $\land view' = [p \in P \mapsto if p \in B \text{ then } new_view[p] \text{ else } view[p]]$ 112  $Next \triangleq$ 113  $\lor$  ByzantineHavoc 114  $\lor \exists p \in P, val \in V, v \in View :$ 115  $\lor$  Vote1(p, val, v) 116  $\lor$  Vote2(p, val, v) 117  $\lor$  Vote3(p, val, v) 118

#### 28

 $\lor$  Vote4(p, val, v) 119  $\lor$  StartView(p, v)120  $Spec \stackrel{\Delta}{=} Init \wedge \Box [Next]_{vars}$ 121 Safety  $\triangleq \forall v1, v2 \in decided : v1 = v2$ 122 Simple properties 123  $VotedFor(p, v, val) \triangleq [view \mapsto v, phase \mapsto 4, value \mapsto val] \in votes[p]$ 124 *One* ValuePerBallot  $\triangleq \forall p \in P \setminus B : \forall vt, vt2 \in votes[p] :$ 125  $vt2.view = vt.view \land vt2.phase = vt.phase \Rightarrow vt2.value = vt.value$ 126 *NoFuture Vote*  $\triangleq \forall p \in P \setminus B : \forall vt \in votes[p] : vt.view \le view[p]$ 127 *OneValuePerPhasePerView*  $\triangleq \forall p \in P \setminus B : \forall vt \in votes[p] :$ 128  $\forall vt2 \in votes[p]:$ 129  $vt2.view = vt.view \land vt2.phase = vt.phase \Rightarrow vt2.value = vt.value$ 130  $VoteHasQuorumInPreviousPhase \triangleq \forall p \in P \setminus B : \forall vt \in votes[p] : vt.phase > 1 \Rightarrow$ 131  $\exists Q \in Quorum : \forall q \in Q \setminus B :$ 132  $[view \mapsto vt.view, phase \mapsto (vt.phase) - 1, value \mapsto vt.value] \in votes[q]$ 133 Now we state the main invariant 134  $DidNotVoteAt(p, v) \triangleq \forall val \in V : \neg VotedFor(p, v, val)$ 135  $CannotVoteAt(p, v) \triangleq view[p] > v \land DidNotVoteAt(p, v)$ 136 NoneOtherChoosableAt(v, val)  $\triangleq \exists Q \in Quorum :$ 137  $\forall p \in Q \setminus B : VotedFor(p, v, val) \lor CannotVoteAt(p, v)$ 138  $SafeAt(v, val) \triangleq \forall w \in View : 0 \le w \land w \le v \Rightarrow NoneOtherChoosableAt(w, val)$ 139  $VotesSafe \stackrel{\Delta}{=} \forall p \in P \setminus B : \forall vt \quad \in votes[p]:$ 140 SafeAt(vt.view, vt.value) 141 The full inductive invariant: 142 This invariant has been verified inductive by the Apalache model-checker for 4 processes (including one Byzantine), 3 values, and 5 views. 143 It took about three hours on a recent (2022) desktop computer 144 This means that Apalache verified that the Safety property holds for all possible executions within those bounds. 145 Invariant  $\triangleq$ 146  $\wedge$  TupeOK 147  $\land$  NoFuture Vote 148  $\land$  One Value PerPhase PerView  $\land$  VoteHasQuorumInPreviousPhase  $\land VotesSafe$ 151  $\land$  Safety 152 153